

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 06/23/2017 |
| 1.1 | 03/16/2020 | 400001009196 | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

SECTION 1. IDENTIFICATION

Product name : ARATHANE® 5750 A

Manufacturer or supplier's details

Company name of supplier : Huntsman Advanced Materials Americas LLC
Address : P.O. Box 4980
The Woodlands,
TX 77387
United States of America (USA)

Telephone : Non-Emergency: (800) 257-5547

E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Component of a Polyurethane System.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Flammable liquids : Category 3
Acute toxicity (Inhalation) : Category 4
Skin irritation : Category 2
Eye irritation : Category 2B
Respiratory sensitisation : Category 1
Skin sensitisation : Category 1
Reproductive toxicity : Category 2
Specific target organ toxicity - single exposure : Category 3 (Respiratory system)
Specific target organ toxicity - repeated exposure : Category 2 (Liver, Lungs, Kidney)
Short-term (acute) aquatic hazard : Category 3

GHS label elements

ARATHANE® 5750 A

Version 1.1 Revision Date: 03/16/2020 SDS Number: 400001009196 Date of last issue: 06/23/2017
Date of first issue: 06/23/2017

Print Date 08/13/2020

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: H226 Flammable liquid and vapour.
H315 + H320 Causes skin and eye irritation.
H317 May cause an allergic skin reaction.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs (Liver, Lungs, Kidney) through prolonged or repeated exposure.
H402 Harmful to aquatic life.

Precautionary statements

: **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P285 In case of inadequate ventilation wear respiratory protection.
Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.1 | 03/16/2020 | 400001009196 | 06/23/2017 |
| | | | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Mixture

Hazardous components

| Chemical name | CAS-No. | Concentration (% w/w) |
|---|------------|-----------------------|
| 4,4'-methylenediphenyl diisocyanate | 101-68-8 | 50 - 70 |
| Benzene, 1,1'-methylenebis[isocyanato-, homopolymer | 39310-05-9 | 20 - 30 |
| toluene | 108-88-3 | 5 - 10 |
| 2,4'-methylenediphenyl diisocyanate | 5873-54-1 | 1 - 5 |
| triethyl phosphate | 78-40-0 | 1 - 5 |

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Do not leave the victim unattended.
Get medical attention immediately if symptoms occur.
Show this safety data sheet to the doctor in attendance.

If inhaled : If breathed in, move person into fresh air.
Call a physician or poison control centre immediately.
Keep patient warm and at rest.
Keep respiratory tract clear.
If breathing is difficult, give oxygen.
If breathing is irregular or stopped, administer artificial respiration.
If unconscious, place in recovery position and seek medical advice.

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.1 | 03/16/2020 | 400001009196 | 06/23/2017 |
| | | | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

Consult a physician immediately if symptoms such as shortness of breath or asthma are observed.

A hyper-reactive response to even minimal concentrations of diisocyanates may develop in sensitised persons.

The exposed person may need to be kept under medical surveillance for 48 hours.

LC50 (rat) : ca. 490 mg/m³ (4 hours) : using experimentally produced respirable aerosol having aerodynamic diameter <5microns.

Methods used to generate the exposure concentrations in the animal studies use extreme laboratory conditions and does not represent actual exposure conditions of the material in the workplace, storage, transportation or expected use on the market due to the very low vapor pressure. Therefore, these test results cannot be used to for hazard classification of the material. Rather, an acute toxicity estimate is calculated based on weight of evidence and expert judgement and is used to justify a modified classification for acute inhalation toxicity.

- | | | |
|---|---|---|
| In case of skin contact | : | <p>In case of contact, immediately flush skin with soap and plenty of water.</p> <p>Take off contaminated clothing and shoes immediately.</p> <p>Wash contaminated clothing before reuse.</p> <p>Thoroughly clean shoes before reuse.</p> <p>Call a physician if irritation develops or persists.</p> <p>An MDI study has demonstrated that a polyglycol-based skin cleanser (such as D-Tam™, PEG-400) or corn oil may be more effective than soap and water.</p> |
| In case of eye contact | : | <p>Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.</p> <p>If easy to do, remove contact lens, if worn.</p> <p>Protect unharmed eye.</p> <p>Keep eye wide open while rinsing.</p> <p>Seek medical advice.</p> |
| If swallowed | : | <p>Gently wipe or rinse the inside of the mouth with water.</p> <p>DO NOT induce vomiting unless directed to do so by a physician or poison control center.</p> <p>Keep respiratory tract clear.</p> <p>Keep at rest.</p> <p>If a person vomits when lying on his back, place him in the recovery position.</p> <p>Never give anything by mouth to an unconscious person.</p> <p>Take victim immediately to hospital.</p> <p>If symptoms persist, call a physician.</p> |
| Most important symptoms and effects, both acute and delayed | : | <p>Severe allergic skin reactions, bronchospasm and anaphylactic shock</p> <p>This product is a respiratory irritant and potential respiratory sensitizer: repeated inhalation of vapour or aerosol at levels above the occupational exposure limit could cause respiratory sensitisation.</p> <p>Symptoms may include irritation to the eyes, nose, throat and lungs, possibly combined with dryness of the throat, tightness</p> |

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.1 | 03/16/2020 | 400001009196 | 06/23/2017 |
| | | | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

of chest and difficulty in breathing.

The onset of the respiratory symptoms may be delayed for several hours after exposure.

A hyper-reactive response to even minimal concentrations of MDI may develop in sensitised persons.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.
It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
First Aid responders should pay attention to self-protection and use the recommended protective clothing

Notes to physician : Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Foam
Carbon dioxide (CO₂)
Dry powder

Unsuitable extinguishing media : Water may be used if no other available and then in copious quantities. Reaction between water and hot isocyanate may be vigorous.

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
The pressure in sealed containers can increase under the influence of heat.
Exposure to decomposition products may be a hazard to health.

Hazardous combustion products : Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons and HCN. In the event of extreme heat (>500 degrees C), aniline is suspected of being formed.

No hazardous combustion products are known

Specific extinguishing methods : Cool containers/tanks with water spray.

Further information : Standard procedure for chemical fires.
Due to reaction with water producing CO₂-gas, a hazardous build-up of pressure could result if contaminated containers

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.1 | 03/16/2020 | 400001009196 | 06/23/2017 |
| | | | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

are re-sealed.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Prevent fire extinguishing water from contaminating surface water or the ground water system.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Immediately evacuate personnel to safe areas.
Use personal protective equipment.
If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.
Ensure adequate ventilation.
Keep people away from and upwind of spill/leak.
Only qualified personnel equipped with suitable protective equipment may intervene.
For additional precautions and advice on safe handling, see section 7.
Never return spills in original containers for re-use.
Make sure that there is a sufficient amount of neutralizing/absorbent material near the storage area.
The danger areas must be delimited and identified using relevant warning and safety signs.
Treat recovered material as described in the section "Disposal considerations".
For disposal considerations see section 13.

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.
Do not allow material to contaminate ground water system.
Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
Local authorities should be advised if significant spillages cannot be contained.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Clean-up methods - small spillage
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Clean contaminated surface thoroughly.
Sweep up or vacuum up spillage and collect in suitable container for disposal.
Neutralize small spillages with decontaminant.
The compositions of liquid decontaminants are given in Section 16.
Remove and dispose of residues.

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.1 | 03/16/2020 | 400001009196 | 06/23/2017 |
| | | | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

Clean-up methods - large spillage
If the product is in its solid form:
Spilled MDI flakes should be picked up carefully.
The area should be vacuum cleaned to remove remaining dust particles completely.
If the product is in its liquid form:
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Leave to react for at least 30 minutes.
Shovel into open-top drums for further decontamination.
Wash the spillage area with water.
Test atmosphere for MDI vapour.
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Technical measures : Ensure that eyewash stations and safety showers are close to the workstation location.

Local/Total ventilation : Use only with adequate ventilation.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : For personal protection see section 8.
Avoid formation of aerosol.
Do not breathe vapours or spray mist.
Do not breathe vapours/dust.
Do not swallow.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Avoid exposure - obtain special instructions before use.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Keep container closed when not in use.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Industrial use of aprotic polar solvents for cleaning can release hazardous primary aromatic amines (>0.1%)

Conditions for safe storage : Keep containers tightly closed in a dry, cool and well-ventilated place.
Keep in properly labelled containers.

ARATHANE® 5750 A

Version
1.1Revision Date:
03/16/2020SDS Number:
400001009196Date of last issue: 06/23/2017
Date of first issue: 06/23/2017

Print Date 08/13/2020

Observe label precautions.

Protect from moisture.

Electrical installations / working materials must comply with the technological safety standards.

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Materials to avoid : For incompatible materials please refer to Section 10 of this SDS.

Recommended storage temperature : 36 - 104 °F / 2 - 40 °C

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-------------------------------------|-----------|----------------------------------|---|-----------|
| 4,4'-methylenediphenyl diisocyanate | 101-68-8 | TWA | 0.005 ppm | ACGIH |
| | | TWA | 0.005 ppm 0.05 mg/m ³ | NIOSH REL |
| | | C | 0.02 ppm 0.2 mg/m ³ | NIOSH REL |
| | | C | 0.02 ppm 0.2 mg/m ³ | OSHA Z-1 |
| toluene | 108-88-3 | TWA | 20 ppm | ACGIH |
| | | TWA | 200 ppm | OSHA Z-2 |
| | | CEIL | 300 ppm | OSHA Z-2 |
| | | Peak | 500 ppm ((10 minutes) | OSHA Z-2 |
| | | TWA | 100 ppm 375 mg/m ³ | NIOSH REL |
| | | ST | 150 ppm 560 mg/m ³ | NIOSH REL |
| 2,4'-methylenediphenyl diisocyanate | 5873-54-1 | C | 0.02 ppm 0.2 mg/m ³ | OSHA Z-1 |
| | | TWA | 0.005 ppm 0.05 mg/m ³ | NIOSH REL |
| | | C | 0.02 ppm 0.2 mg/m ³ | NIOSH REL |

Biological occupational exposure limits

| Components | CAS-No. | Control parameters | Biological specimen | Sampling time | Permissible concentration | Basis |
|------------|----------|--------------------|---------------------|---------------------------------|---------------------------|-----------|
| toluene | 108-88-3 | Toluene | In blood | Prior to last shift of workweek | 0.02 mg/l | ACGIH BEI |

ARATHANE® 5750 AVersion
1.1Revision Date:
03/16/2020SDS Number:
400001009196Date of last issue: 06/23/2017
Date of first issue: 06/23/2017

Print Date 08/13/2020

| | | | | | | |
|--|--|----------|-------|--|---------------------|-----------|
| | | | | k | | |
| | | Toluene | Urine | End of shift (As soon as possible after exposure ceases) | 0.03 mg/l | ACGIH BEI |
| | | o-Cresol | Urine | End of shift (As soon as possible after exposure ceases) | 0.3 mg/g Creatinine | ACGIH BEI |

Personal protective equipment

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
In emergency, non-routine and unknown exposure situations, including confined space entries, a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied air respirator (SAR) with auxiliary self-contained air supply, should be used.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Material : butyl-rubber
Break through time : > 8 h

Material : Solvent-resistant gloves (butyl-rubber)
Material : Nitrile rubber
Break through time : 10 - 480 min

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Protective gloves should be worn when handling freshly made polyurethane products to avoid contact with trace residual materials which may be hazardous in contact with skin.

Use chemical resistant gloves classified under Standard EN374: protective gloves against chemicals and microorganisms. Examples of glove materials that might provide suitable protection include: Butyl rubber, Chlorinated polyethylene, Polyethylene, Ethyl vinyl alcohol copolymers laminated ("EVAL"), Polychloroprene (Neoprene*),

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.1 | 03/16/2020 | 400001009196 | 06/23/2017 |
| | | | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

Nitrile/butadiene rubber ("nitrile" or "NBR"), Polyvinyl chloride ("PVC" or "vinyl"), Fluoroelastomer (Viton*).

When prolonged or frequently repeated contact may occur, a glove with protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN374) is recommended.

When only brief contact is expected, a glove with protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN374) is recommended.

Notice: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all requisite workplace factors such as, but not limited to : other chemicals that may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), as well as instructions/specifications provided by the glove supplier

By industrial use of aprotic polar solvents for cleaning : Butyl rubber (0.7mm), Nitrile rubber (0.4mm), Chloroprene (0.5mm)

- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
Chemical splash goggles.
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.
Ensure that eyewash stations and safety showers are close to the workstation location.
Eye wash bottle with pure water
Tightly fitting safety goggles
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Recommended:
Overall (preferably heavy cotton) or Tyvek-Pro Tech 'C' , Tyvek Pro 'F' disposable coverall.
Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Protective measures : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing
The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Ensure that eye flushing systems and safety showers are located close to the working place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
Wash face, hands and any exposed skin thoroughly after handling.

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.1 | 03/16/2020 | 400001009196 | 06/23/2017 |
| | | | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

Remove contaminated clothing and protective equipment before entering eating areas.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash hands before breaks and immediately after handling the product.
Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|--|
| Appearance | : liquid |
| Colour | : yellow |
| Odour | : aromatic |
| Odour Threshold | : No data is available on the product itself. |
| pH | : No data is available on the product itself. |
| Freezing point | : No data is available on the product itself. |
| Melting point | : No data is available on the product itself. |
| Boiling point | : No data is available on the product itself. |
| Flash point | : 88 °F / 31 °C Method: Pensky-Martens closed cup |
| Evaporation rate | : No data is available on the product itself. |
| Flammability (solid, gas) | : No data is available on the product itself. |
| Flammability (liquids) | : No data is available on the product itself. |
| Upper explosion limit / Upper flammability limit | : No data is available on the product itself. |
| Lower explosion limit / Lower flammability limit | : No data is available on the product itself. |
| Vapour pressure | : No data is available on the product itself. |
| Relative vapour density | : No data is available on the product itself. |
| Relative density | : No data is available on the product itself. |
| Density | : 1.2 g/cm3 |
| Solubility(ies) | |
| Water solubility | : Water reactive (68 °F / 20 °C) |

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.1 | 03/16/2020 | 400001009196 | 06/23/2017 |
| | | | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

| | |
|--|---|
| Solubility in other solvents | : No data is available on the product itself. |
| Partition coefficient: n-octanol/water | : No data is available on the product itself. |
| Auto-ignition temperature | : No data is available on the product itself. |
| Thermal decomposition | : No data is available on the product itself. |
| Self-Accelerating decomposition temperature (SADT) | : No data is available on the product itself. |
| Viscosity | |
| Viscosity, dynamic | : 30 mPa.s |
| Explosive properties | : No data is available on the product itself. |
| Oxidizing properties | : No data is available on the product itself. |
| Particle size | : No data is available on the product itself. |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|---|
| Reactivity | : No dangerous reaction known under conditions of normal use. |
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : Reaction with water (moisture) produces CO ₂ -gas. Exothermic reaction with materials containing active hydrogen groups. The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of the reaction partners is good or is supported by stirring or by the presence of solvents. MDI is insoluble with, and heavier than water and sinks to the bottom but reacts slowly at the interface. A solid water-insoluble layer of polyurea is formed at the interface by liberating carbon dioxide gas. |
| Conditions to avoid | : Extremes of temperature and direct sunlight. Exposure to air or moisture over prolonged periods. |
| Incompatible materials | : Acids Amines Bases Metals water |
| Hazardous decomposition products | : Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons and HCN. In the event of extreme heat (>500 degrees C), aniline is suspected of being formed. |

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.1 | 03/16/2020 | 400001009196 | 06/23/2017 |
| | | | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : No data is available on the product itself.

Acute toxicity

Acute oral toxicity - Product : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity - Product : Assessment: The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.
Remarks: Methods used to generate the exposure concentrations in the animal studies use extreme laboratory conditions and does not represent actual exposure conditions of the material in the workplace, storage, transportation or expected use on the market due to the very low vapor pressure. Therefore, these test results cannot be used to for hazard classification of the material. Rather, an acute toxicity estimate is calculated based on weight of evidence and expert judgement and is used to justify a modified classification for acute inhalation toxicity.

Acute toxicity estimate: 1.66 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Components:

4,4'-methylenediphenyl diisocyanate:

Acute dermal toxicity : LD50 (Rabbit, male and female): > 9,400 mg/kg
Method: OECD Test Guideline 402

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Acute dermal toxicity : LD50 (Rabbit, male and female): > 9,400 mg/kg
Method: OECD Test Guideline 402

toluene:

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

2,4'-methylenediphenyl diisocyanate:

Acute dermal toxicity : LD50 (Rabbit, male and female): > 9,400 mg/kg
Method: OECD Test Guideline 402

triethyl phosphate:

Acute dermal toxicity : LD50 (Rabbit): > 20,000 mg/kg

Acute toxicity (other routes of : No data available

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 06/23/2017 |
| 1.1 | 03/16/2020 | 400001009196 | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

administration)

Skin corrosion/irritation**Components:**

4,4'-methylenediphenyl diisocyanate:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Irritating to skin.

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Species: Rabbit

Result: Skin irritation

toluene:

Species: Rabbit

Method: Directive 67/548/EEC, Annex V, B.4.

Result: Skin irritation

2,4'-methylenediphenyl diisocyanate:

Species: Rabbit

Assessment: Irritant

Method: OECD Test Guideline 404

Result: Irritating to skin.

triethyl phosphate:

Species: Rabbit

Assessment: No skin irritation

Method: OECD Test Guideline 404

Result: No skin irritation

Serious eye damage/eye irritation**Components:**

4,4'-methylenediphenyl diisocyanate:

Species: Rabbit

Result: Mild eye irritation

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Species: Rabbit

Result: Mild eye irritation

Method: OECD Test Guideline 405

toluene:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

2,4'-methylenediphenyl diisocyanate:

Species: Humans

Result: Irritation to eyes, reversing within 7 days

Assessment: Mild eye irritant

Method: OECD Test Guideline 405

Remarks: Mild eye irritation

triethyl phosphate:

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 06/23/2017 |
| 1.1 | 03/16/2020 | 400001009196 | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

Species: Rabbit
Result: Eye irritation
Method: OECD Test Guideline 405

Respiratory or skin sensitisation**Components:**

4,4'-methylenediphenyl diisocyanate:
Exposure routes: Skin
Species: Mouse
Method: OECD Test Guideline 429
Result: May cause sensitisation by skin contact.

Exposure routes: Respiratory Tract
Species: Guinea pig
Result: May cause sensitisation by inhalation.

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:
Exposure routes: Skin
Species: Guinea pig
Method: OECD Test Guideline 406
Result: May cause sensitisation by skin contact.

Exposure routes: Respiratory Tract
Species: Guinea pig
Result: May cause sensitisation by inhalation.

toluene:
Exposure routes: Skin
Species: Guinea pig
Method: Directive 67/548/EEC, Annex V, B.6.
Result: Does not cause skin sensitisation.

2,4'-methylenediphenyl diisocyanate:
Exposure routes: Skin
Species: Mouse
Assessment: May cause sensitisation by skin contact.
Result: Causes sensitisation.

Exposure routes: Respiratory Tract
Species: Guinea pig
Assessment: May cause sensitisation by inhalation.
Result: Causes sensitisation.

triethyl phosphate:
Exposure routes: Skin
Species: Mouse
Method: OECD Test Guideline 429
Result: Does not cause skin sensitisation.

Components:

4,4'-methylenediphenyl diisocyanate:
Assessment: May cause sensitisation by inhalation and skin contact.

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.1 | 03/16/2020 | 400001009196 | 06/23/2017 |
| | | | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

Assessment: May cause sensitisation by inhalation and skin contact.

2,4'-methylenediphenyl diisocyanate:
Assessment: Mild eye irritation**Germ cell mutagenicity****Components:**

4,4'-methylenediphenyl diisocyanate:

Genotoxicity in vitro : Concentration: 200 ug/plate
Metabolic activation: with and without metabolic activation
Method: Directive 67/548/EEC, Annex, B.13/14
Result: negative

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Genotoxicity in vitro : Concentration: ca 50 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

toluene:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

2,4'-methylenediphenyl diisocyanate:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

triethyl phosphate:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negativeMethod: OECD Test Guideline 482
Result: negative**Components:**

4,4'-methylenediphenyl diisocyanate:

Genotoxicity in vivo : Application Route: Inhalation
Exposure time: 3 Weeks
Dose: 118 mg/m3
Method: OECD Test Guideline 474
Result: negative

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Genotoxicity in vivo : Application Route: Inhalation
Exposure time: 3 Weeks
Dose: 118 mg/m3
Method: OECD Test Guideline 474
Result: negative

toluene:

Genotoxicity in vivo : Application Route: Intraperitoneal injection

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.1 | 03/16/2020 | 400001009196 | 06/23/2017 |
| | | | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

Method: OPPTS 870.5385
Result: negative

2,4'-methylenediphenyl diisocyanate:

Genotoxicity in vivo : Application Route: Inhalation
Exposure time: 3 w
Dose: 118 mg/m³
Method: OECD Test Guideline 474
Result: negative

triethyl phosphate:

Genotoxicity in vivo : Application Route: Intraperitoneal injection
Method: OECD Test Guideline 478
Result: negative

Components:

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Germ cell mutagenicity- : Animal testing did not show any mutagenic effects.
Assessment

Carcinogenicity**Product:**

Remarks: Rats have been exposed for two years to a respirable aerosol of polymeric MDI which resulted in a chronic pulmonary irritation at high concentrations. Only at the top level (6 mg/m³), there was a significant incidence of a benign tumour of the lung (adenoma) and one malignant tumour (adenocarcinoma). There were no lung tumours at 1 mg/m³ and no effects at 0.2 mg/m³. Overall, the tumour incidence, both benign and malignant, and the number of animals with the tumours were not different from controls. The increased incidence of lung tumours is associated with prolonged respiratory irritation and the concurrent accumulation of yellow material in the lung, which occurred throughout the study. In the absence of prolonged exposure to high concentrations leading to chronic irritation and lung damage, it is highly unlikely that tumour formation will occur.

Remarks: Industrial use of aprotic polar solvents for cleaning can release hazardous primary aromatic amines (>0.1%)
Based on animal studies, primary aromatic amines are considered as potential carcinogen to humans. Some of those chemicals are proven carcinogens to humans
Provided the recommended personal protective equipment and hygiene measures are applied, no adverse effects to human health are to be expected

Carcinogenicity - : No data available
Assessment

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.1 | 03/16/2020 | 400001009196 | 06/23/2017 |
| | | | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Components:**

toluene:

Effects on fertility

: Species: Rat, male and female

Application Route: Inhalation

General Toxicity - Parent: No observed adverse effect level: 1.875 mg/l

General Toxicity F1: No observed adverse effect level: 1.875 mg/l

Symptoms: Reduced foetal weight

Method: OECD Test Guideline 416

2,4'-methylenediphenyl diisocyanate:

Species: Rat, female

Application Route: Inhalation

Method: OECD Test Guideline 414

Result: Animal testing did not show any effects on fertility.

Species: Rat, male and female

Application Route: Inhalation

Method: OECD Test Guideline 414

Result: Animal testing did not show any effects on fertility.

Components:

4,4'-methylenediphenyl diisocyanate:

Effects on foetal

development

: Species: Rat, female

Application Route: Inhalation

General Toxicity Maternal: No observed adverse effect level: 4 mg/m³

Method: OECD Test Guideline 414

Result: No teratogenic effects

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Species: Rat, female

Application Route: Inhalation

General Toxicity Maternal: No observed adverse effect level: 4 mg/m³

Method: OECD Test Guideline 414

Result: No teratogenic effects

toluene:

Species: Rat, female

Application Route: Inhalation

General Toxicity Maternal: No observed adverse effect level: 2,812 mg/m³

Method: Other guidelines

Result: No teratogenic effects

2,4'-methylenediphenyl diisocyanate:

Species: Rat, male and female

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 06/23/2017 |
| 1.1 | 03/16/2020 | 400001009196 | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

Application Route: Inhalation
General Toxicity Maternal: No observed adverse effect level: 4 mg/m³
Method: OECD Test Guideline 414
Result: No teratogenic effects

triethyl phosphate:

Species: Rat
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level: 125 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Components:

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Reproductive toxicity - : No evidence of adverse effects on sexual function and fertility,
Assessment or on development, based on animal experiments.

toluene:

Reproductive toxicity - : Some evidence of adverse effects on development, based on
Assessment animal experiments.

STOT - single exposure**Components:**

4,4'-methylenediphenyl diisocyanate:

Exposure routes: Inhalation

Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Exposure routes: inhalation (dust/mist/fume)

Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

toluene:

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

2,4'-methylenediphenyl diisocyanate:

Exposure routes: Inhalation

Target Organs: Respiratory system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

STOT - repeated exposure**Components:**

toluene:

Target Organs: Liver, Lungs, Kidney

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 06/23/2017 |
| 1.1 | 03/16/2020 | 400001009196 | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

Assessment: May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity**Components:**

4,4'-methylenediphenyl diisocyanate:

Species: Rat, male and female

NOEC: 0.2 mg/m³

Exposure time: 2 yr

Number of exposures: 5 d

Method: OECD Test Guideline 453

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Species: Rat, male and female

NOEC: 0.2 mg/m³

Test atmosphere: dust/mist

Exposure time: 2 yr

Number of exposures: 5 d

Method: OECD Test Guideline 453

toluene:

Species: Rat, male and female

LOEC: 625 mg/kg, 600 ppm

Application Route: Ingestion

Test atmosphere: vapour

Exposure time: 13 Weeks

Number of exposures: 6 d

Method: OECD Test Guideline 453

2,4'-methylenediphenyl diisocyanate:

Species: Rat, male and female

NOEC: 0.2 mg/m³

Exposure time: 2 yr

Number of exposures: 5 d

Method: OECD Test Guideline 453

triethyl phosphate:

Species: Rat, male and female

NOAEL: 1000 mg/kg

Application Route: Ingestion

Exposure time: 4 Weeks

Number of exposures: 7 d

Method: Subacute toxicity

Components:

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Repeated dose toxicity - : No adverse effect has been observed in chronic toxicity
Assessment tests.

2,4'-methylenediphenyl diisocyanate:

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 06/23/2017 |
| 1.1 | 03/16/2020 | 400001009196 | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

Repeated dose toxicity - : Mild eye irritation
Assessment

Aspiration toxicity**Components:**

toluene:

May be fatal if swallowed and enters airways.

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:**

4,4'-methylenediphenyl diisocyanate:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

toluene:

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.1 | 03/16/2020 | 400001009196 | 06/23/2017 |
| | | | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

Toxicity to fish : LC50: 5.5 mg/l
Exposure time: 96 h
Test Type: flow-through test
Test substance: Fresh water

2,4'-methylenediphenyl diisocyanate:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

triethyl phosphate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water

Components:**4,4'-methylenediphenyl diisocyanate:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 24 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 24 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

toluene:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (Water flea)): 3.78 mg/l
Exposure time: 48 h
Test Type: Other guidelines
Test substance: Fresh water
Method: Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids

2,4'-methylenediphenyl diisocyanate:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 24 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

triethyl phosphate:

Toxicity to daphnia and other aquatic invertebrates : LC50: > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water

Components:

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 06/23/2017 |
| 1.1 | 03/16/2020 | 400001009196 | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 1,640 mg/l
 Exposure time: 72 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 201

triethyl phosphate:

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 901 mg/l
 Exposure time: 72 h
 Test Type: static test
 Test substance: Fresh water

M-Factor (Acute aquatic toxicity) : No data available

Components:

toluene:

Toxicity to fish (Chronic toxicity) : NOEC: 1.39 mg/l
 Exposure time: 40 d
 Test Type: flow-through test
 Test substance: Fresh water

Components:

4,4'-methylenediphenyl diisocyanate:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 10 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Test substance: Fresh water
 Method: OECD Test Guideline 211

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 10 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Test substance: Fresh water
 Method: OECD Test Guideline 211

toluene:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (Water flea)): 0.74 mg/l
 Exposure time: 7 d
 Test Type: Other guidelines
 Test substance: Fresh water
 Method: Daphnid Chronic Toxicity Test

2,4'-methylenediphenyl diisocyanate:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 10 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Test substance: Fresh water
 Method: OECD Test Guideline 211

triethyl phosphate:

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 31.6 mg/l

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.1 | 03/16/2020 | 400001009196 | 06/23/2017 |
| | | | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

| | |
|---|---|
| aquatic invertebrates (Chronic toxicity) | Exposure time: 21 d Test substance: Fresh water Method: OECD Test Guideline 211 |
|---|---|

| | |
|-------------------------------------|---------------------|
| M-Factor (Chronic aquatic toxicity) | : No data available |
|-------------------------------------|---------------------|

Components:

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

| | |
|----------------------------|---|
| Toxicity to microorganisms | : EC50 (activated sludge): > 100 mg/l Exposure time: 3 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 209 |
|----------------------------|---|

2,4'-methylenediphenyl diisocyanate:

| | |
|----------------------------|---|
| Toxicity to microorganisms | : EC50 (activated sludge): > 100 mg/l Exposure time: 3 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 209 |
|----------------------------|---|

triethyl phosphate:

| | |
|----------------------------|---|
| Toxicity to microorganisms | : (Pseudomonas putida): 2,985 mg/l Exposure time: 0.5 h Test Type: static test Test substance: Fresh water |
|----------------------------|---|

Components:

4,4'-methylenediphenyl diisocyanate:

| | |
|-------------------------------------|---|
| Toxicity to soil dwelling organisms | : NOEC (Eisenia fetida (earthworms)): >= 1,000 mg/kg Exposure time: 336 h Method: OECD Test Guideline 207 |
|-------------------------------------|---|

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

| | |
|-------------------------------------|--|
| Toxicity to soil dwelling organisms | : EC50 (Eisenia fetida (earthworms)): > 1,000 mg/kg Exposure time: 336 h Method: OECD Test Guideline 207 |
|-------------------------------------|--|

2,4'-methylenediphenyl diisocyanate:

| | |
|-------------------------------------|---|
| Toxicity to soil dwelling organisms | : NOEC (Eisenia fetida (earthworms)): >= 1,000 mg/kg Exposure time: 336 h Method: OECD Test Guideline 207 |
|-------------------------------------|---|

| | |
|----------------|---------------------|
| Plant toxicity | : No data available |
|----------------|---------------------|

| | |
|-------------------|---------------------|
| Sediment toxicity | : No data available |
|-------------------|---------------------|

| | |
|-----------------------------------|---------------------|
| Toxicity to terrestrial organisms | : No data available |
|-----------------------------------|---------------------|

Ecotoxicology Assessment

| | |
|------------------------|---------------------|
| Acute aquatic toxicity | : No data available |
|------------------------|---------------------|

| | |
|--------------------------|---------------------|
| Chronic aquatic toxicity | : No data available |
|--------------------------|---------------------|

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 06/23/2017 |
| 1.1 | 03/16/2020 | 400001009196 | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

Toxicity Data on Soil : No data available

Other organisms relevant to the environment : No data available

Persistence and degradability**Components:**

4,4'-methylenediphenyl diisocyanate:

Biodegradability : Inoculum: Domestic sewage
Concentration: 30 mg/l
Result: Not biodegradable
Biodegradation: 0 %
Exposure time: 28 d
Method: Inherent Biodegradability: Modified MITI Test (II)

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Biodegradability : Inoculum: Domestic sewage
Concentration: 30 mg/l
Result: Not biodegradable
Biodegradation: 0 %
Exposure time: 28 d
Method: Inherent Biodegradability: Modified MITI Test (II)

toluene:

Biodegradability : Inoculum: Sewage (STP effluent)
Concentration: 10 mg/l
Result: Readily biodegradable.
Biodegradation: 81 %
Exposure time: 5 d

2,4'-methylenediphenyl diisocyanate:

Biodegradability : Inoculum: Domestic sewage
Concentration: 30 mg/l
Result: Not biodegradable
Biodegradation: 0 %
Exposure time: 28 d
Method: Inherent Biodegradability: Modified MITI Test (II)

triethyl phosphate:

Biodegradability : Inoculum: activated sludge
Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Inoculum: activated sludge
Result: Inherently biodegradable.
Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 302B

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.1 | 03/16/2020 | 400001009196 | 06/23/2017 |
| | | | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

Biochemical Oxygen Demand (BOD) : No data available

Chemical Oxygen Demand (COD) : No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon (DOC) : No data available

Physico-chemical removability : No data available

Components:

4,4'-methylenediphenyl diisocyanate:

Stability in water : Degradation half life(DT50): 20 hrs (77 °F / 25 °C)
Remarks: Fresh water

triethyl phosphate:

Stability in water : Degradation half life(DT50): 5.5 yr (77 °F / 25 °C) pH: 7
Remarks: Fresh water

Photodegradation : No data available

Impact on Sewage Treatment : No data available

Bioaccumulative potential**Components:**

4,4'-methylenediphenyl diisocyanate:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 200
Remarks: Bioaccumulation is unlikely.

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 200
Remarks: Bioaccumulation is unlikely.

2,4'-methylenediphenyl diisocyanate:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 200
Remarks: Bioaccumulation is unlikely.

triethyl phosphate:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 0.5 - 0.8
Exposure time: 42 d

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 06/23/2017 |
| 1.1 | 03/16/2020 | 400001009196 | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

Test substance: Fresh water
Method: semi-static test

Components:

4,4'-methylenediphenyl diisocyanate:

Partition coefficient: n-octanol/water : log Pow: 4.51 (68 °F / 20 °C)
pH: 7
Method: OECD Test Guideline 117

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Partition coefficient: n-octanol/water : log Pow: 8.56 (68 °F / 20 °C)

toluene:

Partition coefficient: n-octanol/water : log Pow: 2.73 (68 °F / 20 °C)
pH: 7

2,4'-methylenediphenyl diisocyanate:

Partition coefficient: n-octanol/water : log Pow: 4.51 (68 °F / 20 °C)
pH: 7
Method: OECD Test Guideline 117

triethyl phosphate:

Partition coefficient: n-octanol/water : log Pow: 1.11
Method: Partition coefficient

Mobility in soil

Mobility : No data available

Components:

toluene:

Distribution among environmental compartments : Koc: 34 - 120
Method: OECD Test Guideline 312

Stability in soil : No data available

Other adverse effects

Environmental fate and pathways : No data available

Results of PBT and vPvB assessment : No data available

Endocrine disrupting potential : No data available

Adsorbed organic bound halogens (AOX) : No data available

Hazardous to the ozone layer

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 06/23/2017 |
| 1.1 | 03/16/2020 | 400001009196 | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

Global warming potential (GWP) : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA**

| | |
|--|---------------------|
| UN/ID No. | : UN 1866 |
| Proper shipping name | : Resin solution |
| Class | : 3 |
| Packing group | : III |
| Labels | : Flammable Liquids |
| Packing instruction (cargo aircraft) | : 366 |
| Packing instruction (passenger aircraft) | : 355 |

IMDG

| | |
|----------------------|------------------|
| UN number | : UN 1866 |
| Proper shipping name | : RESIN SOLUTION |

| | |
|------------------|-------------------|
| Class | : 3 |
| Packing group | : III |
| Labels | : 3 |
| EmS Code | : F-E, <u>S-E</u> |
| Marine pollutant | : no |

ARATHANE® 5750 A

Version 1.1 Revision Date: 03/16/2020 SDS Number: 400001009196 Date of last issue: 06/23/2017
 Date of first issue: 06/23/2017

Print Date 08/13/2020

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**DOT Classification**

UN/ID/NA number : UN 1866
 Proper shipping name : RESIN SOLUTION
 Class : 3
 Packing group : III
 Labels : FLAMMABLE LIQUID
 ERG Code : 127
 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|-------------------------------------|----------|--------------------|-----------------------------|
| 4,4'-methylenediphenyl diisocyanate | 101-68-8 | 5000 | 8234 |
| toluene | 108-88-3 | 1000 | 12500 |
| benzene | 71-43-2 | 10 | * |
| acetone | 67-64-1 | 5000 | * |

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
 Acute toxicity (any route of exposure)
 Respiratory or skin sensitisation
 Reproductive toxicity
 Specific target organ toxicity (single or repeated exposure)
 Skin corrosion or irritation
 Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

| | | |
|-------------------------------------|----------|----------------|
| 4,4'-methylenediphenyl diisocyanate | 101-68-8 | >= 50 - < 70 % |
| toluene | 108-88-3 | >= 5 - < 10 % |

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.1 | 03/16/2020 | 400001009196 | 06/23/2017 |
| | | | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

| | |
|------------------------|----------|
| 4,4'-methylenediphenyl | 101-68-8 |
| diisocyanate | |
| toluene | 108-88-3 |

California Prop. 65

WARNING: This product can expose you to chemicals including benzene, naphthalene, ethylbenzene, cumene, which is/are known to the State of California to cause cancer, and toluene, benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

| | |
|--------|---|
| CH INV | : The formulation contains substances listed on the Swiss Inventory |
| DSL | : All components of this product are on the Canadian DSL |
| AICS | : On the inventory, or in compliance with the inventory |
| NZIoC | : On the inventory, or in compliance with the inventory |
| ENCS | : On the inventory, or in compliance with the inventory |
| KECI | : On the inventory, or in compliance with the inventory |
| PICCS | : On the inventory, or in compliance with the inventory |
| IECSC | : On the inventory, or in compliance with the inventory |
| TCSI | : On the inventory, or in compliance with the inventory |
| TSCA | : On the inventory, or in compliance with the inventory |

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.


US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.

ARATHANE® 5750 A

Version 1.1 Revision Date: 03/16/2020 SDS Number: 400001009196 Date of last issue: 06/23/2017
 Date of first issue: 06/23/2017

Print Date 08/13/2020

SECTION 16. OTHER INFORMATION**Further information****NFPA 704:****HMIS® IV:**

| | | |
|------------------------|---|----------|
| HEALTH | * | 2 |
| FLAMMABILITY | | 3 |
| PHYSICAL HAZARD | | 0 |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard

Liquid decontaminants (percentages by weight or volume) :

Decontaminant 1 : *- sodium carbonate : 5 - 10 % *- liquid detergent : 0.2 - 2 % *- water : to make up to 100 %

Decontaminant 2 : *- concentrated ammonia solution : 3 - 8 % *- liquid detergent : 0.2 - 2 % *- water : to make up to 100 %

Decontaminant 1 reacts slower with diisocyanates but is more environmentally friendly than decontaminant 2.

Decontaminant 2 contains ammonia. Ammonia presents health hazards. (See supplier safety information.)

Revision Date : 03/16/2020

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
 ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
 NIOSH REL : USA. NIOSH Recommended Exposure Limits
 OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1
 Limits for Air Contaminants
 OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2
 ACGIH / TWA : 8-hour, time-weighted average
 NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour
 workday during a 40-hour workweek
 NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded
 at any time during a workday
 NIOSH REL / C : Ceiling value not be exceeded at any time.
 OSHA Z-1 / C : Ceiling
 OSHA Z-2 / TWA : 8-hour time weighted average
 OSHA Z-2 / CEIL : Acceptable ceiling concentration
 OSHA Z-2 / Peak : Acceptable maximum peak above the acceptable ceiling
 concentration for an 8-hr shift

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

ARATHANE® 5750 A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 06/23/2017 |
| 1.1 | 03/16/2020 | 400001009196 | Date of first issue: 06/23/2017 |

Print Date 08/13/2020

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.