

LOCTITE[®] LB 8209

Known as LOCTITE[®] Krytox[®] RFE Bearing Lubricant CP
April 2015

PRODUCT DESCRIPTION

LOCTITE[®] LB 8209 provides the following product characteristics:

Technology	Synthetic Grease
Base Oil Type	Perfluoropolyether (PFPE)
Thickener	Polytetrafluoroethylene (PTFE)
Appearance	White to off white buttery grease
Cure	Non-curing
Application	Lubrication
Specific Benefit	<ul style="list-style-type: none"> • Thermally stable • Chemical resistant • Non-flammable • Non-toxic • Waterproof • Compatible with most plastics • Outperforms petroleum-based grease • Can be used with chlorinated systems • Insoluble in all but fluorinated solvents

LOCTITE[®] LB 8209 is a high performance, chemically inert synthetic grease designed specifically to provide long-lasting lubrication in severe chemical environments. Typical applications include bearings, valves, etc. This product is typically used in applications with an operating range of -26 °C to +260 °C.

This lubricant has been evaluated by the German Federal Institute for Materials testing (Bundesanstalt Für Materialprüfung, BAM) for reactivity with gaseous oxygen (BAM 8104-4110). Results of BAM 8104-411 conclude that use of this lubricant should only be used in the following oxygen rich (gaseous) environments under the conditions stated below. The liquid oxygen sensitivity test was in accordance to Marshal Space Flight Center Specification 106B and found to have no reaction after 20 trials. Use of this lubricant under conditions other than stated below is not recommended. Each prospective user should test the proposed application thoroughly before repetitive use, using this data as a guide.

Conditions of Temperature and Pressure

For use with Gaseous Oxygen (BAM 8104-411)

Temperature, °C	Maximum Oxygen Pressure, MPa
≤60	11
60 to 100	10
100 to 175	6

Mechanical Impact in Liquid Oxygen (MSFC 106B)

Temperature	Impact Energy, Joules
Ambient	98

TYPICAL PROPERTIES

Specific Gravity @ 25 °C	1.89 to 1.93
Flash Point - See SDS	
Viscosity, base oil, ASTM D445, cSt: @ 20 °C	810
Oil Separation, ASTM D6184, % wt. loss: 30 hours @ 99 °C	3.0
Consistency, ISO 6743-99, NLGI Class	2
Penetration, ISO 2137, 1/10 mm	265 to 295

GENERAL INFORMATION

For safe handling information on this product, consult the Safety Data Sheet (SDS).

Directions for use:

1. For best results, remove old lubricant and thoroughly clean parts.
2. Lubricate as required to manufacturers specifications.
3. Monitor levels. Lubrication intervals should be extended significantly.

Not for product specifications

The technical data contained herein are intended as reference only. Please contact your local quality department for assistance and recommendations on specifications for this product.

Storage

Store product in the unopened container in a dry location. Storage information may be indicated on the product container labeling.

Optimal Storage: 8 °C to 21 °C. Storage below 8 °C or greater than 28 °C can adversely affect product properties.

Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel Corporation cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Center or Customer Service Representative.

Conversions

(°C x 1.8) + 32 = °F
kV/mm x 25.4 = V/mil
mm / 25.4 = inches
µm / 25.4 = mil
N x 0.225 = lb
N/mm x 5.71 = lb/in
N/mm ² x 145 = psi
MPa x 145 = psi
N·m x 8.851 = lb·in
N·m x 0.738 = lb·ft
N·mm x 0.142 = oz·in
mPa·s = cP

Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0