

Revision Date: 10/04/2022 Version 1.8

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product name** Methyl ethyl ketone

Recommended use of the chemical and restrictions on use

Recommended use Solvent.

Manufacturer or supplier's details

Company Univar Solutions USA, Inc. Address 3075 Highland Pkwy Suite 200

Downers Grove, IL 60515

United States of America (USA)

**Emergency telephone number:** 

Transport North America: CHEMTREC (1-800-424-9300) CHEMTREC INTERNATIONAL Tel # 703-527-3887

Additional Information: Responsible Party: Product Compliance Department

> E-mail: SDSNA@univarsolutions.com SDS Requests: 1-855-429-2661 Website: www.univarsolutions.com

#### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Flammable liquids : Category 2

Eye irritation : Category 2A

Specific target organ toxicity

- single exposure

: Category 3 (Central nervous system)

**GHS** label elements

Hazard pictograms





Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements : Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equip-

P242 Use only non-sparking tools.

SDS Number: 10000004346 1/12 Methyl ethyl ketone



Version 1.8 Revision Date: 10/04/2022

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep confortable for breathing. Call a POISON CENTER/

doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ atten-

tion.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

## Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Substance

#### **Hazardous components**

CAS-No.	Chemical name	Weight percent
78-93-3	Methyl ethyl ketone	90 - 100

Any Concentration shown as a range is due to batch variation.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If on skin, rinse well with water.

If on clothes, remove clothes.

SDS Number: 100000004346 2 / 12 Methyl ethyl ketone



Version 1.8 Revision Date: 10/04/2022

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Do not induce vomiting without medical advice.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during fire-

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

: Carbon oxides

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if nec-

essary.

Use personal protective equipment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec-

tive equipment and emer-

gency procedures

: Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

SDS Number: 100000004346 3 / 12 Methyl ethyl ketone



Version 1.8 Revision Date: 10/04/2022

If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

fire and explosion

: Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot

surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Container may be opened only under exhaust ventilation

hood.

Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

: No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
78-93-3	Methyl ethyl ketone	TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
			200 ppm 590 mg/m3	NIOSH REL
		ST	300 ppm	NIOSH REL

SDS Number: 100000004346 4 / 12 Methyl ethyl ketone



Version 1.8 Revision Date: 10/04/2022

	885 mg/m3	
TWA	200 ppm 590 mg/m3	OSHA Z-1
TWA	200 ppm 590 mg/m3	OSHA P0
STEL	300 ppm 885 mg/m3	OSHA P0

#### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concen-

tration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : Clear, colorless

Odour : characteristic, pungent, sweet

Odour Threshold : No data available

pH : No data available

Freezing Point (Melting point/freezing point)

: -86 °C (-123 °F)

SDS Number: 100000004346 5 / 12 Methyl ethyl ketone



Version 1.8 Revision Date: 10/04/2022

**Boiling Point (Boiling** 

point/boiling range)

: 79 - 81 °C (174 - 178 °F)

Flash point : -9 - -4 °C (16 - 25 °F)

Evaporation rate : < 7.7

(Butyl Acetate = 1)

Flammability (solid, gas) : No data available

Upper explosion limit : 11.5 %(V)

Lower explosion limit : 1 %(V)

Vapour pressure : < 94.500 mmHg @ 20 - 25 °C (68 - 77 °F)

Relative vapour density : < 2.5 @ 20 °C (68 °F)

(Air = 1.0)

Relative density : 0.804 - 0.807 @ 20 °C (68 °F)

Reference substance: (water = 1)

Density : 0.804 - 0.806 g/cm3 @ 20 °C (68 °F)

Solubility(ies)

Water solubility : completely miscible @ 20 °C (68 °F)

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: log Pow: 0.3

Auto-ignition temperature : 404 - 515 °C

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : 0.40 - 0.42 mPa.s @ 20 °C (68 °F)

Viscosity, kinematic : 0.51 mm2/s @ 20 °C (68 °F)

Surface tension : 24.8 mN/m, 20 °C

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

: Vapours may form explosive mixture with air.

SDS Number: 100000004346 6 / 12 Methyl ethyl ketone



Version 1.8 Revision Date: 10/04/2022

Conditions to avoid : Keep away from heat, flame, sparks and other ignition

sources.

Exposure to moisture

Incompatible materials : Alkalis

Chloroform

hydrogen peroxide

Nitric acid

Oxidizing agents

strong reducing agents

Hazardous decomposition

products

: Carbon oxides

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

## Serious eye damage/eye irritation

## **Components:**

78-93-3:

Species: Rabbit

Result: Irritating to eyes. Exposure time: 24 h

Carcinogenicity

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by ACGIH.

#### STOT - single exposure

#### **Components:**

78-93-3:

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single ex-

posure, category 3 with narcotic effects.

SDS Number: 100000004346 7 / 12 Methyl ethyl ketone



Version 1.8 Revision Date: 10/04/2022

#### **Further information**

#### **Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

No data available

#### Persistence and degradability

No data available

#### **Bioaccumulative potential**

No data available

## Mobility in soil

No data available

#### Other adverse effects

### **Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Pro-

tection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological infor-

mation

: No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

## **Disposal methods**

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.

For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Uni-

var Solutions ChemCare: 1-800-637-7922

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SDS Number: 100000004346 8 / 12 Methyl ethyl ketone



# Safety Data Sheet

# Methyl ethyl ketone

Version 1.8 Revision Date: 10/04/2022

#### **SECTION 14. TRANSPORT INFORMATION**

#### **DOT (Department of Transportation):**

UN1193, METHYL ETHYL KETONE, 3, II

## IATA (International Air Transport Association):

UN1193, METHYL ETHYL KETONE, 3, II

#### **IMDG (International Maritime Dangerous Goods):**

UN1193, METHYL ETHYL KETONE, 3, II, Flash Point:-9 - -4 °C(16 - 25 °F)

#### **SECTION 15. REGULATORY INFORMATION**

WHMIS Classification : B2: Flammable liquid

D2B: Toxic Material Causing Other Toxic Effects

### **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Methyl ethyl ketone	78-93-3	5000	5051

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting re-

quirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

78-93-3 Methyl ethyl ketone

#### **Clean Water Act**

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

SDS Number: 100000004346 9 / 12 Methyl ethyl ketone



Version 1.8 Revision Date: 10/04/2022

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

**US State Regulations** 

**Massachusetts Right To Know** 

78-93-3 Methyl ethyl ketone 90 - 100 %

Pennsylvania Right To Know

78-93-3 Methyl ethyl ketone 90 - 100 %

**New Jersey Right To Know** 

78-93-3 Methyl ethyl ketone 90 - 100 %

California Prop 65 : This product does not contain any chemicals known to State

of California to cause cancer, birth defects, or any other re-

productive harm.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PHIL : On the inventory, or in compliance with the inventory


IECSC : On the inventory, or in compliance with the inventory



Version 1.8 Revision Date: 10/04/2022

#### **SECTION16. OTHER INFORMATION**

#### NFPA:



#### HMIS III:

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 =Extreme, \* = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Univar Solutions Product Compliance Department (1-855-429-2661) SDSNA@univarsolutions.com.

Revision Date : 10/04/2022

**Legacy SDS:** : 100000003236

#### Material number:

16185217, 16186791, 16186626, 16184817, 16175887, 16174528, 16176047, 16175573, 16174844, 16180540, 16168306, 16173678, 16162436, 16154234, 16157454, 16143670, 16143669, 16167611, 16146653, 16161621, 16138517, 16137283, 16135359, 16145335, 16144212, 16151224, 16140718, 16143359, 16140526, 16141640, 16140315, 16141059, 16143668, 16146726, 16141669, 16131373, 16128860, 16127492, 16127438, 16120453, 16118417, 16116322, 16108433, 16066722, 16061576, 16066704, 104184, 16077055, 16073964, 16056363, 16056357, 16056358, 16062129, 16054779, 16046240, 16042921, 16025330, 16021759, 16019432, 16015617, 16014535, 16011780, 16010154, 16010153, 16003404, 753188, 744157, 744156, 744155, 743541, 737136, 732888, 105116, 89683, 710843, 554046, 554339, 554259, 710845, 710844, 699274, 675942, 659492, 659543, 609164, 604726, 602950, 573215, 554301, 554258, 554057, 554072, 546939, 547346, 56925, 55985, 55046, 106065, 105122, 89681

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Govern- ment Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level

SDS Number: 100000004346 11 / 12 Methyl ethyl ketone



Version 1.8 Revision Date: 10/04/2022

DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substanc-	NIOSH	National Institute for Occupational
	es List		Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemi-
			cals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect
			Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenar-	OSHA	Occupational Safety & Health
	io Tool		Administration
EOSCA	European Oilfield Specialty Chem-	PEL	Permissible Exposure Limit
	icals Association		
EINECS	European Inventory of Existing	PICCS	Philippines Inventory of Commer-
	Chemical Substances		cial Chemical Substances
MAK	Germany Maximum Concentration	PRNT	Presumed Not Toxic
	Values		
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery
			Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and
			Reauthorization Act.
IARC	International Agency for Research	TLV	Threshold Limit Value
	on Cancer		
IECSC	Inventory of Existing Chemical	TWA	Time Weighted Average
	Substances in China		
ENCS	Japan, Inventory of Existing and	TSCA	Toxic Substance Control Act
	New Chemical Substances		
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composi-
			tion, Complex Reaction Products,
			and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials
			Information System
LC50	Lethal Concentration 50%		

SDS Number: 100000004346 12 / 12 Methyl ethyl ketone