



DOWFROST™ HD Heat Transfer Fluid

Engineering Specifications for Closed-Loop HVAC Systems

Manufacturer

The Dow Chemical Company
Thermal Fluids Business
100 Larkin Center
Midland, MI 48674
(800) 447-4369

General Product Description

DOWFROST™ HD industrially inhibited propylene glycol-based heat transfer fluid is manufactured by The Dow Chemical Company. Aqueous solutions of DOWFROST HD fluid are designed to provide freeze/burst and corrosion protection, as well as efficient heat transfer, in water-based, closed-loop heating and air-conditioning systems.

DOWFROST HD fluid has an operating temperature range of -50°F to 325°F; with fluid freeze protection to below -60°F, and system burst protection to below -100°F. The fluid contains corrosion inhibitors that are specially formulated for HVAC systems to keep pipes free of corrosion without fouling. DOWFROST fluid is low in toxicity. Fluid ingredients are generally recognized as safe (GRAS) by the FDA. DOWFROST fluid can be specified for use in new HVAC systems, or as a replacement fluid for use in existing systems. The fluid is dyed bright yellow to facilitate system leak detection.

DOWFROST fluid is recommended for use in applications where low acute oral toxicity is important or where incidental contact with drinking water is possible.

Since the toxicity of heat transfer

fluids may be adversely altered in HVAC systems, used fluids should be handled with reasonable care, and not be taken internally.

HVAC System Fluid Specification Closed-loop, water-based systems

1. Fluid Material

The propylene glycol fluid to be used in such a system must meet the following requirements:

1.1 The fluid must be industrially inhibited propylene glycol (phosphate-based).

1.2 The fluid must be dyed [bright yellow] to facilitate leak detection.

1.3 The fluid must be easily analyzed for glycol concentration and inhibitor level.

1.4 For systems containing more than 250 gallons of fluid, annual analysis must be provided free of charge by the fluid manufacturer.

1.5 The fluid must pass ASTM D1384 (less than 0.5 mils penetration per year for all system metals).

1.6 The reserve alkalinity of the fluid must be at least 15 to provide long-term resistance to acidic pH.

2. Fluid Installation

Follow these installation procedures:

2.1 Clean new or lightly corroded existing systems with a 1- to-2% solution of trisodium phosphate in water prior to the installation of industrially inhibited propylene glycol fluid.

2.2 Extensively corroded existing systems should be cleaned by an industrial cleaning company and all necessary replacements and

repairs should be made.

2.3 Use only good quality water in solution with the propylene glycol fluid. Use water with low levels (less than 25 ppm) of chloride and sulfate, and less than 50 ppm of hard water ions (Ca⁺⁺, Mg⁺⁺). Distilled or deionized water is recommended. If good quality water is unavailable, purchase pre-diluted solutions of industrially inhibited propylene glycol fluid from the fluid manufacturer, or, if available, from the distributor.

3. System Design Considerations

3.1 Avoid use of automatic water make-up systems to prevent undetected dilution of the propylene glycol and possible contamination of the water system.

4. Technical Data

4.1 DOWFROST Fluid Product Description

Composition, % by weight	
Glycols	94
Inhibitors and water	6
Color	Bright yellow
Specific gravity at 60/60°F	1.053-1.063
pH of solution containing 50% glycol	9.5-10.5
Reserve alkalinity, minimum	15.0 ml

4.2 Typical Properties of Aqueous Solutions[†]

(Glycol percentage by volume)

Physical Property	Temp. °F	30% Glycol Solution	40% Glycol Solution	50% Glycol Solution	60% Glycol Solution
Thermal Conductivity Btu/(hr. • ft. ²)(°F/ft.)	40	0.247	0.225	0.204	0.184
	180	0.279	0.249	0.221	0.195
	325	0.268	0.238	0.210	0.184
Specific Heat Btu/(lb. • °F)	40	0.894	0.872	0.794	0.734
	180	0.947	0.916	0.878	0.833
	325	1.002	0.987	0.965	0.936
Viscosity, centipoise	40	5.75	9.63	14.28	23.65
	180	0.68	0.85	1.08	1.29
	325	0.31	0.39	0.40	0.45
Density (lb./ft. ³)	40	65.30	66.03	66.68	67.23
	180	62.60	63.09	63.50	63.83
	325	57.89	58.18	58.41	58.59

[†]Typical properties, not to be construed as specifications.

4.3 Freezing and Boiling Points of Aqueous Solutions

Freezing Temperature °F	% Glycol by Volume	Boiling Temperature °F
26	10	212
19	20	213
8	30	216
-7	40	219
-28	50	222
-60	60	225
<-60	70	230

For more information, contact us at your convenience:

www.dow.com/heattrans

North America

+1 (800) 447-4369

Latin America

+55 (115) 188-9000

Europe

+8 (003) 694-6367

Asia-Pacific

+8 (007) 776-7776

The Dow Chemical Company

2030 Dow Center

Midland, MI 48674

Notice: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, the Customer is responsible for determining whether products and the information in this document are appropriate for the Customer's use and for ensuring that the Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. The technology represented in this document may not yet be registered, and related products may not yet be available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

Notice: Any photographs of end-use applications in this document represent potential end-use applications but do not necessarily represent current commercial applications, nor do they represent an endorsement by Dow of the actual products. Further, these photographs are for illustration purposes only and do not reflect either an endorsement or sponsorship of any other manufacturer for a specific potential end-use product or application, or for Dow, or for specific products manufactured by Dow.

References to "Dow" or the "Company" mean The Dow Chemical Company and its consolidated subsidiaries unless otherwise expressly noted. [™]Trademark of The Dow Chemical Company.