

# SAFETY DATA SHEET FCCOBOND 104 PART A

Page: 1

Compilation date: 26/10/2015

Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name: ECCOBOND 104 PART A Synonyms: EHC: 28611000000418

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

### 1.3. Details of the supplier of the safety data sheet

Company name: Ellsworth Adhesives (Europe) Ltd

2 Langlands Avenue

Kelvin South Business Park East Kilbride, Glasgow

G75 0YG

United Kingdom

Tel: +44(0) 1355 231122
Fax: +44(0) 1355 235266
Email: eusds@ellsworth.com

### 1.4. Emergency telephone number

Emergency tel: +44(0) 1355 231122

(office hours only)

#### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317; Aquatic Chronic 2: H411

Most important adverse effects: Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS07: Exclamation mark

GHS09: Environmental

#### **ECCOBOND 104 PART A**





Signal words: Warning

Precautionary statements: P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/soap and water.
P333+313: If skin irritation or rash occurs: Get medical advice/attention.

P337+313: If eye irritation persists: Get medical advice/attention.

#### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

#### 3.2. Mixtures

### Hazardous ingredients:

### BISPHENOL A EPOXY RESIN (MW <700) - REACH registered number(s): 01-2119456619-26-XXXX

			T	
EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-033-5	25068-38-6	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319;	70-90%
			Skin Sens. 1: H317; Aquatic Chronic 2: H411	

### Section 4: First aid measures

### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact. May cause sensitisation in

susceptible individuals.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

[cont...]

Page: 2

#### **FCCOBOND 104 PART A**

Page: 3

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises. Show this safety data

sheet to the doctor in attendance.

### Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. Mark out the contaminated area with signs and prevent access to

unauthorised personnel.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the

storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Must only be kept in original packaging.

#### **ECCOBOND 104 PART A**

Page: 4

### 7.3. Specific end use(s)

Specific end use(s): PC1: Adhesives, sealants.

### Section 8: Exposure controls/personal protection

### 8.1. Control parameters

Workplace exposure limits: No data available.

### **DNEL/PNEC Values**

### Hazardous ingredients:

### **BISPHENOL A EPOXY RESIN (MW <700)**

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	12.25 mg/m3	Workers	Systemic
DNEL	Dermal	8.33 mg/kg	Workers	Systemic
PNEC	Fresh water	6 ug/L	-	-
PNEC	Marine water	600 ng/L	-	-
PNEC	Microorganisms in sewage treatment	10 mg/L	-	-
PNEC	Fresh water sediments	996 ug/kg	-	-
PNEC	Marine sediments	99.6 ug/kg	-	-
PNEC	Soil (agricultural)	196 ug/kg	-	-
PNEC	Food chain	11 mg/kg	-	-

### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be

impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Refer to specific Member State legislation for requirements under Community

environmental legislation.

### Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Liquid Colour: Black Odour: Mild

Solubility in water: Insoluble

Boiling point/range°C: >200 Flash point°C: >100

Vapour pressure: <0.01 Pa @ 20C

[cont...]

#### **ECCOBOND 104 PART A**

Page: 5

Relative density: 1.500

VOC g/I: <45

9.2. Other information

Other information: No data available.

### Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat.

### 10.5. Incompatible materials

Materials to avoid: Alcohols. Amines. Oxidising agents. Acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

### Section 11: Toxicological information

### 11.1. Information on toxicological effects

### Hazardous ingredients:

### **BISPHENOL A EPOXY RESIN (MW <700)**

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

### Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact. May cause sensitisation in susceptible individuals.

#### **FCCOBOND 104 PART A**

Page: 6

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

### Section 12: Ecological information

### 12.1. Toxicity

### Hazardous ingredients:

### **BISPHENOL A EPOXY RESIN (MW <700)**

Daphnia magna	48H EC50	1.7	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H ErC50	2.4	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	1.2	mg/l

### 12.2. Persistence and degradability

Persistence and degradability: Not readily biodegradable.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

### 12.4. Mobility in soil

Mobility: Non-volatile. Insoluble in water.

### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Waste code number: 08 04 09

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

### Section 14: Transport information

### 14.1. UN number

UN number: UN3082

#### **ECCOBOND 104 PART A**

Page: 7

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(BISPHENOL A EPOXY RESIN (MW <700))

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.