

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Version: 1.1

Issue date: 12/10/2020 Revision date: 06/02/2023 Supersedes: 12/10/2020

SECTION 1: Identification

Identification

Product form Mixture Product name EP1026 Black A

Recommended use and restrictions on use

Recommended use : Epoxy resin

Restrictions on use : Product for industrial use only

1.3. **Supplier**

ResinLab, LLC

N109 W13300 Ellsworth Drive

Germantown, WI 53022 - United States

T 1-877-259-1669

msds@resinlab.com - www.resinlab.com

Emergency telephone number

Emergency number : CHEMTREC:1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2

Skin sensitization, Category 1

Full text of H statements: see section 16

H315 Causes skin irritation

H319 Causes serious eye irritation

H317 May cause an allergic skin reaction

GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) Warning

Hazard statements (GHS US) H315 - Causes skin irritation

H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray. Precautionary statements (GHS US)

P264 - Wash hands, forearms and face thoroughly after handling.

P272 - Contaminated work clothing must not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 - If on skin: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

P391 - Collect spillage.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance

with local, regional, national and/or international regulation.

Other hazards which do not result in classification

No additional information available

Unknown acute toxicity (GHS US)

Not applicable

03/25/2024 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % |
|--------------|----------------------|---------|
| Epoxy Resin | (CAS-No.) 25068-38-6 | ≥ 90 |
| carbon black | (CAS-No.) 1333-86-4 | 0.5 – 1 |

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs:

Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get

medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of : Toxic fumes may be released, Carbon oxides (CO, CO2), Phenolic compounds

fire

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing

dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

03/25/2024 EN (English US) 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Contains a component(s) that is encapsulated within the product and not expected to be released during normal processing conditions or a foreseeable emergency. Do not breathe dust created by sanding, grinding or machining.

Precautions for safe handling

: Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray.

Hygiene measures

: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Epoxy Resin (25068-3 | 8-6) | |
|-----------------------|--------------------------------|--|
| Not applicable | | |
| carbon black (1333-86 | 3-4) | |
| ACGIH | Local name | Carbon black |
| ACGIH | ACGIH OEL TWA | 3 mg/m³ (Inhalable fraction) |
| ACGIH | Remark (ACGIH) | TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans) |
| ACGIH | Regulatory reference | ACGIH 2023 |
| OSHA | OSHA PEL TWA | 3.5 mg/m³ |
| OSHA | Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |

8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace.

Environmental exposure controls

: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses with side shields

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):







03/25/2024 EN (English US) 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state : Liquid Color : Black Odor : characteristic Odor threshold : No data available No data available Not applicable Melting point : No data available Freezing point : > 200 °C Boiling point

Flash point : 252 °C Relative evaporation rate (butyl acetate=1) : No data available Flammability : Not applicable. Vapor pressure : No data available Relative vapor density at 20°C No data available

: No data available

Density 1.16 g/cm³ Solubility No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature No data available : No data available Decomposition temperature : No data available Viscosity, dynamic **Explosion limits** No data available : No data available Explosive properties Oxidizing properties No data available

VOC content 0 %

SECTION 10: Stability and reactivity

Reactivity

Relative density

The product is non-reactive under normal conditions of use, storage and transport.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Acids. Bases (Alkalis). Oxidizing agent.

Hazardous decomposition products

Refer to section 5.2 for hazardous decomposition products during combustion. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Information on toxicological effects 11.1.

: Not classified Acute toxicity (oral) Acute toxicity (dermal) : Not classified : Not classified Acute toxicity (inhalation)

| Epoxy Resin (25068-38-6) | |
|--------------------------|---|
| LD50 oral rat | > 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method) |
| LD50 dermal rat | > 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)) |

03/25/2024 EN (English US) 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| carbon black (1333-86-4) | |
|--|---|
| LD50 oral rat | > 10000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 28 day(s)) |
| LD50 dermal rabbit | > 8000 mg/kg Source: ECHA |
| Skin corrosion/irritation | : Causes skin irritation. |
| erious eye damage/irritation | Causes serious eye irritation. |
| espiratory or skin sensitization | May cause an allergic skin reaction. |
| Germ cell mutagenicity | Not classified |
| carcinogenicity | Not classified |
| Epoxy Resin (25068-38-6) | |
| NOAEL (chronic,oral,animal/male,2 years) | 15 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxici (migrated information) |
| NOAEL (chronic,oral,animal/female,2 years) | 100 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicit (migrated information) |
| carbon black (1333-86-4) | |
| IARC group | 2B - Possibly carcinogenic to humans |
| eproductive toxicity | Not classified |
| TOT-single exposure | Not classified |
| TOT-repeated exposure | Not classified |
| carbon black (1333-86-4) | |
| LOAEC (inhalation, rat, dust/mist/fume, 90 days) | 0.0071 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study) |
| NOAEL (oral,rat,90 days) | > 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity Study in Rodents) |
| NOAEC (inhalation,rat,dust/mist/fume,90 days) | 0.0011 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study) |
| spiration hazard | Not classified |
| symptoms/effects after skin contact | Irritation. May cause an allergic skin reaction. |

Symptoms/effects after eye contact : Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

| Epoxy Resin (25068-38-6) | |
|--------------------------|---|
| LC50 - Fish [1] | 1.3 mg/l (96 h, Pisces, Literature study) |
| EC50 - Crustacea [1] | ≈ 2 mg/l Test organisms (species): Daphnia magna |
| LOEC (chronic) | 1 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC (chronic) | 0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| carbon black (1333-86-4) | |
| LC50 - Fish [1] | > 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, Lethal) |
| EC50 - Crustacea [1] | > 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect) |
| ErC50 algae | > 10000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration) |

12.2. Persistence and degradability

| Epoxy Resin (25068-38-6) | |
|-------------------------------|-------------------------------------|
| Persistence and degradability | Not readily biodegradable in water. |
| | |

03/25/2024 EN (English US) 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| carbon black (1333-86-4) | |
|-------------------------------|---|
| Persistence and degradability | Biodegradability in soil: not applicable. Biodegradability: not applicable. |
| Chemical oxygen demand (COD) | Not applicable (inorganic) |
| ThOD | Not applicable (inorganic) |

12.3. Bioaccumulative potential

| Epoxy Resin (25068-38-6) | |
|---|--|
| Partition coefficient n-octanol/water (Log Pow) | 3 (Estimated value, 25 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |
| carbon black (1333-86-4) | |
| Bioaccumulative potential | Not bioaccumulative. |

12.4. Mobility in soil

| Epoxy Resin (25068-38-6) | | |
|--------------------------|---|--|
| Surface tension | 59 mN/m (20 °C, 0.09 g/l) | |
| Ecology - soil | No (test)data on mobility of the substance available. | |
| carbon black (1333-86-4) | | |
| Surface tension | Not applicable (solid) | |
| Carrage terreleri | 1101 applicable (00114) | |

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin),

9, III, MARINE POLLUTANT

UN-No. (IMDG) : 3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Epoxy Resin

Class (IMDG) : 9 - Miscellaneous dangerous substances and articles

Packing group (IMDG) : III - substances presenting low danger

Limited quantities (IMDG) : 5 L

Air transport

Transport document description (IATA) : UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin), 9, III

UN-No. (IATA) : 3082

Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s.

Epoxy Resir

Class (IATA) : 9 - Miscellaneous Dangerous Substances and Articles

03/25/2024 EN (English US) 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing group (IATA) : III - Low danger

SECTION 15: Regulatory information

15.1. US Federal regulations

| Epoxy Resin (25068-38-6) | |
|---|---|
| Listed on the United States TSCA (Toxic Substan | ices Control Act) inventory |
| EPA TSCA Regulatory Flag | XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711). |

15.2. International regulations

CANADA

Epoxy Resin (25068-38-6)

Listed on the Canadian DSL (Domestic Substances List)

carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Contains no REACH candidate substance

Epoxy Resin (25068-38-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

carbon black (1333-86-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Epoxy Resin (25068-38-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

15.3. US State regulations



This product can expose you to Epichlorohydrin, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

| Component | State or local regulations |
|-------------------------|--|
| carbon black(1333-86-4) | U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List |

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 06/02/2023

03/25/2024 EN (English US) 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

| H315 | Causes skin irritation |
|------|---|
| H317 | May cause an allergic skin reaction |
| H319 | Causes serious eye irritation |
| H401 | Toxic to aquatic life |
| H411 | Toxic to aquatic life with long lasting effects |

SDS US - ResinLab

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

03/25/2024 EN (English US) 8/8