

SECTION 1: Identification

1.1. Identification

Product name : EP965 Clear B

1.2. Recommended use and restrictions on use

Recommended use : Epoxy hardener
 Restrictions on use : Product for industrial use only

1.3. Supplier

ResinLab, LLC
 N109 W13300 Ellsworth Drive
 Germantown, WI 53022 - United States
 T 1-877-259-1669
msds@resinlab.com - www.resinlab.com

1.4. Emergency telephone number

Emergency number : CHEMTREC:1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 1B	H314	Causes severe skin burns and eye damage
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Reproductive toxicity Category 2	H361	Suspected of damaging fertility or the unborn child

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage
 H317 - May cause an allergic skin reaction
 H361 - Suspected of damaging fertility or the unborn child

Precautionary statements (GHS US) :

- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
- P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 - Wash hands, forearms and face thoroughly after handling.
- P272 - Contaminated work clothing must not be allowed out of the workplace.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
- P302+P352 - If on skin: Wash with plenty of water.
- P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 - If exposed or concerned: Get medical advice/attention.
- P310 - Immediately call a poison center or doctor.
- P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
- P363 - Wash contaminated clothing before reuse.
- P391 - Collect spillage.
- P405 - Store locked up.
- P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EP965 Clear B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Polyamide resin	(CAS-No.) 68082-29-1	30 – 50	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
4-Nonylphenol, branched	(CAS-No.) 84852-15-3	30 – 50	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
N-(2-Aminoethyl)piperazine	(CAS-No.) 140-31-8	10 – 30	Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Skin Sens. 1, H317 Repr. 2, H361 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Triethylenetetramine	(CAS-No.) 112-24-3	1 – 5	Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 3, H402 Aquatic Chronic 3, H412

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Get medical advice/attention if you feel unwell.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Rinse immediately with plenty of water for 15 minutes. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Immediately rinse with plenty of water (for at least 15 minutes). Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.
- First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Obtain medical attention.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Serious damage to eyes.
- Symptoms/effects after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

EP965 Clear B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

4-Nonylphenol, branched (84852-15-3)
Not applicable
N-(2-Aminoethyl)piperazine (140-31-8)
Not applicable
Polyamide resin (68082-29-1)
Not applicable
Triethylenetetramine (112-24-3)
Not applicable

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves. Impervious gloves

Eye protection:

Safety glasses with side shields. Use splash goggles when eye contact due to splashing is possible

EP965 Clear B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation, wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: amber
Odor	: characteristic
Odor threshold	: No data available
pH	: 11 estimated
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 176 °C
Flash point	: > 99 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.97 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
VOC content	No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Acids. Bases (Alkalis). Oxidizing agent. May be corrosive to some metals. Peroxides.

EP965 Clear B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

4-Nonylphenol, branched (84852-15-3)	
LD50 oral rat	1412 mg/kg body weight (Other, Rat, Male / female, Experimental value, Oral)
ATE US (oral)	1412 mg/kg body weight

N-(2-Aminoethyl)piperazine (140-31-8)	
LD50 oral rat	2097 mg/kg body weight (Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	866 mg/kg bw/day (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
ATE US (oral)	2097 mg/kg body weight
ATE US (dermal)	866 mg/kg body weight

Polyamide resin (68082-29-1)	
LD50 oral rat	> 2000 mg/kg body weight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)

Triethylenetetramine (112-24-3)	
LD50 oral rat	2500 mg/kg (Rat, Literature, Oral)
LD50 dermal rabbit	805 mg/kg (Rabbit, Literature, Dermal)
ATE US (oral)	2500 mg/kg body weight
ATE US (dermal)	805 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns.
pH: 11 estimated

Serious eye damage/irritation : Assumed to cause serious eye damage
pH: 11 estimated

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

4-Nonylphenol, branched (84852-15-3)	
LOAEL (oral,rat,90 days)	400 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
NOAEL (oral,rat,90 days)	100 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

Polyamide resin (68082-29-1)	
NOAEL (oral,rat,90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Aspiration hazard : Not classified

Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

EP965 Clear B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life with long lasting effects.

4-Nonylphenol, branched (84852-15-3)	
LC50 - Fish [1]	0.08 mg/l (ASTM E729-96, 96 h, Hybopsis monacha, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	0.084 mg/l (ASTM E729-88, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value)
NOEC chronic fish	0.006 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '91 d'

N-(2-Aminoethyl)piperazine (140-31-8)	
LC50 - Fish [1]	2190 mg/l (96 h, Pimephales promelas, Static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	58 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Experimental value, GLP)
ErC50 algae	> 1000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Fresh water, Experimental value, GLP)

Polyamide resin (68082-29-1)	
LC50 - Fish [1]	7.07 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	7.07 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	4.34 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Experimental value, GLP)

Triethylenetetramine (112-24-3)	
LC50 - Fish [1]	495 mg/l (96 h, Pimephales promelas, Fresh water, Literature study)
EC50 - Crustacea [1]	31.1 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Literature study)
ErC50 algae	≥ 100 mg/l (DIN 38412-9, 72 h, Scenedesmus subspicatus, Literature study, Growth)

12.2. Persistence and degradability

4-Nonylphenol, branched (84852-15-3)	
Persistence and degradability	Biodegradability in soil: no data available. Readily biodegradable in water.

N-(2-Aminoethyl)piperazine (140-31-8)	
Persistence and degradability	Not readily biodegradable in water.
Chemical oxygen demand (COD)	0.56 g O ₂ /g substance

Polyamide resin (68082-29-1)	
Persistence and degradability	Not readily biodegradable in water.

Triethylenetetramine (112-24-3)	
Persistence and degradability	Not readily biodegradable in water.

12.3. Bioaccumulative potential

4-Nonylphenol, branched (84852-15-3)	
BCF - Fish [1]	1200 – 1300 (OECD 305: Bioconcentration: Flow-Through Fish Test, 16 day(s), Gasterosteus aculeatus, Flow-through system, Salt water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	5.4 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 23 °C)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

N-(2-Aminoethyl)piperazine (140-31-8)	
BCF - Fish [1]	0.3 – 6.3 (OECD 305: Bioconcentration: Flow-Through Fish Test, 6 week(s), Cyprinus carpio, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	-1.48 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)
Bioaccumulative potential	Not bioaccumulative.

Polyamide resin (68082-29-1)	
Partition coefficient n-octanol/water (Log Pow)	10.34 (Calculated)
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).

EP965 Clear B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Triethylenetetramine (112-24-3)	
BCF - Other aquatic organisms [1]	3.162 (BCFBAF v3.01, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	-2.65 (Estimated value, KOWWIN)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

4-Nonylphenol, branched (84852-15-3)	
Partition coefficient n-octanol/water (Log Koc)	4.35 – 5.69 (log Koc, Other, Experimental value, GLP)
Ecology - soil	Adsorbs into the soil.
N-(2-Aminoethyl)piperazine (140-31-8)	
Partition coefficient n-octanol/water (Log Koc)	4.57 (log Koc, Read-across, GLP)
Ecology - soil	Low potential for mobility in soil.
Polyamide resin (68082-29-1)	
Surface tension	0.064 N/m (0.15 g/l, EU Method A.5: Surface tension)
Ecology - soil	No (test)data on mobility of the substance available.
Triethylenetetramine (112-24-3)	
Partition coefficient n-octanol/water (Log Koc)	1.885 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT) : UN3267 Corrosive liquid, basic, organic, n.o.s. (4-Nonylphenol, branched ; N-(2-Aminoethyl)piperazine), 8, III

UN-No.(DOT) : UN3267

Proper Shipping Name (DOT) : Corrosive liquid, basic, organic, n.o.s.
4-Nonylphenol, branched ; N-(2-Aminoethyl)piperazine

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : III - Minor Danger

Hazard labels (DOT) : 8 - Corrosive



Dangerous for the environment : Yes

Marine pollutant : Yes



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

EP965 Clear B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 154
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
- DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
- DOT Vessel Stowage Other : 40 - Stow "clear of living quarters", 52 - Stow "separated from" acids
- Emergency Response Guide (ERG) Number : 153
- Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

- Transport document description (IMDG) : UN 3267 CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (4-Nonylphenol, branched ; N-(2-Aminoethyl)piperazine), 8, III
- UN-No. (IMDG) : 3267
CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
4-Nonylphenol, branched ; N-(2-Aminoethyl)piperazine
- Class (IMDG) : 8 - Corrosive substances
- Packing group (IMDG) : III - substances presenting low danger
- Limited quantities (IMDG) : 5 L
- Marine pollutant : Yes



Air transport

- Transport document description (IATA) : UN 3267 Corrosive liquid, basic, organic, n.o.s. (4-Nonylphenol, branched ; N-(2-Aminoethyl)piperazine), 8, III
- UN-No. (IATA) : 3267
- Proper Shipping Name (IATA) : Corrosive liquid, basic, organic, n.o.s.
4-Nonylphenol, branched ; N-(2-Aminoethyl)piperazine
- Class (IATA) : 8 - Corrosives
- Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

4-Nonylphenol, branched	CAS-No. 84852-15-3	30 – 50%
-------------------------	--------------------	----------

EP965 Clear B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4-Nonylphenol, branched (84852-15-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

EPA TSCA Regulatory Flag

SP - SP - indicates a substance that is identified in a proposed Significant New Use Rule.

N-(2-Aminoethyl)piperazine (140-31-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Polyamide resin (68082-29-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

Triethylenetetramine (112-24-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

4-Nonylphenol, branched (84852-15-3)

Listed on the Canadian DSL (Domestic Substances List)

N-(2-Aminoethyl)piperazine (140-31-8)

Listed on the Canadian DSL (Domestic Substances List)

Polyamide resin (68082-29-1)

Listed on the Canadian DSL (Domestic Substances List)

Triethylenetetramine (112-24-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Contains the following REACH ingredient(s): 4-Nonylphenol, branched and linear [substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, covering also UVCB- and well-defined substances which include any of the individual isomers or a combination thereof] (EC 284-325-5, CAS 84852-15-3)

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
N-(2-Aminoethyl)piperazine(140-31-8)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Triethylenetetramine(112-24-3)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 03/25/2021

EP965 Clear B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H361	Suspected of damaging fertility or the unborn child
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS US - ResinLab

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.