

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : EP965SC7 Clear B

#### 1.2. Recommended use and restrictions on use

Recommended use : Epoxy hardener  
 Restrictions on use : Product for industrial use only

#### 1.3. Supplier

ResinLab, LLC  
 N109 W13300 Ellsworth Drive  
 Germantown, WI 53022 - United States  
 T 1-877-259-1669  
[msds@resinlab.com](mailto:msds@resinlab.com) - [www.resinlab.com](http://www.resinlab.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC:1-800-424-9300 (USA); +1 703-527-3887 (International)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Skin corrosion/irritation Category 1B	H314	Causes severe skin burns and eye damage
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Reproductive toxicity Category 2	H361	Suspected of damaging fertility or the unborn child
Specific target organ toxicity (repeated exposure) Category 1	H372	Causes damage to organs through prolonged or repeated exposure

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage  
 H317 - May cause an allergic skin reaction  
 H361 - Suspected of damaging fertility or the unborn child  
 H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P260 - Do not breathe dust/fume/gas/mist/vapors/spray.  
 P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
 P264 - Wash hands, forearms and face thoroughly after handling.  
 P270 - Do not eat, drink or smoke when using this product.  
 P272 - Contaminated work clothing must not be allowed out of the workplace.  
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
 P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.  
 P302+P352 - If on skin: Wash with plenty of water.  
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308+P313 - If exposed or concerned: Get medical advice/attention.  
 P310 - Immediately call a poison center or doctor.  
 P314 - Get medical advice/attention if you feel unwell.  
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
 P363 - Wash contaminated clothing before reuse.

# EP965SC7 Clear B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P391 - Collect spillage.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Polyamide resin	(CAS-No.) 68082-29-1	30 – 50	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Benzyl alcohol	(CAS-No.) 100-51-6	15 - 20	Acute Tox. 4 (Oral), H302
Isophorone diamine	(CAS-No.) 2855-13-2	10 - 20	Acute Tox. 4 (Oral), H302 Skin Corr. 1, H314 Skin Sens. 1, H317 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Amine Epoxy Resin Adduct Trade Secret CAS number		10 - 20	STOT SE 3, H335 STOT RE 1, H372
4-Nonylphenol, branched	(CAS-No.) 84852-15-3	10 – 30	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Triethylenetetramine	(CAS-No.) 112-24-3	1 – 5	Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 3, H402 Aquatic Chronic 3, H412

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Rinse immediately with plenty of water for 15 minutes. Remove/Take off immediately all contaminated clothing. Get immediate medical advice/attention. Thoroughly clean shoes before reuse. Wash clothing before reuse.  
First-aid measures after eye contact : Immediately rinse with plenty of water (for at least 15 minutes). Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.  
First-aid measures after ingestion : Rinse mouth out with water. Do not induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Serious damage to eyes.  
Symptoms/effects after ingestion : Burns.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use water jet to extinguish.

# EP965SC7 Clear B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.2. Specific hazards arising from the chemical

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 4-Nonylphenol, branched (84852-15-3)

Not applicable

#### Polyamide resin (68082-29-1)

Not applicable

#### Triethylenetetramine (112-24-3)

Not applicable

#### Isophorone diamine (2855-13-2)

Not applicable

#### Benzyl alcohol (100-51-6)

Not applicable

#### Amine Epoxy Resin Adduct Trade Secret CAS number

Not applicable

# EP965SC7 Clear B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station, ventilate curing ovens to prevent emissions in the workplace.
- Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses with side shields

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of inadequate ventilation, wear respiratory protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: amber
Odor	: Amine-like
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 176 °C
Flash point	: > 93 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.02 g/cm <sup>3</sup>
Solubility	: Not miscible.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
VOC content	20 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

# EP965SC7 Clear B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Bases (Alkalis). Acids. Oxidizing agent. May slowly corrode copper, aluminum, zinc, and galvanized surfaces. Peroxides. N-Nitrosamines, many of which are known to be potent carcinogens, may be formed when the product comes in contact with nitrous acid, nitrites or atmospheres with high nitrous oxide concentrations.

### 10.6. Hazardous decomposition products

ammonia. Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

<b>4-Nonylphenol, branched (84852-15-3)</b>	
LD50 oral rat	1412 mg/kg body weight (Other, Rat, Male / female, Experimental value, Oral)
ATE US (oral)	1412 mg/kg body weight
<b>Polyamide resin (68082-29-1)</b>	
LD50 oral rat	> 2000 mg/kg body weight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)
<b>Triethylenetetramine (112-24-3)</b>	
LD50 oral rat	2500 mg/kg (Rat, Literature, Oral)
LD50 dermal rabbit	805 mg/kg (Rabbit, Literature, Dermal)
ATE US (oral)	2500 mg/kg body weight
ATE US (dermal)	805 mg/kg body weight
<b>Isophorone diamine (2855-13-2)</b>	
LD50 oral rat	1030 mg/kg (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 5.01 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
ATE US (oral)	1030 mg/kg body weight
<b>Benzyl alcohol (100-51-6)</b>	
LD50 oral rat	1620 mg/kg bw/day (Rat, Male, Experimental value, Oral)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Inconclusive, insufficient data, Dermal)
LC50 Inhalation - Rat	> 8.8 mg/l
ATE US (oral)	1620 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns.  
Serious eye damage/irritation : Assumed to cause serious eye damage  
Respiratory or skin sensitization : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
  
Reproductive toxicity : Suspected of damaging fertility or the unborn child.  
STOT-single exposure : Not classified

### **Amine Epoxy Resin Adduct Trade Secret CAS number**

STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.

# EP965SC7 Clear B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>4-Nonylphenol, branched (84852-15-3)</b>	
LOAEL (oral,rat,90 days)	400 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
NOAEL (oral,rat,90 days)	100 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
<b>Polyamide resin (68082-29-1)</b>	
NOAEL (oral,rat,90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
<b>Isophorone diamine (2855-13-2)</b>	
LOAEL (oral,rat,90 days)	160 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
<b>Benzyl alcohol (100-51-6)</b>	
NOAEL (oral,rat,90 days)	400 mg/kg body weight Animal: rat, Guideline: other:OECD Guideline 451 (Carcinogenicity Studies)
<b>Amine Epoxy Resin Adduct Trade Secret CAS number</b>	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard	: Not classified
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Ecology - water	: Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

<b>4-Nonylphenol, branched (84852-15-3)</b>	
LC50 - Fish [1]	0.08 mg/l (ASTM E729-96, 96 h, Hybopsis monacha, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	0.084 mg/l (ASTM E729-88, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value)
NOEC chronic fish	0.006 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '91 d'
<b>Polyamide resin (68082-29-1)</b>	
LC50 - Fish [1]	7.07 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	7.07 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	4.34 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Experimental value, GLP)
<b>Triethylenetetramine (112-24-3)</b>	
LC50 - Fish [1]	495 mg/l (96 h, Pimephales promelas, Fresh water, Literature study)
EC50 - Crustacea [1]	31.1 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Literature study)
ErC50 algae	≥ 100 mg/l (DIN 38412-9, 72 h, Scenedesmus subspicatus, Literature study, Growth)
<b>Isophorone diamine (2855-13-2)</b>	
LC50 - Fish [1]	110 mg/l (EU Method C.1, 96 h, Leuciscus idus, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	23 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
LOEC (chronic)	10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
<b>Benzyl alcohol (100-51-6)</b>	
LC50 - Fish [1]	460 mg/l (EPA OPP 72-1, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	230 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Fresh water, Experimental value, GLP)

# EP965SC7 Clear B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Benzyl alcohol (100-51-6)</b>	
ErC50 algae	770 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC (chronic)	51 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### 12.2. Persistence and degradability

<b>4-Nonylphenol, branched (84852-15-3)</b>	
Persistence and degradability	Biodegradability in soil: no data available. Readily biodegradable in water.
<b>Polyamide resin (68082-29-1)</b>	
Persistence and degradability	Not readily biodegradable in water.
<b>Triethylenetetramine (112-24-3)</b>	
Persistence and degradability	Not readily biodegradable in water.
<b>Isophorone diamine (2855-13-2)</b>	
Persistence and degradability	Not readily biodegradable in water.
<b>Benzyl alcohol (100-51-6)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.6 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.4 g O <sub>2</sub> /g substance
ThOD	2.5 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

<b>4-Nonylphenol, branched (84852-15-3)</b>	
BCF - Fish [1]	1200 – 1300 (OECD 305: Bioconcentration: Flow-Through Fish Test, 16 day(s), Gasterosteus aculeatus, Flow-through system, Salt water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	5.4 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 23 °C)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).
<b>Polyamide resin (68082-29-1)</b>	
Partition coefficient n-octanol/water (Log Pow)	10.34 (Calculated)
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).
<b>Triethylenetetramine (112-24-3)</b>	
BCF - Other aquatic organisms [1]	3.162 (BCFBAF v3.01, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	-2.65 (Estimated value, KOWWIN)
Bioaccumulative potential	Not bioaccumulative.
<b>Isophorone diamine (2855-13-2)</b>	
BCF - Other aquatic organisms [1]	3.16 (BCFWIN, QSAR)
Partition coefficient n-octanol/water (Log Pow)	0.99 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 23 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Benzyl alcohol (100-51-6)</b>	
Partition coefficient n-octanol/water (Log Pow)	1 – 1.1 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

<b>4-Nonylphenol, branched (84852-15-3)</b>	
Partition coefficient n-octanol/water (Log Koc)	4.35 – 5.69 (log Koc, Other, Experimental value, GLP)
Ecology - soil	Adsorbs into the soil.
<b>Polyamide resin (68082-29-1)</b>	
Surface tension	0.064 N/m (0.15 g/l, EU Method A.5: Surface tension)
Ecology - soil	No (test)data on mobility of the substance available.
<b>Triethylenetetramine (112-24-3)</b>	
Partition coefficient n-octanol/water (Log Koc)	1.885 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

# EP965SC7 Clear B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Isophorone diamine (2855-13-2)	
Surface tension	3.47 N/m (23 °C)
Partition coefficient n-octanol/water (Log Koc)	2.97 (log Koc, QSAR)
Ecology - soil	Low potential for adsorption in soil.
Benzyl alcohol (100-51-6)	
Surface tension	39 mN/m (20 °C)
Ecology - soil	No (test)data on mobility of the substance available.

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT) : UN3267 Corrosive liquid, basic, organic, n.o.s. (4-Nonylphenol, branched ; Isophorone diamine), 8, III

UN-No.(DOT) : UN3267

Proper Shipping Name (DOT) : Corrosive liquid, basic, organic, n.o.s.  
4-Nonylphenol, branched ; Isophorone diamine

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : III - Minor Danger

Hazard labels (DOT) : 8 - Corrosive



Dangerous for the environment : Yes

Marine pollutant : Yes



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154



# EP965SC7 Clear B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Passenger aircraft/rail : 5 L  
(49 CFR 173.27)  
DOT Quantity Limitations Cargo aircraft only (49 : 60 L  
CFR 175.75)  
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  
DOT Vessel Stowage Other : 40 - Stow "clear of living quarters", 52 - Stow "separated from" acids  
Emergency Response Guide (ERG) Number : 153  
Other information : No supplementary information available.

### Transportation of Dangerous Goods

Not applicable

### Transport by sea

Transport document description (IMDG) : UN 3267 CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (4-Nonylphenol, branched ; Isophorone diamine), 8, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS  
UN-No. (IMDG) : 3267  
CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.  
4-Nonylphenol, branched ; Isophorone diamine  
Class (IMDG) : 8 - Corrosive substances  
Packing group (IMDG) : III - substances presenting low danger  
Limited quantities (IMDG) : 5 L  
Marine pollutant : Yes



### Air transport

Transport document description (IATA) : UN 3267 Corrosive liquid, basic, organic, n.o.s. (4-Nonylphenol, branched ; Isophorone diamine), 8, III, ENVIRONMENTALLY HAZARDOUS  
UN-No. (IATA) : 3267  
Proper Shipping Name (IATA) : Corrosive liquid, basic, organic, n.o.s.  
4-Nonylphenol, branched ; Isophorone diamine  
Class (IATA) : 8 - Corrosives  
Packing group (IATA) : III - Minor Danger

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

4-Nonylphenol, branched	CAS-No. 84852-15-3	10 – 30%
<b>4-Nonylphenol, branched (84852-15-3)</b>		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313		
EPA TSCA Regulatory Flag	SP - SP - indicates a substance that is identified in a proposed Significant New Use Rule.	
<b>Polyamide resin (68082-29-1)</b>		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).	
<b>Triethylenetetramine (112-24-3)</b>		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
<b>Isophorone diamine (2855-13-2)</b>		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		

# EP965SC7 Clear B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **Benzyl alcohol (100-51-6)**

Listed on the United States TSCA (Toxic Substances Control Act) inventory

## 15.2. International regulations

### CANADA

#### **4-Nonylphenol, branched (84852-15-3)**

Listed on the Canadian DSL (Domestic Substances List)

#### **Polyamide resin (68082-29-1)**

Listed on the Canadian DSL (Domestic Substances List)

#### **Triethylenetetramine (112-24-3)**

Listed on the Canadian DSL (Domestic Substances List)

#### **Isophorone diamine (2855-13-2)**

Listed on the Canadian DSL (Domestic Substances List)

#### **Benzyl alcohol (100-51-6)**

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

Contains the following REACH ingredient(s): 4-Nonylphenol, branched and linear [substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, covering also UVCB- and well-defined substances which include any of the individual isomers or a combination thereof] (EC 284-325-5, CAS 84852-15-3)

### National regulations

No additional information available

## 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Triethylenetetramine(112-24-3)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Isophorone diamine(2855-13-2)	U.S. - New Jersey - Right to Know Hazardous Substance List
Benzyl alcohol(100-51-6)	U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# EP965SC7 Clear B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H335	May cause respiratory irritation
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS US - ResinLab

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*