

Heartland Adhesives

N117 W18654 Fulton Drive, Germantown, WI 53022

Phone (262) 255-9171 / Fax (262) 255-0719

Technical Data Sheet

H735

Typical Properties

| | |
|----------------------|--|
| Product Description: | Pressure Sensitive Hot Melt Adhesive |
| Physical Properties: | Viscosity ASTM D4440): 2984-5033 cps @ 350F. Melting point (ASTM D4440): 190-207 F. Color: Amber Application Temperature: Application temperature is specific for the application. Please contact Heartland Adhesives for guidance. FDA Status: The components of this product comply with the compositional requirements of the FDA Indirect Food Contact Regulation, 21 CFR 175.105, Adhesive. |
| Suggested Use: | Labeling, plastics, metal and non-woven materials. |
| Machine Application: | Can be extruded, roll coated or swirl sprayed. |
| Characteristics: | High Tack |
| Precautions: | Use oldest stock first. Use solvents only in room temperature pots. Keep container covered to prevent contamination. Do not mix with other adhesives. |

Notice:

Heating for extended periods of time can cause degradation which can affect performance. Please contact your Heartland representative for further information.

We are available to help purchasers obtain best results from information believed to be reliable. However, we have no control over the conditions under which our products are transported to, stored, handled, or used by purchasers and, in any event, all recommendations and sales are made on condition that we will not be held liable for any damages resulting from their use. Date Created: 11-29-16 Date Reviewed: 2-10-17