

# L4145-14H

# **SOLVENT BASED ADHESIVE**

## **KEY FEATURES**

- Good chemical resistance
- Meets BMS 5-14H specification for the aerospace industry

#### **DESCRIPTION**

Bostik L4145-14H is a solvent based, one part adhesive. L4145-14H is based on nitrile rubber and is fast drying as well as high in viscosity. This product is sold against the Boeing Material Specification 5-14H.

## **BENEFITS**

- · Oil and plasticizer resistant
- · Resistant to jet fuel
- · Resistant to water and detergents
- Fast drying
- · Dried film provides tough elastic bonds
- · No curative needed

# **PRODUCT APPLICATIONS**

- Bonding vinyl to flexible and rigid plastics, foam, and metals for automotive, rail, and aerospace interior trim applications
- Bonding fabrics, coated fabrics and vinyl in upholstery applications
- Bonds to a wide variety of fibrous, porous and non-porous materials, including aluminum, ABS, vinyl films and foams, urethanes, nitriles, natural and synthetic fabrics

### **DIRECTIONS FOR USE**

Surfaces should be clean and dry. Apply sufficient adhesive to each surface and allow to dry. Bond with uniform pressure. Alternate method is to apply to one surface and dry at least 20 minutes. Apply to other surface and while still tacky (within 10 minutes) mate two surfaces with firm uniform pressure.



| TYPICAL PHYSICAL PROPERTIES                   |                |
|---|----------------|
| Description                                   | Results        |
| Polymer                                       | Nitrile        |
| Appearance                                    | Light Amber    |
| Total Solids, %                               | 29.5           |
| Viscosity, cP<br>(Brookfield RVT #2 @100 rpm) | 8,000          |
| Density, lbs/gallon                           | 7.34           |
| Flash Point, °F                               | 0              |
| Solvent                                       | MEK/Acetone    |
| Typical Shear Value, psi<br>(nylon web/Al)    | >175           |
| Shelf Life                                    | 270 days @75°F |
| Storage Temperature                           | 55-120°F       |

# **STORAGE AND HANDLING**

Shelf Life: 270 days @75°F

Storage Temperature: 55-120°F

(A prolonged exposure to high heat will prematurely age the adhesive, increasing viscosity irreversibly. Cold temperature will increase viscosity but will return to thinner viscosity when warmed to room temperature.)

#### **FURTHER INFORMATION**

Please refer to SDS for complete details.

#### **LIMITED WARRANTY**

Limited Warranty found at www.bostik-us.com or call 800-726-7845. TO THE MAXIMUM EXTENT ALLOWED BY LAW, BOSTIK DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. UNLESS OTHERWISE STATED IN THE LIMITED WARRANTY, THE SOLE REMEDY FOR BREACH OF WARRANTY IS REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. BOSTIK DISCLAIMS ANY LIABILITY FOR DIRECT, INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES TO THE MAXIMUM EXTENT ALLOWED BY LAW. DISCLAIMERS OF IMPLIED WARRANTIES MAY NOT BE APPLICABLE TO CERTAIN CLASSES OF BUYERS AND SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATIONS MAY NOT APPLY TO YOU. It is the buyer's obligation to test the suitability of the product for an intended use prior to using it. The Limited Warranty extends only to the original purchaser and is not transferable or assignable. Any claim for a defective product must be filed within 30 days of discovery of a problem, and must be submitted with written proof of purchase.

