HumiSeal®















SAFETY DATA SHEET

1. Identification

Product identifier

HumiSeal Thinner 801

Other means of identification

Product code

HumiSeal Thinner 801

Recommended use

Thinner for Protective Coating

Recommended restrictions

None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name

CHASE CORPORATION Zeta Drive Plant

Address

201 Zeta Drive

Pittsburgh, PA 15238

United States

Telephone

1-866-932-0800

E-mail

Not available.

Emergency phone number

1-800-424-9300 (+1)703-527-3887

Chemtrec, US

Chemtrec, outside of US

2. Hazard(s) identification

Physical hazards

Flammable liquids

Category 2

Health hazards

Serious eye damage/eye irritation

Category 2B

Specific target organ toxicity, single exposure

Category 3 narcotic effects

Environmental hazards

Hazardous to the aquatic environment, acute

Category 2

Hazardous to the aquatic environment,

Category 2

long-term hazard

OSHA defined hazards

Not classified.

Label elements



Signal word

Danger

Hazard statement

Highly flammable liquid and vapor. Causes eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces, - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish. Collect spillage.

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Storage

Keep cool. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise classified (HNOC)

Supplemental information

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

71% of the mixture consists of component(s) of unknown acute hazards to the aquatic

environment. 71% of the mixture consists of component(s) of unknown long-term hazards to the

aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Tert-BUTYL ACETATE		540-88-5	70 - < 80
HEXYL ACETATES		88230-35-7	20 - < 30

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

individuals may experience eye tearing, redness, and discomfort.

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes. Exposed

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

General information

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods General fire hazards Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Do not use water jet as an extinguisher, as this will spread the fire.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

SDS US

Use standard firefighting procedures and consider the hazards of other involved materials.

Material name: HumiSeal Thinner 801

Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Avoid spark promoters. Eliminate sources of ignition. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for A	ir Contaminants (29 CFR 1910.	1000)	
Components	Туре	Value	
Tert-BUTYL ACETATE (CAS 540-88-5)	PEL	950 mg/m3	
(3.13 2.13 23 3,		200 ppm	

US. ACGIH Threshold Limit Valu Components	ies Type	Value	
Tert-BUTYL ACETATE (CAS 540-88-5)	TWA	200 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	
Tert-BUTYL ACETATE	TWA	950 mg/m3	

(CAS 540-88-5) 200 ppm No biological exposure limits noted for the ingredient(s). **Biological limit values**

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Chemical respirator with organic vapor cartridge and full facepiece. Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Wear appropriate chemical resistant clothing. Other Chemical respirator with organic vapor cartridge and full facepiece. Respiratory protection

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

When using do not smoke. Always observe good personal hygiene measures, such as washing General hygiene considerations

after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. Liquid. Form Color Colorless Sweet Odor

Odor threshold Not available. pН Does not apply. Melting point/freezing point Not available.

Initial boiling point and boiling

208.04 °F (97.8 °C) estimated

range

48.2 °F (9.0 °C) Flash point

2 BuAc **Evaporation rate** Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

1.5 % estimated

Not available.

(%)

Flammability limit - lower

(%) temperature

1.26

Flammability limit - upper

Flammability limit - upper (%) temperature

6.88

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

45 hPa estimated

Vapor density Relative density Not available. Not available.

Material name: HumiSeal ThInner 801

SDS US

HumiSeal Thinner 801 Version #: 02 Revision date: 05-24-2015 Issue date: 12-09-2014

Solubility(ies)

Solubility (water)

Negligible

Partition coefficient

Not available.

(n-octanol/water)

Auto-ignition temperature

799 °F (426.11 °C) estimated

Decomposition temperature

Not available.

Viscosity

Not available.

Other information

Density

0.87 g/cm3

Flammability class

Flammable IB estimated

Miscible (water)

Negligible

Specific gravity

0.87

VOC (Weight %)

100 %

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

Hazardous polymerization does not occur.

reactions

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials

Nitrates.

Hazardous decomposition

No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Prolonged inhalation may be harmful. May cause drowsiness and dizziness. Headache. Nausea,

vomiting.

Skin contact

Inhalation

No adverse effects due to skin contact are expected.

Eye contact

Causes eye irritation.

Ingestion

Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort.

toxicological characteristics Information on toxicological effects

Acute toxicity

Narcotic effects.

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes eye irritation.

Respiratory or skin sensitization

Respiratory sensitization

Not available.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not available.

Aspiration hazard

Material name: HumiSeal Thinner 801

Not classified.

HumiSeal Thinner 801 Version #: 02 SDS US

5/9

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Product		Species	Test Results
HumiSeal Thinner 801			
Aquatic			
Fish	LC50	Fish	416.9014 mg/l, 96 hours estimated
Components		Species	Test Results

Tert-BUTYL ACETATE (CAS 540-88-5)

Aquatic

Fish

LC50

Fathead minnow (Pimephales promelas) 296 - 362 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Not available.

Partition coefficient n-octanol / water (log Kow)

Tert-BUTYL ACETATE

1.76

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Hazardous waste code

Dispose in accordance with all applicable regulations. The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN1263

UN proper shipping name

Transport hazard class(es)

PAINT RELATED MATERIAL

Class 3 Subsidiary risk Label(s) 3

Packing group н

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB2, T4, TP1

Packaging exceptions 150 202 Packaging non bulk Packaging bulk 242

IATA

UN number UN1263

PAINT RELATED MATERIAL UN proper shipping name

Transport hazard class(es)

3 Class Subsidiary risk II Packing group

Material name: HumiSeal Thinner 801

SDS US

HumiSeal Thinner 801 Version #: 02 **Environmental hazards**

No.

ERG Code

3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed.

aircraft

Cargo aircraft only

Allowed.

IMDG

UN number

UN1263

UN proper shipping name

PAINT RELATED MATERIAL

Transport hazard class(es)

3

Subsidiary risk

-II

Packing group Environmental hazards

Class

"

Marine pollutant

No.

EmS

F-E, S-D

Not available.

Transport in bulk according to

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



General information

DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Tert-BUTYL ACETATE (CAS 540-88-5)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

Tert-BUTYL ACETATE (CAS 540-88-5)

US. New Jersey Worker and Community Right-to-Know Act

Tert-BUTYL ACETATE (CAS 540-88-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Tert-BUTYL ACETATE (CAS 540-88-5)

US. Rhode Island RTK

Tert-BUTYL ACETATE (CAS 540-88-5)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name On inventor	ry (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Ves" indicates that all compo	parts of this product comply with the inventory requirements administered by the governing country/	e)

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

 Issue date
 12-09-2014

 Revision date
 05-24-2015

Version # 02

Material name: HumiSeal Thinner 801 sps us
HumiSeal Thinner 801 Version #: 02 Revision date: 05-24-2015 Issue date: 12-09-2014 8 / 9

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

HMIS® ratings

Health: 2

Flammability: 3 Physical hazard: 0

NFPA ratings

Flammability: 3

Instability: 0

Disclaimer

The information offered in this data sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication, however, no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. This material is intended for industrial use only.

No warranty, expressed or implied is made.

Revision Information

Product and Company Identification: Product and Company Identification Handling and storage: Conditions for safe storage, including any incompatibilities