Safety Data Sheet



Revision Number: 002.0 Issue date: 11/17/2023

PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE FREKOTE 770-NC known as IDH number:

LOCTITE FREKOTE 770NC

Product type/use: Coating Item number: 83468 Restriction of Use: None identified Region: **United States** Contact information:

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

416032

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

Contains one or more components for which a Toxic Substances Control Act (TSCA) Low Volume Exemption (LVE) applies. See Section 15.

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOUR.

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

CAUSES SKIN IRRITATION.

MAY CAUSE DROWSINESS OR DIZZINESS.

| HAZARD CLASS | HAZARD CATEGORY |
|--|-----------------|
| FLAMMABLE LIQUID | 2 |
| SKIN IRRITATION | 2 |
| SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE | 3 |
| ASPIRATION HAZARD | 1 |

PICTOGRAM(S)



Precautionary Statements

Storage:

IDH number: 416032

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly

closed. No release into water. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective

gloves, eye protection, and face protection.

IF SWALLOWED: Immediately call a physician or poison control center. If on skin (or hair): Response:

Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

Dispose of contents and/or container according to Federal, State/Provincial and local Disposal:

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* |
|---|--------------|-------------|
| Hydrocarbons, C7-C9, isoalkanes | 1174921-67-5 | 80 - 100 |
| Reaction product of tris(n- methylamino)methylsilane (TMAS) and silanol terminated polydimethylsiloxane (PDMS) | 1432471-92-5 | 1 - 5 |
| 2,2,4-trimethylpentane | 540-84-1 | 0.1 - 1 |

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Get medical attention. If breathing is difficult, give oxygen. If not breathing,

give artificial respiration. Move to fresh air.

Skin contact: Wash clothing before reuse. If skin irritation persists, call a physician. Remove

contaminated clothing and footwear. Immediately flush skin with plenty of

water (using soap, if available).

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get immediate medical attention.

Ingestion: Never give anything by mouth to an unconscious person. Get immediate

medical attention. Keep individual calm. If vomiting occurs, prevent aspiration by keeping the patient's head below the knees. Do not induce vomiting:

contains petroleum distillates and/or aromatic solvents.

Symptoms: See Section 11.

IDH number: 416032

Notes to physician: This material is an aspiration hazard. Potential danger from aspiration must

be weighed against possible oral toxicity when deciding whether to induce

vomiting.

5. FIRE FIGHTING MEASURES

Extinguishing media: Dry powder. Alcohol-resistant foam Carbon dioxide. Water spray or fog. Do

not use high volume water jet.

Special firefighting procedures: Keep personnel upwind of fire. Wear self-contained breathing apparatus and

full protective clothing, such as turn-out gear. Water may be unsuitable as an extinguishing media, but may be helpful in keeping adjacent containers cool.

Unusual fire or explosion hazards: Vapors may form explosive mixtures with air. Do not handle or store near an

open flame, heat or other sources of ignition. Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a significantly high level, sparks can form that may ignite vapors of

flammable liquids.

Hazardous combustion products: Collect contaminated fire extinguishing water separately. This must not be

discharged into drains. Oxides of nitrogen. Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways. This product is insoluble in

water and will float on surface. Prevent further leakage or spillage if safe to do so. Advise authorities if product has entered or may enter sewers, water

sources or extensive land areas.

Product name: LOCTITE FREKOTE 770-NC known as LOCTITE FREKOTE 770NC Page 2 of 6

Clean-up methods: Remove all sources of ign

Remove all sources of ignition. Ventilate area. Store in a closed metal container until ready for disposal. Wear suitable protective clothing, gloves and eye/face protection. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep upwind of the spilled material and isolate exposure.

7. HANDLING AND STORAGE

Handling: For operations where eye or face contact could occur, provide safety shower

and eyewash fountain. During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Make sure containers are properly grounded before use or transfer of material. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling.

Storage: Keep container closed. Store away from heat, sparks, flames, or other sources

of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|---|----------------------------|------------------------------|-----------|-------|
| Hydrocarbons, C7-C9, isoalkanes | None | None | None | None |
| Reaction product of tris(n- methylamino)methylsilane (TMAS) and silanol terminated polydimethylsiloxane (PDMS) | None | None | None | None |
| 2,2,4-trimethylpentane | 300 ppm TWA 300 ppm TWA | 500 ppm (2,350 mg/m3) PEL | None | None |

Engineering controls: Use explosion-proof mechanical ventilation and local exhaust to control

contaminants to within their occupational exposure limits during the use of this

product.

Respiratory protection: Use a NIOSH approved supplied air respirator with an organic cartridge if the

potential to exceed established exposure limits exists.

Eyelface protection: Wear chemical goggles or a full face shield. Safety showers and eye wash

stations should be available. Safety goggles or safety glasses with side

shields.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Color: Clear

Odor: Of hydrocarbons Odor threshold: Not available. Not applicable pH: Vapor pressure: Not available. Boiling point/range: Not available. Melting point/ range: Not available. Specific gravity: 0.720 Vapor density: Not available.

Flash point: 7 °C (44.6 °F) Tagliabue closed cup

Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Not available.
Not available.
Flammability:
Evaporation rate:
Solubility in water:
Partition coefficient (n-octanol/water):
Not available.
Not available.
Not available.

VOC content: 98.5 %; 710 g/l Estimated

Viscosity: Not available.

Decomposition temperature: Not available.

IDH number: 416032 Product name: LOCTITE FREKOTE 770-NC known as LOCTITE FREKOTE 770NC

Page 3 of 6

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Risk of ignition.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

Hydrocarbons.

Incompatible materials: Strong oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Keep away from open flames, hot surfaces and sources of ignition. Avoid static discharge.

Exposure to air or moisture over prolonged periods. Spray mist may be flammable at temperatures below the flash point. Fire or intense heat may cause violent rupture of

packages. Vapors may form explosive mixtures with air.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Ingestion, Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Skin contact:

IDH number: 416032

Inhalation: Vapors and mists will irritate nose and throat and possibly eyes. High vapor concentrations

(greater than approximately 1000 ppm) may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death. Causes skin irritation. Solvent action can dry and defat the skin, causing the skin to crack,

leading to dermatitis.

Eye contact: Causes serious eye irritation.

Ingestion: Central nervous system depression, including dizziness, drowsiness, fatigue, nausea,

headache, unconsciousness. Aspiration may occur during swallowing or vomiting, resulting in

lung damage.

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects |
|---|---|--|
| Hydrocarbons, C7-C9, isoalkanes | None | No Data |
| Reaction product of tris(n- methylamino)methylsilane (TMAS) and silanol terminated polydimethylsiloxane (PDMS) | None | No Data |
| 2,2,4-trimethylpentane | Inhalation LC50 (Rat, 4 h) = > 33.52 mg/l | Lung, Irritant, Central nervous system, Liver, Kidney |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|---|----------------|-----------------|--|
| Hydrocarbons, C7-C9, isoalkanes | No | No | No |
| Reaction product of tris(n- methylamino)methylsilane (TMAS) and silanol terminated polydimethylsiloxane (PDMS) | No | No | No |
| 2,2,4-trimethylpentane | No | No | No |

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

Page 4 of 6

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Resin solution
Hazard class or division: 3
Identification number: UN 1866

Packing group:

International Air Transportation (ICAO/IATA)

Proper shipping name: Resin solution

Hazard class or division: 3
Identification number: UN 1866
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: RESIN SOLUTION (Isoalkane C7 - C10)

Hazard class or division: 3
Identification number: UN 1866
Packing group: II

Marine pollutant: Isoalkane C7 - C10

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

This product contains one or more components with a Low Volume Exemption (LVE) in

accordance with 40 CFR 723.50. Quantities may be limited.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health, Fire

CERCLA/SARA Section 313: None above reporting de minimis.

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

IDH number: 416032

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the

Domestic Substances List or the Non-Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 9, 14

Prepared by: Product Safety and Regulatory Affairs

Issue date: 11/17/2023

Product name: LOCTITE FREKOTE 770-NC known as LOCTITE FREKOTE 770NC Page 5 of 6

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.