



Revision Number: 007.0

Issue date: 04/24/2025

## 1. IDENTIFICATION

**Product name:** LOCTITE SF 712 ACCELLORATORS FOR CA known as Tak Pak® 712 Accelerator Meter

**IDH number:** 229783

**Product type/Recommended use:** Accelerator

**Item number:** 18636

**Restriction of Use:** None identified

**Region:** United States

**Company address:** Henkel Corporation  
One Henkel Way  
Rocky Hill, Connecticut 06067

**Contact information:**  
Telephone: +1 (860) 571-5100  
MEDICAL EMERGENCY Phone: Poison Control Center  
1-877-671-4608 (toll free) or 1-303-592-1711  
TRANSPORT EMERGENCY Phone: CHEMTREC  
1-800-424-9300 (toll free) or 1-703-527-3887  
MEDICAL EMERGENCY Phone: Poison Control Center  
1-877-671-4608 (toll free) or 1-303-592-1711  
TRANSPORT EMERGENCY Phone: CHEMTREC  
1-800-424-9300 (toll free) or 1-703-527-3887  
Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**DANGER:** H222 - EXTREMELY FLAMMABLE AEROSOL.  
H229 - PRESSURIZED CONTAINER: MAY BURST IF HEATED.  
H319 - CAUSES SERIOUS EYE IRRITATION.  
H336 - MAY CAUSE DROWSINESS OR DIZZINESS.  
H373 - MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
AEROSOL	1
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2

### PICTOGRAM(S)



### Precautionary Statements

**Prevention:** P210 - Keep away from heat, sparks, open flames, hot surfaces - no smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.  
P260 - Do not breathe dust or fumes.  
P264 - Wash affected area thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear eye and face protection.

**Response:** P304+P340+P312 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P314 - Get medical attention if you feel unwell.  
P337+P313 - If eye irritation persists: Get medical attention.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

**Storage:**

IDH number: 229783

Product name: LOCTITE SF 712 ACCELLORATORS FOR CA known as Tak Pak® 712 Accelerator Meter

**Disposal:** P405 - Store locked up.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

**Other hazards** Not available.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
2-Propanol	67-63-0	60 - 80
butane	106-97-8	10 - 30
propane	74-98-6	10 - 30
N,N-Dimethyl-p-toluidine	99-97-8	1 - 5

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

#### First Aid Measures by likely routes of exposure

<b>Inhalation:</b>	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.
<b>Skin contact:</b>	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention. Wash clothing before reuse.
<b>Eye contact:</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Ingestion:</b>	DO NOT induce vomiting unless directed to do so by medical personnel. Get medical attention. Never give anything by mouth to an unconscious person.
<b>Most important symptoms and effects (acute and delayed):</b>	The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.
<b>Indication of any immediate medical attention / special treatment needed:</b>	Aspiration may cause pulmonary edema or aspiration pneumonia.

### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Foam, dry chemical or carbon dioxide.
<b>Improper extinguishing agents:</b>	Not available.
<b>Special firefighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Water should be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.
<b>Unusual fire or explosion hazards:</b>	Contents under pressure. Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back. Exposure to temperatures above 49°C (120°F) may cause container to burst. Do not puncture or incinerate pressurized containers.

**Hazardous combustion products:**

Oxides of carbon. Oxides of nitrogen. Irritating organic vapours.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:**

Do not allow product to enter sewer or waterways.

**Clean-up methods:**

Remove all sources of ignition. Ensure adequate ventilation. Wear appropriate personal protective equipment. Keep unnecessary personnel away. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Rinse spill area with water. Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Wear suitable protective clothing, gloves and eye/face protection. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

**Handling:**

During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not puncture or incinerate pressurized containers. Refer to Section 8.

**Storage:**

For safe storage, store at or below 49 °C (120.2 °F)  
Keep in a cool, well ventilated area away from heat, sparks and open flame.  
Keep container tightly closed until ready for use.

**Shelf Life Statement:** Not available.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
2-Propanol	200 ppm TWA 400 ppm STEL	400 ppm (980 mg/m3) PEL	None	None
butane	1,000 ppm STEL (Simple asphyxiant.)	None	None	None
propane	D: Simple asphyxiant, EX: Explosion hazard (Simple asphyxiant.)	1,000 ppm (1,800 mg/m3) PEL	None	None
N,N-Dimethyl-p-toluidine	None	None	0.5 ppm TWA	None
Ethanol	1,000 ppm STEL	1,000 ppm (1,900 mg/m3) PEL	None	None

**Engineering controls:**

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Respiratory protection:**

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:**

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

**Skin protection:**

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Aerosol
Color:	Clear
Odor:	Alcoholic
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	33 mm hg (21 °C (69.8 °F))
Boiling point/range:	82 °C (179.6 °F)
Melting point/ range:	Not available.
Density/Relative density:	0.79
Relative vapor density:	2.1
Flash point:	> -109 °C (> -164.2 °F) Open cup; (value for propellant).
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Extremely flammable aerosol.
Evaporation rate:	7.7 (Ether = 1)
Solubility:	Partially soluble Water
Partition coefficient n-octanol/water (logarithmic value):	Not available.
VOC content:	99.9 %; 789 g/l EPA Method 24
Dynamic viscosity:	Not available.
Kinematic viscosity:	Not available.
Particle characteristics:	Not available.
Decomposition temperature:	Not available.

## 10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Irritating organic vapours.
Incompatible materials:	Strong oxidizing agents. Strong acids and strong bases. Aluminum. Aldehydes.
Reactivity:	Not available.
Conditions to avoid:	Do not puncture, incinerate, or expose to temperatures above 48.9 °C (120 °F). Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

## 11. TOXICOLOGICAL INFORMATION

Likely routes of exposure:	Skin, Inhalation, Eyes, Ingestion
----------------------------	-----------------------------------

### Potential Health Effects/Symptoms

<b>Inhalation:</b>	May cause dizziness, incoordination, headache, nausea, and vomiting.
<b>Skin contact:</b>	Causes skin irritation. May cause allergic skin reaction.
<b>Eye contact:</b>	Causes serious eye irritation. Tearing. Redness.
<b>Ingestion:</b>	Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing large amounts may be harmful. Aspiration may occur during swallowing or vomiting, resulting in lung damage.

Hazardous Component(s)	LD50s and LC50s
2-Propanol	Oral LD50 (Rat) = 5,045 mg/kg Oral LD50 (Mouse) = 3,600 mg/kg Oral LD50 (Rabbit) = 6,410 mg/kg Oral LD50 (Rat) = 4.7 g/kg Oral LD50 (Mouse) = 4.5 g/kg Oral LD50 (Rabbit) = 8.0 g/kg Oral LD50 (Rabbit) = 5.03 g/kg Dermal LD50 (Rabbit) = 12,800 mg/kg
butane	None
propane	Inhalation LC50 (Rat, 4 h) = > 13023 ppm Inhalation LC50 (Rat, 4 h) = > 13023 ppm
N,N-Dimethyl-p-toluidine	Inhalation LC50 (Rat, 4 h) = 1,400 mg/m3 Inhalation LC50 (Mouse, 4 h) = 52 ppm

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
2-Propanol	Irritant	Allergen	Central nervous system
butane	Irritant		Cardiac Central nervous system
propane	Irritant		Cardiac Central nervous system
N,N-Dimethyl-p-toluidine		Allergen	Mutagen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
2-Propanol	No	Group 1	No
butane	No	No	No
propane	No	No	No
N,N-Dimethyl-p-toluidine	No	Group 2B	No

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Aerosols  
Hazard class or division: 2.1  
Identification number: UN 1950  
Packing group: None

### International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, flammable  
Hazard class or division: 2.1  
Identification number: UN 1950  
Packing group: None  
Exceptions: May Qualify as Consumer Commodity, (Not more than 500 ml), ID8000

**Water Transportation (IMO/IMDG)**

Proper shipping name:	AEROSOLS
Hazard class or division:	2.1
Identification number:	UN 1950
Packing group:	None
Exceptions:	Limited quantity (Not more than 1 L).

**15. REGULATORY INFORMATION****United States Regulatory Information**

<b>TSCA 8 (b) Inventory Status:</b>	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
<b>TSCA 12 (b) Export Notification:</b>	None above reporting de minimis
<b>CERCLA/SARA Section 302 EHS:</b>	None above reporting de minimis.
<b>CERCLA/SARA Section 311/312:</b>	Please refer to the GHS classification in Section 2
<b>CERCLA/SARA Section 313:</b>	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). 2-Propanol (CAS# 67-63-0) 100 lbs. (45.4 kg)
<b>CERCLA Reportable quantity:</b>	2-Propanol (CAS# 67-63-0) 100 lbs. (45.4 kg) butane (CAS# 106-97-8) 100 lbs. (45.4 kg) propane (CAS# 74-98-6) 100 lbs. (45.4 kg) Ethanol (CAS# 64-17-5) 100 lbs. (45.4 kg)
<b>California Proposition 65:</b>	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

**Canada Regulatory Information**

<b>CEPA DSL/NDL Status:</b>	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
-----------------------------	---

**16. OTHER INFORMATION**

**This safety data sheet contains changes from the previous version in sections:** New Safety Data Sheet format., Expanded chemical information in Section 2 and related sections.

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 04/24/2025

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.