

# ThermoGrip® H284-332

# **HOT MELT ADHESIVE**

## **KEY FEATURES**

- Aggressive tack for excellent pick-up
- Reliable and easy to use
- Works with Bostik liquid lap adhesives

### **PRODUCT**

H284-332 is a hot melt labeling adhesive.

### **DESCRIPTION**

H284-332, an industry standard in roll through labeling, offers aggressive tack for excellent and reliable pick-up. H284-332 works in conjunction with Bostik's liquid lap adhesives in non-permanent applications.

### **BASIC USES**

H284-332 is designed for superior performance in labeling to three piece metal cans or fiber containers.

### **PACKAGING**

H284-332 is available in an easy to use Pick-et<sup>™</sup> form.

### CLEAN UP

Mineral oil or paraffin wax, not to exceed flash point as stated on the SDS, followed by a thorough purge with the adhesive itself.

# **FDA 21 CFR Numbers**

175.105

We do not knowingly add any substances derived from animal sources to this product.

# **SHELF LIFE**

Can be stored 730 days in a clean dry place, in its original package at an average temperature of 25°C or below. Storage temperature should not exceed 40°C.

# **HEALTH AND SAFETY PRECAUTIONS**

The Safety Data Sheet should be consulted for proper handling, clean up, and spill containment before use. Keep containers covered to minimize contamination. For FDA



TYPICAL PHYSICAL PROPERTIES	
Description	Results
Thermosel Viscosity (Brookfield - ASTM D3236)	1350 cP @ 200°F (93°C) 525 cP @ 225°F (107°C) 300 cP @ 250°F (121°C) 175 cP @ 275°F (135°C)
Density	1.1 g/cc @ 77°F (25°C)
Softening Point (Herzog - ASTM E28)	150°F (66°C)
Suggested Running Temperature	250-275°F (121-135°C)

**VISCOSITY CURVE** 

# 1500 1200 900 600 300 0 200°F 225°F 250°F 275°F

Temperature (°F)

regulations and additional clearances, please contact the Regulatory Affairs Depar tment at 414-774-2250.

### **LIMITED WARRANTY**

Limited Warranty found at www.bostik-us.com or call 800-726-7845. TO THE MAXIMUM EXTENT ALLOWED BY LAW, BOSTIK DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. UNLESS OTHERWISE STATED IN THE LIMITED WARRANTY, THE SOLE REMEDY FOR BREACH OF WARRANTY IS REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. BOSTIK DISCLAIMS ANY LIABILITY FOR DIRECT, INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES TO THE MAXIMUM EXTENT ALLOWED BY LAW. DISCLAIMERS OF IMPLIED WARRANTIES MAY NOT BE APPLICABLE TO CERTAIN CLASSES OF BUYERS AND SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATIONS MAY NOT APPLY TO YOU. It is the buyer's obligation to test the suitability of the product for an intended use prior to using it. The Limited Warranty extends only to the original purchaser and is not transferable or assignable. Any claim for a defective product must be filed within 30 days of discovery of a problem, and must be submitted with written proof of purchase.



This document supersedes all previously published literature. 10.23.14  $\,$