# Safety Data Sheet



**Revision Number: 010.2** Issue date: 06/12/2023

## 1. PRODUCT AND COMPANY IDENTIFICATION

**LOCTITE AA 3106 UV CURING** Product name:

ADHESIVE known as 3106 UV Curing

**General Purpose** 

Product type/use: Ultraviolet adhesive Restriction of Use: None identified

Company address: Henkel Corporation

Rocky Hill, Connecticut 06067

One Henkel Way

IDH number: 168331

Item number: 23698 Region: **United States** 

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGÉNCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

DANGER: DO NOT SPRAY. DO NOT HEAT.

COMBUSTIBLE LIQUID.

HARMFUL IF SWALLOWED OR IN CONTACT WITH SKIN.

CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE DAMAGE.

SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	4
ACUTE TOXICITY ORAL	4
ACUTE TOXICITY DERMAL	4
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1
REPRODUCTIVE TOXICITY	2





#### **Precautionary Statements**

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed

out of the workplace. Wear protective gloves, clothing, eye and face protection.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of Response: soap and water. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry

chemical or carbon dioxide to extinguish.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

IDH number: 168331 Product name: LOCTITE AA 3106 UV CURING ADHESIVE known as 3106 UV Curing General

Purpose

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

#### See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Isobornyl acrylate	5888-33-5	30 - 60	
N,N-Dimethylacrylamide	2680-03-7	10 - 30	
Gamma-glycidoxypropyl trimethoxysilane	2530-83-8	1 - 5	
Silica, amorphous, fumed, crystfree	112945-52-5	0.1 - 1	
diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide	75980-60-8	0.1 - 1	
Acrylic acid	79-10-7	0.1 - 1	
2-Hydroxyethyl acrylate	818-61-1	0.1 - 1	

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

**Skin contact:** Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. If symptoms develop and persist, get

medical attention. Wash clothing before reuse.

**Eye contact:** Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get immediate medical attention.

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious

person. Keep individual calm. Get immediate medical attention.

Symptoms: See Section 11.

## 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Unusual fire or explosion hazards: Uncontrolled polymerization may occur at high temperatures resulting in

explosions or rupture of storage containers.

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Oxides of silicon. Toxic and irritating

vapors. Collect contaminated fire extinguishing water separately. This must

not be discharged into drains.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Remove all sources of ignition. Do not allow product to enter sewer or

waterways.

Clean-up methods: Ensure adequate ventilation. Soak up with inert absorbent material (e.g. sand,

silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls /

Personal Protection" prior to clean up.

IDH number: 168331 Product name: LOCTITE AA 3106 UV CURING ADHESIVE known as 3106 UV Curing General Purpose

# 7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not taste or swallow. DO NOT heat or spray. Use only in area provided with

appropriate exhaust ventilation. Refer to Section 8.

**Storage:** For safe storage, store at or below 26 °C (78.8 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Isobornyl acrylate	None	None	None	None
N,N-Dimethylacrylamide	None	None	None	0.1 mg/m3 TWA (Skin) 0.025 ppm TWA (Skin)
Gamma-glycidoxypropyl trimethoxysilane	None	None	None	None
Silica, amorphous, fumed, crystfree	3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	20 MPPCF TWA 0.8 mg/m3 TWA 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide	None	None	None	None
Acrylic acid	2 ppm TWA (SKIN)	None	None	1 ppm TWA 3 ppm STEL (SKIN)
2-Hydroxyethyl acrylate	None	None	None	None

Engineering controls: Local exhaust ventilation is recommended when general ventilation is not

sufficient to control airborne contamination below occupational exposure

limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s). If this material is handled at elevated temperatures or under mist forming conditions, without engineering controls, a NIOSH approved respirator

must be used.

**Eye/face protection:** Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists.

**Skin protection:** Use impermeable gloves and protective clothing as necessary to prevent skin

contact. Neoprene gloves.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Color: Transparent, Slightly Hazy

Odor: Mild

Odor threshold: Not available.

pH: Not applicable, Product reacts with water.

Vapor pressure: $< 5 \text{ mm hg} (20 ^{\circ}\text{C} (68^{\circ}\text{F}))$ Boiling point/range: $> 93 ^{\circ}\text{C} (> 199.4 ^{\circ}\text{F})$ 

Melting point/ range: Not applicable, Product is a liquid

Specific gravity: 1.078 Vapor density: > 1.20 °C

Flash point: 77.8 °C (172.04 °F)
Flammable/Explosive limits - lower: Not available.
Flammable/Explosive limits - upper: Not available.

IDH number: 168331 Product name: LOCTITE AA 3106 UV CURING ADHESIVE known as 3106 UV Curing General

Purpose

Autoignition temperature: Not applicable

Flammability: The product is not flammable.

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

Not available.

Not available.

VOC content: 2.16 %; 23.28 g/l (process)

1.05 %; 11.32 g/l (potential) 3.21 %; 34.60 g/l (total) (ASTM D5403)

Viscosity: Not available.

Decomposition temperature: Not available.

# 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: May occur.

**Hazardous decomposition**Oxides of carbon. Oxides of nitrogen. Oxides of silicon. Irritating organic vapours. Isocyanates.
Hydrogen cyanide. Amines.

**Incompatible materials:** Strong oxidizing agents. Strong acids. Strong bases. Amines. Alkalis. Peroxides. Free radical

initiators.

Reactivity: Not available.

IDH number: 168331

Conditions to avoid: Keep away from heat, spark and flame. Avoid temperatures above 26°C (80°F). Store away

from incompatible materials. Direct sunlight. Ultraviolet radiation. Freezing conditions.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Product name: LOCTITE AA 3106 UV CURING ADHESIVE known as 3106 UV Curing General Purpose

#### Potential Health Effects/Symptoms

**Inhalation:** Modified acrylamide is harmful if inhaled. Causes respiratory tract irritation. Vapors and mists

will irritate nose and throat and possibly eyes. Headache. Nausea. DO NOT heat or spray as

this increases the inhalation hazard.

Skin contact: Causes skin irritation. May cause allergic skin reaction. Modified acrylamide may be absorbed

through skin in harmful amounts.

**Eye contact:** Causes serious eye damage.

**Ingestion:** Modified acrylamide is harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Isobornyl acrylate	None	Irritant, Allergen	
N,N-Dimethylacrylamide	None	Irritant, Eyes, Mutagen, Kidney, Less weight gain and food intake.	
Gamma-glycidoxypropyl trimethoxysilane	Inhalation LC50 (Rat, 4 h) = > 5.3 mg/l	Allergen, Irritant	
Silica, amorphous, fumed, crystfree	None	No Data	
diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide	None	No Records	
Acrylic acid	Oral LD50 (Rat) = 33.5 mg/kg Oral LD50 (Mouse) = 2,400 mg/kg Oral LD50 (Rat) = 2.5 g/kg Oral LD50 (Rat) = 193 mg/kg Oral LD50 (Rat) = 1,250 mg/kg Inhalation LC50 (Rat, 4 h) = 3.6 mg/l Inhalation LC50 (Rat, 4 h) = > 3.9 - < 4.8 mg/l Inhalation LC50 (Rat, 4 h) = > 5.1 mg/l	Allergen, Corrosive, Irritant, Kidney, Liver	
2-Hydroxyethyl acrylate	Dermal LD50 (Rabbit) = 1,010 mg/kg	Allergen, Central nervous system, Heart, Irritant, Kidney, Liver, Lung, Some evidence of carcinogenicity, Spleen	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Isobornyl acrylate	No	No	No
N,N-Dimethylacrylamide	No	No	No
Gamma-glycidoxypropyl trimethoxysilane	No	No	No
Silica, amorphous, fumed, crystfree	No	No	No
diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide	No	No	No
Acrylic acid	No	No	No
2-Hydroxyethyl acrylate	No	No	No

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

# 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

IDH number: 168331

Proper shipping name: Combustible liquid, n.o.s. (Modified Acrylamide)

Hazard class or division: Combustible Liquid

Identification number: NA 1993
Packing group: III

Product name: LOCTITE AA 3106 UV CURING ADHESIVE known as 3106 UV Curing General Purpose

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (2,2-Dimethoxy-1,2-

diphenylethan-1-one, Isobornyl acrylate)

Hazard class or division:

Identification number: UN 3082 Packing group: Ш

Water Transportation (IMO/IMDG)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-Proper shipping name:

Dimethoxy-1,2-diphenylethan-1-one, Isobornyl acrylate)

Hazard class or division: Identification number: UN 3082 Packing group: Ш

Marine pollutant: 2,2-Dimethoxy-1,2-diphenylethan-1-one, Isobornyl acrylate

#### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis. CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire CERCLA/SARA Section 313: None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

IDH number: 168331

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3, 8, 9, 11

Prepared by: Product Safety and Regulatory Affairs

Issue date: 06/12/2023

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

> Product name: LOCTITE AA 3106 UV CURING ADHESIVE known as 3106 UV Curing General Purpose