



Revision Number: 006.0

Issue date: 12/10/2020

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE EA E-20NS A RESIN known as DB EPOXY ADH E-20NS 50 ML RESIN
IDH number: 702001
Product type/use: Epoxy resin
Item number: 29334_209540
Restriction of Use: None identified
Region: United States
Company address:
 Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067
Contact information:
 Telephone: +1 (860) 571-5100
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CAUSES SKIN IRRITATION.
 MAY CAUSE AN ALLERGIC SKIN REACTION.
 CAUSES SERIOUS EYE IRRITATION.
 MAY CAUSE RESPIRATORY IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3



Precautionary Statements

Prevention: Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.

Response: IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
------------------------	------------	-------------

Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	30 - 60
Talc	14807-96-6	30 - 60
Bisphenol-F Epichlorohydrin resin	9003-36-5	10 - 30
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	1 - 5
Titanium dioxide	13463-67-7	0.1 - 1
Quartz (SiO ₂) respirable particulates (RCS) ≥10%	14808-60-7	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	May decompose above 149°C (300°F). May polymerize above 260°C (500°F) in which case closed containers may rupture or explode. Fumes and vapors from thermal decompositions vary in composition and toxicity. In case of fire, keep containers cool with water spray.
Hazardous combustion products:	Oxides of carbon. Phenolics. Acids. Aldehydes. Formaldehyde. Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.

Storage: Store in original container until ready to use. Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Protect from direct sunlight. Store away from heat, sparks, flames, or other sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None
Talc	2 mg/m ³ TWA Respirable fraction.	0.1 mg/m ³ TWA Respirable. 20 MPPCF TWA 2.4 MPPCF TWA Respirable.	None	50 ppm
Bisphenol-F Epichlorohydrin resin	None	None	None	None
Siloxanes and Silicones, di-Me, reaction products with silica	10 mg/m ³ TWA Inhalable dust. 3 mg/m ³ TWA Respirable fraction.	15 mg/m ³ TWA Total dust. 5 mg/m ³ TWA Respirable fraction.	None	None
Titanium dioxide	10 mg/m ³ TWA	15 mg/m ³ PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m ³ TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m ³ TWA Respirable fraction.	None	None
Quartz (SiO ₂) respirable particulates (RCS) >=10%	0.025 mg/m ³ TWA Respirable fraction.	0.05 mg/m ³ TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m ³ OSHA_ACT (Respirable dust.) 0.05 mg/m ³ PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m ³ TWA Respirable.	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Viscous, Liquid
Color: Off white
Odor: Mild
Odor threshold: Not available.

pH:	Not available.
Vapor pressure:	Nil
Boiling point/range:	> 260 °C (> 500°F)
Melting point/ range:	Not available.
Vapor density:	Not available.
Flash point:	> 93 °C (> 199.4 °F) Setaflash Closed Cup
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	< 1 %; < 10 g/l Estimated
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Reaction with some curing agents may produce an exothermic reaction which in large masses could cause runaway polymerization.
Hazardous decomposition products:	Oxides of carbon. Phenolics. Acids. Aldehydes. Formaldehyde. Irritating vapors.
Incompatible materials:	Acids. Bases. Oxidizing agents. Amines.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials. Protect from direct sunlight. Note: Heating the epoxy resin in this product above 148.9 °C (300 °F) in the presence of air may cause slow oxidative decomposition. Above 260 °C (500 °F) polymerization of the epoxy resin may occur. Aliphatic polyamines can produce exothermic reactions with epoxy resins which in large masses can cause runaway polymerization and charring of the reactants. Fumes and vapors from these thermal and chemical decompositions vary widely in composition and toxicity. Do not breathe fumes.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapors or mists of the product may be irritating to the respiratory system. May cause irritation to nose and throat. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.
Skin contact:	Causes skin irritation. May cause allergic skin reaction. Itching. Redness.
Eye contact:	Causes serious eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	Allergen, Irritant
Talc	None	Irritant, Lung, Some evidence of carcinogenicity
Bisphenol-F Epichlorhydrin resin	None	Allergen, Irritant
Siloxanes and Silicones, di-Me, reaction products with silica	None	No Data
Titanium dioxide	Inhalation LC50 (Rat, 4 h) = > 2.28 mg/l Inhalation LC50 (Rat, 4 h) = > 6.82 mg/l Inhalation LC50 (Rat, 4 h) = > 3.56 mg/l	Irritant, Respiratory, Some evidence of carcinogenicity
Quartz (SiO ₂) respirable particulates (RCS) >=10%	None	No Data

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No
Talc	No	No	No
Bisphenol-F Epichlorhydrin resin	No	No	No
Siloxanes and Silicones, di-Me, reaction products with silica	No	No	No
Titanium dioxide	No	Group 2B	No
Quartz (SiO ₂) respirable particulates (RCS) >=10%	Known To Be Human Carcinogen.	Group 1	Yes

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorhydrin resin)
Hazard class or division:	9
Identification number:	UN 3082
Packing group:	III

Water Transportation (IMO/IMDG)**Proper shipping name:**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorhydrin resin)

Hazard class or division:

9

Identification number:

UN 3082

Packing group:

III

Marine pollutant:

Bisphenol-A Epichlorhydrin resin

15. REGULATORY INFORMATION**United States Regulatory Information****TSCA 8 (b) Inventory Status:** All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.**TSCA 12 (b) Export Notification:** None above reporting de minimis**CERCLA/SARA Section 302 EHS:** None above reporting de minimis.**CERCLA/SARA Section 311/312:** Immediate Health**CERCLA/SARA Section 313:** None above reporting de minimis.**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.**Canada Regulatory Information****CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.**16. OTHER INFORMATION****This safety data sheet contains changes from the previous version in sections: 3,8,11,13****Prepared by:** Product Safety and Regulatory Affairs**Issue date:** 12/10/2020

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.