## Safety Data Sheet



**Revision Number: 006.0** Issue date: 10/25/2023

## PRODUCT AND COMPANY IDENTIFICATION

**LOCTITE 567 TB 50ML EN** IDH number: Product name: Product type/use: Adhesive/Sealant Item number: 2087067 Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

Region: **United States** 

Contact information: Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

| EMERGENCY OVERVIEW                   |  |  |  |
|--------------------------------------|--|--|--|
| MAY CAUSE AN ALLERGIC SKIN REACTION. |  |  |  |
| ١                                    |  |  |  |

| HAZARD CLASS       | HAZARD CATEGORY |
|--------------------|-----------------|
| SKIN SENSITIZATION | 1               |

## PICTOGRAM(S)



#### **Precautionary Statements**

Avoid breathing vapors, mist, or spray. Contaminated work clothing should not be allowed out Prevention:

of the workplace. Wear protective gloves.

Response: IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention.

Wash contaminated clothing before reuse.

Storage: Not prescribed

Dispose of contents and/or container according to Federal, State/Provincial and local Disposal:

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### **COMPOSITION / INFORMATION ON INGREDIENTS**

| Hazardous Component(s)                 | CAS Number  | Percentage* |  |
|--|-------------|-------------|--|
| 3,3,5 Trimethylcyclohexyl methacrylate | 7779-31-9   | 10 - 30     |  |
| Ethene, tetrafluoro-, homopolymer      | 9002-84-0   | 5 - 10      |  |
| Ethene, homopolymer                    | 9002-88-4   | 5 - 10      |  |
| Titanium dioxide                       | 13463-67-7  | 1 - 5       |  |
| Silica, amorphous, fumed, crystal-free | 112945-52-5 | 1 - 5       |  |
| Propane-1,2-diol                       | 57-55-6     | 1 - 5       |  |
| Cumene hydroperoxide                   | 80-15-9     | 0.1 - 1     |  |

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If not

breathing, give artificial respiration. If breathing is difficult, give oxygen. If

symptoms develop and persist, get medical attention.

Skin contact: IF ON SKIN: Wash with plenty of soap and water. If skin irritation persists, call

a physician.

Eye contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If eye irritation persists, consult a specialist.

**Ingestion:** DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical

attention.

Symptoms: See Section 11.

## 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Uncontrolled polymerization may occur at high temperatures resulting in

explosions or rupture of storage containers.

Hazardous combustion products: Oxides of carbon and nitrogen, aldehydes, acids and undetermined organics.

Toxic fluorine compounds. Ketones.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to

prevent entry into water system; wear full protective equipment during cleanup. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure

Controls / Personal Protection" prior to clean up.

# 7. HANDLING AND STORAGE

**Handling:** Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed. Refer to Section 8.

**Storage:** Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use. Store frost-free.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)                 | ACGIH TLV   | OSHA PEL   | AIHA WEEL                        | OTHER   |
|--|---|--|----------------------------------|---|
| 3,3,5 Trimethylcyclohexyl methacrylate | None  | None   | None                             | None  |
| Ethene, tetrafluoro-, homopolymer      | None  | None   | None                             | 10 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. |
| Ethene, homopolymer                    | 10 mg/m3 TWA<br>Inhalable particles.<br>3 mg/m3 TWA<br>Respirable particles.  | 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. | None                             | None  |
| Titanium dioxide                       | 0.2 mg/m3 TWA Respirable nanoscale particles 2.5 mg/m3 TWA Respirable finescale particles   | 15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction.                                  | None                             | None  |
| Silica, amorphous, fumed, crystal-free | 10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles. | 20 MPPCF TWA 0.8 mg/m3 TWA 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.                                | None                             | None  |
| Propane-1,2-diol                       | None  | None   | 10 mg/m3 TWA<br>Aerosol.         | None  |
| Cumene hydroperoxide                   | None  | None   | 1 ppm (6 mg/m3)<br>TWA<br>(SKIN) | None  |

**Engineering controls:** Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Use NIOSH approved respirator if there is potential to exceed exposure Respiratory protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety Eye/face protection:

showers and eye wash stations should be available.

Use chemical resistant, impermeable clothing including gloves and either an Skin protection:

apron or body suit to prevent skin contact. Neoprene gloves.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste, Liquid Color: Off white Mild Odor: Odor threshold: Not available.

pH: Not applicable, Product is non-polar/aprotic.

. Vapor pressure: < 0.30 mbar (20 °C (68°F))

Boiling point/range: > 150 °C (> 302°F)no method / method unknown

Not applicable, Product is a liquid Melting point/ range:

Product name: LOCTITE 567 TB 50ML EN IDH number: 2087067

Specific gravity:

Vapor density:

Flash point:

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

1.15

> 1 20 °C

> 100 °C (> 212°F)

Not available.

Not available.

Not available.

**Flammability**: The product is not flammable.

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

Not available.

Not available.

 VOC content:
 0.13 % (ASTM D5403)

 Viscosity:
 300,000 - 800,000 mPa.s

**Decomposition temperature:** Not available.

## 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing. Polymerization may occur at elevated temperature or in the

presence of incompatible materials.

Hazardous decomposition

products:

Oxides of carbon and nitrogen, aldehydes, acids and undetermined organics. Toxic fluorine

compounds. Ketones.

Incompatible materials: Strong oxidizing agents. Strong reducing agents. Free radical initiators. Inert gases. Oxygen

scavengers.

Reactivity: Not available.

Conditions to avoid: Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from

incompatible materials.

### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

**Inhalation:** Inhalation of vapors or mists of the product may be irritating to the respiratory system.

**Skin contact:** Causes skin irritation. May cause allergic skin reaction.

**Eye contact:** Causes serious eye irritation.

**Ingestion:** May cause gastrointestinal tract irritation if swallowed.

| Hazardous Component(s)                 | LD50s and LC50s  | Immediate and Delayed Health Effects                           |  |
|--|--|--|--|
| 3,3,5 Trimethylcyclohexyl methacrylate | None   | No Records   |  |
| Ethene, tetrafluoro-, homopolymer      | None   | No Target Organs   |  |
| Ethene, homopolymer                    | None   | No Target Organs   |  |
| Titanium dioxide                       | Inhalation LC50 (Rat, 4 h) = > 6.82 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 2.28 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 3.56 mg/l | Irritant, Respiratory, Some evidence of carcinogenicity        |  |
| Silica, amorphous, fumed, crystal-free | None   | Nuisance dust  |  |
| Propane-1,2-diol                       | Oral LD50 (Rabbit) = 18 g/kg<br>Oral LD50 (Mouse) = 23.9 g/kg<br>Oral LD50 (Rat) = 30 g/kg                                       | Irritant   |  |
| Cumene hydroperoxide                   | None   | Allergen, Central nervous system, Corrosive, Irritant, Mutagen |  |

| Hazardous Component(s)                 | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--|----------------|-----------------|--|
| 3,3,5 Trimethylcyclohexyl methacrylate | No             | No              | No                                       |
| Ethene, tetrafluoro-, homopolymer      | No             | No              | No                                       |
| Ethene, homopolymer                    | No             | No              | No                                       |
| Titanium dioxide                       | No             | Group 2B        | No                                       |
| Silica, amorphous, fumed, crystal-free | No             | No              | No                                       |
| Propane-1,2-diol                       | No             | No              | No                                       |
| Cumene hydroperoxide                   | No             | No              | No                                       |

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: RQ, Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division: 9
Identification number: UN 3082

Packing group: III

DOT Hazardous Substance(s): alpha,alpha-Dimethylbenzylhydroperoxide

International Air Transportation (ICAO/IATA)

**Proper shipping name:** RQ, Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division: 9
Identification number: UN 3082
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard class or division: 9
Identification number: UN 3082
Packing group: III

## 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.
Immediate Health, Delayed Health
None above reporting de minimis.

CERCLA Reportable quantity: Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other

components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

Please contact Regulatory Affairs for additional details.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3,8,11

Prepared by: Product Safety and Regulatory Affairs

**Issue date:** 10/25/2023

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.