

Revision Number: 002.6 Issue date: 08/30/2018

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE EA 9203 GAL AERO known

as HYSOL EA 9203 GAL

**Product type:** Preparation for adhesive bonding in the

aerospace industry

Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way Rocky Hill, Connecticut 06067 **IDH number:** 549888

Item number: PR9014018

Region: United States

**Contact information:** 

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC

1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOR.

CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.
MAY CAUSE DROWSINESS OR DIZZINESS.

CAUSES DAMAGE TO ORGANS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

## PICTOGRAM(S)



#### **Precautionary Statements**

IDH number: 549888

Prevention:

Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.

Response: If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim

to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed: Call a poison center or physician. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry

chemical or carbon dioxide to extinguish.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Ethanol	64-17-5	80 - 90	
Methanol	67-56-1	1 - 5	
Ethyl acetate	141-78-6	0.1 - 1	
Methyl isobutyl ketone	108-10-1	0.1 - 1	
N-(3- (Trimethoxysilyl)propyl)ethylenediamir	ne 1760-24-3	0.1 - 1	

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If symptoms

develop and persist, get medical attention.

**Skin contact:** Remove contaminated clothing and footwear. Immediately wash skin

thoroughly with soap and water. If symptoms develop and persist, get medical

attention.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

**Ingestion:** Get immediate medical attention. Do not induce vomiting.

Symptoms: See Section 11.

IDH number: 549888

Notes to physician: Treat symptomatically and supportively.

## 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: Vapors may travel considerable distance to source of ignition and flash back.

May liberate large quantities of dense, foul-smelling smoke which may contain

unidentified toxic gasses.

Hazardous combustion products:

IDH number: 549888

Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons. Oxides of nitrogen.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Do not allow product to

enter sewer or waterways.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

### 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do

not take internally. Avoid breathing vapors or mists of this product. Remove all sources of ignition. Do not cut, grind, weld, or drill on or near this container.

Storage: For safe storage, store between 0 °C (32°F) and 25 °C (77°F)

Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Ethanol	1,000 ppm STEL	1,000 ppm (1,900 mg/m3) PEL	None	None
Methanol	200 ppm TWA (SKIN) 250 ppm STEL	200 ppm (260 mg/m3) PEL	None	None
Ethyl acetate	400 ppm TWA	400 ppm (1,400 mg/m3) PEL	None	None
Methyl isobutyl ketone	20 ppm TWA 75 ppm STEL	100 ppm (410 mg/m3) PEL	None	None
N-(3- (Trimethoxysilyl)propyl)ethylenediamine	None	None	None	None

Engineering controls: Use local ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of

vapor/mist/fume/dust, appropriate NIOSH/MSHA respiratory protection must

be provided.

**Eye/face protection:** Wear chemical goggles; face shield (if splashing is possible).

Skin protection: Wear impervious gloves for prolonged contact. Use of impervious apron and

boots are recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:BlueOdor:AlcoholOdor threshold:Not available.pH:Not determined

 Vapor pressure:
 44.6 mm hg (20 °C (68°F))

 Boiling point/range:
 78 °C (172.4 °F)1,013 hPa

Melting point/ range: Not available.

Specific gravity: 0.8

Vapor density:

Flash point:

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

3.3 %

Flammable/Explosive limits - upper:

31 %

Autoignition temperature:

Flammability:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

Not determined

Not applicable

Soluble

Not available.

VOC content: 757.49 g/l per SCAQMD Rule 1124 [EPA Test Method 24/304-91] (estimated)

Viscosity: Not available.

Decomposition temperature: Not available.

## 10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 549888

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons. Oxides of nitrogen.

Incompatible materials: Keep away from strong oxidizing agents, strong Lewis or mineral acids.

Reactivity: Not available.

Conditions to avoid: Heat, flames, sparks and other sources of ignition.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

#### Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors or mists of the product may be irritating to the respiratory system. Vapors

may cause headaches, nausea, dizziness and respiratory tract irritation.

Skin contact: May cause severe irritation due to defatting of skin. May cause allergic skin reaction. May be

harmful if absorbed through skin.

Eve contact: Vapors may irritate eyes. Contact with eyes will cause irritation.

Ingestion: Not expected under normal conditions of use. May be harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Ethanol	Oral LD50 (Rat) = 9.9 g/kg Oral LD50 (Rat) = 6.2 g/kg Oral LD50 (Rat) = 17.8 g/kg Oral LD50 (Rat) = 11.5 g/kg Oral LD50 (Mouse) = 3,450 mg/kg Oral LD50 (Rat) = 10.6 g/kg Oral LD50 (Rat) = 7,060 mg/kg	Central nervous system, Irritant	
Methanol	Oral LD50 (Rat) = 5,628 mg/kg Oral LD50 (Mouse) = 7,300 mg/kg Oral LD50 (Rabbit) = 14.4 g/kg Dermal LD50 (Rabbit) = 15,800 mg/kg	Eyes, Irritant, Metabolic, Nervous System	
Ethyl acetate	Oral LD50 (Rat) = 5.6 g/kg Oral LD50 (Mouse) = 0.44 g/kg	Blood, Central nervous system, Irritant	
Methyl isobutyl ketone	Oral LD50 (Rat) = 2,080 mg/kg Dermal LD50 (Rabbit) = > 16,000 mg/kg	Irritant, Central nervous system	
N-(3- (Trimethoxysilyl)propyl)ethylenediamine	None	Irritant, Allergen	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Ethanol	No	No	No
Methanol	No	No	No
Ethyl acetate	No	No	No
Methyl isobutyl ketone	No	Group 2B	No
N-(3- (Trimethoxysilyl)propyl)ethylenediamine	No	No	No

# 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

# 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

If discarded, this product is considered a RCRA ignitable waste, D001. Hazardous waste number:

#### TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Ethanol solutions

Hazard class or division: Identification number:

UN 1170

Packing group:

International Air Transportation (ICAO/IATA)

Proper shipping name: Ethanol solution

Hazard class or division: 3

Identification number: UN 1170

Packing group:

Proper shipping name: ETHANOL SOLUTION

Hazard class or division: 3

Identification number: UN 1170

Packing group:

### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

Water Transportation (IMO/IMDG)

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313: None above reporting de minimis. Immediate Health, Delayed Health, Fire

This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Methanol (CAS# 67-56-1).

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

IDH number: 549888

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other

components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

Please contact Regulatory Affairs for additional details.

#### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Regulatory Affairs

**Issue date:** 08/30/2018

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.