

Revision Number: 003.0 Issue date: 04/10/2018

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name: LOCTITE SI 5056 LIGHT CURE** 

SILICONE known as LOCTITE®

5056™ LIGHT CURE ADHE

Product type: Silicone Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

IDH number: 1214249

1214249 Item number: Region: **United States** 

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC

1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

DANGER: COMBUSTIBLE LIQUID.

CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE DAMAGE.

| HAZARD CLASS       | HAZARD CATEGORY |
|--------------------|-----------------|
| FLAMMABLE LIQUID   | 4               |
| SKIN IRRITATION    | 2               |
| SERIOUS EYE DAMAGE | 1               |
| SKIN SENSITIZATION | 1               |





#### **Precautionary Statements**

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Avoid breathing vapors,

mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face

protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing. In case of fire: Use foam,

dry chemical or carbon dioxide to extinguish.

Store in a well-ventilated place. Keep cool. Storage:

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

IDH number: 1214249 Product name: LOCTITE SI 5056 LIGHT CURE SILICONE known as LOCTITE® 5056™ LIGHT CURE

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* |
|------------------------|------------|-------------|
| Isobornyl acrylate     | 5888-33-5  | 30 - 40     |
| N,N-Dimethylacrylamide | 2680-03-7  | 1 - 5       |

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). If symptoms develop and persist, get

medical attention. Wash clothing before reuse.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least

15 minutes, holding eyelids open all the time. Get medical attention.

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious

person. Get medical attention.

Symptoms: See Section 11.

# 5. FIRE FIGHTING MEASURES

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

**Unusual fire or explosion hazards:** In case of fire, keep containers cool with water spray.

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Hydrocarbons. Irritating organic

vapours. Oxides of silicon. Formaldehyde.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to

prevent entry into water system; wear full protective equipment during cleanup. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a

closed container until ready for disposal.

## 7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation. Keep

container closed.

For safe storage, store between 10 °C (50°F) and 32 °C (89.6 °F) Storage:

Keep containers closed when not in use.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER  |
|------------------------|-----------|----------|-----------|--|
| Isobornyl acrylate     | None      | None     | None      | None   |
| N,N-Dimethylacrylamide | None      | None     | None      | 0.1 mg/m3 TWA<br>(Skin)<br>0.025 ppm TWA<br>(Skin) |

**Engineering controls:** Use local ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

Respiratory protection: Use a NIOSH approved supplied air respirator if the potential to exceed

established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Neoprene, Butyl-rubber, or nitrile-

rubber gloves.

1 Approximately

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Transparent, Light yellow Color:

Odor: Slight, Acrylate Odor threshold: Not available. Not available. pH:

Vapor pressure: < 5 mm hg (20 °C (68°F)) Boiling point/range: > 93 °C (> 199.4 °F) Melting point/ range: Not available.

Vapor density:

Specific gravity:

> 1 Flash point: 82 °C (179.6 °F) Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flammability: Not applicable Evaporation rate: Not available.

Solubility in water: Slight Not available. Partition coefficient (n-octanol/water):

**VOC** content: 0.62 %; 6.2 g/l ASTM D5403 Process volatiles

1.46 %; 14.6 g/l (potential) 2.08 %; 20.8 g/l (total)

Viscosity: Not available. **Decomposition temperature:** Not available.

IDH number: 1214249 Product name: LOCTITE SI 5056 LIGHT CURE SILICONE known as LOCTITE® 5056™ LIGHT CURE ADHE

# 10. STABILITY AND REACTIVITY

**Stability**: Stable under normal conditions of storage and use.

**Hazardous reactions:** Polymerization may occur at elevated temperatures or upon depletion of inhibitor.

Hazardous decomposition

products:

IDH number: 1214249

Oxides of carbon. Oxides of nitrogen. Hydrocarbons. Irritating organic vapours. Oxides of

silicon. Formaldehyde.

Incompatible materials: Strong oxidizing agents. Strong acids and strong bases. Peroxides.

Reactivity: Not available.

Conditions to avoid: High temperatures.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

**Inhalation:** Modified acrylamide is harmful if inhaled. Inhalation of mist or spray may cause irritation of the

respiratory tract and nasal passages. When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor

concentrations below the OSHA permissible limit.

**Skin contact:** Causes skin irritation. May cause allergic skin reaction.

**Eye contact:** Causes serious eye damage.

Ingestion: Modified acrylamide is harmful if swallowed. May cause gastrointestinal tract irritation if

swallowed.

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects                               |
|------------------------|-----------------|--|
| Isobornyl acrylate     | None            | Irritant, Allergen   |
| N,N-Dimethylacrylamide | None            | Irritant, Eyes, Mutagen, Kidney, Less weight gain and food intake. |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|------------------------|----------------|-----------------|--|
| Isobornyl acrylate     | No             | No              | No                                       |
| N.N-Dimethylacrylamide | No             | No              | No                                       |

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

#### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D001: Ignitable.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Combustible liquid, n.o.s. (Modified Acrylamide) (Up to 450 I max per inner/primary

package when shipped as originally packed)

Hazard class or division: Combustible Liquid

Identification number: NA 1993 Packing group: III

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Isobornyl acrylate) (Up to 450

I max per inner/primary package when shipped as originally packed)

Hazard class or division: 9

Identification number: UN 3082 Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl

acrylate) (Up to 450 I max per inner/primary package when shipped as originally

packed)

Hazard class or division: 9
Identification number: UN 3082

Packing group:

Marine pollutant: Isobornyl acrylate

#### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.
None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2, 11

IDH number: 1214249 Product name: LOCTITE SI 5056 LIGHT CURE SILICONE known as LOCTITE® 5056™ LIGHT CURE ADHE

Prepared by: Product Safety and Regulatory Affairs

**Issue date:** 04/10/2018

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 1214249 Product name: LOCTITE SI 5056 LIGHT CURE SILICONE known as LOCTITE® 5056™ LIGHT CURE