

**CAMIE-CAMPBELL, INC.** Aerosol and Bulk Industrial Specialty Chemicals



9225 Watson Industrial Park St. Louis, MO 63126-1581 314-968-3222 800-325-9572 fax: 314-968-0741 E-mail: camie@camie.com www.camie.com

## **CAMIE A1000 PRODUCT DATA SHEET**

Camie A1000 Dry Lubricant Release Agent is a white, tetrafluoroethylene telomer dispersion that imparts a fine, dry film and produces a slick, friction-free surface with excellent lubricity and antistatic properties. The film is chemically stable, insoluble in water and solvents, non-flammable and thermally stable. These properties make it an excellent dry film lubricant for leather, plastics, elastomers, cord, twine, rope and cable. It reduces friction on metal, saw blades, guides, threaded connections and connectors.

Applications	Camie A1000 is an excellent release agent for molded rubber parts, molded plastics, gaskets, pressure-sensitive labels, thermoplastic rubber, paint, spray booths and provides no interfer- ence with post decorating.
Container Size	20 Fluid Ounce Can
Product Description	Dry Lubricant Release Agent
Net Weight	13 Ounces
Cans Per Case	12
Case Dimensions - Inches	11.75" L X 8.75" W X 10.5" H
Case Weight	14 Pounds
Cases Per Pallet	72
Appearance	Dry Translucent White Film
Odor	Mild solvent when wet / Odorless when dry
Solvent System	Acetone, IPA
Propellant	Hydrocarbon
Heat Resistance	-65° F - 450°F
Solids	1%
Spray Pattern	Conical Mist
VOC%	48.8
VOC Compliant for CA & OTC	Yes
NSF Registered	No
Aerosol Flammability Level	Level 3 Aerosols
Warranty Period	One Year from date of shipment
DOT Proper Shipping Name	Consumer Commodity ORM-D for do- mestic ground shipment. (See MSDS for additional shipping information)



In as much as CAMIE-CAMPBELL, INC. has no control over the use to which others may put the material, it does not guarantee that the same results described herein will be obtained. Each user should make his own tests to determine the material's suitability for his own particular use.