



Revision Number: 004.1

Issue date: 08/22/2023

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product name:</b>	<b>LOCTITE EA E-4100 known as LOCTITE E-4100 5KG CAN</b>	<b>IDH number:</b>	1215344
<b>Product type/use:</b>	Epoxy resin	<b>Item number:</b>	1215344
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	United States
<b>Company address:</b>	Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067	<b>Contact information:</b>	Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

**2. HAZARDS IDENTIFICATION**

EMERGENCY OVERVIEW	
<b>WARNING:</b>	CAUSES SKIN IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION. SUSPECTED OF CAUSING CANCER.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
CARCINOGENICITY	2

PICTOGRAM(S)

**Precautionary Statements**

<b>Prevention:</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.
<b>Response:</b>	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
<b>Storage:</b>	Store locked up.
<b>Disposal:</b>	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Hazardous Component(s)	CAS Number	Percentage*
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	30 - 60

Limestone	1317-65-3	10 - 30
Aluminum	7429-90-5	5 - 10
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	1 - 5
Modified epoxy resin	Proprietary	1 - 5
Epoxy resin	Proprietary	1 - 5
Diuron	330-54-1	0.1 - 1
Quartz (SiO <sub>2</sub> ), <1% respirable	14808-60-7	0 - 0.1

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
<b>Skin contact:</b>	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention. Wash clothing before reuse.
<b>Eye contact:</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Ingestion:</b>	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
<b>Symptoms:</b>	See Section 11.

## 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Water spray (fog), foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
<b>Unusual fire or explosion hazards:</b>	In case of fire, keep containers cool with water spray. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
<b>Hazardous combustion products:</b>	Oxides of carbon. Irritating organic fragments. Aldehydes. Acids.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not allow product to enter sewer or waterways.
<b>Clean-up methods:</b>	Remove all sources of ignition. Immediately contact emergency personnel. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Clean residue with soap and water. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.
<b>Storage:</b>	Store in original container until ready to use. Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None
Limestone	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Aluminum	1 mg/m3 TWA Respirable fraction.	15 mg/m3 PEL (as Al) Total dust. 5 mg/m3 PEL (as Al) Respirable fraction. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Siloxanes and Silicones, di-Me, reaction products with silica	None	None	None	None
Modified epoxy resin	None	None	None	None
Epoxy resin	None	None	None	None
Diuron	10 mg/m3 TWA	None	None	None
Quartz (SiO <sub>2</sub> ), <1% respirable	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None

<b>Engineering controls:</b>	Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.
<b>Respiratory protection:</b>	Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.
<b>Eye/face protection:</b>	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.
<b>Skin protection:</b>	Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid
<b>Color:</b>	Gray
<b>Odor:</b>	Negligible
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not applicable
<b>Vapor pressure:</b>	Negligible vapor pressure at ambient temperatures.

<b>Boiling point/range:</b>	Not determined
<b>Melting point/ range:</b>	Not available.
<b>Specific gravity:</b>	1.3
<b>Vapor density:</b>	Not available.
<b>Flash point:</b>	> 93.33 °C (> 199.99 °F) Setaflash Closed Cup
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Autoignition temperature:</b>	Not available.
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	Not available.
<b>Solubility in water:</b>	Insoluble
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	0 %; 0 g/l
<b>Viscosity:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of storage and use.
<b>Hazardous reactions:</b>	None under normal processing.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Irritating organic fragments. Acids. Aldehydes.
<b>Incompatible materials:</b>	Strong acids. Strong bases. Strong oxidizing agents. Amines. Water.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Store away from incompatible materials. Elevated temperatures. Heat, flames, sparks and other sources of ignition.

## 11. TOXICOLOGICAL INFORMATION

<b>Relevant routes of exposure:</b>	Skin, Inhalation, Eyes
-------------------------------------	------------------------

### Potential Health Effects/Symptoms

**Inhalation:** May cause irritation to nose and throat. Mild respiratory tract irritation. Coughing.  
**Skin contact:** Allergic skin reaction. Itching. Redness. Moderate skin irritation.  
**Eye contact:** Moderate eye irritation. Redness.  
**Ingestion:** Not expected to be harmful by ingestion.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	Allergen, Irritant
Limestone	None	Nuisance dust
Aluminum	Inhalation LC50 (Rat, 4 h) = > 0.888 mg/l Inhalation LC50 (Rat, 4 h) = > 2.3 mg/l	Central nervous system, Irritant, Lung
Siloxanes and Silicones, di-Me, reaction products with silica	None	No Data
Modified epoxy resin	None	Irritant, Allergen
Epoxy resin	None	Irritant, Allergen
Diuron	Oral LD50 (Rat) = 3,400 mg/kg Oral LD50 (Rat) = 1,017 mg/kg Inhalation LC50 (Rat, 4 h) = > 223 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5.05 mg/l	Irritant, Developmental, Liver
Quartz (SiO <sub>2</sub> ), <1% respirable	None	Immune system, Lung, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No
Limestone	No	No	No
Aluminum	No	No	No
Siloxanes and Silicones, di-Me, reaction products with silica	No	No	No
Modified epoxy resin	No	No	No
Epoxy resin	No	No	No
Diuron	No	No	No
Quartz (SiO <sub>2</sub> ), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Not regulated (Up to 5 gallons max per inner/primary package when shipped as originally packaged only)  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** RQ, Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorohydrin resin) (Up to 5 gallons max per inner/primary package when shipped as originally packaged only)  
**Hazard class or division:** 9  
**Identification number:** UN 3082  
**Packing group:** III

**Water Transportation (IMO/IMDG)****Proper shipping name:**RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Bisphenol-A Epichlorhydrin resin) (Up to 5 gallons max per inner/primary package when shipped as originally packaged only)**Hazard class or division:**

9

**Identification number:**

UN 3082

**Packing group:**

III

**Marine pollutant:**

Bisphenol-A Epichlorhydrin resin

**15. REGULATORY INFORMATION****United States Regulatory Information****TSCA 8 (b) Inventory Status:**

All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

**TSCA 12 (b) Export Notification:**

None above reporting de minimis

**CERCLA/SARA Section 302 EHS:**

None above reporting de minimis.

**CERCLA/SARA Section 311/312:**

Immediate Health, Delayed Health

**CERCLA/SARA Section 313:**

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Aluminum (CAS# 7429-90-5).

**CERCLA Reportable quantity:**

Diuron (CAS# 330-54-1) 100 lbs. (45.4 kg)

**California Proposition 65:**

This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

**Canada Regulatory Information****CEPA DSL/NDSL Status:**

All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

**16. OTHER INFORMATION****This safety data sheet contains changes from the previous version in sections: 3, 8, 11****Prepared by:**

Product Safety and Regulatory Affairs

**Issue date:**

08/22/2023

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.