



Revision Number: 002.0

Issue date: 08/17/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE LB 8007 C5-A AE known as LOCTITE LB C5-A	IDH number:	1786073
Product type:	Antiseize	Item number:	1786073
Restriction of Use:	None identified	Region:	United States
Company address:	Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067	Contact information:	Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CONTENTS UNDER PRESSURE.
FLAMMABLE AEROSOL.
CAUSES SKIN IRRITATION.
CAUSES SERIOUS EYE DAMAGE.
MAY CAUSE DROWSINESS OR DIZZINESS.
CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL	2
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	1

PICTOGRAM(S)



Precautionary Statements

Prevention:

Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe mist or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection, and face protection.

Response:

IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if you feel unwell. If skin irritation occurs: Get medical attention. Take off contaminated clothing.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
n-Heptane	142-82-5	10 - 20
Acetone	67-64-1	10 - 20
Propane/Isobutane	68476-86-8	10 - 20
Copper	7440-50-8	10 - 20
Graphite	7782-42-5	10 - 20
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	5 - 10
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	5 - 10
Calcium dihydroxide	1305-62-0	1 - 5
Quartz (SiO ₂)	14808-60-7	1 - 5
Calcium dodecylbenzene sulfonate	26264-06-2	1 - 5

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If symptoms develop and persist, get medical attention.
Skin contact:	If symptoms develop and persist, get medical attention. Wash affected area immediately with soap and water.
Eye contact:	Get medical attention. Immediately flush eyes with plenty of water for at least 15 minutes.
Ingestion:	Do not induce vomiting: contains petroleum distillates and/or aromatic solvents. Aspiration may cause pulmonary edema and pneumonitis. Get immediate medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Water should be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat. Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. Do not puncture or incinerate pressurized containers.

Hazardous combustion products: Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Eliminate ignition sources including sources of electrical, static or frictional sparks. Wipe up with adsorbent material (e.g. cloth, fleece). Rinse spill area with water. Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling: Keep away from heat, spark and flame. Avoid contact with eyes, skin and clothing. Do not breathe gas/fumes/vapor/spray.

Storage: Keep in a cool, well ventilated area. Store away from heat, sparks, flames, or other sources of ignition. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
n-Heptane	400 ppm TWA 500 ppm STEL	500 ppm (2,000 mg/m ³) PEL	None	None
Acetone	250 ppm TWA 500 ppm STEL	1,000 ppm (2,400 mg/m ³) PEL	None	None
Propane/Isobutane	None	None	None	None
Copper	0.2 mg/m ³ TWA (as Cu) Fume. 1 mg/m ³ TWA (as Cu) Dust and mist.	1 mg/m ³ PEL (as Cu) Dust and mist. 0.1 mg/m ³ PEL (as Cu) Fume.	None	None
Graphite	2 mg/m ³ TWA Respirable fraction.	5 mg/m ³ PEL Respirable fraction. 15 mg/m ³ PEL Total dust. 15 MPPCF TWA	None	None
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m ³ TWA mist 10 mg/m ³ STEL mist Exposure by all routes should be carefully controlled to levels as low as possible. Included in the regulation but with no data values. See regulation for further details	5 mg/m ³ TWA mist 500 ppm (2,000 mg/m ³) PEL 5 mg/m ³ PEL Mist.	None	None
Distillates (petroleum), hydrotreated light naphthenic	Included in the regulation but with no data values. See regulation for further details Exposure by all routes should be carefully controlled to levels as low as possible.	5 mg/m ³ TWA mist 10 mg/m ³ TWA mist 5 mg/m ³ PEL Mist. 500 ppm (2,000 mg/m ³) PEL	None	None
Calcium dihydroxide	5 mg/m ³ TWA	5 mg/m ³ PEL Respirable fraction. 15 mg/m ³ PEL Total dust.	None	None
Quartz (SiO ₂)	0.025 mg/m ³ TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m ³ TWA Respirable. 0.05 mg/m ³ TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m ³ OSHA_ACT (Respirable dust.) 0.05 mg/m ³ PEL Respirable dust.	None	None
Calcium dodecylbenzene sulfonate	None	None	None	None

Engineering controls:

Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination.

Respiratory protection:	When workplace hazards warrant the use of a respirator, appropriate respirators must be used, and a program that follows 29 CFR 1910.134 must be followed.
Eyeface protection:	Safety goggles or safety glasses with side shields.
Skin protection:	Chemical resistant, impermeable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Aerosol, Liquid or paste
Color:	Copper
Odor:	Ketone
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Vapor density:	Not available.
Flash point:	< -17 °C (< 1.4 °F)
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Not available.
Partition coefficient (n-octanol/water):	Not available.
VOC content:	35.9 %
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	Not available.
Hazardous decomposition products:	Oxides of carbon.
Incompatible materials:	Oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Extremes of temperature and direct sunlight.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation: Vapor overexposure may cause drowsiness. Prolonged or excessive inhalation may cause respiratory tract irritation. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.

Skin contact: Causes skin irritation.

Eye contact: Causes serious eye damage.

Ingestion: May cause gastrointestinal tract irritation if swallowed. Central nervous system depression, including dizziness, drowsiness, fatigue, nausea, headache, unconsciousness.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
n-Heptane	Inhalation LC50 (Rat, 4 h) = 103 mg/l	Central nervous system, Irritant
Acetone	Oral LD50 (Mouse) = 5.2 g/kg Oral LD50 (Mouse) = 3,000 mg/kg Oral LD50 (Rabbit) = 5,340 mg/kg Oral LD50 (Rat) = 5,800 mg/kg Oral LD50 (Rat) = 9,800 mg/kg Dermal LD50 (Rabbit) = 20,000 mg/kg Inhalation LC50 (Rat, 4 h) = 76 mg/l	Central nervous system, Irritant
Propane/Isobutane	None	No Records
Copper	None	Allergen, Blood, Central nervous system, Developmental, Gastrointestinal, Immune system, Irritant, Kidney, Liver, Mutagen, Sensory, Skin
Graphite	None	Lung
Distillates (petroleum), hydrotreated heavy naphthenic	None	Irritant
Distillates (petroleum), hydrotreated light naphthenic	None	Irritant
Calcium dihydroxide	Oral LD50 (Rat) = 7,340 mg/kg	Irritant, Corrosive
Quartz (SiO ₂)	None	Immune system, Lung, Some evidence of carcinogenicity
Calcium dodecylbenzene sulfonate	None	Eyes, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
n-Heptane	No	No	No
Acetone	No	No	No
Propane/Isobutane	No	No	No
Copper	No	No	No
Graphite	No	No	No
Distillates (petroleum), hydrotreated heavy naphthenic	Known To Be Human Carcinogen.	Group 1	No
Distillates (petroleum), hydrotreated light naphthenic	Known To Be Human Carcinogen.	Group 1	No
Calcium dihydroxide	No	No	No
Quartz (SiO ₂)	Known To Be Human Carcinogen.	Group 1	Yes
Calcium dodecylbenzene sulfonate	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D001: Ignitable.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Aerosols
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None
Marine pollutant: Copper
DOT Hazardous Substance(s): Copper, Acetone

International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, flammable
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: AEROSOLS (Copper, n-Heptane)
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None
Marine pollutant: Copper, n-Heptane

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Fire, Pressure, Immediate Health, Delayed Health
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Copper (CAS# 7440-50-8).
CERCLA Reportable quantity: Copper (CAS# 7440-50-8) 5,000 lbs. (2,270 kg)
Calcium dodecylbenzene sulfonate (CAS# 26264-06-2) 1,000 lbs. (454 kg)
n-Heptane (CAS# 142-82-5) 100 lbs. (45.4 kg)
Acetone (CAS# 67-64-1) 5,000 lbs. (2,270 kg)
California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2, 11

Prepared by: Cara R. Rivera, Regulatory Affairs Specialist

Issue date: 08/17/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.