

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: Product Use/Class: LORD MAXLOK® T18 Acrylic Adhesive, Part 1 of 2

LORD Corporation 111 LORD Drive Cary, NC 27511-7923 USA

Telephone: 814 868-3180 Non-Transportation Emergency: 814 763-2345 Chemtrec 24 Hr Transportation Emergency No. 800 424-9300 (Outside Continental U.S. 703 527-3887)

**EFFECTIVE DATE:** 12/17/2024

## 2. HAZARDS IDENTIFICATION

#### **GHS CLASSIFICATION:**

Flammable liquids Category 2 Skin corrosion/irritation Category 1B Serious eye damage/eye irritation Category 1 Skin sensitization Category 1 Carcinogenicity Category 2 Specific target organ systemic toxicity (single exposure) Category 3 Specific target organ systemic toxicity (repeated exposure) Category 1 Respiratory system, Nervous System Hazardous to the aquatic environment - acute hazard Category 2 Hazardous to the aquatic environment - chronic hazard Category 2

#### GHS LABEL ELEMENTS: Symbol(s)



Signal Word DANGER

## Hazard statements

Highly flammable liquid and vapor. Causes severe skin burns and eye damage. Causes serious eye damage. May cause an allergic skin reaction. Suspected of causing cancer. May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure.(Respiratory system, Nervous System) Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

## **Precautionary statements**

#### Prevention

Keep away from heat, sparks, open flames, hot surfaces. - No smoking. Ground, bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves, protective clothing, eye protection, face protection.

Use personal protective equipment as required.

Do not breathe dust, fume, mist, vapors, spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

#### Response

In case of fire: refer to section 5 of SDS for extinguishing media.

Immediately call a POISON CENTER or doctor, physician.

Specific treatment (see supplemental first aid instructions on this label).

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF ON SKIN (or hair): Remove, take off immediately all contaminated clothing. Rinse skin with water, shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Wash contaminated clothing before reuse.

Collect spillage.

## Storage

Store in a well-ventilated place. Keep cool. Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

## **Disposal:**

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

## Other hazards:

#### This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).

Acute: Vapor harmful; may affect the brain or nervous system causing dizziness, headache or nausea. Possible irritation of the respiratory system can occur causing a variety of symptoms such as dryness of the throat, tightness of the chest, and shortness of breath. May cause central nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma. Harmful if absorbed through skin. May be harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

Chronic: No additional hazards determined for this product outside of the GHS classification.

## **3. COMPOSITION/INFORMATION ON INGREDIENTS**

| Hazardous ingredients above the thre | shold concentration |
|--------------------------------------|---------------------|
| Chaminal Nama                        | CAC Number          |

| Chemical Name                      | CAS Number  | Range       |
|------------------------------------|-------------|-------------|
| Methyl methacrylate                | 80-62-6     | 45 - 50 %   |
| Methacrylic acid                   | 79-41-4     | 1 - 5 %     |
| Methacrylate phosphate ester       | PROPRIETARY | 1 - 5 %     |
| Methacrylate monomer               | PROPRIETARY | 1 - 5 %     |
| 2-Propenoic acid, tetradecyl ester | 2549-53-3   | 1 - 5 %     |
| Methacrylate blend                 | PROPRIETARY | 0.1 - 0.9 % |
| N,N-Dimethylaniline                | 121-69-7    | 0.1 - 0.9 % |
| Methacrylate monomer               | PROPRIETARY | 0.1 - 0.9 % |
| Phenol                             | 108-95-2    | 0.1 - 0.9 % |

Any "PROPRIETARY" component(s) in the above table is considered trade secret, thus the specific chemical and its exact concentration is being withheld.

## 4. FIRST AID MEASURES

**FIRST AID - EYE CONTACT:** Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

**FIRST AID - SKIN CONTACT:** Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

**FIRST AID - INHALATION:** Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

**FIRST AID - INGESTION:** If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

# **5. FIRE-FIGHTING MEASURES**

SUITABLE EXTINGUISHING MEDIA: Carbon Dioxide, Dry chemical, Foam, Water fog UNSUITABLE EXTINGUISHING MEDIA: Do not use water jet as this may spread the fire.

**SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL:** Flammable liquid and vapor. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Keep container tightly closed. Isolate from heat, electrical equipment, sparks, open flame, and other sources of ignition. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

**SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS:** Wear full firefighting protective clothing, including self contained breathing apparatus. Water spray may be ineffective. If water is used, fog nozzles are preferable.

## 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:** Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid contact. Avoid breathing vapors. Use self-contained breathing equipment.

**ENVIRONMENTAL PRECAUTIONS:** Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

**METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP:** Keep non-essential personnel a safe distance away from the spill area. Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid breathing vapors. Use self-contained breathing equipment. Notify appropriate authorities if necessary. Before attempting cleanup, refer to hazard caution information in other sections of this safety data sheet. Contain and remove with inert absorbent material and non-sparking tools. Avoid contact.

# 7. HANDLING AND STORAGE

**HANDLING:** Keep closure tight and container upright to prevent leakage. Ground and bond containers when transferring material. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation. Because empty containers may retain product residue and flammable vapors, keep away from heat, sparks and flame; do not cut, puncture or weld on or near the empty container. Do not smoke where this product is used or stored.

**STORAGE:** Do not store or use near heat, sparks, or open flame. Store only in well-ventilated areas. Do not puncture, drag, or slide container. Keep container closed when not in use. Refer to OSHA 29CFR Part 1910.106 "Flammable and Combustible Liquids" for specific storage requirements.

| <u>Chemical Name</u>               | ACGIH TLV-<br>TWA | ACGIH TLV-<br>STEL | OSHA PEL-<br>TWA     | OSHA PEL-<br>CEILING | <u>Skin</u>    |
|------------------------------------|-------------------|--------------------|----------------------|----------------------|----------------|
| Methyl methacrylate                | 50 ppm            | 100 ppm            | 410 mg/m3<br>100 ppm | N.E.                 | Not applicable |
| Methacrylic acid                   | 20 ppm            | N.E.               | N.E.                 | N.E.                 | S              |
| Methacrylate phosphate ester       | N.E.              | N.E.               | N.E.                 | N.E.                 | Not applicable |
| Methacrylate monomer               | N.E.              | N.E.               | N.E.                 | N.E.                 | Not applicable |
| 2-Propenoic acid, tetradecyl ester | N.E.              | N.E.               | N.E.                 | N.E.                 | Not applicable |
| Methacrylate blend                 | N.E.              | N.E.               | N.E.                 | N.E.                 | Not applicable |
| N,N-Dimethylaniline                | 5 ppm             | 10 ppm             | 25 mg/m3<br>5 ppm    | N.E.                 | S              |
| Methacrylate monomer               | N.E.              | N.E.               | N.E.                 | N.E.                 | Not applicable |
| Phenol                             | 5 ppm             | N.E.               | 19 mg/m3<br>5 ppm    | N.E.                 | S              |

INCOMPATIBILITY: Strong acids, bases, and strong oxidizers.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

ENGINEERING CONTROLS: Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits. Caution: Solvent vapors are heavier than air and collect in lower levels of the work area. Sufficient ventilation (using explosion-proof equipment) should be provided to prevent flammable vapor/air mixtures from accumulating.

## PERSONAL PROTECTION MEASURES/EQUIPMENT:

Respiratory protection: Use a NIOSH approved chemical/mechanical filter respirator designed to remove a combination of particulates and organic vapor if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. For respirator use observe OSHA regulations (29CFR 1910.134) or use in accordance with applicable laws and regulations of your country or particular locality.

Skin protection: Use neoprene, nitrile, or rubber gloves to prevent skin contact. If contact with the product is prolonged or repeated, Silver Shield or Butyl rubber gloves are recommended.

Eye protection: Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

**Other protective equipment:** Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

Hygienic practices: Wash hands before eating, smoking, or using toilet facility. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Typical values, not to be used for specification purposes.

| Odor:                      | Sweet                  | Vapor Pressure:        | N.D.                     |
|----------------------------|------------------------|------------------------|--------------------------|
| Appearance:                | Off-white              | Vapor density:         | Heavier than Air         |
| Physical state:            | Paste                  | Lower explosion limit: | 1 %(V)                   |
| Flash point:               | 59 °F, 15 °C Setaflash | Upper explosive limit: | 8.8 %(V)                 |
|                            | Closed Cup             |                        |                          |
| <b>Boiling range:</b>      | > 35 °C                | Evaporation rate:      | Faster than n-butyl-     |
|                            |                        |                        | acetate.                 |
| Autoignition temperature:  | N.D.                   | Density:               | 1.04 g/cm3 (8.63 lb/gal) |
| Decomposition temperature: | N.D.                   | Viscosity, dynamic:    | ≥135,000 mPa.s @ 25 °C   |
| Odor threshold:            | N.D.                   | Viscosity, kinematic:  | ≥129,808 mm2/s @ 25      |
|                            |                        |                        |                          |

| Solubility in H2O:                     | Insoluble |
|--|-----------|
| pH:                                    | N.A.      |
| Freeze point:                          | N.D.      |
| Coefficient of water/oil distribution: | N.D.      |

Volatile by weight: Volatile by volume: VOC Calculated:

°C 0.04 % 0.04 % 0 lb/gal, 0 g/l

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

# 10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Hazardous polymerisation will not occur under normal conditions.

**STABILITY:** Product is stable under normal storage conditions.

CONDITIONS TO AVOID: High temperatures. Sources of ignition.

**INCOMPATIBILITY:** Strong acids, bases, and strong oxidizers.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Does not decompose when used and stored as recommended., Carbon monoxide, carbon dioxide.

## **11. TOXICOLOGICAL INFORMATION**

**EXPOSURE PATH:** Refer to section 2 of this SDS.

**SYMPTOMS:** Refer to section 2 of this SDS.

## **TOXICITY MEASURES:**

| Chemical Name                      | LD50/LC50   |  |
|------------------------------------|---|--|
| Methyl methacrylate                | Oral LD50: Rat 8,420 - 10,000 mg/kg                                     |  |
|                                    | Dermal LD50: Rabbit > 5 g/kg  |  |
|                                    | Dermal LD50: Rabbit 5,000 - 7,500 mg/kg                                 |  |
|                                    | GHS LC50 (vapour): Rat 29.8 mg/1 /4 h                                   |  |
| Methacrylic acid                   | Oral LD50: Rat 1,320 mg/kg  |  |
|                                    | Dermal LD50: Rabbit 500 - 1,000 mg/kg                                   |  |
|                                    | GHS LC50 (vapour): Acute toxicity point estimate 11 mg/l GHS LC50       |  |
|                                    | (dust and mist): Rat 7.1 mg/l /4 h                                      |  |
| Methacrylate phosphate ester       | Oral LD50: rat > 5,000 mg/kg  |  |
|                                    |   |  |
| Methacrylate monomer               | Oral LD50: Rat $> 5 \text{ g/kg}$                                       |  |
|                                    | Dermal LD50: Rabbit > 3,000 mg/kg                                       |  |
|                                    |   |  |
| 2-Propenoic acid, tetradecyl ester | Dermal LD50: Rabbit > 3,000 mg/kg                                       |  |
|                                    |   |  |
| Methacrylate blend                 | Oral LD50: rat > 5,000 mg/kg  |  |
|                                    | Dermal LD50: Rat > 2,000 mg/kg  |  |
|                                    | Inhalation LC50: Mouse 55 mg/l /3 h GHS LC50 (vapour): Rat 29.8 mg/l /4 |  |
|                                    | h   |  |
| N,N-Dimethylaniline                | Oral LD50: Rat 951 mg/kg  |  |
|                                    | Dermal LD50: Rabbit 1,770 mg/kg   |  |
|                                    | GHS LC50 (vapour): Acute toxicity point estimate 3.0 mg/l               |  |
| Methacrylate monomer               | Oral LD50: Rat 5,564 mg/kg  |  |
|                                    | Dermal LD50: Rabbit > 5,000 mg/kg                                       |  |
|                                    | 0 11D50 D (240 4  |  |
| Phenol                             | Oral LD50: Rat 340 mg/kg  |  |
|                                    | Oral LD50: Mouse 270 mg/kg  |  |
|                                    | Dermal LD50: Rabbit 630 mg/kg   |  |
| 1                                  | GHS LC50 (dust and mist): Acute toxicity point estimate 0.55 mg/l       |  |

Germ cell mutagenicity: No classification proposed

**Carcinogenicity:** Category 2 - Suspected of causing cancer.

Components contributing to classification: N,N-Dimethylaniline.

Reproductive toxicity: No classification proposed

# **12. ECOLOGICAL INFORMATION**

## **ECOTOXICITY:**

| Chemical Name                      | <u>Ecotoxicity</u>  |
|------------------------------------|---|
| Methyl methacrylate                | Fish:Oncorhynchus mykiss > 79 mg/l96 hOncorhynchus mykiss > 100 mg/l96 hInvertebrates:Daphnia magna 69 mg/l48 hPlants:Pseudokirchneriella subcapitata 170 mg/l96 hPseudokirchneriella subcapitata 110 mg/l72 h  |
| Methacrylic acid                   | <u>Fish:</u> Oncorhynchus mykiss 85 mg/l96 h flow-through<br><u>Invertebrates:</u> Daphnia magna > 130 mg/l48 h<br>Daphnia magna >= 53 mg/l21 d semi-static   |
| Methacrylate phosphate ester       | <u>Fish:</u> Oncorhynchus mykiss > 112 mg/l96 h Static  |
| Methacrylate monomer               | <u>Invertebrates:</u> Daphnia magna $\geq 5.73 \mu g/l21 d$ semi-static   |
| 2-Propenoic acid, tetradecyl ester | N.D.  |
| Methacrylate blend                 | <u>Fish:</u> Danio rerio 590 mg/196 h flow-through<br><u>Invertebrates:</u> Daphnia magna 37 mg/121 d semi-static   |
| N,N-Dimethylaniline                | Fish:Pimephales promelas 52.6 mg/l96 hPimephales promelas 65.6 mg/l96 hPoecilia reticulata 53.7 mg/l96 h semi-staticBrachydanio rerio 51.1 mg/l96 h semi-staticBrachydanio rerio 0.183 - 0.186 mg/l96 hInvertebrates:Daphnia magna 5 mg/l48 hPlants:Desmodesmus subspicatus 340 mg/l96 h  |
| Methacrylate monomer               | <u>Fish:</u> Pimephales promelas 213 - 242 mg/l96 h flow-through<br>Pimephales promelas 227 mg/l96 h<br>Oryzias latipes > 100 mg/l96 h<br><u>Invertebrates:</u> Daphnia magna 380 mg/l48 h<br>Daphnia magna 24.1 mg/l21 d Static  |
| Phenol                             | Fish:Pimephales promelas 20.5 - 25.6 mg/l96 hPimephales promelas 32 mg/l96 hOncorhynchus mykiss 5.449 - 6.789 mg/l96 hOncorhynchus mykiss 5.449 - 6.789 mg/l96 hOncorhynchus mykiss 7.5 - 14 mg/l96 hStaticOncorhynchus mykiss 4.23 - 7.49 mg/l96 hStaticLepomis macrochirus 13.5 mg/l96 hStaticLepomis macrochirus 11.9 - 25.3 mg/l96 hIcepomis macrochirus 11.9 - 25.3 mg/l96 hPoecilia reticulata 34.09 - 47.64 mg/l96 hStaticPoecilia reticulata 31 mg/l96 hSenchydanio rerio 27.8 mg/l96 hOryzias latipes 33.9 - 43.3 mg/l96 hOryzias latipes 23.4 - 36.6 mg/l96 hStaticPimephales promelas 11.9 - 50.5 mg/l96 hOncorhynchus mykiss 8.9 mg/l96 hInvertebrates:Daphnia magna 4.24 - 10.7 mg/l48 hStaticDaphnia dubia 0.0994 mg/l48 hPlants:Pseudokirchneriella subcapitata 46.42 mg/l96 hDesmodesmus subspicatus 187 - 279 mg/l72 hStatic |

PERSISTENCE AND DEGRADABILITY: Not determined for this product.

BIOACCUMULATIVE: Not determined for this product.

MOBILITY IN SOIL: Not determined for this product.

**OTHER ADVERSE EFFECTS:** Not determined for this product.

## **13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

## **14. TRANSPORT INFORMATION**

| <u>US DOT Road</u><br>Proper Shipping Name:<br>Hazard Class:<br>Secondary hazard:<br>UN/NA Number:<br>Packing group:<br>Emergency Response Guide Number: | Adhesives<br>3<br>None<br>1133<br>II<br>128      |
|--|--|
| IATA Cargo<br>Proper shipping name:<br>Hazard Class:<br>Hazard class:<br>UN number:<br>Packing group:<br>EmS:  | Adhesives<br>3<br>None<br>1133<br>II<br>3L       |
| <u>IMDG</u><br>Proper shipping name:<br>Hazard Class:<br>Hazard class:<br>UN number:<br>Packing group:<br>EmS:   | Adhesives<br>3<br>None<br>1133<br>II<br>F-E; S-D |

The listed transportation classification applies to non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. For the most accurate shipping information, refer to your transportation/compliance department.

## **15. REGULATORY INFORMATION**

## **U.S. FEDERAL REGULATIONS: AS FOLLOWS:**

## **SARA SECTION 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.:

| Chemical Name       | CAS Number | Weight percent less than |
|---------------------|------------|--------------------------|
| Methyl methacrylate | 80-62-6    | 50.0 %                   |
| N,N-Dimethylaniline | 121-69-7   | 0.9 %                    |
| Phenol              | 108-95-2   | 0.9 %                    |

## TOXIC SUBSTANCES CONTROL ACT:

#### **INVENTORY STATUS**

The chemical substances in this product are on the active TSCA Section 8 Inventory or exempt.

## **EXPORT NOTIFICATION**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None

## **16. OTHER INFORMATION**

Under HazCom 2012 it is optional to continue using the HMIS rating system. It is important to ensure employees have been trained to recognize the different numeric ratings associated with the HazCom 2012 and HMIS schemes.

HMIS RATINGS - HEALTH: 2\* FLAMMABILITY: 3 PHYSICAL HAZARD: 1
\* - Indicates a chronic hazard; see Section 2

Revision: Section 9, Section 11

**Effective Date:** 12/17/2024

## DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.