

# USA SAFETY DATA SHEET

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: LORD 7650
Product Use/Class: Adhesive

LORD Corporation 111 LORD Drive Cary, NC 27511-7923 USA

Telephone: 814 868-3180

Non-Transportation Emergency: 814 763-2345 Chemtrec 24 Hr Transportation Emergency No. 800 424-9300 (Outside Continental U.S. 703 527-3887)

EFFECTIVE DATE: 06/01/2021

# 2. HAZARDS IDENTIFICATION

#### **GHS CLASSIFICATION:**

Flammable liquids Category 2

Acute toxicity Inhalation - Dust and Mist Category 4 - 57.5% of the mixture consists of ingredient(s) of unknown toxicity.

Acute toxicity Inhalation - Vapours Category 4 - 57.5% of the mixture consists of ingredient(s) of unknown toxicity.

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Skin sensitization Category 1A

Respiratory sensitization Category 1

Reproductive toxicity Category 2

Specific target organ systemic toxicity (single exposure) Category 3

Specific target organ systemic toxicity (single exposure) Category 2 Kidney

Specific target organ systemic toxicity (single exposure) Category 1 Respiratory system, Central nervous system, Specific target organ systemic toxicity (repeated exposure) Category 1 Respiratory system, Central nervous system,

Kidney, Nervous system

Hazardous to the aquatic environment - acute hazard Category 3 Hazardous to the aquatic environment - chronic hazard Category 3

# **GHS LABEL ELEMENTS:**

Symbol(s)







# Signal Word

**DANGER** 

### **Hazard Statements**

Highly flammable liquid and vapor.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Suspected of damaging fertility or the unborn child.

May cause harm to breast-fed children.

May cause drowsiness or dizziness.

May cause respiratory irritation.

May cause damage to organs.(Kidney)

300000001151

Causes damage to organs.(Respiratory system, Central nervous system)

Causes damage to organs through prolonged or repeated exposure. (Respiratory system, Central nervous system,

Kidney, Nervous system)

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

## **Precautionary Statements**

#### **Prevention**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/Bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of inadequate ventilation wear respiratory protection.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

## Response

In case of fire: refer to section 5 of SDS for extinguishing media.

Call a POISON CENTER or doctor/physician if you feel unwell.

IF exposed: Call a POISON CENTER or doctor/physician.

Specific treatment (see supplemental first aid instructions on this label).

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation or rash occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

### Storage

Store in a well-ventilated place. Keep cool.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

### **Disposal:**

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

#### Other Hazards:

This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).

**Acute:** Vapor harmful; may affect the brain or nervous system causing dizziness, headache or nausea. Possible irritation of the respiratory system can occur causing a variety of symptoms such as dryness of the throat, tightness of the chest, and shortness of breath. May cause central nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma. May cause lung damage. Animal tests have indicated that respiratory sensitization can result from skin contact with certain isocyanates. May be harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

**Chronic:** May cause long-term lung damage.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Range
Methyl ethyl ketone	78-93-3	25 - 30 %
Toluene	108-88-3	5 - 10 %

4,4'-Diphenylmethane diisocy	ranate	101-68-8	5 - 10 %
Aromatic isocyanate		PROPRIETARY	1 - 5 %

Any "PROPRIETARY" component(s) in the above table is considered trade secret, thus the specific chemical and its exact concentration is being withheld.

### 4. FIRST AID MEASURES

**FIRST AID - EYE CONTACT:** Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

**FIRST AID - SKIN CONTACT:** Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

**FIRST AID - INHALATION:** Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

**FIRST AID - INGESTION:** If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

#### 5. FIRE-FIGHTING MEASURES

**SUITABLE EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog **UNSUITABLE EXTINGUISHING MEDIA:** Not determined for this product.

**SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL:** Flammable liquid and vapor. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, open flame, and other sources of ignition. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

**SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS:** Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water spray may be ineffective. If water is used, fog nozzles are preferable.

## 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:** Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid contact. Avoid breathing vapors. Use self-contained breathing equipment.

**ENVIRONMENTAL PRECAUTIONS:** Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

**METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP:** Keep non-essential personnel a safe distance away from the spill area. Notify appropriate authorities if necessary. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the SDS form. Contain and remove with inert absorbent material.

# 7. HANDLING AND STORAGE

**HANDLING:** Keep closure tight and container upright to prevent leakage. Ground and bond containers when transferring material. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation. Because empty containers may retain product residue and flammable vapors, keep away from heat, sparks and flame; do not cut, puncture or weld on or near the empty container. Do not smoke where this product is used or stored.

**STORAGE:** Do not store or use near heat, sparks, or open flame. Store only in well-ventilated areas. Do not puncture, drag, or slide container. Keep container closed when not in use. Refer to OSHA 29CFR Part 1910.106 "Flammable and Combustible Liquids" for specific storage requirements.

Page: 3

**INCOMPATIBILITY:** Amines, acids, water, hydroxyl, or active hydrogen compounds.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### COMPONENT EXPOSURE LIMIT

<u>Chemical Name</u>	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL- TWA	OSHA PEL- CEILING	Skin
Methyl ethyl ketone	200 ppm	300 ppm	590 mg/m3 200 ppm	N.E.	N.A.
Toluene	20 ppm	N.E.	200 ppm	300 ppm	N.A.
4,4'-Diphenylmethane diisocyanate	0.005 ppm	N.E.	N.E.	0.2 mg/m3 0.02 ppm	N.A.
Aromatic isocyanate	0.05 mg/m3	N.E.	N.E.	0.2 mg/m3	N.A.

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

**Engineering controls:** Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits. Caution: Solvent vapors are heavier than air and collect in lower levels of the work area. Sufficient ventilation (using explosion-proof equipment) should be provided to prevent flammable vapor/air mixtures from accumulating.

### PERSONAL PROTECTION MEASURES/EQUIPMENT:

**RESPIRATORY PROTECTION:** This product contains isocyanates which have poor odor warning properties. If occupational exposure limits are exceeded, a NIOSH approved supplied-air respirator is required. For respirator use observe OSHA regulations (29CFR 1910.134) or use in accordance with applicable laws and regulations of your country or particular locality.

**SKIN PROTECTION:** Use neoprene, nitrile, or rubber gloves to prevent skin contact.

**EYE PROTECTION:** Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

**OTHER PROTECTIVE EQUIPMENT:** Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

**HYGIENIC PRACTICES:** Wash hands before eating, smoking, or using toilet facility. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Typical values, not to be used for specification purposes.

ODOR: Solvent VAPOR PRESSURE: N.D.

APPEARANCE: Tan VAPOR DENSITY: Heavier than Air PHYSICAL STATE: Liquid LOWER EXPLOSIVE LIMIT: 1,2 %(V)
FLASH POINT: 27 °F, -2 °C Setaflash UPPER EXPLOSIVE LIMIT: 11.4 %(V)

Closed Cup

BOILING RANGE: 80 - 111 °C EVAPORATION RATE: Not Applicable

AUTOIGNITION TEMPERATURE: N.D. DENSITY: 1.03 g/cm3 (8.59 lb/gal)

DECOMPOSITION TEMPERATURE: N.D. VISCOSITY, DYNAMIC: ≥400 mPa.s @ 25 °C

ODOR THRESHOLD: N.D. VISCOSITY, KINEMATIC: ≥388 mm2/s @ 25 °C

SOLUBILITY IN H2O: Insoluble VOLATILE BY WEIGHT: 35.64 % PH: N.A. VOLATILE BY VOLUME: 44.95 %

FREEZE POINT: N.D. VOC CALCULATED: 3.06 lb/gal, 367 g/l

COEFFICIENT OF WATER/OIL N.D.

 $\begin{tabular}{ll} \textbf{DISTRIBUTION:} \\ \end{tabular}$ 

**LEGEND:** N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

# 10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur under normal conditions.

**STABILITY:** Product is stable under normal storage conditions.

**CONDITIONS TO AVOID:** High temperatures. Sources of ignition.

INCOMPATIBILITY: Amines, acids, water, hydroxyl, or active hydrogen compounds.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Monomeric isocyanate, traces of hydrogen cyanide, nitrogen dioxide, Carbon monoxide, carbon dioxide

## 11. TOXICOLOGICAL INFORMATION

**EXPOSURE PATH:** Refer to section 2 of this SDS.

**SYMPTOMS:** Refer to section 2 of this SDS.

#### **TOXICITY MEASURES:**

Chemical Name	<u>LD50/LC50</u>
Methyl ethyl ketone	Oral LD50: Rat 2,483 mg/kg
	Dermal LD50: Rabbit 5,000 mg/kg
	Inhalation LC50: Rat 11700 ppm/4 h
Toluene	Oral LD50: Rat 2,600 mg/kg
	Dermal LD50: Rabbit 12,000 mg/kg
	Inhalation LC50: Rat 12.5 mg/l /4 h
4,4'-Diphenylmethane diisocyanate	Oral LD50: Rat 31,600 mg/kg
	Dermal LD50: rabbit > 5,000 mg/kg
	GHS LC50 (vapour): Acute toxicity point estimate 11 mg/l /4 h GHS LC50
	(dust and mist): Acute toxicity point estimate 1.5 mg/l /4 h
Aromatic isocyanate	N.D.

Germ cell mutagenicity: No classification proposed

Carcinogenicity: No classification proposed

**Reproductive toxicity:** Category 2 - Suspected of damaging fertility or the unborn child. May cause harm to breastfold children

fed children.

Components contributing to classification: Toluene.

# 12. ECOLOGICAL INFORMATION

## **ECOTOXICITY:**

Chemical Name	<b>Ecotoxicity</b>	
Methyl ethyl ketone	Fish: Pimephales promelas 3,130 - 3,320 mg/l96 h flow-through Invertebrates: Daphnia magna > 520 mg/l48 h	
	Daphnia magna 5,091 mg/l48 h Daphnia magna 4,025 - 6,440 mg/l48 h Static	
	Dapinna magna 4,023 - 0,440 mg/146 m Static	
Toluene	Fish: Pimephales promelas 15.22 - 19.05 mg/l96 h flow-through	
	Pimephales promelas 12.6 mg/l96 h Static	
	Oncorhynchus mykiss 5.89 - 7.81 mg/l96 h flow-through	
	Oncorhynchus mykiss 14.1 - 17.16 mg/l96 h Static	
	Oncorhynchus mykiss 5.8 mg/l96 h semi-static	
	Lepomis macrochirus 11.0 - 15.0 mg/l96 h Static	
	Oryzias latipes 54 mg/l96 h Static	
	Poecilia reticulata 28.2 mg/l96 h semi-static	
	Poecilia reticulata 50.87 - 70.34 mg/l96 h Static	
	Invertebrates: Daphnia magna 5.46 - 9.83 mg/l48 h Static	
	Daphnia magna 11.5 mg/l48 h	
	Plants: Pseudokirchneriella subcapitata > 433 mg/l96 h	
	Pseudokirchneriella subcapitata 12.5 mg/l72 h Static	
4,4'-Diphenylmethane diisocyanate	<u>Fish:</u> Species > 1,000 mg/l96 h	

		Invertebrates: Daphnia magna > 1,000 mg/148 h
A	romatic isocyanate	N.D.

**PERSISTENCE AND DEGRADABILITY:** Not determined for this product.

**BIOACCUMULATIVE:** Not determined for this product.

MOBILITY IN SOIL: Not determined for this product.

OTHER ADVERSE EFFECTS: Not determined for this product.

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

## 14. TRANSPORT INFORMATION

**US DOT Road** 

Proper Shipping Name: Adhesives

Hazard Class:3SECONDARY HAZARD:NoneUN/NA Number:1133Packing Group:IIEmergency Response Guide Number:128

IATA Cargo

**PROPER SHIPPING NAME:** Adhesives

Hazard Class: 3
HAZARD CLASS: None
UN NUMBER: 1133
PACKING GROUP: II
EMS: 3L

**IMDG** 

**PROPER SHIPPING NAME:** Adhesives

Hazard Class: 3
HAZARD CLASS: None
UN NUMBER: 1133
PACKING GROUP: II
EMS: F-E

The listed transportation classification applies to non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. For the most accurate shipping information, refer to your transportation/compliance department.

## 15. REGULATORY INFORMATION

# U.S. FEDERAL REGULATIONS: AS FOLLOWS:

#### **SARA SECTION 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.:

Chemical Name	CAS Number	Weight % Less Than
Toluene	108-88-3	10.0 %
4,4'-Diphenylmethane diisocyanate	101-68-8	10.0 %

Page: 6

### TOXIC SUBSTANCES CONTROL ACT:

# INVENTORY STATUS

The chemical substances in this product are on the active TSCA Section 8 Inventory or exempt.

#### **EXPORT NOTIFICATION**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None

# 16. OTHER INFORMATION

Under HazCom 2012 it is optional to continue using the HMIS rating system. It is important to ensure employees have been trained to recognize the different numeric ratings associated with the HazCom 2012 and HMIS schemes.

HMIS RATINGS - HEALTH: 2\* FLAMMABILITY: 3 PHYSICAL HAZARD: 1

\* - Indicates a chronic hazard; see Section 2

**Revision:** Section 2, Section 11

**Effective Date:** 06/01/2021

### **DISCLAIMER**

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.