

# **USA SAFETY DATA SHEET**

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: LORD ACCELERATOR 26
Product Use/Class: Acrylic Adhesive, Part 2 of 2

LORD Corporation 111 LORD Drive Cary, NC 27511-7923 USA

Telephone: 814 868-3180

Non-Transportation Emergency: 814 763-2345 Chemtrec 24 Hr Transportation Emergency No. 800 424-9300 (Outside Continental U.S. 703 527-3887)

**EFFECTIVE DATE:** 07/06/2021

#### 2. HAZARDS IDENTIFICATION

#### **GHS CLASSIFICATION:**

Flammable liquids Category 3

Acute toxicity Oral Category 4

Acute toxicity Dermal Category 4

Acute toxicity Inhalation - Vapours Category 4

Acute toxicity Inhalation - Dust and Mist Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Skin sensitization Category 1

Germ cell mutagenicity Category 2

Carcinogenicity Category 2

Reproductive toxicity Category 2

Specific target organ systemic toxicity (single exposure) Category 3

Specific target organ systemic toxicity (single exposure) Category 2 Central nervous system

Specific target organ systemic toxicity (single exposure) Category 1 Respiratory system

Specific target organ systemic toxicity (repeated exposure) Category 1 Bone, Central nervous system

Aspiration hazard Category 1

Hazardous to the aquatic environment - acute hazard Category 2 Hazardous to the aquatic environment - chronic hazard Category 2

# **GHS LABEL ELEMENTS:**

#### Symbol(s)









# Signal Word

**DANGER** 

#### **Hazard Statements**

Flammable liquid and vapor.

Harmful if swallowed.

Harmful in contact with skin.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause respiratory irritation.

May cause damage to organs.(Central nervous system)

Causes damage to organs.(Respiratory system)

Causes damage to organs through prolonged or repeated exposure. (Bone, Central nervous system)

May be fatal if swallowed and enters airways.

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

#### **Precautionary Statements**

#### Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/Bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

#### Response

In case of fire: refer to section 5 of SDS for extinguishing media.

Call a POISON CENTER or doctor/physician if you feel unwell.

IF exposed: Call a POISON CENTER or doctor/physician.

Specific treatment (see supplemental first aid instructions on this label).

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation or rash occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Rinse mouth.

Do NOT induce vomiting.

Collect spillage.

### Storage

Store in a well-ventilated place. Keep cool.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

#### Disposal:

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

# Other Hazards:

This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).

**Acute:** Vapor harmful; may affect the brain or nervous system causing dizziness, headache or nausea. Possible irritation of the respiratory system can occur causing a variety of symptoms such as dryness of the throat, tightness of the chest, and shortness of breath. May cause central nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma. May be absorbed through the skin in harmful amounts.

**Chronic:** Repeated exposure to smoke or fumes generated by heating this product may lead to respiratory sensitization (asthma) in susceptible individuals. Repeated exposure to n-butyl acetate caused fetotoxic and developmental effects in laboratory animals. ACGIH considers the cyclohexanone in this product to be an A3 carcinogen (confirmed animal carcinogen with unknown relevance in humans).

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Range
Cyclohexanone	108-94-1	85 - 90 %
Dibenzoyl peroxide	94-36-0	5 - 10 %
N-Butyl acetate	123-86-4	1 - 5 %

Any "PROPRIETARY" component(s) in the above table is considered trade secret, thus the specific chemical and its exact concentration is being withheld

#### 4. FIRST AID MEASURES

**FIRST AID - EYE CONTACT:** Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

**FIRST AID - SKIN CONTACT:** Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

**FIRST AID - INHALATION:** Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

**FIRST AID - INGESTION:** If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

### 5. FIRE-FIGHTING MEASURES

**SUITABLE EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog **UNSUITABLE EXTINGUISHING MEDIA:** Not determined for this product.

**SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL:** Combustible liquid and vapor. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, open flame, and other sources of ignition. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. WARNING: This product contains benzoyl peroxide. If the solvents are allowed to evaporate, the dried residue may ignite with heat, friction, shock, or contact with combustible material.

**SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS:** Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). If water is used, fog nozzles are preferable. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

### 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:** Avoid breathing vapors. Use self-contained breathing equipment. Avoid contact.

**ENVIRONMENTAL PRECAUTIONS:** Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

**METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP:** Keep non-essential personnel a safe distance away from the spill area. Notify appropriate authorities if necessary. Contain and remove with inert absorbent material. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the SDS form.

### 7. HANDLING AND STORAGE

**HANDLING:** Keep closure tight and container upright to prevent leakage. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Warning: This product contains benzoyl peroxide. If the solvents are allowed to evaporate, the dried residue may ignite with heat, friction, shock, or contact with combustible material. Use with adequate ventilation. Do not smoke where this product is used or stored.

**STORAGE:** Do not store or use near heat, sparks, or open flame. Refer to OSHA 29CFR Part 1910.106 "Flammable and Combustible Liquids" for specific storage requirements. Store only in well-ventilated areas. Do not puncture, drag, or slide container. Keep container closed when not in use.

**INCOMPATIBILITY:** Strong acids, bases, and strong oxidizers.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### COMPONENT EXPOSURE LIMIT

Chemical Name	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL- TWA	OSHA PEL- CEILING	Skin
Cyclohexanone	20 ppm	50 ppm	200 mg/m3 50 ppm	N.E.	S
Dibenzoyl peroxide	5 mg/m3	N.E.	5 mg/m3	N.E.	N.A.
N-Butyl acetate	150 ppm	200 ppm	710 mg/m3 150 ppm	N.E.	N.A.

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

**Engineering controls:** Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits. Caution: Solvent vapors are heavier than air and collect in lower levels of the work area.

#### PERSONAL PROTECTION MEASURES/EQUIPMENT:

**RESPIRATORY PROTECTION:** Use a NIOSH approved air-purifying organic vapor respirator if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. For respirator use observe OSHA regulations (29CFR 1910.134) or use in accordance with applicable laws and regulations of your country or particular locality.

**SKIN PROTECTION:** Use butyl gloves to prevent skin contact.

**EYE PROTECTION:** Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

**OTHER PROTECTIVE EQUIPMENT:** Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

**HYGIENIC PRACTICES:** Wash hands before eating, smoking, or using toilet facility. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Typical values, not to be used for specification purposes.

ODORVAPOR PRESSURE: Solvent NDAPPEARANCE: VAPOR DENSITY: Heavier than Air Opaque PHYSICAL STATE: LOWER EXPLOSIVE LIMIT: Liquid 1.1 %(V) 109 °F, 42 °C FLASH POINT: **UPPER EXPLOSIVE LIMIT:** 8.1 %(V)

Setaflash Closed Cup

BOILING RANGE: 126 - 156 °C EVAPORATION RATE: Slower than n-butyl-

acetate

AUTOIGNITION TEMPERATURE: N.D. DENSITY: 0.97 g/cm3 (8.07 lb/gal)

DECOMPOSITION TEMPERATURE:<br/>ODOR THRESHOLD:<br/>SOLUBILITY IN H2O:N.D.VISCOSITY, DYNAMIC:<br/>VISCOSITY, KINEMATIC:<br/>VOLATILE BY WEIGHT:N.D.SOLUBILITY IN H2O:InsolubleVOLATILE BY WEIGHT:90.71 %

Product: LORD ACCELERATOR 26, Effective Date: 07/06/2021

pH: N.A. VOLATILE BY VOLUME: 92.94 %

FREEZE POINT: N.D. VOC CALCULATED: 7.32 lb/gal, 877 g/l

COEFFICIENT OF WATER/OIL N.D.

DISTRIBUTION:

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

### 10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur under normal conditions.

**STABILITY:** Product is stable under normal storage conditions.

**CONDITIONS TO AVOID:** Dried material is flammable, sensitive to shock and heat.; Direct sunlight, shock, and

temperatures in excess of 90F.

**INCOMPATIBILITY:** Strong acids, bases, and strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide

# 11. TOXICOLOGICAL INFORMATION

**EXPOSURE PATH:** Refer to section 2 of this SDS.

**SYMPTOMS:** Refer to section 2 of this SDS.

#### **TOXICITY MEASURES:**

Chemical Name	<u>LD50/LC50</u>	
Cyclohexanone	Oral LD50: Rat 1,544 mg/kg	
	Dermal LD50: Rabbit 947 mg/kg	
	Inhalation LC50: Rat 8000 ppm/4 h	
Dibenzoyl peroxide	Oral LD50: Rat 7,710 mg/kg	
N-Butyl acetate	Oral LD50: Rat 10,768 mg/kg	
	Dermal LD50: Rabbit > 17,600 mg/kg	
	Inhalation LC50: Rat 390 ppm/4 h Inhalation LC50: rat 22 mg/1 /4 h	

Germ cell mutagenicity: Category 2 - Suspected of causing genetic defects.

Components contributing to classification: Cyclohexanone.

**Carcinogenicity:** Category 2 - Suspected of causing cancer. Components contributing to classification: Cyclohexanone.

Reproductive toxicity: Category 2 - Suspected of damaging fertility or the unborn child.

Components contributing to classification: Cyclohexanone.

### 12. ECOLOGICAL INFORMATION

### **ECOTOXICITY:**

Chemical Name	<b>Ecotoxicity</b>	
Cyclohexanone	<u>Fish:</u> Pimephales promelas 481 - 578 mg/l96 h flow-through Pimephales promelas 8.9 mg/l96 h	
Dibenzoyl peroxide	Fish: Oncorhynchus mykiss 0.0602 mg/l96 h semi-static	
N-Butyl acetate	<u>Fish:</u> Lepomis macrochirus 100 mg/l96 h Static Pimephales promelas 17 - 19 mg/l96 h flow-through <u>Plants:</u> Desmodesmus subspicatus 674.7 mg/l72 h	

PERSISTENCE AND DEGRADABILITY: Not determined for this product.

Product: LORD ACCELERATOR 26, Effective Date: 07/06/2021

**BIOACCUMULATIVE:** Not determined for this product.

**MOBILITY IN SOIL:** Not determined for this product.

OTHER ADVERSE EFFECTS: Not determined for this product.

# 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

### 14. TRANSPORT INFORMATION

#### **US DOT Road**

**Proper Shipping Name:** Adhesives

Hazard Class:3SECONDARY HAZARD:NoneUN/NA Number:1133Packing Group:IIIEmergency Response Guide Number:128

#### IATA Cargo

**PROPER SHIPPING NAME:** Adhesives

Hazard Class: 3
HAZARD CLASS: None
UN NUMBER: 1133
PACKING GROUP: III
EMS: 3L

# **IMDG**

**PROPER SHIPPING NAME:** Adhesives

Hazard Class: 3
HAZARD CLASS: None
UN NUMBER: 1133
PACKING GROUP: III
EMS: F-E

The listed transportation classification applies to non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. For the most accurate shipping information, refer to your transportation/compliance department.

# 15. REGULATORY INFORMATION

# U.S. FEDERAL REGULATIONS: AS FOLLOWS:

### **SARA SECTION 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.:

Chemical NameCAS NumberWeight % Less ThanDibenzoyl peroxide94-36-010.0 %

## TOXIC SUBSTANCES CONTROL ACT:

#### INVENTORY STATUS

The chemical substances in this product are on the active TSCA Section 8 Inventory or exempt.

### **EXPORT NOTIFICATION**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None

### 16. OTHER INFORMATION

Under HazCom 2012 it is optional to continue using the HMIS rating system. It is important to ensure employees have been trained to recognize the different numeric ratings associated with the HazCom 2012 and HMIS schemes.

**HMIS RATINGS -** HEALTH: 2\* FLAMMABILITY: 2 PHYSICAL HAZARD: 1

\* - Indicates a chronic hazard; see Section 2

Revision: Company Logo

**Effective Date:** 07/06/2021

### DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.