

SAFETY DATA SHEET DC1 - NO-CLEAN FLUX REMOVER, VERICLEAN - BULK

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

Product name DC1 - NO-CLEAN FLUX REMOVER, VERICLEAN - BULK

Product number MCC-DC1L, MCC-DC1G, MCC-DC1D, MCC-DC1GL, MCC-DC1GG

Synonyms; trade names DC1-VERICLEAN FLUX REMOVER, NON AEROSOL

Recommended use of the chemical and restrictions on use

Application Cleaning agent.

Details of the supplier of the safety data sheet

Supplier MICROCARE CORPORATION

Manufacturer MICROCARE CORPORATION

595 John Downey Drive New Britain, CT 06051 United States of America

CAGE: OATV9

Tel: +1 860-827-0626 Fax: +1 860-827-8105 techsupport@microcare.com

Emergency telephone number

Emergency telephone CHEMTREC 1-800-424-9300 (within the U.S.)

+1 703-741-5970 (from anywhere in the world)

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Flam. Liq. 2 - H225

Health hazards Not Classified

Environmental hazards Aquatic Acute 1 - H400

Human health Splashes in the eyes may cause redness and irritation. Keep out of the reach of children. See

Section 11 for additional information on health hazards.

Physicochemical The product is highly flammable. Vapors may form explosive mixtures with air.

Label elements

Pictogram





Signal word Danger

DC1 - NO-CLEAN FLUX REMOVER, VERICLEAN - BULK

Hazard statements H225 Highly flammable liquid and vapor.

H400 Very toxic to aquatic life.

Precautionary statements P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.

P240 Ground/ bond container and receiving equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P273 Avoid release to the environment.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

Supplemental label

information

Safety data sheet available on request. For use in industrial installations only.

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

HEXAMETHYLDISILOXANE (Methyl siloxane)

60-100%

CAS number: 107-46-0 M factor (Acute) = 1

Classification

Flam. Liq. 2 - H225 Aquatic Acute 1 - H400

1-METHOXY-2-PROPANOL

10-30%

CAS number: 107-98-2

Classification

Flam. Liq. 3 - H226 STOT SE 3 - H336

The full text for all hazard statements is displayed in Section 16.

Composition comments The exact percentage (concent

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of CFR 1900.1200 TSCA: The ingredients of this product are

on the TSCA Inventory.

Composition

4. First-aid measures

Description of first aid measures

General information Promptly remove any clothing that becomes wet or contaminated. Move affected person to

fresh air at once. Get medical attention if any discomfort continues.

Inhalation Move affected person to fresh air at once. When breathing is difficult, properly trained

personnel may assist affected person by administering oxygen. Keep affected person warm

and at rest. Get medical attention immediately.

Ingestion Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink.

Never give anything by mouth to an unconscious person. Consult a physician for specific

advice.

Skin Contact Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

DC1 - NO-CLEAN FLUX REMOVER, VERICLEAN - BULK

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Get medical attention if any discomfort continues.

Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Indication of immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray,

fog or mist.

Special hazards arising from the substance or mixture

Specific hazardsThe product is flammable. Heating may generate flammable vapors. Oxides of carbon.

Protection against nuisance dust must be used when the airborne concentration exceeds 10

mg/m3.

Advice for firefighters

Protective actions during

firefighting

Containers close to fire should be removed or cooled with water. Use water to keep fire

exposed containers cool and disperse vapors.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. Unless the assessment indicates a higher degree of protection is

required, the following protection should be worn: Tight-fitting safety glasses.

Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Never use water by itself on

spillage; this will spread the spill and cause further contamination.

Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,

clothing or apron, as appropriate. If leakage cannot be stopped, evacuate area. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into

containers.

7. Handling and storage

Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and

eyes. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air

contamination is above an acceptable level. Keep out of the reach of children.

Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame.

DC1 - NO-CLEAN FLUX REMOVER, VERICLEAN - BULK

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

Reference to other sections. Store away from incompatible materials (see Section 10).

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

1-METHOXY-2-PROPANOL

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm 184 mg/m³ Short-term exposure limit (15-minute): ACGIH 100 ppm 369 mg/m³

A4

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

Additional Occupational

Exposure Limits

Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn:

Chemical splash goggles or face shield.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapor contact.

Hygiene measures Do not smoke in work area. Wash at the end of each work shift and before eating, smoking

and using the toilet. Promptly remove any clothing that becomes wet or contaminated. When

using do not eat, drink or smoke.

Respiratory protection No specific recommendations. Respiratory protection must be used if the airborne

contamination exceeds the recommended occupational exposure limit.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Liquid.

Color Clear liquid. Colorless.

Odor Slight. Ether.

Odor threshold No information available. pΗ No information available. Melting point No information available.

DC1 - NO-CLEAN FLUX REMOVER, VERICLEAN - BULK

Initial boiling point and range 98°C/210°F @ 101.3 kPa

Flash point -4.0°C/25°F Method: TCC (Tag closed cup).

Evaporation rate

No information available.

Evaporation factor

No information available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or

explosive limits

Upper flammable/explosive limit: 18.6 %(V) Lower flammable/explosive limit: 1.25 %(V)

Vapor pressure 5.95 kPa @ 20°C

Vapor density > 1.0

Relative density

No information available.

Bulk density

No information available.

Solubility(ies) Insoluble in water.

Partition coefficient No information available.

Auto-ignition temperature 365°C/689°F

Decomposition TemperatureNo information available.ViscosityNo information available.Explosive propertiesNo information available.

Refractive index No information available.

Particle size Not applicable.

Molecular weight Not applicable.

Volatility 100%

Saturation concentration No information available.

Critical temperature No information available.

Volatile organic compound This product contains a maximum VOC content of 87 g/litre.

10. Stability and reactivity

Reactivity There are no known reactivity hazards associated with this product.

Stability Stable at normal ambient temperatures.

Possibility of hazardous

reactions

Will not polymerize.

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Strong oxidizing agents. Strong alkalis. Strong mineral acids.

Materials to avoid Strong oxidizing agents.

Hazardous decomposition

products

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors. Vapors/gases/fumes of: Silicon dioxide Formaldehyde

DC1 - NO-CLEAN FLUX REMOVER, VERICLEAN - BULK

11. Toxicological information

Information on toxicological effects

Other health effects There is no evidence that the product can cause cancer.

Inhalation May cause respiratory system irritation. Vapors may cause headache, fatigue, dizziness and

nausea. Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion No harmful effects expected from quantities likely to be ingested by accident.

Skin Contact Product has a defatting effect on skin. May cause skin irritation/eczema.

Eye contact Irritating to eyes.

Toxicological information on ingredients.

HEXAMETHYLDISILOXANE (Methyl siloxane)

Acute toxicity - inhalation

Acute toxicity inhalation 106.0

(LC50 vapours mg/l)

Species Rat

12. Ecological Information

Ecotoxicity There are no data on the ecotoxicity of this product.

Ecological information on ingredients.

HEXAMETHYLDISILOXANE (Methyl siloxane)

Toxicity Very toxic to aquatic organisms.

Acute aquatic toxicity

LE(C)₅₀ $0.1 < L(E)C50 \le 1$

M factor (Acute)

Acute toxicity - fish LC₅₀, 96 hours: 0.46 mg/l mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅₀, 72 hours: 0.79 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅o, 96 hours: > 0.93 mg/l, Selenastrum capricornutum

Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient No information available.

Mobility in soil

Mobility The product contains volatile substances which may spread in the atmosphere.

Other adverse effects

DC1 - NO-CLEAN FLUX REMOVER, VERICLEAN - BULK

Other adverse effects Not available.

13. Disposal considerations

Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in

accordance with the requirements of the local Waste Disposal Authority.

Disposal methods

Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

14. Transport information

UN Number

UN No. (IMDG) UN 1993 UN No. (ICAO) UN1993

UN proper shipping name

Proper shipping name (TDG) UN1993, FLAMMABLE LIQUID, N.O.S.(Hexamethyldisiloxane), 3, PGII

Proper shipping name (IMDG) UN1993, FLAMMABLE LIQUID, N.O.S.(Hexamethyldisiloxane), 3, PGII

Proper shipping name (ICAO) UN1993, FLAMMABLE LIQUID, N.O.S.(Hexamethyldisiloxane), 3, PGII

Proper shipping name (DOT) UN1993, FLAMMABLE LIQUID, N.O.S.(Hexamethyldisiloxane), 3, PGII

Transport hazard class(es)

TDG class 3

IMDG Class 3

ICAO class/division 3

Packing group

TDG Packing Group

IMDG packing group

ICAO packing group

DOT packing group

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

EmS F-E, S-E

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

US Federal Regulations

DC1 - NO-CLEAN FLUX REMOVER, VERICLEAN - BULK

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

Not listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

Not listed.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

Not listed.

SARA 313 Emission Reporting

Not listed.

CAA Accidental Release Prevention

Not listed.

SARA (311/312) Hazard Categories

Fire

OSHA Highly Hazardous Chemicals

Not listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

Not listed.

California Air Toxics "Hot Spots" (A-II)

Not listed.

Inventories

Canada - DSL/NDSL

DSL

US - TSCA

Yes

16. Other information

Revision date 4/17/2017

Revision 32

Supersedes date 4/17/2017

SDS No. BULK - DC1

SDS status Approved.

Hazard statements in full H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.