

SAFETY DATA SHEET PW2 - LEAD-FREE FLUX REMOVER - POWERCLEAN, AEROSOL

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

Product name PW2 - LEAD-FREE FLUX REMOVER - POWERCLEAN, AEROSOL

Product number MCC-PW210Y, MCC-PW210A, MCC-PW2101, MCC-PW2105, MCC-PW2106

Recommended use of the chemical and restrictions on use

Application Cleaning agent.

Details of the supplier of the safety data sheet

Supplier MICROCARE CORPORATION

Manufacturer MICROCARE CORPORATION

595 John Downey Drive New Britain, CT 06051 United States of America

CAGE: OATV9

Tel: + 1 800 638 0125, +1 860-827-0626

Fax: +1 860-827-8105 techsupport@microcare.com

Emergency telephone number

Emergency telephone CHEMTREC 1-800-424-9300 (within the U.S.)

+1 703-741-5970 (from anywhere in the world)

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H332

Environmental hazards Aquatic Chronic 3 - H412

Human health Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. Mild

dermatitis, allergic skin rash.

Environmental The product contains a substance which is harmful to aquatic organisms and which may

cause long-term adverse effects in the aquatic environment.

Physicochemical Vapors are heavier than air and may travel along the floor and accumulate in the bottom of

containers. Not considered to be a significant hazard due to the small quantities used. Gas or

vapor displaces oxygen available for breathing (asphyxiant).

Label elements

PW2 - LEAD-FREE FLUX REMOVER - POWERCLEAN, AEROSOL

Pictogram



Signal word Warning

Hazard statements H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use

P261 Avoid breathing spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with local regulations.

Supplemental label

information

Safety data sheet available on request. For use in industrial installations only.

Contains trans-DICHLOROETHYLENE

3. Composition/information on ingredients

Mixtures

trans-DICHLOROETHYLENE

30-60%

CAS number: 156-60-5

Classification

Flam. Liq. 2 - H225 Acute Tox. 4 - H332 Aquatic Chronic 3 - H412

HFC-134a Tetrafluoroethane

10-30%

CAS number: 811-97-2

Classification

Press. Gas, Liquefied - H280

1,1,1,2,2,3,4,5,5,5-decafluoropentane

10-30%

CAS number: 138495-42-8

Classification

Aquatic Chronic 3 - H412

The full text for all hazard statements is displayed in Section 16.

Composition comments The exact percentage (concentration) of composition has been withheld as a trade secret in

accordance with paragraph (i) of CFR 1900.1200 TSCA: The ingredients of this product are

on the TSCA Inventory.

Ingredient notes A MIXTURE OF: (R,R)-1,1,1,2,2,3,4,5,5,5-DECAFLUOROPENTANE, (S,S)-

1,1,1,2,2,3,4,5,5,5-DECAFLUOROPENTANE has been revised to 1,1,1,2,2,3,4,5,5,5-

decafluoropentane. No change in chemistry. 20JUL17

Composition

PW2 - LEAD-FREE FLUX REMOVER - POWERCLEAN, AEROSOL

4. First-aid measures

Description of first aid measures

General information Never give anything by mouth to an unconscious person. Do not induce vomiting. Place

unconscious person on the side in the recovery position and ensure breathing can take place.

If breathing stops, provide artificial respiration.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. When breathing is difficult, properly trained personnel may assist affected person

by administering oxygen.

Ingestion Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink.

Consult a physician for specific advice.

Skin Contact Remove contaminated clothing and rinse skin thoroughly with water.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Consult a physician for specific advice.

Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Vapors may cause headache, fatigue, dizziness and nausea. Difficulty in breathing. Upper

respiratory irritation. Severe irritation of nose and throat.

Ingestion May cause stomach pain or vomiting. Drowsiness, diszriness, disorientation, vertigo.

Skin contact Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.

Eye contact Irritation of eyes and mucous membranes. Irritating to eyes. Symptoms following

overexposure may include the following: Redness. Pain.

Indication of immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

Special hazards arising from the substance or mixture

Flammability Class The product is not flammable.

Specific hazards Keep away from heat, sparks and open flame. Thermal decomposition or combustion

products may include the following substances: Toxic and corrosive gases or vapors. Aerosol

containers can explode when heated, due to excessive pressure build-up.

Hazardous combustion

products

Heating may generate the following products: Toxic and corrosive gases or vapors. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

Oxides of carbon. Oxides of nitrogen.

Advice for firefighters

Protective actions during

firefighting

Move containers from fire area if it can be done without risk. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Bursting

aerosol containers may be propelled from a fire at high speed.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

PW2 - LEAD-FREE FLUX REMOVER - POWERCLEAN, AEROSOL

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Warn everybody of potential hazards and evacuate if necessary. Provide adequate ventilation.

Avoid inhalation of vapors. Use approved respirator if air contamination is above an

acceptable level.

Environmental precautions

Environmental precautionsContain spillage with sand, earth or other suitable non-combustible material. Avoid release to

the environment.

Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,

clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames

or other sources of ignition near spillage. Provide adequate ventilation.

Reference to other sections See Section 11 for additional information on health hazards.

7. Handling and storage

Precautions for safe handling

Usage precautions Provide adequate ventilation. Avoid inhalation of vapors/spray and contact with skin and eyes.

Keep away from heat, sparks and open flame. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapors.

Conditions for safe storage, including any incompatibilities

Storage precautions Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

Reference to other sections. Store away from incompatible materials (see Section 10).

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

trans-DICHLOROETHYLENE

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 793 mg/m³

HFC-134a Tetrafluoroethane

Long-term exposure limit (8-hour TWA): OES 4240 mg/m³

1,1,1,2,2,3,4,5,5,5-decafluoropentane

No information available that would effect occupational exposure limit values.

ACGIH = American Conference of Governmental Industrial Hygienists.

Additional Occupational

Exposure Limits

Ingredient comments ACGIH = US Standard.

Exposure controls

PW2 - LEAD-FREE FLUX REMOVER - POWERCLEAN, AEROSOL

Protective equipment





Appropriate engineering

controls

No specific ventilation requirements. This product must not be handled in a confined space

without adequate ventilation.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. Unless the assessment indicates a higher degree of protection is

required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible.

Other skin and body

protection

Wear suitable protective clothing as protection against splashing or contamination. Wear

apron or protective clothing in case of contact.

Hygiene measures No specific hygiene procedures recommended but good personal hygiene practices should

always be observed when working with chemical products. When using do not eat, drink or

smoke.

Respiratory protection Vapors are heavier than air and may travel along the floor and accumulate in the bottom of

containers. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn.

Wear self-contained breathing apparatus with full facepiece.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Clear liquid. Aerosol.

Color Colorless.

Odor Slight. Ether.

Odor threshold No information available.

pH No information available.

Melting point No information available.

Initial boiling point and range 39°C/102°F @ 101.3 kPa

Flash point The product is not flammable.

Evaporation rate

No information available.

Evaporation factor

No information available.

Upper/lower flammability or

explosive limits

Upper flammable/explosive limit: 13 %(V) Lower flammable/explosive limit: 5.5 %(V)

Other flammability The product is not flammable. Aerosol ignition distance: none at 0.0 cm

Vapor pressure 55.3 kPa @ 25°C

Vapor density 3.7

Relative density 1.27

Bulk density No information available.

Solubility(ies) 0.3 g/100 g water @ 20°C Slightly soluble in water.

Partition coefficient No information available.

PW2 - LEAD-FREE FLUX REMOVER - POWERCLEAN, AEROSOL

Auto-ignition temperature

No information available.

Decomposition Temperature

No information available.

Viscosity

No information available.

Explosive properties No information available.

Oxidizing properties Not known.

Comments Aerosol.

Refractive index

No information available.

Particle size

No information available.

Molecular weight

No information available.

Volatility 100%

Saturation concentration No information available.

Critical temperature No information available.

Volatile organic compound This product contains a maximum VOC content of 1080 g/l.

Flammability The product is not flammable.

10. Stability and reactivity

Reactivity The following materials may react with the product: Strong alkalis.

Stability Stable at normal ambient temperatures and when used as recommended.

Possibility of hazardous

reactions

Will not polymerize.

Conditions to avoid Keep away from heat, sparks and open flame. Thermal decomposition or combustion

products may include the following substances: Toxic and corrosive gases or vapors.

Materials to avoid Alkali metals. Alkaline earth metals. Powdered metal.

Hazardous decomposition

products

Heating may generate the following products: Toxic and corrosive gases or vapors.

Halogenated hydrocarbons. Hydrogen fluoride (HF). Carbon dioxide (CO2). Carbon monoxide

(CO).

11. Toxicological information

Information on toxicological effects

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 19.05

Inhalation Vapors may irritate throat/respiratory system. A single exposure may cause the following

adverse effects: Coughing. Difficulty in breathing.

Ingestion May cause stomach pain or vomiting. May cause nausea, headache, dizziness and

intoxication.

Skin Contact Product has a defatting effect on skin. May cause allergic contact eczema.

Eye contact May cause temporary eye irritation.

PW2 - LEAD-FREE FLUX REMOVER - POWERCLEAN, AEROSOL

Medical Symptoms Gas or vapor in high concentrations may irritate the respiratory system. Symptoms following

overexposure may include the following: Headache. Fatigue. Nausea, vomiting.

Toxicological information on ingredients.

trans-DICHLOROETHYLENE

Other health effects There is no evidence that the product can cause cancer.

HFC-134a Tetrafluoroethane

Other health effects There is no evidence that the product can cause cancer.

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ gases ppmV)

567,000.0

Species Rat

ATE inhalation (gases

ppm)

567,000.0

Inhalation Vapors irritate the respiratory system. May cause coughing and difficulties in

breathing.

Ingestion May cause stomach pain or vomiting. May cause nausea, headache, dizziness and

intoxication.

Skin Contact May cause allergic contact eczema. Contact with liquid form may cause frostbite.

Eye contact May cause temporary eye irritation.

1,1,1,2,2,3,4,5,5,5-decafluoropentane

Acute toxicity - oral

Acute toxicity oral (LD50

5,000.0

mg/kg)

Species Rat

ATE oral (mg/kg) 5,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 5,000.0

mg/kg)

Species

Rat

ATE dermal (mg/kg) 5,000.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l)

114.0

Species

Rat

ATE inhalation (vapours

mg/l)

114.0

_..

Skin corrosion/irritation

PW2 - LEAD-FREE FLUX REMOVER - POWERCLEAN, AEROSOL

Animal data Not irritating. Rabbit

Human skin model test Data lacking.

Extreme pH Not applicable. Not corrosive to skin.

Serious eye damage/irritation

Serious eye Not irritating. Rabbit

damage/irritation

Respiratory sensitization

Respiratory sensitization Data lacking.

Skin sensitization

Skin sensitization Not sensitizing. - Guinea pig: Not sensitizing.

Germ cell mutagenicity

Genotoxicity - in vitroThis substance has no evidence of mutagenic properties.

Genotoxicity - in vivo This substance has no evidence of mutagenic properties.

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

IARC carcinogenicity Not listed.

NTP carcinogenicity Not listed.

OSHA Carcinogenicity Not listed.

Reproductive toxicity

Reproductive toxicity -

fertility

No evidence of reproductive toxicity in animal studies.

Skin Contact Skin irritation should not occur when used as recommended. May cause defatting

of the skin but is not an irritant.

Eye contact May cause eye irritation.

Acute and chronic health

hazards

There is no evidence that the product can cause cancer.

12. Ecological Information

Ecological information on ingredients.

trans-DICHLOROETHYLENE

Ecotoxicity Low acute toxicity to aquatic organisms.

1,1,1,2,2,3,4,5,5,5-decafluoropentane

Ecotoxicity It is unlikely that the substance will dissolve in water in amounts big enough to have

a toxic effect on fish and daphnies.

Ecological information on ingredients.

trans-DICHLOROETHYLENE

PW2 - LEAD-FREE FLUX REMOVER - POWERCLEAN, AEROSOL

Acute toxicity - fish LC₅₀, 96 hours: 1350 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 220 mg/l, Daphnia magna

HFC-134a Tetrafluoroethane

Acute toxicity - fish LC₅₀, 96 hours: 450 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅o, 48 hours: 980 mg/l, Daphnia magna

1,1,1,2,2,3,4,5,5,5-decafluoropentane

Acute toxicity - fish LC₅₀, 96 hours: 13.9 mg/l, Onchorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

LC₅₀, 48 hours: 11.7 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅₀, 72 hours: >120 mg/l, Algae

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient No information available.

Ecological information on ingredients.

trans-DICHLOROETHYLENE

Bio-Accumulative Potential Bioaccumulation is unlikely to be significant because of the low water-solubility of

this product.

HFC-134a Tetrafluoroethane

Partition coefficient Pow: 1.06

1,1,1,2,2,3,4,5,5,5-decafluoropentane

Bio-Accumulative Potential Bioaccumulation is unlikely to be significant because of the low water-solubility of

this product.

Partition coefficient Pow: 2.7

Mobility in soil

Mobility The product contains volatile substances which may spread in the atmosphere.

Ecological information on ingredients.

trans-DICHLOROETHYLENE

Mobility The product has poor water-solubility.

Other adverse effects

Other adverse effects The product contains a substance or substances that will contribute to global warming

(greenhouse effect).

13. Disposal considerations

PW2 - LEAD-FREE FLUX REMOVER - POWERCLEAN, AEROSOL

Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site

in accordance with the requirements of the local Waste Disposal Authority.

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

14. Transport information

UN Number

UN No. (IMDG) 1950 **UN No. (ICAO)** 1950

UN proper shipping name

Proper shipping name (TDG) LIMITED QUANTITY

Proper shipping name (IMDG) UN1950 AEROSOLS, NON-FLAMMABLE, 2.2, LIMITED QUANTITY

Proper shipping name (ICAO) UN1950 AEROSOLS, NON-FLAMMABLE, 2.2, LIMITED QUANTITY

Proper shipping name (DOT) LIMITED QUANTITY

Transport hazard class(es)

IMDG Class 2.2 LIMITED QUANTITY
ICAO class/division 2.2 LIMITED QUANTITY

ICAO subsidiary risk N/A

Packing group

IMDG packing group N/A
ICAO packing group N/A

Special precautions for user

EmS F-C, S-V

Transport in bulk according to Not applicable. No information required.

and the IBC Code

15. Regulatory information

Annex II of MARPOL 73/78

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities Not listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

trans-DICHLOROETHYLENE

Final CERCLA RQ: 1000(454) pounds (Kilograms)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

Not listed.

SARA 313 Emission Reporting

Not listed.

PW2 - LEAD-FREE FLUX REMOVER - POWERCLEAN, AEROSOL

CAA Accidental Release Prevention

Not listed.

SARA (311/312) Hazard Categories

Acute Pressure

OSHA Highly Hazardous Chemicals

Not listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

Not listed.

California Air Toxics "Hot Spots" (A-I)

Not listed.

California Air Toxics "Hot Spots" (A-II)

Not listed.

California Directors List of Hazardous Substances

trans-DICHLOROETHYLENE

Present.

Massachusetts "Right To Know" List

trans-DICHLOROETHYLENE

Present.

Rhode Island "Right To Know" List

Not listed.

Minnesota "Right To Know" List

HFC-134a Tetrafluoroethane

Present.

New Jersey "Right To Know" List

Not listed.

Pennsylvania "Right To Know" List

trans-DICHLOROETHYLENE

Present.

Inventories

Canada - DSL/NDSL

Present.

US - TSCA

Yes

PW2 - LEAD-FREE FLUX REMOVER - POWERCLEAN, AEROSOL

1,1,1,2,2,3,4,5,5,5-decafluoropentane

Present.

1,1,1,2,2,3,4,5,5,5-DECAFLUOROPENTANE (CAS# 138495-42-8) is controlled by TSCA Section 5, Significant New Use Rule

(SNUR; 40 CFR 721.5645) The approved uses are: precision and general cleaning, carrier fluid, displacement drying, printed circuit board cleaning, particulate removal and film cleaning, process medium, heat transfer fluid (dielectric and non-dielectric), and test fluid. Processors and users of this substance must also comply with the applicable general SNUR requirements set forth in 40 CFR 721 subpart A,

including export notification requirements if applicable (40 CFR 721.20), and the applicable record keeping requirements

set forth at 40 CFR 721.125.

1,1,1,2,2,3,4,5,5,5-Decafluoropentane 138495-42-8

The United States Environmental Protection Agency (USEPA) has established a Significant New Use Rule (SNUR) for one of the components in this product. This material contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D:

HFC-134a Tetrafluoroethane

Present.

trans-DICHLOROETHYLENE

Present.

16. Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 11/21/2017

Revision 58

Supersedes date 9/5/2017

SDS No. AEROSOL - PW2

SDS status Approved.

Hazard statements in full H225 Highly flammable liquid and vapor.

H280 Contains gas under pressure; may explode if heated.

H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.