



## Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	19-8269-3	<b>Version Number:</b>	10.04
<b>Issue Date:</b>	09/06/23	<b>Supersedes Date:</b>	09/22/22

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive DP100FR Cream, Part B

#### Product Identification Numbers

LA-D100-0165-3, LA-D100-0165-4, LA-D100-0165-5, LA-D100-2252-8, LA-D100-2252-9

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Adhesive, Structural adhesive

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Industrial Adhesives and Tapes Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 2.

Carcinogenicity: Category 2.

#### 2.2. Label elements

##### Signal word

Warning

##### Symbols

Exclamation mark | Health Hazard |

##### Pictograms

**Hazard Statements**

Causes eye irritation.  
 May cause an allergic skin reaction.  
 Suspected of damaging fertility or the unborn child.  
 Suspected of causing cancer.

**Precautionary Statements****Prevention:**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Avoid breathing dust/fume/gas/mist/vapors/spray.  
 Wear protective gloves.  
 Wash thoroughly after handling.  
 Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical advice/attention.  
 IF ON SKIN: Wash with plenty of soap and water.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Wash contaminated clothing before reuse.  
 IF exposed or concerned: Get medical advice/attention.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

## SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Epoxy resin	25068-38-6	68 - 80 Trade Secret *
Ammonium Polyphosphate	68333-79-9	10 - 30 Trade Secret *
Titanium Dioxide	13463-67-7	1 - 5 Trade Secret *
Melamine	108-78-1	<= 0.5 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic skin reaction (redness, swelling, blistering, and itching).

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products****Substance**

Aldehydes

Hydrocarbons

Carbon monoxide

Carbon dioxide

Hydrogen Chloride

Ketones

Ammonia

Oxides of Nitrogen

Toxic Vapor, Gas, Particulate

**Condition**

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

**5.3. Special protective actions for fire-fighters**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent

material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Melamine	108-78-1	AIHA	TWA(inhalable particulates):3 mg/m <sup>3</sup>	
Titanium Dioxide	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m <sup>3</sup> ;TWA(Respirable finescale particles):2.5 mg/m <sup>3</sup>	A3: Confirmed animal carcin.
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m <sup>3</sup>	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance****Physical state**

Liquid

**Color**

White

**Specific Physical Form:**

Viscous Liquid

**Odor**

Epoxy

**Odor threshold***No Data Available***pH***No Data Available***Melting point***Not Applicable***Boiling Point***No Data Available***Flash Point**> 201 °F [*@ 1 atm*] [*Test Method: Closed Cup*]**Evaporation rate**

Negligible

**Flammability (solid, gas)**

Not Applicable

**Flammable Limits(LEL)***No Data Available***Flammable Limits(UEL)***No Data Available***Vapor Pressure***No Data Available***Vapor Density***No Data Available***Density**1.2 g/ml [*Ref Std: WATER=1*]**Specific Gravity**1.2 [*Ref Std: WATER=1*]**Solubility in Water**

Negligible

**Solubility- non-water***No Data Available***Partition coefficient: n-octanol/ water***No Data Available***Autoignition temperature***No Data Available***Decomposition temperature***No Data Available***Viscosity**60,000 - 80,000 centipoise [*Test Method: Brookfield*]**Hazardous Air Pollutants**0 % weight [*Test Method: Calculated*]**Molecular weight***No Data Available***VOC Less H2O & Exempt Solvents**0 g/l [*Test Method: calculated SCAQMD rule 443.1*]  
[*Details: when used as intended with Part A*]**VOC Less H2O & Exempt Solvents**0 g/l [*Test Method: calculated SCAQMD rule 443.1*] [*Details: as*]

VOC Less H2O & Exempt Solvents

supplied]  
0 % [*Test Method*:calculated SCAQMD rule 443.1]  
[*Details*:when used as intended with Part A]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

### 10.5. Incompatible materials

Strong acids

Strong oxidizing agents

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion:**

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:****Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Melamine	108-78-1	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Epoxy resin	Dermal	Rat	LD50 > 1,600 mg/kg
Epoxy resin	Ingestion	Rat	LD50 > 1,000 mg/kg
Ammonium Polyphosphate	Dermal	Rat	LD50 > 5,000 mg/kg
Ammonium Polyphosphate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 4.85 mg/l
Ammonium Polyphosphate	Ingestion	Rat	LD50 > 300, < 2,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Melamine	Dermal	Rabbit	LD50 > 1,000 mg/kg
Melamine	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.19 mg/l
Melamine	Ingestion	Rat	LD50 3,161 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Epoxy resin	Rabbit	Mild irritant
Ammonium Polyphosphate	In vitro data	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Melamine	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Epoxy resin	Rabbit	Moderate irritant
Ammonium Polyphosphate	Rabbit	Moderate irritant
Titanium Dioxide	Rabbit	No significant irritation

Melamine	Rabbit	No significant irritation
----------	--------	---------------------------

**Skin Sensitization**

Name	Species	Value
Epoxy resin	Human and animal	Sensitizing
Ammonium Polyphosphate	similar compounds	Not classified
Titanium Dioxide	Human and animal	Not classified
Melamine	Guinea pig	Not classified

**Respiratory Sensitization**

Name	Species	Value
Epoxy resin	Human	Not classified

**Germ Cell Mutagenicity**

Name	Route	Value
Epoxy resin	In vivo	Not mutagenic
Epoxy resin	In Vitro	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
Melamine	In Vitro	Not mutagenic
Melamine	In vivo	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Epoxy resin	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic
Melamine	Ingestion	Multiple animal species	Carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Epoxy resin	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy resin	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy resin	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
Epoxy resin	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Melamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,227 mg/kg/day	2 generation
Melamine	Ingestion	Not classified for development	Rat	NOAEL 1,060 mg/kg/day	during organogenesis



Melamine	Ingestion	Toxic to male reproduction	Rat	NOAEL 89 mg/kg/day	2 generation
----------	-----------	----------------------------	-----	--------------------	--------------

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Ammonium Polyphosphate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Epoxy resin	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Epoxy resin	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Epoxy resin	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Melamine	Ingestion	kidney and/or bladder	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 44.6 mg/kg/day	90 days
Melamine	Ingestion	heart   skin   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   respiratory system	Not classified	Rat	NOAEL 1,400 mg/kg/day	90 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material

and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** Not regulated

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### EPCRA 311/312 Hazard Classifications:

##### Physical Hazards

Not applicable

##### Health Hazards

Carcinogenicity

Reproductive toxicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

**NFPA Hazard Classification****Health: 2 Flammability: 1 Instability: 1 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	19-8269-3	<b>Version Number:</b>	10.04
<b>Issue Date:</b>	09/06/23	<b>Supersedes Date:</b>	09/22/22

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**