



Safety Data Sheet

Copyright,2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 10-2686-3 | Version Number: | 22.04 |
| Issue Date: | 07/27/22 | Supersedes Date: | 05/06/21 |

SECTION 1: Identification

1.1. Product identifier

3M(TM) Scotch-Weld(TM) Metal Primer 3901

Product Identification Numbers

| ID Number | UPC | ID Number | UPC |
|----------------|------------------|----------------|-----|
| 62-3901-3525-9 | 00-21200-21087-7 | 62-3901-3530-9 | |

7000000907, 7010367612

1.2. Recommended use and restrictions on use

Recommended use

Metal Primer, Primer

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

1.3. Supplier's details

| | |
|----------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | Industrial Adhesives and Tapes Division |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Flammable Liquid: Category 2.
 Acute Toxicity (oral): Category 3.
 Acute Toxicity (dermal): Category 4.
 Acute Toxicity (inhalation): Category 4.
 Serious Eye Damage/Irritation: Category 2B.
 Skin Sensitizer: Category 1.
 Reproductive Toxicity: Category 2.
 Specific Target Organ Toxicity (single exposure): Category 1.
 Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Skull and crossbones | Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

Highly flammable liquid and vapor.

Toxic if swallowed.

Harmful in contact with skin.

Causes eye irritation.

May cause an allergic skin reaction.

Harmful if inhaled.

May cause drowsiness or dizziness.

Suspected of damaging fertility or the unborn child.

Causes damage to organs:
sensory organs |

Precautionary Statements

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves, protective clothing, and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Rinse mouth.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see Notes to Physician on this label).

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Keep cool.

Keep container tightly closed.

Store locked up in a well-ventilated place.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Notes to Physician:

This product contains methanol. If there is a reasonable suspicion of methanol poisoning, intravenous (IV) administration with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management.

Supplemental Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|--------------------|------------|--------------------------|
| Methyl Alcohol | 67-56-1 | 99 - 99.9 Trade Secret * |
| Amino Silane | 1760-24-3 | < 0.5 Trade Secret * |
| Methylene Chloride | 75-09-2 | < 0.01 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Toxic if swallowed. Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

This product contains methanol. If there is a reasonable suspicion of methanol poisoning, intravenous (IV) administration with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management.

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products**Substance**

Formaldehyde
Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash

contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|--------------------|-------------------|---------------|--------------------------|--------------------------------|
| Methyl Alcohol | 67-56-1 | ACGIH | TWA:200 ppm;STEL:250 ppm | Danger of cutaneous absorption |
| Methyl Alcohol | 67-56-1 | OSHA | TWA:260 mg/m3(200 ppm) | |
| Methylene Chloride | 75-09-2 | ACGIH | TWA:50 ppm | A3: Confirmed animal carcin. |
| Methylene Chloride | 75-09-2 | OSHA | TWA:25 ppm;STEL:125 ppm | 29 CFR 1910.1052, SKIN |

ACGIH : American Conference of Governmental Industrial Hygienists
 AIHA : American Industrial Hygiene Association
 CMRG : Chemical Manufacturer's Recommended Guidelines
 OSHA : United States Department of Labor - Occupational Safety and Health Administration
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an

exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid

Color

Red

Odor

Strong Solvent

Odor threshold

No Data Available

pH

No Data Available

Melting point

No Data Available

Boiling Point

148 °F

Flash Point

52 °F [*Test Method*:Closed Cup]

Evaporation rate

5.9 [*Ref Std*:ETHER=1]

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

6 % volume

Flammable Limits(UEL)

36.5 % volume

Vapor Pressure

94 mmHg

Vapor Density

1.1 [*Ref Std*:AIR=1]

Density

0.80 g/ml

Specific Gravity

0.8 [*Ref Std*:WATER=1]

Solubility in Water

Soluble

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

3 - 8 centipoise

Hazardous Air Pollutants

98.9 - 99.3 % weight [*Test Method*:Calculated]

Molecular weight

No Data Available

VOC Less H₂O & Exempt Solvents

794 g/l [*Test Method*:calculated SCAQMD rule 443.1]

VOC Less H₂O & Exempt Solvents

99.3 % [*Test Method*:calculated per CARB title 2]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Harmful in contact with skin. Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Toxic if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

May cause blindness.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

| Ingredient | CAS No. | Class Description | Regulation |
|--------------------------------------|---------|-------------------------------|---|
| Dichloromethane (methylene chloride) | 75-09-2 | Grp. 2A: Probable human carc. | International Agency for Research on Cancer |
| DICHLOROMETHANE (METHYLENE CHLORIDE) | 75-09-2 | Anticipated human carcinogen | National Toxicology Program Carcinogens |
| METHYLENE CHLORIDE | 75-09-2 | Cancer hazard | OSHA Carcinogens |

Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--------------------|--------------------------------|---------|---|
| Overall product | Dermal | | No data available; calculated ATE >1,000 - =2,000 mg/kg |
| Overall product | Inhalation-Vapor(4 hr) | | No data available; calculated ATE >10 - =20 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >50 - =300 mg/kg |
| Methyl Alcohol | Dermal | | LD50 estimated to be 1,000 - 2,000 mg/kg |
| Methyl Alcohol | Inhalation-Vapor | | LC50 estimated to be 10 - 20 mg/l |
| Methyl Alcohol | Ingestion | | LD50 estimated to be 50 - 300 mg/kg |
| Amino Silane | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| Amino Silane | Inhalation-Dust/Mist (4 hours) | Rat | LC50 >1.49, <2.44 mg/l |
| Amino Silane | Ingestion | Rat | LD50 1,897 mg/kg |
| Methylene Chloride | Dermal | Rat | LD50 > 2,000 mg/kg |
| Methylene Chloride | Inhalation-Vapor (4 hours) | Rat | LC50 63.7 mg/l |
| Methylene Chloride | Ingestion | Rat | LD50 1,410 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--------------------|---------|---------------|
| Methyl Alcohol | Rabbit | Mild irritant |
| Amino Silane | Rabbit | Mild irritant |
| Methylene Chloride | Rabbit | Irritant |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--------------------|---------|-------------------|
| Methyl Alcohol | Rabbit | Moderate irritant |
| Amino Silane | Rabbit | Corrosive |
| Methylene Chloride | Rabbit | Severe irritant |

Skin Sensitization

| Name | Species | Value |
|----------------|------------|----------------|
| Methyl Alcohol | Guinea pig | Not classified |

| | | |
|--------------|-------------------------|-------------|
| Amino Silane | Multiple animal species | Sensitizing |
|--------------|-------------------------|-------------|

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|--------------------|----------|--|
| Methyl Alcohol | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Methyl Alcohol | In vivo | Some positive data exist, but the data are not sufficient for classification |
| Methylene Chloride | In vivo | Not mutagenic |
| Methylene Chloride | In Vitro | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|--------------------|------------|-------------------------|------------------|
| Methyl Alcohol | Inhalation | Multiple animal species | Not carcinogenic |
| Methylene Chloride | Inhalation | Multiple animal species | Carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|--------------------|------------|--|-------------------------|-----------------------|----------------------|
| Methyl Alcohol | Ingestion | Not classified for male reproduction | Rat | NOAEL 1,600 mg/kg/day | 21 days |
| Methyl Alcohol | Ingestion | Toxic to development | Mouse | LOAEL 4,000 mg/kg/day | during organogenesis |
| Methyl Alcohol | Inhalation | Toxic to development | Mouse | NOAEL 1.3 mg/l | during organogenesis |
| Methylene Chloride | Inhalation | Not classified for female reproduction | Rat | NOAEL 5.2 mg/l | 2 generation |
| Methylene Chloride | Inhalation | Not classified for male reproduction | Rat | NOAEL 5.2 mg/l | 2 generation |
| Methylene Chloride | Inhalation | Not classified for development | Multiple animal species | NOAEL 4.3 mg/l | during gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|----------------|------------|-----------------------------------|--|---------|---------------------|------------------------|
| Methyl Alcohol | Inhalation | blindness | Causes damage to organs | Human | NOAEL Not available | occupational exposure |
| Methyl Alcohol | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | not available |
| Methyl Alcohol | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL Not available | 6 hours |
| Methyl Alcohol | Ingestion | blindness | Causes damage to organs | Human | NOAEL Not available | poisoning and/or abuse |
| Methyl Alcohol | Ingestion | central nervous | May cause drowsiness or | Human | NOAEL Not | poisoning |

| | | | | | | |
|--------------------|------------|-----------------------------------|--|-------|---------------------|-----------------------|
| | | system depression | dizziness | | available | and/or abuse |
| Methylene Chloride | Dermal | blood | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL Not available | 4 hours |
| Methylene Chloride | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | occupational exposure |
| Methylene Chloride | Inhalation | blood | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Methylene Chloride | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--------------------|------------|------------------------|--|-------------------------|-----------------------|-------------------|
| Methyl Alcohol | Inhalation | liver | Not classified | Rat | NOAEL 6.55 mg/l | 4 weeks |
| Methyl Alcohol | Inhalation | respiratory system | Not classified | Rat | NOAEL 13.1 mg/l | 6 weeks |
| Methyl Alcohol | Ingestion | liver nervous system | Not classified | Rat | NOAEL 2,500 mg/kg/day | 90 days |
| Amino Silane | Inhalation | respiratory system | May cause damage to organs though prolonged or repeated exposure | Rat | NOAEL 0.015 mg/l | 90 days |
| Methylene Chloride | Inhalation | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 6.95 mg/l | 2 years |
| Methylene Chloride | Inhalation | liver | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 0.17 mg/l | 2 years |
| Methylene Chloride | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Multiple animal species | LOAEL 35 mg/l | 8 weeks |
| Methylene Chloride | Inhalation | heart | Not classified | Human | NOAEL Not available | |
| Methylene Chloride | Inhalation | immune system | Not classified | Rat | NOAEL 18 mg/l | 28 days |
| Methylene Chloride | Ingestion | liver | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 1,200 mg/kg/day | 3 months |
| Methylene Chloride | Ingestion | blood | Not classified | Rat | NOAEL 249 mg/kg/day | 2 years |
| Methylene Chloride | Ingestion | kidney and/or bladder | Not classified | Rat | NOAEL 1,469 mg/kg/day | 3 months |
| Methylene Chloride | Ingestion | eyes | Not classified | Rat | NOAEL 249 mg/kg/day | 104 weeks |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

Health Hazards

Acute toxicity

Reproductive toxicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

| <u>Ingredient</u> | <u>C.A.S. No</u> | <u>% by Wt</u> |
|-------------------|------------------|------------------------|
| Methyl Alcohol | 67-56-1 | Trade Secret 99 - 99.9 |

This material contains a chemical which requires export notification under TSCA Section 12[b]:

| <u>Ingredient (Category if applicable)</u> | <u>C.A.S. No</u> | <u>Regulation</u> | <u>Status</u> |
|--|------------------|--|---------------|
| Methylene Chloride | 75-09-2 | Toxic Substances Control Act (TSCA) 6 Banned or Restricted Use Chemicals | Applicable |

Additional TSCA Information

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 3 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 10-2686-3 | Version Number: | 22.04 |
| Issue Date: | 07/27/22 | Supersedes Date: | 05/06/21 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com