



Safety Data Sheet

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	05-6796-6	Version Number:	16.01
Issue Date:	03/09/22	Supersedes Date:	05/21/20

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive DP125 Translucent, Part A

Product Identification Numbers

LA-D100-2964-6

1.2. Recommended use and restrictions on use

Recommended use

Structural adhesive

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Industrial Adhesives and Tapes Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Skin Sensitizer: Category 1A.

Reproductive Toxicity: Category 1B.

Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms

**Hazard Statements**

May cause an allergic skin reaction.
 May cause drowsiness or dizziness.
 May damage fertility or the unborn child.

Precautionary Statements**Prevention:**

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Avoid breathing dust/fume/gas/mist/vapors/spray.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves.
 Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 IF exposed or concerned: Get medical advice/attention.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
 Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Supplemental Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Aliphatic Polymer Diamine	68911-25-1	85 - 99 Trade Secret *
Calcium Salt	55120-75-7	1 - 10 Trade Secret *
4,7,10-Trioxatridecane-1,13-Diamine	4246-51-9	< 5 Trade Secret *
Toluene	108-88-3	< 1 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

Hazardous Decomposition or By-Products**Substance**

Amine Compounds
Carbon monoxide
Carbon dioxide
Hydrogen Fluoride
Oxides of Nitrogen

Condition

During Combustion
During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions

on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe thermal decomposition products. For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant
Toluene	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use a positive pressure supplied-air respirator.

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid

Color

Light Amber

Specific Physical Form:

Viscous

Odor

Slight Amine

Odor threshold

No Data Available

pH

Not Applicable

Melting point

Not Applicable

Boiling Point

≥ 305 °F

Flash Point

305 °F [*Test Method*:Closed Cup]

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure

No Data Available

Vapor Density

No Data Available

Density

1.03 g/ml

Specific Gravity

1.03 [*Ref Std*:WATER=1]

Solubility in Water

Nil

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

42,000 centipoise [*@* 73.4 °F]

Hazardous Air Pollutants

0 % weight [*Test Method*:Calculated]

Molecular weight

No Data Available

VOC Less H₂O & Exempt Solvents

< 5 g/l [*Test Method*:calculated SCAQMD rule 443.1]
[*Details*:when used as intended with Part B]

VOC Less H₂O & Exempt Solvents

< 0.5 % [*Test Method*:calculated per CARB title 2]
[*Details*:when used as intended with Part B]

VOC Less H₂O & Exempt Solvents

< 10 g/l [*Test Method*:calculated SCAQMD rule 443.1]
[*Details*:as supplied]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5. Incompatible materials

Strong acids

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - ≤5,000 mg/kg
Aliphatic Polymer Diamine	Dermal	Rat	LD50 > 2,000 mg/kg
Aliphatic Polymer Diamine	Ingestion	Rat	LD50 > 2,000 mg/kg
Calcium Salt	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Calcium Salt	Ingestion	Rat	LD50 > 2,000 mg/kg
4,7,10-Trioxatridecane-1,13-Diamine	Dermal	Rabbit	LD50 2,500 mg/kg
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	Rat	LD50 3,160 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	In vitro data	No significant irritation
Aliphatic Polymer Diamine	Rat	Irritant
Calcium Salt	Rabbit	Minimal irritation
4,7,10-Trioxatridecane-1,13-Diamine	Rabbit	Corrosive
Toluene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	In vitro data	No significant irritation
Aliphatic Polymer Diamine	In vitro data	Severe irritant
Calcium Salt	Rabbit	Corrosive
4,7,10-Trioxatridecane-1,13-Diamine	similar health hazards	Corrosive
Toluene	Rabbit	Moderate irritant

Skin Sensitization

Name	Species	Value
Aliphatic Polymer Diamine	Guinea pig	Sensitizing
Calcium Salt	Guinea pig	Not classified
Toluene	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Aliphatic Polymer Diamine	In Vitro	Not mutagenic
Calcium Salt	In Vitro	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Aliphatic Polymer Diamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Aliphatic Polymer Diamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	29 days
Aliphatic Polymer Diamine	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Aliphatic Polymer Diamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	Irritation Positive	
Aliphatic Polymer Diamine	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	
Calcium Salt	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	

4,7,10-Trioxatridecane-1,13-Diamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Aliphatic Polymer Diamine	Ingestion	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days
Toluene	Inhalation	auditory system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105	4 weeks

					mg/kg/day	
--	--	--	--	--	-----------	--

Aspiration Hazard

Name	Value
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include HF. Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Not applicable

Health Hazards

Reproductive toxicity

Respiratory or Skin Sensitization

Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 **Flammability:** 1 **Instability:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

The NFPA Health code of 3 is due to emergency situations where the material may thermally decompose and release Hydrogen Fluoride. During normal use conditions, please reference Section 2 and Section 11 of the SDS for additional health hazard information.

Document Group:	05-6796-6	Version Number:	16.01
Issue Date:	03/09/22	Supersedes Date:	05/21/20

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com