



## Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document Group:** 08-9434-5  
**Issue Date:** 06/06/25

**Version Number:** 19.00  
**Supersedes Date:** 05/13/25

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Polyurethane Adhesive Sealant 560, White, Gray, Black

#### Product Identification Numbers

62-5487-3532-3, 62-5487-3932-5, 62-5487-3937-4, 62-5487-5230-2, 62-5487-8532-8, 62-5488-3532-1, 62-5488-3932-3, 62-5488-5230-0, 62-5495-3532-6, 62-5495-3932-8, 62-5495-5230-5, 62-5495-5238-8  
7000121524, 7100005901, 7000000945, 7100202624, 7100202627, 7100198015, 7100198012, 7100198014, 7100198011, 7100197998, 7100198013, 7100198010

#### 1.2. Recommended use and restrictions on use

##### Recommended use

One component, moisture curing product which forms permanent elastic bonds., Sealant

#### 1.3. Supplier's details

**MANUFACTURER:** 3M  
**DIVISION:** Industrial Adhesives and Tapes Division  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA  
**Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Respiratory Sensitizer: Category 1.  
Skin Sensitizer: Category 1A.  
Reproductive Toxicity: Category 2.  
Carcinogenicity: Category 2.  
Specific Target Organ Toxicity (single exposure): Category 1.  
Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Health Hazard |

### Pictograms



### Hazard Statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Suspected of causing cancer.

Causes damage to organs:

sensory organs |

Causes damage to organs through prolonged or repeated exposure:

nervous system |

respiratory system |

May cause damage to organs through prolonged or repeated exposure:

sensory organs |

### Precautionary Statements

#### Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

In case of inadequate ventilation wear respiratory protection.

Wear protective gloves.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

#### Response:

IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

#### Storage:

Store locked up.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

#### Supplemental Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

## SECTION 3: Composition/information on ingredients

| <b>Ingredient</b>                                | <b>C.A.S. No.</b> | <b>% by Wt</b>       |
|--|-------------------|----------------------|
| Urethane Polymer (NJTS Reg. No. 04499600-6718)   | Trade Secret*     | 30 - 40              |
| Plasticizer                                      | 70775-94-9        | 10 - 35              |
| Poly(Vinyl Chloride) Polymer                     | 9002-86-2         | 20 - 30              |
| Xylene   | 1330-20-7         | 3 - 6 Trade Secret * |
| Amorphous Silica                                 | 67762-90-7        | 1 - 5                |
| Titanium Dioxide                                 | 13463-67-7        | < 4.7                |
| Calcium Oxide                                    | 1305-78-8         | 1 - 3 Trade Secret * |
| p,p'-Methylenebis(phenyl isocyanate)             | 101-68-8          | 1 - 2 Trade Secret * |
| Petroleum Distillates                            | 64742-47-8        | 1 - 2 Trade Secret * |
| Ethylbenzene                                     | 100-41-4          | < 1.1 Trade Secret * |
| Carbon Black                                     | 1333-86-4         | < 0.3                |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate | 41556-26-7        | < 0.09               |

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### **If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects. See Section 11 for additional details. Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

**Substance**

Carbon monoxide  
Carbon dioxide  
Hydrogen Chloride  
Hydrogen Cyanide  
Oxides of Nitrogen  
Oxides of Sulfur

**Condition**

During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion

**5.3. Special protective actions for fire-fighters**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

**7.2. Conditions for safe storage including any incompatibilities**

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from amines.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient                           | C.A.S. No. | Agency | Limit type   | Additional Comments                       |
|--------------------------------------|------------|--------|--|---|
| Ethylbenzene                         | 100-41-4   | ACGIH  | TWA:20 ppm   | A3: Confirmed animal carcin., Ototoxicant |
| Ethylbenzene                         | 100-41-4   | OSHA   | TWA:435 mg/m3(100 ppm)   |   |
| p,p'-Methylenebis(phenyl isocyanate) | 101-68-8   | ACGIH  | TWA:0.005 ppm  |   |
| p,p'-Methylenebis(phenyl isocyanate) | 101-68-8   | OSHA   | CEIL:0.2 mg/m3(0.02 ppm)   |   |
| Calcium Oxide                        | 1305-78-8  | ACGIH  | TWA:2 mg/m3  |   |
| Calcium Oxide                        | 1305-78-8  | OSHA   | TWA:5 mg/m3  |   |
| Xylene                               | 1330-20-7  | ACGIH  | TWA:20 ppm   | A4: Not class. as human carcin            |
| Xylene                               | 1330-20-7  | OSHA   | TWA:435 mg/m3(100 ppm)   |   |
| Carbon Black                         | 1333-86-4  | ACGIH  | TWA(inhalable fraction):3 mg/m3  | A3: Confirmed animal carcin.              |
| Carbon Black                         | 1333-86-4  | OSHA   | TWA:3.5 mg/m3  |   |
| Titanium Dioxide                     | 13463-67-7 | ACGIH  | TWA(Respirable nanoscale particles):0.2 mg/m3;TWA(Respirable finescale particles):2.5 mg/m3                                      | A3: Confirmed animal carcin.              |
| Titanium Dioxide                     | 13463-67-7 | OSHA   | TWA(as total dust):15 mg/m3  |   |
| Kerosine (petroleum)                 | 64742-47-8 | ACGIH  | TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3   | A3: Confirmed animal carcin., SKIN        |
| MINERAL OILS, HIGHLY-REFINED OILS    | 64742-47-8 | ACGIH  | TWA(inhalable fraction):5 mg/m3  | A4: Not class. as human carcin            |
| SILICA, AMORPHOUS                    | 67762-90-7 | OSHA   | TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3   |   |
| DUST, INERT OR NUISANCE              | 9002-86-2  | OSHA   | TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m3);TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m3) |   |
| Poly(Vinyl Chloride) Polymer         | 9002-86-2  | ACGIH  | TWA(respirable fraction):1 mg/m3   | A4: Not class. as human carcin            |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

Physical state

Solid

Color

Multicolor

#### Specific Physical Form:

Paste

#### Odor

Mild Xylene

#### Odor threshold

*No Data Available*

#### pH

*Not Applicable*

#### Melting point

*No Data Available*

#### Boiling Point

$\geq 137^{\circ}\text{C}$

#### Flash Point

No flash point

#### Evaporation rate

*No Data Available*

#### Flammability (solid, gas)

Not Classified

#### Flammable Limits(LEL)

*Not Applicable*

#### Flammable Limits(UEL)

*Not Applicable*

#### Vapor Pressure

*Not Applicable*

#### Vapor Density

*Not Applicable*

#### Density

1.17 g/ml

#### Specific Gravity

1.17 [Ref Std: WATER=1]

#### Solubility in Water

Nil

#### Solubility- non-water

*No Data Available*

#### Partition coefficient: n-octanol/ water

*No Data Available*

#### Autoignition temperature

$\geq 200^{\circ}\text{C}$

#### Decomposition temperature

*No Data Available*

#### Viscosity

$\geq 300,000$  centipoise [ @  $73.4^{\circ}\text{F}$  ]

#### Hazardous Air Pollutants

6.2 % weight [ *Test Method*: Calculated ]

#### Molecular weight

*No Data Available*

#### VOC Less H<sub>2</sub>O & Exempt Solvents

56 g/l [ *Test Method*: tested per EPA method 24 ]

#### Solids Content

$> 95\%$

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Amines

Alcohols

Water

### 10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known.      |                  |

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

#### Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

**Prolonged or repeated exposure may cause target organ effects:**

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

| <b>Ingredient</b> | <b>CAS No.</b> | <b>Class Description</b>      | <b>Regulation</b>                           |
|-------------------|----------------|-------------------------------|---|
| Carbon black      | 1333-86-4      | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |
| Ethylbenzene      | 100-41-4       | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |
| Titanium dioxide  | 13463-67-7     | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

**Additional Information:**

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

| <b>Name</b>                  | <b>Route</b>                   | <b>Species</b> | <b>Value</b>                                   |
|------------------------------|--------------------------------|----------------|--|
| Overall product              | Dermal                         |                | No data available; calculated ATE >5,000 mg/kg |
| Overall product              | Inhalation-Vapor(4 hr)         |                | No data available; calculated ATE >50 mg/l     |
| Overall product              | Ingestion                      |                | No data available; calculated ATE >5,000 mg/kg |
| Plasticizer                  | Dermal                         | Rat            | LD50 > 1,000 mg/kg                             |
| Plasticizer                  | Ingestion                      | Rat            | LD50 > 5,000 mg/kg                             |
| Poly(Vinyl Chloride) Polymer | Dermal                         |                | LD50 estimated to be > 5,000 mg/kg             |
| Poly(Vinyl Chloride) Polymer | Ingestion                      |                | LD50 estimated to be > 5,000 mg/kg             |
| Xylene                       | Dermal                         | Rabbit         | LD50 > 4,200 mg/kg                             |
| Xylene                       | Inhalation-Vapor (4 hours)     | Rat            | LC50 29 mg/l                                   |
| Xylene                       | Ingestion                      | Rat            | LD50 3,523 mg/kg                               |
| Titanium Dioxide             | Dermal                         | Rabbit         | LD50 > 10,000 mg/kg                            |
| Titanium Dioxide             | Inhalation-Dust/Mist (4 hours) | Rat            | LC50 > 6.82 mg/l                               |
| Titanium Dioxide             | Ingestion                      | Rat            | LD50 > 10,000 mg/kg                            |
| Calcium Oxide                | Ingestion                      | Rat            | LD50 > 2,500 mg/kg                             |



|  |                                |                       |  |
|--|--------------------------------|-----------------------|--|
| Calcium Oxide                                      | Dermal                         | similar compounds     | LD50 > 2,500 mg/kg                       |
| p,p'-Methylenebis(phenyl isocyanate)               | Dermal                         | Rabbit                | LD50 > 5,000 mg/kg                       |
| p,p'-Methylenebis(phenyl isocyanate)               | Inhalation-Dust/Mist (4 hours) | Rat                   | LC50 0.368 mg/l                          |
| p,p'-Methylenebis(phenyl isocyanate)               | Ingestion                      | Rat                   | LD50 31,600 mg/kg                        |
| Amorphous Silica                                   | Dermal                         | Rabbit                | LD50 > 5,000 mg/kg                       |
| Amorphous Silica                                   | Inhalation-Dust/Mist (4 hours) | Rat                   | LC50 > 0.691 mg/l                        |
| Amorphous Silica                                   | Ingestion                      | Rat                   | LD50 > 5,110 mg/kg                       |
| Petroleum Distillates                              | Ingestion                      | Rat                   | LD50 > 15,000 mg/kg                      |
| Petroleum Distillates                              | Dermal                         | similar compounds     | LD50 > 5,000 mg/kg                       |
| Ethylbenzene                                       | Dermal                         | Rabbit                | LD50 15,433 mg/kg                        |
| Ethylbenzene                                       | Inhalation-Vapor (4 hours)     | Rat                   | LC50 17.4 mg/l                           |
| Ethylbenzene                                       | Ingestion                      | Rat                   | LD50 4,769 mg/kg                         |
| Carbon Black                                       | Dermal                         | Rabbit                | LD50 > 3,000 mg/kg                       |
| Carbon Black                                       | Ingestion                      | Rat                   | LD50 > 8,000 mg/kg                       |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny)l) sebacate | Dermal                         | Professional judgment | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny)l) sebacate | Ingestion                      | Rat                   | LD50 3,125 mg/kg                         |

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

| Name   | Species                 | Value                     |
|--|-------------------------|---------------------------|
| Poly(Vinyl Chloride) Polymer                       | Professional judgment   | No significant irritation |
| Xylene   | Rabbit                  | Mild irritant             |
| Titanium Dioxide                                   | Rabbit                  | No significant irritation |
| Calcium Oxide                                      | Human                   | Corrosive                 |
| p,p'-Methylenebis(phenyl isocyanate)               | official classification | Irritant                  |
| Amorphous Silica                                   | Rabbit                  | No significant irritation |
| Petroleum Distillates                              | similar compounds       | Mild irritant             |
| Ethylbenzene                                       | Rabbit                  | Mild irritant             |
| Carbon Black                                       | Rabbit                  | No significant irritation |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny)l) sebacate | Rabbit                  | Minimal irritation        |

### Serious Eye Damage/Irritation

| Name                                 | Species                 | Value                     |
|--------------------------------------|-------------------------|---------------------------|
| Overall product                      | Rabbit                  | Mild irritant             |
| Xylene                               | Rabbit                  | Mild irritant             |
| Titanium Dioxide                     | Rabbit                  | No significant irritation |
| Calcium Oxide                        | Rabbit                  | Corrosive                 |
| p,p'-Methylenebis(phenyl isocyanate) | official classification | Severe irritant           |
| Amorphous Silica                     | Rabbit                  | No significant irritation |
| Petroleum Distillates                | similar                 | No significant irritation |

|  | compounds |                           |
|--|-----------|---------------------------|
| Ethylbenzene                                       | Rabbit    | Moderate irritant         |
| Carbon Black                                       | Rabbit    | No significant irritation |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny)l) sebacate | Rabbit    | Mild irritant             |

**Skin Sensitization**

| Name   | Species           | Value          |
|--|-------------------|----------------|
| Titanium Dioxide                                   | Human and animal  | Not classified |
| p,p'-Methylenebis(phenyl isocyanate)               | Mouse             | Sensitizing    |
| Amorphous Silica                                   | Human and animal  | Not classified |
| Petroleum Distillates                              | similar compounds | Not classified |
| Ethylbenzene                                       | Human             | Not classified |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny)l) sebacate | Guinea pig        | Sensitizing    |

**Respiratory Sensitization**

| Name                                 | Species | Value       |
|--------------------------------------|---------|-------------|
| p,p'-Methylenebis(phenyl isocyanate) | Human   | Sensitizing |

**Germ Cell Mutagenicity**

| Name   | Route    | Value  |
|--|----------|--|
| Poly(Vinyl Chloride) Polymer                       | In Vitro | Not mutagenic  |
| Xylene   | In Vitro | Not mutagenic  |
| Xylene   | In vivo  | Not mutagenic  |
| Titanium Dioxide                                   | In Vitro | Not mutagenic  |
| Titanium Dioxide                                   | In vivo  | Not mutagenic  |
| Calcium Oxide                                      | In Vitro | Not mutagenic  |
| p,p'-Methylenebis(phenyl isocyanate)               | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Amorphous Silica                                   | In Vitro | Not mutagenic  |
| Petroleum Distillates                              | In Vitro | Not mutagenic  |
| Ethylbenzene                                       | In vivo  | Not mutagenic  |
| Ethylbenzene                                       | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Carbon Black                                       | In Vitro | Not mutagenic  |
| Carbon Black                                       | In vivo  | Some positive data exist, but the data are not sufficient for classification |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny)l) sebacate | In vivo  | Not mutagenic  |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny)l) sebacate | In Vitro | Some positive data exist, but the data are not sufficient for classification |

**Carcinogenicity**

| Name                         | Route         | Species                 | Value  |
|------------------------------|---------------|-------------------------|--|
| Poly(Vinyl Chloride) Polymer | Not Specified | Rat                     | Some positive data exist, but the data are not sufficient for classification |
| Xylene                       | Dermal        | Rat                     | Not carcinogenic   |
| Xylene                       | Ingestion     | Multiple animal species | Not carcinogenic   |
| Xylene                       | Inhalation    | Human                   | Some positive data exist, but the data are not sufficient for classification |
| Titanium Dioxide             | Ingestion     | Multiple animal species | Not carcinogenic   |

|                                      |               |                         |  |
|--------------------------------------|---------------|-------------------------|--|
| Titanium Dioxide                     | Inhalation    | Rat                     | Carcinogenic   |
| p,p'-Methylenebis(phenyl isocyanate) | Inhalation    | Rat                     | Some positive data exist, but the data are not sufficient for classification |
| Amorphous Silica                     | Not Specified | Mouse                   | Some positive data exist, but the data are not sufficient for classification |
| Ethylbenzene                         | Inhalation    | Multiple animal species | Carcinogenic   |
| Carbon Black                         | Dermal        | Mouse                   | Not carcinogenic   |
| Carbon Black                         | Ingestion     | Mouse                   | Not carcinogenic   |
| Carbon Black                         | Inhalation    | Rat                     | Carcinogenic   |

## Reproductive Toxicity

### Reproductive and/or Developmental Effects

| Name   | Route         | Value                                  | Species                 | Test Result           | Exposure Duration            |
|--|---------------|--|-------------------------|-----------------------|------------------------------|
| Poly(Vinyl Chloride) Polymer                     | Not Specified | Not classified for development         | Mouse                   | NOAEL Not available   | during gestation             |
| Xylene   | Inhalation    | Not classified for female reproduction | Human                   | NOAEL Not available   | occupational exposure        |
| Xylene   | Ingestion     | Not classified for development         | Mouse                   | NOAEL Not available   | during organogenesis         |
| Xylene   | Inhalation    | Not classified for development         | Multiple animal species | NOAEL Not available   | during gestation             |
| p,p'-Methylenebis(phenyl isocyanate)             | Inhalation    | Not classified for development         | Rat                     | NOAEL 0.004 mg/l      | during organogenesis         |
| Amorphous Silica                                 | Ingestion     | Not classified for female reproduction | Rat                     | NOAEL 509 mg/kg/day   | 1 generation                 |
| Amorphous Silica                                 | Ingestion     | Not classified for male reproduction   | Rat                     | NOAEL 497 mg/kg/day   | 1 generation                 |
| Amorphous Silica                                 | Ingestion     | Not classified for development         | Rat                     | NOAEL 1,350 mg/kg/day | during organogenesis         |
| Ethylbenzene                                     | Inhalation    | Not classified for development         | Rat                     | NOAEL 4.3 mg/l        | premating & during gestation |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate | Ingestion     | Not classified for male reproduction   | Rat                     | NOAEL 1,493 mg/kg/day | 29 days                      |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate | Ingestion     | Not classified for development         | Rat                     | NOAEL 209 mg/kg/day   | premating into lactation     |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate | Ingestion     | Toxic to female reproduction           | Rat                     | NOAEL 804 mg/kg/day   | premating into lactation     |

## Lactation

| Name   | Route     | Species | Value  |
|--------|-----------|---------|--|
| Xylene | Ingestion | Mouse   | Not classified for effects on or via lactation |

## Target Organ(s)

### Specific Target Organ Toxicity - single exposure

| Name   | Route      | Target Organ(s)                   | Value  | Species | Test Result         | Exposure Duration |
|--------|------------|-----------------------------------|--|---------|---------------------|-------------------|
| Xylene | Inhalation | auditory system                   | Causes damage to organs  | Rat     | LOAEL 6.3 mg/l      | 8 hours           |
| Xylene | Inhalation | central nervous system depression | May cause drowsiness or dizziness  | Human   | NOAEL Not available |                   |
| Xylene | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification | Human   | NOAEL Not available |                   |

|                                      |            |                                   |  |                         |                     |                       |
|--------------------------------------|------------|-----------------------------------|--|-------------------------|---------------------|-----------------------|
| Xylene                               | Inhalation | eyes                              | Not classified   | Rat                     | NOAEL 3.5 mg/l      | not available         |
| Xylene                               | Inhalation | liver                             | Not classified   | Multiple animal species | NOAEL Not available |                       |
| Xylene                               | Ingestion  | central nervous system depression | May cause drowsiness or dizziness  | Multiple animal species | NOAEL Not available |                       |
| Xylene                               | Ingestion  | eyes                              | Not classified   | Rat                     | NOAEL 250 mg/kg     | not applicable        |
| Calcium Oxide                        | Inhalation | respiratory irritation            | May cause respiratory irritation   | Not available           | NOAEL Not available | occupational exposure |
| p,p'-Methylenebis(phenyl isocyanate) | Inhalation | respiratory irritation            | May cause respiratory irritation   | official classification | NOAEL Not available |                       |
| Petroleum Distillates                | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification | similar health hazards  | NOAEL Not available |                       |
| Ethylbenzene                         | Inhalation | central nervous system depression | May cause drowsiness or dizziness  | Human                   | NOAEL Not available |                       |
| Ethylbenzene                         | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification | Human and animal        | NOAEL Not available |                       |

### Specific Target Organ Toxicity - repeated exposure

| Name                         | Route      | Target Organ(s)  | Value  | Species                 | Test Result           | Exposure Duration |
|------------------------------|------------|--|--|-------------------------|-----------------------|-------------------|
| Poly(Vinyl Chloride) Polymer | Inhalation | respiratory system   | Not classified   | Multiple animal species | NOAEL 0.013 mg/l      | 22 months         |
| Xylene                       | Inhalation | nervous system   | Causes damage to organs through prolonged or repeated exposure               | Rat                     | LOAEL 0.4 mg/l        | 4 weeks           |
| Xylene                       | Inhalation | auditory system  | May cause damage to organs through prolonged or repeated exposure            | Rat                     | LOAEL 7.8 mg/l        | 5 days            |
| Xylene                       | Inhalation | liver  | Not classified   | Multiple animal species | NOAEL Not available   |                   |
| Xylene                       | Inhalation | heart   endocrine system   gastrointestinal tract   hematopoietic system   muscles   kidney and/or bladder   respiratory system                | Not classified   | Multiple animal species | NOAEL 3.5 mg/l        | 13 weeks          |
| Xylene                       | Ingestion  | auditory system  | Not classified   | Rat                     | NOAEL 900 mg/kg/day   | 2 weeks           |
| Xylene                       | Ingestion  | kidney and/or bladder  | Not classified   | Rat                     | NOAEL 1,500 mg/kg/day | 90 days           |
| Xylene                       | Ingestion  | liver  | Not classified   | Multiple animal species | NOAEL Not available   |                   |
| Xylene                       | Ingestion  | heart   skin   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   respiratory system | Not classified   | Mouse                   | NOAEL 1,000 mg/kg/day | 103 weeks         |
| Titanium Dioxide             | Inhalation | respiratory system   | Some positive data exist, but the data are not sufficient for classification | Rat                     | LOAEL 0.01 mg/l       | 2 years           |
| Titanium Dioxide             | Inhalation | pulmonary fibrosis   | Not classified   | Human                   | NOAEL Not             | occupational      |

|   |            |   |  |                         | available             | exposure              |
|---|------------|---|--|-------------------------|-----------------------|-----------------------|
| p,p'-Methylenebis(phenyl isocyanate)              | Inhalation | respiratory system  | Causes damage to organs through prolonged or repeated exposure               | Rat                     | LOAEL 0.004 mg/l      | 13 weeks              |
| Amorphous Silica                                  | Inhalation | respiratory system   silicosis  | Not classified   | Human                   | NOAEL Not available   | occupational exposure |
| Petroleum Distillates                             | Inhalation | liver   | Not classified   | Rat                     | NOAEL 6 mg/l          | 13 weeks              |
| Petroleum Distillates                             | Inhalation | kidney and/or bladder   | Not classified   | Rat                     | LOAEL 1.5 mg/l        | 13 weeks              |
| Petroleum Distillates                             | Inhalation | hematopoietic system  | Not classified   | Rat                     | NOAEL 6 mg/l          | 13 weeks              |
| Petroleum Distillates                             | Ingestion  | liver   | Not classified   | Rat                     | NOAEL 1,000 mg/kg/day | 13 weeks              |
| Petroleum Distillates                             | Ingestion  | kidney and/or bladder   | Not classified   | Rat                     | LOAEL 100 mg/kg/day   | 13 weeks              |
| Petroleum Distillates                             | Ingestion  | hematopoietic system   eyes   | Not classified   | Rat                     | NOAEL 1,000 mg/kg/day | 13 weeks              |
| Ethylbenzene                                      | Inhalation | kidney and/or bladder   | Some positive data exist, but the data are not sufficient for classification | Rat                     | NOAEL 1.1 mg/l        | 2 years               |
| Ethylbenzene                                      | Inhalation | liver   | Some positive data exist, but the data are not sufficient for classification | Mouse                   | NOAEL 1.1 mg/l        | 103 weeks             |
| Ethylbenzene                                      | Inhalation | hematopoietic system  | Not classified   | Rat                     | NOAEL 3.4 mg/l        | 28 days               |
| Ethylbenzene                                      | Inhalation | auditory system   | Not classified   | Rat                     | NOAEL 2.4 mg/l        | 5 days                |
| Ethylbenzene                                      | Inhalation | endocrine system  | Not classified   | Mouse                   | NOAEL 3.3 mg/l        | 103 weeks             |
| Ethylbenzene                                      | Inhalation | gastrointestinal tract  | Not classified   | Rat                     | NOAEL 3.3 mg/l        | 2 years               |
| Ethylbenzene                                      | Inhalation | bone, teeth, nails, and/or hair   muscles   | Not classified   | Multiple animal species | NOAEL 4.2 mg/l        | 90 days               |
| Ethylbenzene                                      | Inhalation | heart   immune system   respiratory system  | Not classified   | Multiple animal species | NOAEL 3.3 mg/l        | 2 years               |
| Ethylbenzene                                      | Ingestion  | liver   kidney and/or bladder   | Not classified   | Rat                     | NOAEL 680 mg/kg/day   | 6 months              |
| Carbon Black                                      | Inhalation | pneumoconiosis  | Not classified   | Human                   | NOAEL Not available   | occupational exposure |
| Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate | Ingestion  | eyes  | Some positive data exist, but the data are not sufficient for classification | Rat                     | NOAEL 300 mg/kg/day   | 28 days               |
| Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate | Ingestion  | gastrointestinal tract   liver   immune system   heart   endocrine system   hematopoietic system   nervous system   kidney and/or bladder | Not classified   | Rat                     | NOAEL 1,493 mg/kg/day | 29 days               |

### Aspiration Hazard

| Name                  | Value             |
|-----------------------|-------------------|
| Xylene                | Aspiration hazard |
| Petroleum Distillates | Aspiration hazard |
| Ethylbenzene          | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

## Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

## Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact manufacturer for more information

#### EPCRA 311/312 Hazard Classifications:

##### Physical Hazards

Not applicable

##### Health Hazards

Carcinogenicity

Reproductive toxicity

Respiratory or Skin Sensitization

Specific target organ toxicity (single or repeated exposure)

#### Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

| <u>Ingredient</u>  | <u>C.A.S. No</u> | <u>% by Wt</u>     |
|--|------------------|--------------------|
| Xylene   | 1330-20-7        | Trade Secret 3 - 6 |
| Xylene (Benzene, dimethyl-)  | 1330-20-7        | Trade Secret 3 - 6 |
| p,p'-Methylenebis(phenyl isocyanate)   | 101-68-8         | Trade Secret 1 - 2 |
| p,p'-Methylenebis(phenyl isocyanate) (Benzene, 1,1'-methylenebis[4-isocyanato-]) | 101-68-8         | Trade Secret 1 - 2 |
| p,p'-Methylenebis(phenyl isocyanate) (DIISOCYANATES (CERTAIN CHEMICALS ONLY))    | 101-68-8         | Trade Secret 1 - 2 |

Ethylbenzene

100-41-4

Trade Secret &lt; 1.1

## 15.2. State Regulations

Contact manufacturer for more information

## 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. One or more chemical components of this material have been commercialized under the TSCA polymer exemption at 40CFR723.250. Polymers subject to this exemption are not listed on the TSCA Inventory, but are in compliance with TSCA requirements.

Contact manufacturer for more information

## 15.4. International Regulations

Contact manufacturer for more information

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: Other information

### NFPA Hazard Classification

**Health:** 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Document Group:** 08-9434-5

**Version Number:** 19.00

**Issue Date:** 06/06/25

**Supersedes Date:** 05/13/25

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**

