

Permabond®

Engineering Adhesives

SAFETY DATA SHEET

Permabond ET500A

1. Identification

Product identifier

Product name Permabond ET500A

Recommended use of the chemical and restrictions on use

Application Adhesive.

Details of the supplier of the safety data sheet

Supplier Permabond LLC
14 Robinson Street
Pottstown, PA 19464
USA
Telephone: 732-868-1372 or 800-640-7599
Website: www.permabond.com

Emergency telephone number

Emergency telephone Medical: Poison Control Center 866-827-6282 (toll free) or 303-389-1109 Transport: CHEMTREC 800-424-9300

2. Hazard(s) identification

Classification of the substance or mixture

OSHA Regulatory Status Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Skin Sens. 1 - H317

Label elements

Pictogram



Signal word Warning

Hazard statements H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Permabond ET500A

| | |
|---------------------------------|--|
| Precautionary statements | <p>P261 Avoid breathing vapor/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P272 Contaminated work clothing must not be allowed out of the workplace.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 If on skin: Wash with plenty of water.</p> <p>P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.</p> |
|---------------------------------|--|

Contains EPOXY RESIN (Number average MW <= 700)

3. Composition/information on ingredients

Mixtures

| | |
|---|----------------|
| EPOXY RESIN (Number average MW <= 700) | 60-100% |
| CAS number: 25068-38-6 | |
| Classification Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Skin Sens. 1 - H317 Not relevant. | |

The full text for all hazard statements is displayed in Section 16.

Composition comments Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. First-aid measures

Description of first aid measures

| | |
|---------------------|---|
| Inhalation | Move the exposed person to fresh air. Get medical attention if any discomfort continues. |
| Ingestion | Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention if any discomfort continues. |
| Skin Contact | Remove contaminated clothing. Wash skin thoroughly with soap and water. If symptoms develop, obtain medical attention |
| Eye contact | Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove any contact lenses and open eyelids wide apart. Get medical attention if any discomfort continues. |

Most important symptoms and effects, both acute and delayed

| | |
|---------------------|--|
| Skin contact | Causes skin irritation. May cause an allergic skin reaction. |
| Eye contact | Causes serious eye irritation. |

Indication of immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Permabond ET500A

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Hazardous combustion products Burning produces irritating, toxic and obnoxious fumes. Carbon monoxide, carbon dioxide, and unknown hydrocarbons.

Advice for firefighters

Protective actions during firefighting Use water to keep fire exposed containers cool and disperse vapors.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses.

Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Transfer to suitable, labelled containers for disposal.

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Avoid contact with skin, eyes and clothing. Do not breathe vapour/spray. Wash hands thoroughly after handling. Keep container tightly sealed when not in use.

Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Specific end uses(s)

Specific end use(s) Adhesive.

8. Exposure Controls/personal protection

Ingredient comments No exposure limits known for ingredient(s).

Exposure controls

Appropriate engineering controls Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for slashing or spraying exists.

Hand protection Nitrile rubber or Viton™ gloves are recommended. Cotton or other absorbent gloves should not be worn.

Other skin and body protection Employee must wear appropriate protective clothing and equipment to prevent any possibility of skin contact with this substance.

Permabond ET500A

| | |
|-------------------------------|--|
| Hygiene measures | Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Use of good industrial hygiene practices is required. |
| Respiratory protection | Respiratory protection may be required if excessive airborne contamination occurs. Use NIOSH approved respirator if there is potential to exceed exposure limit(s). |

9. Physical and Chemical Properties

Information on basic physical and chemical properties

| | |
|---|---|
| Appearance | Liquid. |
| Color | Colorless. |
| Odor | Mild. |
| Odor threshold | No information available. |
| pH | Not relevant. |
| Melting point | Not available. |
| Initial boiling point and range | Not relevant. |
| Flash point | >100°C |
| Evaporation rate | Not available. |
| Evaporation factor | Not available. |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or explosive limits | Not available. |
| Vapor pressure | Not available. |
| Vapor density | Not available. |
| Relative density | 1.17 |
| Solubility(ies) | Insoluble in water. Soluble in the following materials: Organic solvents. |
| Partition coefficient | Not available. |
| Auto-ignition temperature | Not applicable. |
| Decomposition Temperature | Not available. |
| Viscosity | ~15000 mPa s @ 23°C |
| Explosive properties | Not relevant. |
| Oxidizing properties | Not applicable. |
| Other information | Not relevant. |
| Volatile organic compound | <2 %, 20 grams/liter (Estimated) |

10. Stability and reactivity

| | |
|-------------------|---|
| Reactivity | The following materials may react with the product: Strong oxidizing agents. Acids. |
| Stability | Stable at normal ambient temperatures. Polymerizes when heated. |

PermaBond ET500A

| | |
|---|--|
| Possibility of hazardous reactions | Reactions with the following materials may generate heat: Amines. |
| Conditions to avoid | Do not store near heat sources or expose to high temperatures. |
| Materials to avoid | Amines. Strong oxidizing agents. |
| Hazardous decomposition products | Thermal decomposition could produce carbon monoxide, carbon dioxide, and unidentified organic compounds. |

11. Toxicological information

Information on toxicological effects

Toxicological effects The toxicological properties of this product have not been fully evaluated. Use of good industrial hygiene practices is required. Avoid direct contact with skin or eyes. Do not ingest or inhale.

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Skin sensitization

Skin sensitization May cause sensitisation by skin contact.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Inhalation

Unlikely to be hazardous by inhalation because of the low vapor pressure of the product at ambient temperature. In high concentrations, vapors may irritate throat and respiratory system and cause coughing.

Ingestion

No harmful effects expected from quantities likely to be ingested by accident.

Skin Contact

Irritating to skin. May cause sensitisation by skin contact.

Eye contact

Irritating and may cause redness and pain.

Toxicological information on ingredients.

PermaBond ET500A

EPOXY RESIN (Number average MW <= 700)

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 11,400.0

Species Rat

ATE oral (mg/kg) 11,400.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.1

Species Rabbit

ATE dermal (mg/kg) 2,000.1

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No specific test data are available.

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Animal data Edema score: Very slight oedema - barely perceptible (1).

Serious eye damage/irritation

Serious eye damage/irritation Not irritating.

Respiratory sensitization

Respiratory sensitization No specific test data are available.

Skin sensitization

Skin sensitization Local Lymph Node Assay (LLNA) - Mouse: Sensitizing.

Germ cell mutagenicity

Genotoxicity - in vitro Conclusive data but not sufficient for classification.

Carcinogenicity

Carcinogenicity Conclusive data but not sufficient for classification.

Reproductive toxicity

Reproductive toxicity - fertility Fertility - NOAEL 750 mg/kg/day, Oral, Rat

Reproductive toxicity - development Developmental toxicity: - NOAEL: 180 mg/kg/day, Oral, Rat

Specific target organ toxicity - single exposure

STOT - single exposure No specific test data are available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Conclusive data but not sufficient for classification.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

PermaBond ET500A

12. Ecological Information

Toxicity No data available.

Bioaccumulative potential

Partition coefficient Not available.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information Empty containers may contain product residue; follow SDS and label warnings even after they have been emptied.

Disposal methods Dispose of according to Federal, State and local governmental regulations.

14. Transport information

Sea transport notes Applies only to inner containers >5 litres. See 2.10.2.7 of the IMDG code.

Air transport notes Applies only to inner containers >5 liters. See SP A197 (375)

DOT transport notes Applies only to inner containers >5 liters. See CFR 49173.155 and 172.102.173

UN Number

3082

UN No. (TDG) 3082

UN No. (DOT) 3082

UN proper shipping name

Environmentally hazardous substance, liquid, n.o.s. (contains Epoxy resin)

Transport hazard class(es)

9

Transport labels



Packing group

III

Environmental hazards

Environmentally Hazardous Substance



15. Regulatory information

US Federal Regulations

Permabond ET500A

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None above reporting levels

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None above reporting limits

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None above reporting limits

SARA 313 Emission Reporting

None above reporting limits

SARA (311/312) Hazard Categories

Acute
Chronic

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm

Inventories

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None above reporting limits

16. Other information

| | |
|----------------------------------|--|
| Revision date | 1/26/2018 |
| Revision | 2 |
| Supersedes date | 5/5/2015 |
| Hazard statements in full | H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.