

SAFETY DATA SHEET Permabond 940

1. Identification

Product identifier

Product name Permahond 940

Recommended use of the chemical and restrictions on use

Application Adhesive.

Details of the supplier of the safety data sheet

Supplier Permabond LLC

14 Robinson Street Pottstown, PA 19464

USA

Telephone: 732-868-1372 or 800-640-7599

Website: www.permabond.com

Emergency telephone number

Emergency telephone Medical: Poison Control Center 866-827-6282 (toll free) or 303-389-1109 Transport:

CHEMTREC 800-424-9300

2. Hazard(s) identification

Classification of the substance or mixture

OSHA Regulatory Status Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200)

and is consistent with the provisions of the United Nations Globally Harmonized System of

Classification and Labeling of Chemicals (GHS).

Physical hazards Not Classified

Health hazards Not Classified

Label elements

Hazard statements NC Not Classified

Other hazards

None under normal conditions.

3. Composition/information on ingredients

Mixtures

Composition comments None of the ingredients are required to be listed.

4. First-aid measures

Description of first aid measures

Inhalation Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give

oxygen. If symptoms develop and persist, get medical attention.

Ingestion On contact, immediate bonding of mouth could occur. Do not induce vomiting. Get medical

attention.

Permabond 940

Skin Contact On contact, immediate bonding of the skin will occur. No attempt should be made to remove

material from skin or to remove contaminated clothing, as the bonded skin can be easily torn.

Wash skin thoroughly with soap and water.

Eye contact Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. If adhesive

bonding occurs, do not force eyelids apart. Apply a pad soaked in warm water and allow the eyelids to separate. Get medical attention. Cured adhesive will not bond well to surface of

eye, but corneal damage from abrasion may result.

Most important symptoms and effects, both acute and delayed

Inhalation Irritation of nose, throat and airway.

Ingestion On contact, immediate bonding of mouth could occur.

Skin contact Prolonged skin contact may cause redness and irritation.

Eye contact Irritating and may cause redness and pain.

Indication of immediate medical attention and special treatment needed

Notes for the doctor SKIN BONDING. Prise the skin apart slowly working from the edge of the bonded area. This

can be eased by using warm soapy water. EYE BONDING. DO NOT force eyelids apart.

Apply a pad soaked in warm water and allow the eye to separate itself.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Special hazards arising from the substance or mixture

Specific hazards Cloths used to wipe up spills may cause rapid polymerization that could generate sufficient

heat to ignite the cloth.

Hazardous combustion

products

Trace amounts of toxic and/or irritating organic vapors may be generated. The use of

breathing apparatus is recommended.

Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapors.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. Provide adequate ventilation.

Environmental precautions

Environmental precautions Ventilate area. Prevent product from entering drains or waterways.

Methods and material for containment and cleaning up

Methods for cleaning up Small spills: wipe up with cloth. Immediately soak cloth with water to polymerize the adhesive.

Caution! Cloth containing adhesive may undergo autoignition if not soaked with water Large

spills: flood area with water. When cured, remove film with a scraper.

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

7. Handling and storage

Permabond 940

Precautions for safe handling

Do not breathe vapor and mist. Wash thoroughly after handling. Keep away from fabric and paper goods. Contact with these materials may cause rapid polymerization which can

generate smoke and strong irritating vapors and cause thermal burns.

Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry and cool place. Keep away from heat, sparks

and open flame. Keep container closed when not in use.

Specific end uses(s)

Specific end use(s) Adhesive.

8. Exposure Controls/personal protection

Ingredient commentsNo exposure limits known for ingredient(s).

Exposure controls

Appropriate engineering

controls

Use positive down draft exhaust ventilation if general ventilation is insufficient to maintain

vapor concentrations below established exposure limits.

Eye/face protection Wear approved safety goggles. Use face shield in case of splash risk.

Hand protection Nitrile rubber or Viton™ gloves are recommended. Cotton or other absorbent gloves should

not be worn.

Other skin and body

protection

Uniforms, coveralls, or a lab coat should be worn

Respiratory protectionNo specific recommendations. Respiratory protection must be used if the airborne

contamination exceeds the recommended occupational exposure limit.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Liquid.

Color Colorless.

Odor Pungent. Irritating.

Odor threshold 1 - 2 ppm

pH Not applicable.

Melting point Not applicable.

Initial boiling point and range >149°C (300°F)

Flash point $80^{\circ}\text{C} - 93^{\circ}\text{C} (176^{\circ}\text{F} - 199.94^{\circ}\text{F})$

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or

explosive limits

Not available.

Vapor pressure ~0.6 mbar @ 25°C

Vapor density Not applicable.

Relative density 1.1

Permabond 940

Bulk density Not applicable.

Solubility(ies) Hardens in contact with water. Insoluble in water. Miscible with the following materials:

acetone

Partition coefficient Not applicable.

Auto-ignition temperature Not available.

Decomposition Temperature Not available.

Viscosity ≈5 mPa s @ 23°C

Volatile organic compound <2 %, 20 grams/liter (Estimated)

10. Stability and reactivity

Reactivity The product reacts with water and will generate heat.

Stability Stable at normal ambient temperatures and when used as recommended.

Possibility of hazardous

reactions

Reactions with the following materials may generate heat: Water Alcohols. Alkalis. Amines.

Conditions to avoid Do not add water directly to the product. It may cause a violent reaction.

Materials to avoid Water. Amines. Alkalis. Alcohols.

Hazardous decomposition

products

Toxic/Irritating fumes

11. Toxicological information

Information on toxicological effects

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

Permabond 940

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Inhalation The product is considered to be a low hazard under normal conditions of use. May cause

discomfort.

Ingestion On contact, immediate bonding of mouth could occur.

Skin Contact On contact, immediate bonding of the skin will occur. Prolonged skin contact may cause

temporary irritation.

Eye contact Prolonged and frequent contact may cause redness and irritation. On contact, will bond

eyelids together. Vapours are lachrymatory.

Route of exposure Ingestion Inhalation Skin and/or eye contact

12. Ecological Information

Ecotoxicity There are no data on the ecotoxicity of this product.

Bioaccumulative potential

Partition coefficient Not applicable.

13. Disposal considerations

Waste treatment methods

General information Empty containers may contain product residue; follow SDS and label warnings even after they

have been emptied.

Disposal methods Dispose of according to Federal, State and local governmental regulations.

14. Transport information

Sea transport notes Not classified.

Air transport notes Applies only to inner containers > 500ml. Inner packaging containing less than 500ml are

unregulated for air transportation and may be shipped unrestricted. But inner packages containing more than 500ml meet the criteria of IATA 3.9.2.1 and are regulated. The "inner package" is the individual bottle, tube or drum, not the outer packaging such as a fiberboard

box or carton containing many bottles.

Permabond 3g, 20gr, 1 ounce (28.4 gr), 1 pound (454gr) and 500ml, are not restricted for air

transportation.

DOT transport notesThis product is not regulated for road transportation in accordance with 49 CFR Exceptions.

Please note that Cyanoacrylates are not restricted for domestic ground transportation in non bulk containers (The DOT defines a bulk container as a "Package" containing more than 450 liters. The "Package" is the individual bottle, tube or drum, not a carton containing many

bottles

UN Number

UN No. (IMDG) Not Regulated

UN No. (ICAO) 3334

UN No. (DOT) NA1993

UN proper shipping name

Permabond 940

Proper shipping name (IMDG) Not regulated

Proper shipping name (ICAO) AVIATION REGULATED LIQUID, N.O.S. (contains 2-methoxyethyl 2-cyanoacrylate)

Proper shipping name (DOT) COMBUSTIBLE LIQUID, N.O.S. (Cyanoacrylate ester)

Transport hazard class(es)

DOT hazard class Combustible Liquid

IMDG Class Not applicable

ICAO class/division 9

Packing group

IMDG packing group Not Applicable

ICAO packing group III

DOT packing group III

Environmental hazards

Environmentally Hazardous Substance

No.

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None above reporting levels

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None above reporting limits

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None above reporting limits

SARA 313 Emission Reporting

None above reporting limits

SARA (311/312) Hazard Categories

Acute Chronic Fire Reactivity

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm

Inventories

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US-TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None above reporting limits

Permabond 940

16. Other information

Revision date 1/25/2018

Revision 3

Supersedes date 5/5/2015

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.