

SAFETY DATA SHEET Permabond 101

1. Identification

Product identifier

Product name Permahond 101

Recommended use of the chemical and restrictions on use

Application Adhesive.

Details of the supplier of the safety data sheet

Supplier Permabond LLC

14 Robinson Street Pottstown, PA 19464

USA

Telephone: 732-868-1372 or 800-640-7599

Website: www.permabond.com

Emergency telephone number

Emergency telephone Medical: Poison Control Center 866-827-6282 (toll free) or 303-389-1109 Transport:

CHEMTREC 800-424-9300

2. Hazard(s) identification

Classification of the substance or mixture

OSHA Regulatory Status Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200)

and is consistent with the provisions of the United Nations Globally Harmonized System of

Classification and Labeling of Chemicals (GHS).

Physical hazards Flam. Liq. 4 - H227

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 STOT SE 3 - H335

Label elements

Hazard symbols



Signal word Warning

Hazard statements H227 Combustible liquid.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

Permabond 101

Precautionary statements P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.

P261 Avoid breathing vapor/ spray.

P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/ doctor if you feel unwell.
P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Contains ETHYL 2-CYANOACRYLATE

Other hazards

None under normal conditions.

3. Composition/information on ingredients

Mixtures

ETHYL 2-CYANOACRYLATE

60-100%

CAS number: 7085-85-0

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 STOT SE 3 - H335

The full text for all hazard statements is displayed in Section 16.

Composition comments Exact percentage is a trade secret. Concentration range is provided to assist users in

providing appropriate protections.

4. First-aid measures

Description of first aid measures

Inhalation Get medical attention if any discomfort continues.

Ingestion On contact, immediate bonding of mouth could occur. Do not induce vomiting. Get medical

attention.

Skin Contact On contact, immediate bonding of the skin will occur. No attempt should be made to remove

material from skin or to remove contaminated clothing, as the bonded skin can be easily torn.

Wash skin thoroughly with soap and water.

Eye contact Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. If adhesive

bonding occurs, do not force eyelids apart. Apply a pad soaked in warm water and allow the eyelids to separate. Get medical attention. Cured adhesive will not bond well to surface of

eye, but corneal damage from abrasion may result.

Permabond 101

Most important symptoms and effects, both acute and delayed

Inhalation Irritation of nose, throat and airway.

Ingestion On contact, immediate bonding of mouth could occur.

Skin contact Prolonged skin contact may cause redness and irritation.

Eye contact Irritating and may cause redness and pain.

Indication of immediate medical attention and special treatment needed

Notes for the doctor SKIN BONDING. Prise the skin apart slowly working from the edge of the bonded area. This

can be eased by using warm soapy water. EYE BONDING. DO NOT force eyelids apart.

Apply a pad soaked in warm water and allow the eye to separate itself.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Special hazards arising from the substance or mixture

Specific hazards Cloths used to wipe up spills may cause rapid polymerization that could generate sufficient

heat to ignite the cloth.

Hazardous combustion

products

Decomposes upon heating to release toxic fumes of nitrogen oxides, carbon monoxide,

carbon dioxide, and hydrogen cyanide.

Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapors.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. Provide adequate ventilation.

Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

Methods and material for containment and cleaning up

Methods for cleaning up Small spills: wipe up with cloth. Immediately soak cloth with water to polymerize the adhesive.

Caution! Cloth containing adhesive may undergo autoignition if not soaked with water Large

spills: flood area with water. When cured, remove film with a scraper.

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Ensure adequate ventilation of the working area. Avoid contact with skin, eyes and clothing.

Avoid breathing vapours. Always replace cap after use.

Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry and cool place. Keep away from heat, sparks

and open flame. Keep container tightly sealed when not in use.

Permabond 101

Specific end uses(s)

Specific end use(s) Adhesive.

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

ETHYL 2-CYANOACRYLATE

Long-term exposure limit (8-hour TWA): ACGIH 0.2 ppm Short-term exposure limit (15-minute): ACGIH 1 ppm

DSens, RSens

ACGIH = American Conference of Governmental Industrial Hygienists.

DSens = Dermal sensitizer. RSens = Respiratory sensitizer.

Exposure controls

Appropriate engineering

controls

Observe any occupational exposure limits for the product or ingredients. Mechanical

ventilation or local exhaust ventilation may be required.

Chemical splash goggles or face shield. Personal protective equipment for eye and face Eye/face protection

protection should comply with OSHA 1910.133.

Hand protection Nitrile rubber or Viton™ gloves are recommended. Cotton or other absorbent gloves should

not be worn.

Other skin and body

protection

Uniforms, coveralls, or a lab coat should be worn

Respiratory protection No specific recommendations. Respiratory protection must be used if the airborne

contamination exceeds the recommended occupational exposure limit.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance Liquid. Color Colorless. Odor Pungent.

Odor threshold 1 - 2 ppm

pН Not applicable. Melting point Not applicable.

Initial boiling point and range >149°C (300°F)

Flash point 80°C - 93°C (176°F - 199.94°F)

Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or Not available.

explosive limits

Vapor pressure ~0.6 mbar @ 25°C

Vapor density Not applicable.

Relative density 1.05

Bulk density Not applicable.

Permabond 101

Solubility(ies) Hardens in contact with water. Insoluble in water. Miscible with the following materials:

acetone

Partition coefficient Not available.

Auto-ignition temperature Not available.

Decomposition Temperature Not available.

Viscosity ≈3 mPa s @ 23°C

Oxidizing properties Not applicable.

Volatile organic compound <2 %, 20 grams/liter (Estimated)

10. Stability and reactivity

Reactivity The product reacts with water and will generate heat.

Stability Stable at normal ambient temperatures and when used as recommended.

Possibility of hazardous

reactions

Reactions with the following materials may generate heat: Water Alcohols. Alkalis. Amines.

Conditions to avoid Do not add water directly to the product. It may cause a violent reaction.

Materials to avoid Water. Amines. Alkalis. Alcohols.

Hazardous decomposition

products

 $Heating \ may \ generate \ the \ following \ products: \ Toxic \ gases/vapors/fumes \ of: \ Carbon \ dioxide$

(CO2). Carbon monoxide (CO). Nitrous gases (NOx). Hydrogen cyanide (HCN).

11. Toxicological information

Information on toxicological effects

Toxicological effectsThe toxicological properties of this product have not been fully evaluated. Avoid direct contact

with skin or eyes. Do not ingest or inhale.

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitizationBased on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

Permabond 101

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H335

Target organs Respiratory system, lungs

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after a single exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

. . .

Inhalation May cause respiratory system irritation.

Ingestion On contact, immediate bonding of mouth could occur.

Skin Contact On contact, immediate bonding of the skin will occur. May cause skin irritation.

Eye contact Irritating to eyes. On contact, will bond eyelids together. Vapours are lachrymatory.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target Organs Respiratory system, lungs

Toxicological information on ingredients.

ETHYL 2-CYANOACRYLATE

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Not available.

Skin corrosion/irritation

Animal data Dose: 0.5g, 24 hours, Rabbit Slightly irritating.

Serious eye damage/irritation

Serious eye

damage/irritation

Method: OECD 405, Rabbit Irritating to eyes.

Skin sensitization

Skin sensitization - Guinea pig: Not sensitizing.

Germ cell mutagenicity

Genotoxicity - in vitroGene mutation: Negative. Chromosome aberration: Negative. Bacterial reverse

mutation test: Negative.

Carcinogenicity

Carcinogenicity No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Reproductive toxicity -

Technically not feasible.

fertility

Reproductive toxicity -

development

Technically not feasible.

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

Permabond 101

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard Not available.

12. Ecological information

Ecotoxicity There are no data on the ecotoxicity of this product.

Bioaccumulative potential

Partition coefficient Not available.

13. Disposal considerations

Waste treatment methods

General information Dispose of according to Federal, State/Provincial and local regulations. Refer to section 8

before handling.

14. Transport information

Sea transport notes Not classified.

Air transport notes Applies only to inner containers > 500ml. Inner packaging containing less than 500ml are

unregulated for air transportation and may be shipped unrestricted. But inner packages containing more than 500ml meet the criteria of IATA 3.9.2.1 and are regulated. The "inner package" is the individual bottle, tube or drum, not the outer packaging such as a fiberboard

box or carton containing many bottles.

Permabond 3g, 20gr, 1 ounce (28.4 gr), 1 pound (454gr) and 500ml, are not restricted for air

transportation.

DOT transport notesThis product is not regulated for road transportation in accordance with 49 CFR Exceptions.

Please note that Cyanoacrylates are not restricted for domestic ground transportation in non bulk containers (The DOT defines a bulk container as a "Package" containing more than 450 liters. The "Package" is the individual bottle, tube or drum, not a carton containing many

bottles

UN Number

UN No. (IMDG) Not applicable

UN No. (ICAO) 3334

UN No. (DOT) NA1993

UN proper shipping name

Proper shipping name (IMDG) Not applicable

Proper shipping name (ICAO) AVIATION REGULATED LIQUID, N.O.S (Cyanoacrylate ester)

Proper shipping name (DOT) COMBUSTIBLE LIQUID, N.O.S. (Cyanoacrylate ester)

Transport hazard class(es)

IMDG Class Not applicable

ICAO class/division 9

Packing group

IMDG packing group Not applicable

ICAO packing group

Permabond 101

DOT packing group

Environmental hazards

Environmentally Hazardous Substance

No.

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None above reporting limits.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None above reporting limits

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None above reporting limits

SARA 313 Emission Reporting

None above reporting limits

SARA (311/312) Hazard Categories

Acute Chronic Fire

Reactivity

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm

Inventories

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US-TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None above reporting limits

16. Other information

Classification abbreviations Eye Irrit. = Eye irritation

and acronyms Skin Irrit. = Skin irritation

STOT SE = Specific target organ toxicity-single exposure

Revision date 12/14/2021

Revision 5

Supersedes date 10/1/2018

Hazard statements in full H227 Combustible liquid.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

Permabond 101

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.