



SAFETY DATA SHEET

Permabond 922

1. Identification

Product identifier

Product name Permabond 922

Recommended use of the chemical and restrictions on use

Application Adhesive.

Details of the supplier of the safety data sheet

Supplier Permabond LLC
 14 Robinson Street
 Pottstown, PA 19464
 USA
 Telephone: 732-868-1372 or 800-640-7599
 Website: www.permabond.com

Emergency telephone number

Emergency telephone Medical: Poison Control Center 866-827-6282 (toll free) or 303-389-1109 Transport: CHEMTREC 800-424-9300

2. Hazard(s) identification

Classification of the substance or mixture

OSHA Regulatory Status Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Physical hazards Flam. Liq. 4 - H227

Health hazards Not Classified

Label elements

Signal word Warning

Hazard statements H227 Combustible liquid.

Precautionary statements P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
 P403+P235 Store in a well-ventilated place. Keep cool.
 Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Other hazards

None under normal conditions.

3. Composition/information on ingredients

Mixtures

Permabond 922

Composition comments This product does not contain any hazardous ingredients, or ingredients with national workplace exposure limits.

4. First-aid measures

Description of first aid measures

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.

Ingestion On contact, immediate bonding of mouth could occur. Do not induce vomiting. Get medical attention.

Skin Contact On contact, immediate bonding of the skin will occur. No attempt should be made to remove material from skin or to remove contaminated clothing, as the bonded skin can be easily torn. Wash skin thoroughly with soap and water.

Eye contact Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. If adhesive bonding occurs, do not force eyelids apart. Apply a pad soaked in warm water and allow the eyelids to separate. Get medical attention. Cured adhesive will not bond well to surface of eye, but corneal damage from abrasion may result.

Most important symptoms and effects, both acute and delayed

Inhalation Irritation of nose, throat and airway.

Ingestion On contact, immediate bonding of mouth could occur.

Skin contact Prolonged skin contact may cause redness and irritation.

Eye contact Irritating and may cause redness and pain.

Indication of immediate medical attention and special treatment needed

Notes for the doctor SKIN BONDING. Prise the skin apart slowly working from the edge of the bonded area. This can be eased by using warm soapy water. EYE BONDING. DO NOT force eyelids apart. Apply a pad soaked in warm water and allow the eye to separate itself.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Special hazards arising from the substance or mixture

Specific hazards Cloths used to wipe up spills may cause rapid polymerization that could generate sufficient heat to ignite the cloth.

Hazardous combustion products Decomposes upon heating to release toxic fumes of nitrogen oxides, carbon monoxide, carbon dioxide, and hydrogen cyanide.

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapors.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. Provide adequate ventilation.

Environmental precautions

Permabond 922

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses.

Methods and material for containment and cleaning up

Methods for cleaning up Small spills: wipe up with cloth. Immediately soak cloth with water to polymerize the adhesive. Caution! Cloth containing adhesive may undergo autoignition if not soaked with water Large spills: flood area with water. When cured, remove film with a scraper.

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Ensure adequate ventilation of the working area. Avoid contact with skin and eyes. Always replace cap after use.

Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry and cool place. Keep away from heat, sparks and open flame. Keep container tightly sealed when not in use.

Specific end uses(s)

Specific end use(s) Adhesive.

8. Exposure controls/Personal protection

Ingredient comments No exposure limits known for ingredient(s).

Exposure controls

Appropriate engineering controls Good general ventilation should be adequate to control worker exposure to airborne contaminants.

Eye/face protection Use approved safety goggles or face shield.

Hand protection Nitrile rubber or Viton™ gloves are recommended. Cotton or other absorbent gloves should not be worn.

Other skin and body protection Uniforms, coveralls, or a lab coat should be worn

Respiratory protection No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance Liquid.

Color Colorless.

Odor Pungent. Irritating.

Odor threshold 1 - 2 ppm

pH Not applicable.

Melting point Not applicable.

Initial boiling point and range >149°C (300°F)

Flash point 95°C

Evaporation rate Not available.

Permabond 922

Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not available.
Vapor pressure	<0.5 mbar @ 25°C
Vapor density	Not applicable.
Relative density	1.1
Bulk density	Not applicable.
Solubility(ies)	Hardens in contact with water. Insoluble in water. Miscible with the following materials: acetone
Partition coefficient	Not applicable.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	≈1600 mPa s @ 23°C
Volatile organic compound	<2 %, 20 grams/liter (Estimated)

10. Stability and reactivity

Reactivity	The product reacts with water and will generate heat.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	Reactions with the following materials may generate heat: Water Alcohols. Alkalis. Amines.
Conditions to avoid	Do not add water directly to the product. It may cause a violent reaction.
Materials to avoid	Water. Amines. Alkalis. Alcohols.
Hazardous decomposition products	Toxic/Irritating fumes

11. Toxicological information

Information on toxicological effects

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Permabond 922

Carcinogenicity	Does not contain any substances known to be carcinogenic.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Based on available data the classification criteria are not met.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.
Inhalation	The product is considered to be a low hazard under normal conditions of use. May cause discomfort.
Ingestion	On contact, immediate bonding of mouth could occur.
Skin Contact	On contact, immediate bonding of the skin will occur. Prolonged skin contact may cause temporary irritation.
Eye contact	Prolonged and frequent contact may cause redness and irritation. On contact, will bond eyelids together. Vapours are lachrymatory.
Route of exposure	Ingestion Inhalation Skin and/or eye contact

12. Ecological information

Ecotoxicity	There are no data on the ecotoxicity of this product.
<u>Bioaccumulative potential</u>	
Partition coefficient	Not applicable.

13. Disposal considerations

Waste treatment methods

General information	Empty containers may contain product residue; follow SDS and label warnings even after they have been emptied.
Disposal methods	Dispose of according to Federal, State/Provincial and local regulations. Refer to section 8 before handling.

14. Transport information

Sea transport notes	Not classified.
Air transport notes	Applies only to inner containers > 500ml. Inner packaging containing less than 500ml are unregulated for air transportation and may be shipped unrestricted. But inner packages containing more than 500ml meet the criteria of IATA 3.9.2.1 and are regulated. The "inner package" is the individual bottle, tube or drum, not the outer packaging such as a fiberboard box or carton containing many bottles. Permabond 3g, 20gr, 1 ounce (28.4 gr), 1 pound (454gr) and 500ml, are not restricted for air transportation.

Permabond 922

DOT transport notes This product is not regulated for road transportation in accordance with 49 CFR Exceptions. Please note that Cyanoacrylates are not restricted for domestic ground transportation in non bulk containers (The DOT defines a bulk container as a "Package" containing more than 450 liters. The "Package" is the individual bottle, tube or drum, not a carton containing many bottles

UN Number

UN No. (IMDG) Not Regulated

UN No. (ICAO) 3334

UN No. (DOT) NA1993

UN proper shipping name

Proper shipping name (IMDG) Not regulated

Proper shipping name (ICAO) AVIATION REGULATED LIQUID, N.O.S. (contains allyl 2-cyanoacrylate)

Proper shipping name (DOT) COMBUSTIBLE LIQUID, N.O.S. (Cyanoacrylate ester)

Transport hazard class(es)

DOT hazard class Combustible Liquid

IMDG Class Not applicable

ICAO class/division 9

Packing group

IMDG packing group Not Applicable

ICAO packing group III

DOT packing group III

Environmental hazards

Environmentally Hazardous Substance

No.

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None above reporting limits.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None above reporting limits

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None above reporting limits

SARA 313 Emission Reporting

None above reporting limits

SARA (311/312) Hazard Categories

Acute
Chronic
Fire
Reactivity

US State Regulations

PermaBond 922

California Proposition 65 Carcinogens and Reproductive Toxins

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm

Inventories

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None above reporting limits

16. Other information

Classification abbreviations and acronyms	Flam. Liq. = Flammable liquid
Revision date	2/10/2021
Revision	5
Supersedes date	10/1/2018
Hazard statements in full	H227 Combustible liquid.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.