

1 Identification

- **Product identifier**
- **Trade name:** *Urethane 51606LV BLACK PART A*
- **Article number:** UR51606LVBPT A
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Resin Designs, LLC
11 State Street
WOBURN, MA 01801
USA
epoznysz@resindesigns.com
- **Information department:** Product safety department
- **Emergency telephone number:** During normal opening times: +1 (781) 935-3133

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Harmful

Harmful by inhalation. Limited evidence of a carcinogenic effect. Harmful: danger of serious damage to health by prolonged exposure through inhalation.



Irritant

Irritating to eyes, respiratory system and skin. May cause sensitisation by inhalation and skin contact.

- **Information concerning particular hazards for human and environment:**

The product has to be labeled due to the calculation procedure of international guidelines.

- **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- **Label elements**

- **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with directives on hazardous materials.

(Contd. on page 2)

Trade name: *Urethane 51606LV BLACK PART A*

(Contd. of page 1)

· **Code letter and hazard designation of product:**

Harmful

· **Hazard-determining components of labeling:**4,4'-methylenediphenyl diisocyanate
methylenediphenyl diisocyanate· **Risk phrases:**Harmful by inhalation.
Irritating to eyes, respiratory system and skin.
Limited evidence of a carcinogenic effect.
May cause sensitisation by inhalation and skin contact.
Harmful: danger of serious damage to health by prolonged exposure through inhalation.· **Safety phrases:**Keep locked up and out of the reach of children.
Do not breathe dust.
Wear suitable protective clothing and gloves.
In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Dispose of this material and its container to hazardous or special waste collection point.
In case of accident by inhalation: remove casualty to fresh air and keep at rest.· **Special labeling of certain preparations:**

Contains isocyanates. See information supplied by the manufacturer.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**Health = 3
Fire = 1
Reactivity = 0· **HMIS-ratings (scale 0 - 4)**Health = *2
Fire = 1
Reactivity = 0· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.**3 Composition/information on ingredients**· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

101-68-8	4,4'-methylenediphenyl diisocyanate	50-100%
26447-40-5	methylenediphenyl diisocyanate	10-25%

US

(Contd. on page 3)

Trade name: *Urethane 51606LV BLACK PART A*

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Thorough dedusting.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of dust.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.

(Contd. on page 4)

Trade name: *Urethane 51606LV BLACK PART A*

(Contd. of page 3)

- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

101-68-8 4,4'-methylenediphenyl diisocyanate

PEL	Ceiling limit value: 0.2 mg/m ³ , 0.02 ppm
REL	Long-term value: 0.05 mg/m ³ , 0.005 ppm Ceiling limit value: 0.2* mg/m ³ , 0.02* ppm *10-min
TLV	Long-term value: 0.051 mg/m ³ , 0.005 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

US

(Contd. on page 5)

Trade name: *Urethane 51606LV BLACK PART A*

(Contd. of page 4)

9 Physical and chemical properties· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**· **Form:** Liquid· **Color:** Clear· **Odor:** Characteristic· **Odour threshold:** Not determined.· **pH-value:** Not applicable.· **Change in condition**· **Melting point/Melting range:** Undetermined.· **Boiling point/Boiling range:** 208 °C (406 °F)· **Flash point:** 212 °C (414 °F)· **Flammability (solid, gaseous):** Not determined.· **Ignition temperature:** 520 °C (968 °F)· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** Product does not present an explosion hazard.· **Explosion limits:**· **Lower:** 0.4 Vol %· **Upper:** Not determined.· **Vapor pressure:** Not applicable.· **Density at 20 °C (68 °F):** 1.2 g/cm³ (10.014 lbs/gal)· **Relative density** Not determined.· **Vapour density** Not applicable.· **Evaporation rate** Not applicable.· **Solubility in / Miscibility with**· **Water:** Insoluble.· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**· **Dynamic:** Not applicable.· **Kinematic:** Not applicable.· **Solvent content:**· **Organic solvents:** 0.0 %· **Solids content:** 100.0 %· **Other information** No further relevant information available.**10 Stability and reactivity**· **Reactivity**· **Chemical stability**· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.· **Possibility of hazardous reactions** No dangerous reactions known.· **Conditions to avoid** No further relevant information available.

(Contd. on page 6)

Trade name: *Urethane 51606LV BLACK PART A*

(Contd. of page 5)

- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2200 mg/kg (mouse)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

- **Sensitization:**

Sensitization possible through inhalation.
Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

101-68-8 4,4'-methylenediphenyl diisocyanate

3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

US

(Contd. on page 7)

Trade name: *Urethane 51606LV BLACK PART A*

(Contd. of page 6)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, ADN, IMDG, IATA	not regulated
· UN proper shipping name	
· DOT, ADN, IMDG, IATA	not regulated
· Transport hazard class(es)	
· DOT, ADN, IMDG, IATA	
· Class	not regulated
· Packing group	
· DOT, IMDG, IATA	not regulated
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	-

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture	
· Sara	
· Section 355 (extremely hazardous substances):	None of the ingredients is listed.
· Section 313 (Specific toxic chemical listings):	101-68-8 4,4'-methylenediphenyl diisocyanate
· TSCA (Toxic Substances Control Act):	All ingredients are listed.
· Proposition 65	
· Chemicals known to cause cancer:	None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for females:	None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for males:	None of the ingredients is listed.

(Contd. on page 8)

Trade name: *Urethane 51606LV BLACK PART A*

(Contd. of page 7)

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

101-68-8 4,4'-methylenediphenyl diisocyanate

D, CBD

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**

Harmful

· **Hazard-determining components of labeling:**4,4'-methylenediphenyl diisocyanate
methylenediphenyl diisocyanate· **Risk phrases:**Harmful by inhalation.
Irritating to eyes, respiratory system and skin.
Limited evidence of a carcinogenic effect.
May cause sensitisation by inhalation and skin contact.
Harmful: danger of serious damage to health by prolonged exposure through inhalation.· **Safety phrases:**Keep locked up and out of the reach of children.
Do not breathe dust.
Wear suitable protective clothing and gloves.
In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Dispose of this material and its container to hazardous or special waste collection point.
In case of accident by inhalation: remove casualty to fresh air and keep at rest.· **Special labeling of certain preparations:**

Contains isocyanates. See information supplied by the manufacturer.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** Mr. Edward Poznysz, VP of Technologies: epoznysz@resindesigns.com
- **Date of preparation / last revision** 05/27/2015 / -
- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation

(Contd. on page 9)

Trade name: Urethane 51606LV BLACK PART A

(Contd. of page 8)

IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Carc. 2: Carcinogenicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

US