

CONATHANE® EN-21 PART A Urethane Prepolymer (1G)

Version 4 Revision Date 03/08/2021 Print Date 03/08/2021

SECTION 1. IDENTIFICATION

Product name : CONATHANE® EN-21 PART A Urethane Prepolymer (1G)

Manufacturer or supplier's details

Company : ELANTAS PDG, INC.

5200 North 2nd Street St. Louis MO 63147

Telephone : (314) 621-5700 Visit our web site : www.elantas.com

E-mail address : Todd.Thomas@altana.com

Emergency telephone

number

INFOTRAC - 1-800-535-5053

Recommended use of the chemical and restrictions on use

Recommended use : Casting Resin

Restrictions on use : This product is for industrial use only. It is not intended for

consumer use or retail sale.

Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Specific target organ toxicity

- single exposure

: Category 3 (Respiratory system)

Specific target organ toxicity

- repeated exposure

: Category 2

GHS label elements



CONATHANE® EN-21 PART A Urethane Prepolymer (1G)

Version 4 Revision Date 03/08/2021 Print Date 03/08/2021

Hazard pictograms





Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or

repeated exposure.

Precautionary statements : **Prevention**:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

P285 In case of inadequate ventilation wear respiratory

protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/

doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

Disposal:



CONATHANE® EN-21 PART A Urethane Prepolymer (1G)

Version 4 Revision Date 03/08/2021 Print Date 03/08/2021

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Isocyanate Prepolymer

Hazardous components

Component	CAS-No.	Concentration (%)
Isocyanates	101-68-8	>= 37 - < 38
Diphenylmethane Diisocyanate	25686-28-6	>= 15 - < 16
Methylenediphenyl diisocyanate	26447-40-5	>= 1 -< 2

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Call a physician or poison control centre immediately.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES



CONATHANE® EN-21 PART A Urethane Prepolymer (1G)

Version 4 Revision Date 03/08/2021 Print Date 03/08/2021

Unsuitable extinguishing

media

: High volume water jet

Further information : Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage : Store under conditions specified on the product Technical

Data Sheet to maintain product quality.

Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.



CONATHANE® EN-21 PART A Urethane Prepolymer (1G)

Version 4 Revision Date 03/08/2021 Print Date 03/08/2021

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Isocyanates	101-68-8	TWA	0.005 ppm	ACGIH
Isocyanates		С	0.02 ppm	OSHA Z-1
			0.2 mg/m3	
Methylenediphenyl	26447-40-5	С	0.02 ppm	OSHA Z-1
diisocyanate			0.2 mg/m3	
Methylenediphenyl		С	0.02 ppm	OSHA P0
diisocyanate			0.2 mg/m3	

Hazardous components without workplace control parameters

Engineering measures : Use with adequate ventilation.

All application areas should be ventilated in accordance with applicable OSHA regulations. (e.g. 29 CFR 1910.94) Isocyanates may be released during the curing process. Repeated overexposure to isocyanates can cause respiratory

tract sensitization.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an

approved filter.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES



CONATHANE® EN-21 PART A Urethane Prepolymer (1G)

Version 4 Revision Date 03/08/2021 Print Date 03/08/2021

Appearance : liquid

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

: No data available

Vapour pressure : No data available

Flash point : $> 201 \, ^{\circ}\text{F} \, (> 94 \, ^{\circ}\text{C})$

Method: No information available.

Information taken from reference works and the literature.

Upper explosion limit : No data available

Lower explosion limit : No data available

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Relative vapour density : No data available

Relative Density/Specific

Gravity

: No data available

Density : 1.14 g/cm3 (77 °F (25 °C))

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Ignition temperature : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 21 mm2/s (104 °F (40 °C))



CONATHANE® EN-21 PART A Urethane Prepolymer (1G)

Version 4 Revision Date 03/08/2021 Print Date 03/08/2021

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : No data available

Hazardous decomposition

products

: Carbon monoxide in a fire. Nitrogen oxides in a fire.

Isocyanates

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 2.77 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Components:

101-68-8 Isocyanates:

Acute oral toxicity : LD50 (Rat): 2,200 mg/kg

LD50 (Rat, male and female): > 2,000 mg/kg Method: Tested according to Annex V of Directive

67/548/EEC. GLP: yes

Acute inhalation toxicity : LC50 (Rat): 178 mg/l

LC50 (Rat, male): 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: yes

Acute dermal toxicity : (Rabbit): > 10,000 mg/kg



CONATHANE® EN-21 PART A Urethane Prepolymer (1G)

Version 4 Revision Date 03/08/2021 Print Date 03/08/2021

25686-28-6 Diphenylmethane Diisocyanate:

Acute oral toxicity : LD50 (Rat, female): > 5,000 mg/kg

Method: OECD Test Guideline 425

GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 9,400 mg/kg

Method: OECD Test Guideline 402

26447-40-5 Methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 (Rat): 15,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 490 ppm

Acute dermal toxicity : LD50 : Remarks: No data available

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

101-68-8 Isocyanates:

Species: Rabbit

Result: Mild skin irritation

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: yes

25686-28-6 Diphenylmethane Diisocyanate:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Skin irritation

GLP: yes

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Components:

101-68-8 Isocyanates:

Species: Rabbit

Result: Moderate eye irritation

Method: Draize Test

Species: Rabbit

Result: No eye irritation



CONATHANE® EN-21 PART A Urethane Prepolymer (1G)

Version 4 Revision Date 03/08/2021 Print Date 03/08/2021

Method: OECD Test Guideline 405

25686-28-6 Diphenylmethane Diisocyanate:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

GLP: yes

Respiratory or skin sensitisation

Product:

Remarks: Causes sensitisation.

Components:

101-68-8 Isocyanates:

Species: Guinea pig Method: Draize Test

Result: Causes sensitisation.

Test Type: Buehler Test Exposure routes: Dermal Species: Guinea pig

Method: OECD Test Guideline 406 Result: Does not cause skin sensitisation.

GLP: yes

25686-28-6 Diphenylmethane Diisocyanate:

Test Type: Maximisation Test

Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

GLP: yes

Species: Rat

Result: May cause sensitisation by inhalation.

GLP: yes

Germ cell mutagenicity

Components:

101-68-8 Isocyanates:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test

Test species: Rat (male) Application Route: Inhalation



CONATHANE® EN-21 PART A Urethane Prepolymer (1G)

Version 4 Revision Date 03/08/2021 Print Date 03/08/2021

Exposure time: 3x1 h/ day over 3 weeks Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity-

Assessment

: In vitro tests did not show mutagenic effects, In vivo tests did

not show mutagenic effects

Carcinogenicity

Components:

101-68-8 Isocyanates:

Species: Rat, (male and female)

Exposure time: 2 hrs Dose: 0 - 0,2 - 1 - 6 mg/m3

Frequency of Treatment: 6 hours/day, 5 days/ week

Method: OECD Test Guideline 453

Carcinogenicity - : Suspected of causing cancer if inhaled.

Assessment

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Components:

101-68-8 Isocyanates:

Effects on foetal : Species: Rat, female

development Application Route: Inhalation Dose: 0 - 1 - 4 - 12 mg/m3

12 mg/m3 4 mg/m3

Number of exposures: 6 hours/day Method: OECD Test Guideline 414

Reproductive toxicity -

Assessment

: Based on available data, the classification criteria are not met.

Did not show teratogenic effects in animal experiments.

STOT - single exposure

Components:



CONATHANE® EN-21 PART A Urethane Prepolymer (1G)

Version 4 Revision Date 03/08/2021 Print Date 03/08/2021

101-68-8 Isocyanates:

Exposure routes: Inhalation
Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Components:

101-68-8 Isocyanates:

Exposure routes: Inhalation
Target Organs: Respiratory Tract

Assessment: May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

101-68-8 Isocyanates:

Species: Rat, male and female

NOAEL: 0,2 mg/m3

Application Route: Inhalation

Exposure time: 2 hrs

Number of exposures: 6 hours/ day, 5 days/ week

Dose: 0 - 0,2 - 1 - 6 mg/m3

Method: OECD Test Guideline 453 Target Organs: Lungs, Nasal inner lining

Repeated dose toxicity - : Harmful if inhaled., The product causes irritation of eyes, skin

Assessment and mucous membranes.

Aspiration toxicity

Components:

101-68-8 Isocyanates:

No aspiration toxicity classification

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available



CONATHANE® EN-21 PART A Urethane Prepolymer (1G)

Version 4 Revision Date 03/08/2021 Print Date 03/08/2021

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a

Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

: WC: B

EPA Hazardous Waste

Code(s)

: none

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.



CONATHANE® EN-21 PART A Urethane Prepolymer (1G)

Version 4 Revision Date 03/08/2021 Print Date 03/08/2021

National Regulations

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Isocyanates	101-68-8	5000	13186

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA

harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for

reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This product contains the following toxic chemical(s) subject

to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and

40 CFR part 372.

Isocyanates 101-68-8 37.9 %

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61): Isocyanates 101-68-8 37.9 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):



CONATHANE® EN-21 PART A Urethane Prepolymer (1G)

Version 4 Revision Date 03/08/2021 Print Date 03/08/2021

Isocyanates 101-68-8 37.9 %

Non-volatile (Wt) : Refer to the product technical data sheet for VOC information.

Massachusetts Right To Know

Isocyanates 101-68-8

Pennsylvania Right To Know

Castor Oil MDI Polymer -

Isocyanates 101-68-8
Diphenylmethane Diisocyanate 25686-28-6
Benzoyl Chloride 98-88-4

New Jersey Right To Know

Castor Oil MDI Polymer -

Isocyanates 101-68-8
Diphenylmethane Diisocyanate 25686-28-6
Methylenediphenyl diisocyanate 26447-40-5

New Jersey Trade Secret : Not Applicable

Registry Number for the product (NJ TSRN)

California Prop. 65

MARNING: This product can expose you to chemicals including Ethyl acrylate, which is/are known to the State of California to cause cancer, and Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : All components of this product are listed active and/or are

exempt

Section 4 / 12(b) : Not applicable

Section 5 Not applicable

Section 6 Not applicable




CONATHANE® EN-21 PART A Urethane Prepolymer (1G)

Version 4 Revision Date 03/08/2021 Print Date 03/08/2021

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard

HMIS III:

HEALTH	3*
FLAMMABILITY	1
PHYSICAL HAZARD	1

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

Revision Date : 03/08/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.