

Reviewed on 02/12/2018

1 Identification

Product identifier

Trade name: URETHANE 1006 BLACK PART A

Article number: UR 1006 BLK PT A

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Resin Designs 11 State Street WOBURN, MA 01801

Information department: Product safety department

Emergency telephone number:

Within the U.S. call Chemtrec: +1 (800) 262-8200 Outside the U.S. call Chemtrec: +1 (703) 741-5500

2 Hazard(s) identification

Classification of the substance or mixture



GHS06 Skull and crossbones

Acute Tox. 2 H330 Fatal if inhaled.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







- Signal word Danger
- · Hazard-determining components of labeling:

4,4'-methylenedi(cyclohexyl isocyanate)

Hazard statements

H330 Fatal if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 2)



Reviewed on 02/12/2018

Trade name: URETHANE 1006 BLACK PART A

(Contd. of page 1)

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray. P260

Wash thoroughly after handling. P264

Use only outdoors or in a well-ventilated area. P271

Contaminated work clothing must not be allowed out of the workplace. P272

Wear protective gloves / eye protection / face protection. P280

[In case of inadequate ventilation] wear respiratory protection. P284

If on skin: Wash with plenty of soap and water. P302+P352

IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

Immediately call a poison center/doctor. P310 Specific treatment is urgent (see on this label). P320

Take off contaminated clothing and wash it before reuse. P362+P364 If skin irritation or rash occurs: Get medical advice/attention. P333+P313 P337+P313 If eye irritation persists: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor. P342+P311

Wash contaminated clothing before reuse. P363

Store in a well-ventilated place. Keep container tightly closed. P403+P233

Store locked up. P405

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

· Classification system:

NFPA ratings (scale 0 - 4)



Health = 2Fire = 1Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = *2 1 Fire = 1 Reactivity = 0

- · Other hazards Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- •vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

5124-30-1 4,4'-methylenedi(cyclohexyl isocyanate)

25-50%



Reviewed on 02/12/2018

Trade name: URETHANE 1006 BLACK PART A

(Contd. of page 2)

4 First-aid measures

- *Description of first aid measures
- «General information:

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- *After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

0.015 ppm
0.29 ppm

(Contd. on page 4)



Reviewed on 02/12/2018

Trade name: URETHANE 1006 BLACK PART A

(Contd. of page 3)

7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- * Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- Control parameters
- · Components with limit values that require monitoring at the workplace:

5124-30-1 4,4'-methylenedi(cyclohexyl isocyanate)

REL Ceiling limit value: 0.11 mg/m³, 0.01 ppm

TLV Long-term value: 0.054 mg/m³, 0.005 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

*Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



Reviewed on 02/12/2018

Trade name: URETHANE 1006 BLACK PART A

Penetration time of glove material

(Contd. of page 4)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

Information on basic physical and o	chemical properties	
General Information Appearance:		
Appearance: Color:	Black	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	251 °C (483.8 °F)	
Flash point:	200 °C (392 °F)	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	0.0 Vol %	
Upper:	0.0 Vol %	
Vapor pressure:	Not determined.	
Density at 25 °C (77 °F):	1.00 g/cm³ (8.345 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:	.8	
VOC content:	0.00 %	



Reviewed on 02/12/2018

Trade name: URETHANE 1006 BLACK PART A

(Contd. of page 5)

Other information

No further relevant information available.

10 Stability and reactivity

- Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:
- LD/LC50 values that are relevant for classification:

5124-30-1 4,4'-methylenedi(cyclohexyl isocyanate)

Oral	LD50	18,200 mg/kg (rat)
Dermal	LD50	>7,000 mg/kg (rat)
Inhalative	LC50/4 h	0.464 mg/l (rat)

- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eve: Irritating effect.
- Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

Harmful

Irritant

Very toxic

- Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

·OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

(Contd. on page 7)

(Contd. of page 6)



Safety Data Sheet acc. to OSHA HCS

Reviewed on 02/12/2018

Trade name: URETHANE 1006 BLACK PART A

· Behavior in environmental systems:

· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment

- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

4 4	F 8 3			
	1000 1300	וידמנו	1111/100	133 IS E178 PS
_				mation

· UN-Number	
· DOT	UN3082
· ADN, IMDG	not regulated
TATA	I INI2224

UN proper shipping name

Environmentally hazardous substances, liquid, n.o.s. (4,4'-

methylenedi(cyclohexyl isocyanate))

• ADN, IMDG not regulated

Aviation regulated liquid, n.o.s. (4,4'-methylenedi(cyclohexyl isocyanate))

- · Transport hazard class(es)
- · DOT, IATA



* Class 9 Miscellaneous dangerous substances and articles

Label

ADN/R Class: not regulated

Packing group

DOT, IATA

• IMDG not regulated

· Environmental hazards:

Marine pollutant: No

(Contd. on page 8)



Reviewed on 02/12/2018

Trade name: URETHANE 1006 BLACK PART A

(Contd. of page 7) Not applicable.

· Special precautions for user

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

Transport/Additional information:

· DOT

 Quantity limitations On passenger aircraft/rail: No limit

On cargo aircraft only: No limit

• UN "Model Regulation": not regulated

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):

5124-30-1 4,4'-methylenedi(cyclohexyl isocyanate)

TSCA (Toxic Substances Control Act):

All ingredients are listed.

- Proposition 65
- Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Carcinogenic categories
- EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS06

GHS07



Reviewed on 02/12/2018

Trade name: URETHANE 1006 BLACK PART A

(Contd. of page 8)

Signal word Danger

Hazard-determining components of labeling:

4,4'-methylenedi(cyclohexyl isocyanate)

Hazard statements

H330 Fatal if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

*Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection. P284 [In case of inadequate ventilation] wear respiratory protection.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor. Specific treatment is urgent (see on this label). P320

Take off contaminated clothing and wash it before reuse. P362+P364 P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse. P363

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Mr. Edward Poznysz, VP of Technologies: epoznysz@resindesigns.com
- · Date of preparation / last revision 02/12/2018 / 2
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 10)



Reviewed on 02/12/2018

Trade name: URETHANE 1006 BLACK PART A

(Contd. of page 9)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Acute Tox. 2: Acute toxicity – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3