

**CONATHANE® EN-20 Part A Urethane Prepolymer**

Version 5

Revision Date 07/09/2024

Print Date 07/09/2024

**SECTION 1. IDENTIFICATION**

Product name : CONATHANE® EN-20 Part A Urethane Prepolymer

**Manufacturer or supplier's details**

Company : ELANTAS PDG, INC.  
5200 North 2nd Street  
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : [www.elantas.com](http://www.elantas.com)

E-mail address : [Todd.Thomas@altana.com](mailto:Todd.Thomas@altana.com)

Emergency telephone : INFOTRAC - 1-800-535-5053  
number

**Recommended use of the chemical and restrictions on use**

Recommended use : Electrical Insulation

Restrictions on use : This product is for industrial use only. It is not intended for consumer use or retail sale.  
Refer to Section 15 for any restrictions that may apply

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Specific target organ toxicity : Category 3 (Respiratory system)  
- single exposure

Specific target organ toxicity : Category 1 (Respiratory Tract)  
- repeated exposure

Specific target organ toxicity : Category 2  
- repeated exposure

**GHS label elements**

**CONATHANE® EN-20 Part A Urethane Prepolymer**

Version 5

Revision Date 07/09/2024

Print Date 07/09/2024

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 May cause respiratory irritation.  
H351 Suspected of causing cancer.  
H372 Causes damage to organs (Respiratory Tract) through prolonged or repeated exposure.  
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

: **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P285 In case of inadequate ventilation wear respiratory protection.  
**Response:**  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.  
**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

**CONATHANE® EN-20 Part A Urethane Prepolymer**

Version 5

Revision Date 07/09/2024

Print Date 07/09/2024

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Isocyanate Prepolymer

**Hazardous components**

| Component                      | CAS-No.    | Concentration (%)  |
|--------------------------------|------------|--------------------|
| Isocyanates                    | 101-68-8   | $\geq 30$ - $< 60$ |
| Polyurethane Prepolymer        | 52747-01-0 | $\geq 20$ - $< 30$ |
| Methylenediphenyl diisocyanate | 26447-40-5 | $\geq 1$ - $< 5$   |

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control centre immediately.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.  
Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

**CONATHANE® EN-20 Part A Urethane Prepolymer**

Version 5

Revision Date 07/09/2024

Print Date 07/09/2024

**SECTION 5. FIREFIGHTING MEASURES**

- Unsuitable extinguishing media : High volume water jet
- Further information : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Store under conditions specified on the product Technical Data Sheet to maintain product quality.  
Keep container tightly closed in a dry and well-ventilated place.  
Observe label precautions.

**CONATHANE® EN-20 Part A Urethane Prepolymer**

Version 5

Revision Date 07/09/2024

Print Date 07/09/2024

Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Components with workplace control parameters**

| Components                     | CAS-No.    | Value type<br>(Form of exposure) | Control parameters /<br>Permissible concentration | Basis    |
|--------------------------------|------------|----------------------------------|---|----------|
| Isocyanates                    | 101-68-8   | TWA                              | 0.005 ppm   | ACGIH    |
| Isocyanates                    |            | C                                | 0.02 ppm<br>0.2 mg/m3                             | OSHA Z-1 |
| Methylenediphenyl diisocyanate | 26447-40-5 | C                                | 0.02 ppm<br>0.2 mg/m3                             | OSHA Z-1 |
| Methylenediphenyl diisocyanate |            | C                                | 0.02 ppm<br>0.2 mg/m3                             | OSHA P0  |

**Hazardous components without workplace control parameters**

**Engineering measures** : Use with adequate ventilation.  
All application areas should be ventilated in accordance with applicable OSHA regulations. (e.g. 29 CFR 1910.94)  
Isocyanates may be released during the curing process.  
Repeated overexposure to isocyanates can cause respiratory tract sensitization.

**Personal protective equipment**

**Respiratory protection** : In the case of vapour formation use a respirator with an approved filter.

**Hand protection**  
**Remarks** : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

**Eye protection** : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

**Skin and body protection** : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**Hygiene measures** : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

**CONATHANE® EN-20 Part A Urethane Prepolymer**

Version 5

Revision Date 07/09/2024

Print Date 07/09/2024

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

|   |   |
|---|---|
| Appearance                              | : liquid  |
| Odour Threshold                         | : No data available   |
| pH                                      | : No data available   |
| Melting point/freezing point            | : No data available   |
| Initial boiling point and boiling range | : No data available   |
| Vapour pressure                         | : No data available   |
| Flash point                             | : > 201 °F (> 94 °C)<br>Method: No information available.<br>Information taken from reference works and the literature. |
| Upper explosion limit                   | : No data available   |
| Lower explosion limit                   | : No data available   |
| Evaporation rate                        | : No data available   |
| Flammability (solid, gas)               | : No data available   |
| Relative vapour density                 | : No data available   |
| Relative Density/Specific Gravity       | : No data available   |
| Density                                 | : 1.14 g/cm <sup>3</sup> (77 °F (25 °C))  |
| Solubility(ies)                         |   |
| Water solubility                        | : No data available   |
| Solubility in other solvents            | : No data available   |
| Partition coefficient: n-octanol/water  | : No data available   |
| Ignition temperature                    | : No data available   |
| Thermal decomposition                   | : No data available   |
| Viscosity                               |   |
| Viscosity, dynamic                      | : No data available   |

**CONATHANE® EN-20 Part A Urethane Prepolymer**

Version 5

Revision Date 07/09/2024

Print Date 07/09/2024

Viscosity, kinematic : > 21 mm<sup>2</sup>/s (104 °F (40 °C))**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : No data available

Hazardous decomposition products : Carbon monoxide in a fire.  
Nitrogen oxides in a fire.  
Isocyanates

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure****Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 2.16 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

**Components:****101-68-8 Isocyanates:**

Acute oral toxicity : LD50 (Rat): 2,200 mg/kg  
  
LD50 (Rat, male and female): > 2,000 mg/kg  
Method: Tested according to Annex V of Directive 67/548/EEC.  
GLP: yes

Acute inhalation toxicity : LC50 (Rat): 178 mg/l  
  
LC50 (Rat, male): 1.5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
GLP: yes

**CONATHANE® EN-20 Part A Urethane Prepolymer**

Version 5

Revision Date 07/09/2024

Print Date 07/09/2024

Acute dermal toxicity : (Rabbit): > 10,000 mg/kg

**26447-40-5 Methylenediphenyl diisocyanate:**

Acute oral toxicity : LD50 (Rat): 15,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 490 ppm

Acute dermal toxicity : LD50 : Remarks: No data available

**Skin corrosion/irritation****Product:**

Remarks: May cause skin irritation and/or dermatitis.

**Components:****101-68-8 Isocyanates:**

Species: Rabbit

Result: Mild skin irritation

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: yes

**Serious eye damage/eye irritation****Product:**

Remarks: May cause irreversible eye damage.

**Components:****101-68-8 Isocyanates:**

Species: Rabbit

Result: Moderate eye irritation

Method: Draize Test

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

**Respiratory or skin sensitisation****Product:**

Remarks: Causes sensitisation.

**Components:****101-68-8 Isocyanates:**

Species: Guinea pig

Method: Draize Test

Result: Causes sensitisation.



**CONATHANE® EN-20 Part A Urethane Prepolymer**

Version 5

Revision Date 07/09/2024

Print Date 07/09/2024

Test Type: Buehler Test  
Exposure routes: Dermal  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: Does not cause skin sensitisation.  
GLP: yes

**Germ cell mutagenicity****Components:****101-68-8 Isocyanates:**

|                                       |  |
|---------------------------------------|--|
| Genotoxicity in vitro                 | : Test Type: Ames test<br>Test species: Salmonella typhimurium<br>Metabolic activation: with and without metabolic activation<br>Method: OECD Test Guideline 471<br>Result: negative         |
| Genotoxicity in vivo                  | : Test Type: Micronucleus test<br>Test species: Rat (male)<br>Application Route: Inhalation<br>Exposure time: 3x1 h/ day over 3 weeks<br>Method: OECD Test Guideline 474<br>Result: negative |
| Germ cell mutagenicity-<br>Assessment | : In vitro tests did not show mutagenic effects, In vivo tests did not show mutagenic effects  |

**Carcinogenicity****Components:****101-68-8 Isocyanates:**

Species: Rat, (male and female)  
Exposure time: 2 hrs  
Dose: 0 - 0,2 - 1 - 6 mg/m<sup>3</sup>  
Frequency of Treatment: 6 hours/ day, 5 days/ week  
Method: OECD Test Guideline 453

|                                 |   |
|---------------------------------|---|
| Carcinogenicity -<br>Assessment | : Suspected of causing cancer if inhaled. |
|---------------------------------|---|

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

**CONATHANE® EN-20 Part A Urethane Prepolymer**

Version 5

Revision Date 07/09/2024

Print Date 07/09/2024

by NTP.

**Reproductive toxicity****Components:****101-68-8 Isocyanates:**Effects on foetal  
development

: Species: Rat, female  
Application Route: Inhalation  
Dose: 0 - 1 - 4 - 12 mg/m<sup>3</sup>  
12 mg/m<sup>3</sup>  
4 mg/m<sup>3</sup>  
Number of exposures: 6 hours/day  
Method: OECD Test Guideline 414

Reproductive toxicity -  
Assessment

: Based on available data, the classification criteria are not met.  
Did not show teratogenic effects in animal experiments.

**STOT - single exposure****Components:****101-68-8 Isocyanates:**

Exposure routes: Inhalation

Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

**STOT - repeated exposure****Components:****101-68-8 Isocyanates:**

Exposure routes: Inhalation

Target Organs: Respiratory Tract

Assessment: May cause damage to organs through prolonged or repeated exposure.

**Repeated dose toxicity****Components:****101-68-8 Isocyanates:**

Species: Rat, male and female

NOAEL: 0,2 mg/m<sup>3</sup>

Application Route: Inhalation

Exposure time: 2 hrs

Number of exposures: 6 hours/ day, 5 days/ week

Dose: 0 - 0,2 - 1 - 6 mg/m<sup>3</sup>

Method: OECD Test Guideline 453

Target Organs: Lungs, Nasal inner lining

Repeated dose toxicity -  
Assessment

: Harmful if inhaled., The product causes irritation of eyes, skin  
and mucous membranes.

**CONATHANE® EN-20 Part A Urethane Prepolymer**

Version 5

Revision Date 07/09/2024

Print Date 07/09/2024

**Aspiration toxicity****Components:****101-68-8 Isocyanates:**

No aspiration toxicity classification

**Further information****Product:**

Remarks: No data available

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological  
information

: No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

: WC: B

EPA Hazardous Waste  
Code(s)

: none

Waste from residues

: Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.

**CONATHANE® EN-20 Part A Urethane Prepolymer**

Version 5

Revision Date 07/09/2024

Print Date 07/09/2024

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

| Components  | CAS-No.  | Component RQ<br>(lbs) | Calculated product RQ<br>(lbs) |
|-------------|----------|-----------------------|--------------------------------|
| Isocyanates | 101-68-8 | 5000                  | 12634                          |

**SARA 304 - Emergency Release Notification**

This material does not contain any components with a section 304 EHS RQ.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III  
Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**CONATHANE® EN-20 Part A Urethane Prepolymer**

Version 5

Revision Date 07/09/2024

Print Date 07/09/2024

**SARA 313**

: This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

|             |          |        |
|-------------|----------|--------|
| Isocyanates | 101-68-8 | 39.5 % |
|-------------|----------|--------|

**Clean Air Act**

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

|             |          |        |
|-------------|----------|--------|
| Isocyanates | 101-68-8 | 39.5 % |
|-------------|----------|--------|

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

|             |          |        |
|-------------|----------|--------|
| Isocyanates | 101-68-8 | 39.5 % |
|-------------|----------|--------|

Non-volatile (Wt) : Refer to the product technical data sheet for VOC information.

**Massachusetts Right To Know**

|             |          |
|-------------|----------|
| Isocyanates | 101-68-8 |
|-------------|----------|

**Pennsylvania Right To Know**

|                          |            |
|--------------------------|------------|
| Isocyanates              | 101-68-8   |
| Polyurethane Pre-polymer | 68525-78-0 |
| Polyurethane Prepolymer  | 52747-01-0 |

**New Jersey Right To Know**

**New Jersey Trade Secret Registry Number for the product (NJ TSRN)** : Not Applicable

**California Prop. 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

TSCA : All components of this product are listed active and/or are exempt

Section 4 / 12(b) : Not applicable

Section 5 : Not applicable


Section 6 : Not applicable

**CONATHANE® EN-20 Part A Urethane Prepolymer**

Version 5

Revision Date 07/09/2024

Print Date 07/09/2024

**SECTION 16. OTHER INFORMATION****Further information****NFPA:****HMIS III:**

|                        |           |
|------------------------|-----------|
| <b>HEALTH</b>          | <b>2*</b> |
| <b>FLAMMABILITY</b>    | <b>1</b>  |
| <b>PHYSICAL HAZARD</b> | <b>1</b>  |

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

Revision Date : 07/09/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.