

CONATHANE® CE-1155-35 Part A Urethane Prepolymer

Version 1

Revision Date 10/10/2017

Print Date 10/10/2017

SECTION 1. IDENTIFICATION

Product name : CONATHANE® CE-1155-35 Part A Urethane Prepolymer

Manufacturer or supplier's details

Company : ELANTAS PDG, INC.
5200 North 2nd Street
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : www.elantas.com

E-mail address : Todd.Thomas@altana.com

Emergency telephone number : INFOTRAC - 1-800-535-5053

Recommended use of the chemical and restrictions on use

Recommended use :

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity - repeated exposure : Category 2

GHS label elements

Hazard pictograms :



CONATHANE® CE-1155-35 Part A Urethane Prepolymer

Version 1

Revision Date 10/10/2017

Print Date 10/10/2017

Signal word	: Danger
Hazard statements	: H226 Flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	: Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P285 In case of inadequate ventilation wear respiratory protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse.

CONATHANE® CE-1155-35 Part A Urethane Prepolymer

Version 1

Revision Date 10/10/2017

Print Date 10/10/2017

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS
Hazardous components

Component	CAS-No.	Concentration (%)
Aromatic Polyisocyanate	-	>= 35 - < 36
1-Methoxy-2-propanol acetate	108-65-6	>= 34 - < 35
Toluene	108-88-3	>= 19 - < 20
Xylene	1330-20-7	>= 8 - < 9
Ethyl benzene (component of Xylene)	100-41-4	>= 1 - < 2
Toluene diisocyanate	584-84-9	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.
- If inhaled : Call a physician or poison control centre immediately.
 If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
 If on skin, rinse well with water.
 If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
 Remove contact lenses.
 Protect unharmed eye.
 Keep eye wide open while rinsing.
 If eye irritation persists, consult a specialist.

CONATHANE® CE-1155-35 Part A Urethane Prepolymer

Version 1

Revision Date 10/10/2017

Print Date 10/10/2017

If swallowed : Keep respiratory tract clear.
 Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
 Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam
 Carbon dioxide (CO₂)
 Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
 Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
 For safety reasons in case of fire, cans should be stored separately in closed containments.
 Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
 Ensure adequate ventilation.
 Remove all sources of ignition.
 Evacuate personnel to safe areas.
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

CONATHANE® CE-1155-35 Part A Urethane Prepolymer

Version 1

Revision Date 10/10/2017

Print Date 10/10/2017

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.
 Do not breathe vapours/dust.
 Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Take precautionary measures against static discharges.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Open drum carefully as content may be under pressure.
 Dispose of rinse water in accordance with local and national regulations.
 Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Store under conditions specified on the product Technical Data Sheet to maintain product quality.
 No smoking.
 Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1-Methoxy-2-propanol acetate	108-65-6	TWA	50 ppm	US WEEL
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2
		TWA	100 ppm 375 mg/m ³	OSHA P0
		STEL	150 ppm 560 mg/m ³	OSHA P0
Xylene	1330-20-7	TWA	100 ppm 435 mg/m ³	OSHA Z-1

CONATHANE® CE-1155-35 Part A Urethane Prepolymer

Version 1

Revision Date 10/10/2017

Print Date 10/10/2017

		STEL	150 ppm 655 mg/m ³	OSHA P0
		TWA	100 ppm 435 mg/m ³	OSHA P0
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
Ethyl benzene (component of Xylene)	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m ³	OSHA Z-1
		TWA	100 ppm 435 mg/m ³	OSHA P0
		STEL	125 ppm 545 mg/m ³	OSHA P0
Toluene diisocyanate	584-84-9	TWA	0.005 ppm	ACGIH
		STEL	0.02 ppm	ACGIH
		C	0.02 ppm 0.14 mg/m ³	OSHA Z-1
		TWA	0.005 ppm 0.04 mg/m ³	OSHA P0
		STEL	0.02 ppm 0.15 mg/m ³	OSHA P0

Engineering measures : Use with adequate ventilation.
 All application areas should be ventilated in accordance with applicable OSHA regulations. (29 CFR 1910.94)
 Isocyanates may be released during the curing process.
 Repeated overexposure to isocyanates can cause respiratory tract sensitization.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection
 Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
 Tightly fitting safety goggles
 Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
 When using do not smoke.
 Wash hands before breaks and at the end of workday.

CONATHANE® CE-1155-35 Part A Urethane Prepolymer

Version 1

Revision Date 10/10/2017

Print Date 10/10/2017

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Vapour pressure	: No data available
Flash point	: 90 °F (32 °C) Method: Tag closed cup
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 1.05 g/cm ³ (77 °F (25 °C))
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	

CONATHANE® CE-1155-35 Part A Urethane Prepolymer

Version 1

Revision Date 10/10/2017

Print Date 10/10/2017

Viscosity, dynamic : No data available

Viscosity, kinematic : > 22 mm²/s (104 °F (40 °C))

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Hazardous decomposition products : Carbon monoxide in a fire.
Nitrogen oxides in a fire.
Isocyanates

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 109.9 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:**108-65-6 1-Methoxy-2-propanol acetate:**

Acute oral toxicity : LD50 (Rat, female): 5,155 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 100 ppm
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

CONATHANE® CE-1155-35 Part A Urethane Prepolymer

Version 1

Revision Date 10/10/2017

Print Date 10/10/2017

108-88-3 Toluene:

Acute oral toxicity : LD50 (Rat): 2,600 mg/kg

1330-20-7 Xylene:Acute oral toxicity : LD50 (Rat, male): 3,523 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.Acute inhalation toxicity : LC50 (Rat): 5000 ppm
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg

100-41-4 Ethyl benzene (component of Xylene):

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 5,510 mg/kg

584-84-9 Toluene diisocyanate:

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

LD50 (Rat, male): 5,110 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 14 ppm

Acute dermal toxicity : LD50 (Rabbit): > 9,400 mg/kg

LD50 (Rabbit, male and female): > 9,400 mg/kg
Method: OECD Test Guideline 402**Skin corrosion/irritation****Product:**

Remarks: May cause skin irritation and/or dermatitis.

Components:**1330-20-7 Xylene:**

Species: Rabbit

Result: Moderate skin irritation

100-41-4 Ethyl benzene (component of Xylene):

Species: Rabbit

Result: Moderate skin irritation

584-84-9 Toluene diisocyanate:

Species: Rabbit

Result: Moderate skin irritation

CONATHANE® CE-1155-35 Part A Urethane Prepolymer

Version 1

Revision Date 10/10/2017

Print Date 10/10/2017

Serious eye damage/eye irritation
Product:

Remarks: May cause irreversible eye damage.

Components:
1330-20-7 Xylene:

Species: Rabbit

Result: Eye irritation

100-41-4 Ethyl benzene (component of Xylene):

Species: Rabbit

Result: Moderate eye irritation

584-84-9 Toluene diisocyanate:

Species: Rabbit

Result: Eye irritation

Respiratory or skin sensitisation
Product:

Remarks: Causes sensitisation.

Carcinogenicity

IARC	Group 2B: Possibly carcinogenic to humans	
	Ethyl benzene (component of Xylene)	100-41-4
	Toluene diisocyanate	584-84-9
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.	
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	
NTP	Reasonably anticipated to be a human carcinogen	
	Toluene diisocyanate	584-84-9

Further information
Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

CONATHANE® CE-1155-35 Part A Urethane Prepolymer

Version 1

Revision Date 10/10/2017

Print Date 10/10/2017

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity
Components:
584-84-9 Toluene diisocyanate:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 133 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 12.5 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202
- Toxicity to algae : ErC50 (Chlorella vulgaris (Fresh water algae)): 4,300 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 201
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1.1 mg/l
 Exposure time: 21 d
 End point: Reproduction
 Method: OECD Test Guideline 211
 GLP: yes

Persistence and degradability
Components:
584-84-9 Toluene diisocyanate:

- Biodegradability : Result: Not biodegradable

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects
Product:

- Results of PBT and vPvB assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
- Regulation : 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
- Remarks : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act

CONATHANE® CE-1155-35 Part A Urethane Prepolymer

Version 1

Revision Date 10/10/2017

Print Date 10/10/2017

Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS
Disposal methods

EPA Hazardous Waste Code(s) : D001: Ignitable

Waste from residues : Do not dispose of waste into sewer.
 Do not contaminate ponds, waterways or ditches with chemical or used container.
 Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Do not re-use empty containers.
 Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION
International Regulations
IATA-DGR

UN/ID No. : UN 1866
 Proper shipping name : Resin solution
 Class : 3
 Packing group : III
 Labels : Flammable liquid
 Packing instruction (cargo aircraft) : 366
 Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1866
 Proper shipping name : RESIN SOLUTION
 Class : 3
 Packing group : III
 Labels : 3
 EmS Code : F-E, S-E
 Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

CONATHANE® CE-1155-35 Part A Urethane Prepolymer

Version 1

Revision Date 10/10/2017

Print Date 10/10/2017

49 CFR

UN/ID/NA number : UN 1866
 Proper shipping name : Resin solution
 Class : 3
 Packing group : III
 Labels : Flammable liquid
 ERG Code : 127
 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	1,232

SARA 304 - Emergency Release Notification

Calculated RQ exceeds reasonably attainable upper limit.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : The following components are subject to reporting levels established by SARA Title III, Section 302:

Toluene diisocyanate 584-84-9 .1 %

SARA 313 : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Toluene 108-88-3 19.4 %

Xylene 1330-20-7 8.1 %

CONATHANE® CE-1155-35 Part A Urethane Prepolymer

Version 1

Revision Date 10/10/2017

Print Date 10/10/2017

Ethyl benzene (component of Xylene)	100-41-4	1.8 %
Toluene diisocyanate	584-84-9	.1 %

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Toluene	108-88-3	19.4 %
Xylene	1330-20-7	8.1 %
Ethyl benzene (component of Xylene)	100-41-4	1.8 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):

Toluene	108-88-3	19.4 %
Xylene	1330-20-7	8.1 %
Ethyl benzene (component of Xylene)	100-41-4	1.8 %

Non-volatile (Wt) : Refer to the product technical data sheet for VOC information.

US State Regulations
Massachusetts Right To Know

Toluene	108-88-3
Xylene	1330-20-7
Ethyl benzene (component of Xylene)	100-41-4
Toluene diisocyanate	584-84-9
2-Methyl-m-phenylene diisocyanate	91-08-7

Pennsylvania Right To Know

Aromatic Polyisocyanate	-
1-Methoxy-2-propanol acetate	108-65-6
Toluene	108-88-3
Xylene	1330-20-7
Ethyl benzene (component of Xylene)	100-41-4
Toluene diisocyanate	584-84-9
2-Methyl-m-phenylene diisocyanate	91-08-7

New Jersey Right To Know

Aromatic Polyisocyanate	-
1-Methoxy-2-propanol acetate	108-65-6
Toluene	108-88-3
Xylene	1330-20-7
Ethyl benzene (component of Xylene)	100-41-4
Toluene diisocyanate	584-84-9

CONATHANE® CE-1155-35 Part A Urethane Prepolymer

Version 1

Revision Date 10/10/2017

Print Date 10/10/2017

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : Not Applicable

California Prop 65 WARNING! This product contains a chemical known to the State of California to cause cancer.
 Ethyl benzene (component of Xylene) 100-41-4
 WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
 Toluene 108-88-3


The components of this product are reported in the following inventories:

TSCA : We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).

Section 4 / 12(b) : Not applicable

Section 5 : Not applicable

DSL : We certify that all of the components of this product are listed on the DSL.

SECTION 16. OTHER INFORMATION
Further information
NFPA:

HMIS III:

HEALTH	3*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

Revision Date : 10/10/2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a

CONATHANE® CE-1155-35 Part A Urethane Prepolymer

Version 1

Revision Date 10/10/2017

Print Date 10/10/2017

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.