

**SAFETY DATA SHEET****H.B. Fuller® DOUBLE/BUBBLE® Urethane High Peel Strength D50  
Part B (04022)**

Version 1.1

Revision Date 12/14/2023

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : H.B. Fuller® DOUBLE/BUBBLE® Urethane High Peel  
Strength D50 Part B (04022)  
Product code : 100000017819

**Manufacturer or supplier's details**

Company : H.B. Fuller Company  
Address : 1200 Willow Lake Boulevard  
Vadnais Heights, MN 55110  
Telephone : 1-888-423-8553

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

**Recommended use of the chemical and restrictions on use**

Recommended use : Polyol  
Restrictions on use : For industrial use only.

**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Appearance	liquid
Color	off-white
Odor	characteristic

**GHS Classification**

Not a hazardous substance or mixture.

**GHS label elements**

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

**Potential Health Effects****Carcinogenicity:**

**IARC** Group 1: Carcinogenic to humans  
Quartz (SiO<sub>2</sub>) 14808-60-7

**OSHA** No component of this product present at levels greater than or

## SAFETY DATA SHEET

**H.B. Fuller® DOUBLE/BUBBLE® Urethane High Peel Strength D50  
Part B (04022)**

Version 1.1

Revision Date 12/14/2023

**NTP**equal to 0.1% is on OSHA's list of regulated carcinogens.  
Known to be human carcinogenQuartz (SiO<sub>2</sub>) 14808-60-7**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous ingredients**

Chemical name	CAS-No.	Concentration [%]
Propane-1,2-diol, propoxylated	25322-69-4	30 - 50
Limestone	1317-65-3	20 - 30
kaolin	1332-58-7	20 - 30
Titanium dioxide	13463-67-7	1 - 5
Quartz (SiO <sub>2</sub> )	14808-60-7	0.1 - 1

Actual concentration is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- General advice : Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off with soap and water.
- In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- If swallowed : Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this SDS.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SAFETY DATA SHEET**
**H.B. Fuller® DOUBLE/BUBBLE® Urethane High Peel Strength D50  
 Part B (04022)**

Version 1.1

Revision Date 12/14/2023

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed in sections 7 and 8.  
 Methods and materials for containment and cleaning up : Scrape up.  
 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
 Shovel into suitable container for disposal.

**SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : No special precautions are needed in handling this material.  
 Conditions for safe storage : Keep in a dry, cool place.  
 Materials to avoid : No special restrictions on storage with other products.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propane-1,2-diol, propoxylated	25322-69-4	TWA (aerosol)	10 mg/m <sup>3</sup>	US WEEL
Limestone	1317-65-3	TWA (Respirable)	5 mg/m <sup>3</sup>	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup>	NIOSH REL
		TWA (Respirable)	5 mg/m <sup>3</sup>	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup>	NIOSH REL
		TWA (Respirable)	5 mg/m <sup>3</sup>	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup>	NIOSH REL
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Total)	15 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable fraction)	5 mg/m <sup>3</sup>	OSHA P0

**SAFETY DATA SHEET**
**H.B. Fuller® DOUBLE/BUBBLE® Urethane High Peel Strength D50  
 Part B (04022)**

Version 1.1

Revision Date 12/14/2023

		TWA (Total dust)	15 mg/m <sup>3</sup>	OSHA P0
		TWA (respirable dust fraction)	5 mg/m <sup>3</sup>	OSHA P0
kaolin	1332-58-7	TWA (Respirable particulate matter)	2 mg/m <sup>3</sup>	ACGIH
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Total)	10 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable fraction)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (Total dust)	10 mg/m <sup>3</sup>	OSHA P0
		TWA (respirable dust fraction)	5 mg/m <sup>3</sup>	OSHA P0
Titanium dioxide	13463-67-7	TWA	10 mg/m <sup>3</sup>	ACGIH
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Total)	10 mg/m <sup>3</sup>	OSHA P0
		TWA (Total dust)	10 mg/m <sup>3</sup>	OSHA P0
Quartz (SiO <sub>2</sub> )	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m <sup>3</sup>	ACGIH
		TWA (total dust)	30 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup>	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m <sup>3</sup>	CAL PEL
		TWA	0.1 mg/m <sup>3</sup>	OSHA P0

**SAFETY DATA SHEET**
**H.B. Fuller® DOUBLE/BUBBLE® Urethane High Peel Strength D50  
 Part B (04022)**

Version 1.1

Revision Date 12/14/2023

	(respirable dust fraction)	
--	-------------------------------	--

**Personal protective equipment**

- Respiratory protection : No personal respiratory protective equipment normally required.  
 In case of insufficient ventilation, wear suitable respiratory equipment.
- Hand protection  
 Material : Nitrile rubber
- Eye protection : Safety glasses

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid  
 Color : off-white  
 Odor : characteristic  
 Odor Threshold : no data available  
 pH : Not applicable  
 Melting point/freezing point : is not determined  
 Initial boiling point and boiling range : is not determined  
 Flash point : > 96 °C  
 Evaporation rate : is not determined  
 Flammability (solid, gas) : Not classified as a flammability hazard
- Upper explosion limit : Upper flammability limit  
 Not applicable
- Lower explosion limit : Lower flammability limit  
 Not applicable
- Vapor pressure : is not determined  
 Density : 1.48 g/cm<sup>3</sup>  
 Solubility(ies)  
 Water solubility : dispersible  
 Partition coefficient: n-octanol/water : no data available  
 Autoignition temperature : is not determined
- Viscosity  
 Viscosity, kinematic : is not determined

**SAFETY DATA SHEET****H.B. Fuller® DOUBLE/BUBBLE® Urethane High Peel Strength D50  
Part B (04022)**

Version 1.1

Revision Date 12/14/2023

---

**SECTION 10. STABILITY AND REACTIVITY**

Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Hazardous polymerization does not occur.
Hazardous decomposition products	:	Stable under normal conditions.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

No data available

**Skin corrosion/irritation**

No data available

**Serious eye damage/eye irritation**

No data available

**Respiratory or skin sensitization**

No data available

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**STOT-single exposure**

No data available

**STOT-repeated exposure**

No data available

**Aspiration toxicity**

No data available

**SAFETY DATA SHEET****H.B. Fuller® DOUBLE/BUBBLE® Urethane High Peel Strength D50  
Part B (04022)**

Version 1.1

Revision Date 12/14/2023

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Components:****Propane-1,2-diol, propoxylated :**

Partition coefficient: n- : log Pow: -0.68 - 0.01 (25 °C)  
octanol/water pH: 12  
GLP: no

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**SAFETY DATA SHEET****H.B. Fuller® DOUBLE/BUBBLE® Urethane High Peel Strength D50  
Part B (04022)**

Version 1.1

Revision Date 12/14/2023

---

**Domestic regulation****49 CFR**Not regulated as a dangerous good

---

**SECTION 15. REGULATORY INFORMATION****SARA 311/312 Hazards** : No SARA Hazards**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.

This material does not contain any components with a section 302 EHS TPQ.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

**US State Regulations****California Prop 65** Please contact Supplier for more information.**The ingredients of this product are reported in the following inventories:****TSCA** All substances listed as active on the TSCA inventory  
**Inventories Legend** TSCA (USA), DSL (Canada), REACH(Europe), AIIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

---

**SECTION 16. OTHER INFORMATION**


Prepared by: Global Regulatory Office - phone: 1-651-236-5842 - email: msds.request@hbfuller.com



**SAFETY DATA SHEET**
**H.B. Fuller® DOUBLE/BUBBLE® Urethane High Peel Strength D50  
 Part B (04022)**

Version 1.1

Revision Date 12/14/2023

**Further information**
**NFPA:**

**HMIS III:**

<b>HEALTH</b>	<b>0/</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 =Slight,  
 2 = Moderate, 3 = High  
 4 = Extreme, \* = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.