



PRODUCT INFORMATION

D670

D/C Tuff Tape III™

Description

An aggressive adhesive highly resistant to water and moisture. Holds up in extreme cold, heat and humidity. Excellent adhesion to irregular surfaces.

Features

- Resistant to plasticizers
- Withstands temperature variations
- Water, moisture resistant

Carrier	1.2 mils Polypropylene	.031 mm
Adhesive	3.5 mils each side-Acrylic	.089 mm
Liner	White Silicone Release Paper	
Adhesion to Stainless Steel	80 oz/in	22N/25 mm
Temperature Range	-40°F to 200°F	-40°C to 93°C
Color	Clear	
Total Tape Thickness (Excluding Liner)	8.2 mils	.208 mm

Application

High performance bonding to vinyl, plastic and smooth or textured surfaces. Also available in red, for splice-n-locate applications.

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.

800-545-8273 · 262-835-0748 · Fax: 262-835-0749 · www.specialtytapes.net
4221 Courtney Road · Franksville, WI 53126