

CONATHANE® EN-4 Part A Urethane Prepolymer

Version 6

Revision Date 08/02/2022

Print Date 08/02/2022

SECTION 1. IDENTIFICATION

Product name : CONATHANE® EN-4 Part A Urethane Prepolymer

Manufacturer or supplier's detailsCompany : ELANTAS PDG, INC.
5200 North 2nd Street
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : www.elantas.comE-mail address : Todd.Thomas@altana.com

Emergency telephone number : INFOTRAC - 1-800-535-5053

Recommended use of the chemical and restrictions on use

Recommended use : Casting Resin

Restrictions on use : This product is for industrial use only. It is not intended for consumer use or retail sale.
Refer to Section 15 for any restrictions that may apply**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Acute toxicity (Inhalation) : Category 2

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 2

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H317 May cause an allergic skin reaction.
H330 Fatal if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H351 Suspected of causing cancer.Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.

CONATHANE® EN-4 Part A Urethane Prepolymer

Version 6

Revision Date 08/02/2022

Print Date 08/02/2022

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P284 Wear respiratory protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Modified Polyol Blend

Hazardous components

Component	CAS-No.	Concentration (%)
Toluene diisocyanate	584-84-9	>= 5 - < 10
2-Methyl-m-phenylene diisocyanate	91-08-7	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Consult a physician.
 Show this safety data sheet to the doctor in attendance.
 Symptoms of poisoning may appear several hours later.
 Do not leave the victim unattended.

CONATHANE® EN-4 Part A Urethane Prepolymer

Version 6

Revision Date 08/02/2022

Print Date 08/02/2022

- | | |
|-------------------------|--|
| If inhaled | : Call a physician or poison control centre immediately.
If unconscious, place in recovery position and seek medical advice. |
| In case of skin contact | : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital. |

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---|---|
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during firefighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.
Ensure adequate ventilation.
Evacuate personnel to safe areas. |
| Environmental precautions | : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for | : Soak up with inert absorbent material (e.g. sand, silica gel, |

CONATHANE® EN-4 Part A Urethane Prepolymer

Version 6

Revision Date 08/02/2022

Print Date 08/02/2022

containment and cleaning up

acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling

: Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage

: Store under conditions specified on the product Technical Data Sheet to maintain product quality.
Prevent unauthorized access.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Toluene diisocyanate	584-84-9	TWA	0.005 ppm	ACGIH
Toluene diisocyanate		STEL	0.02 ppm	ACGIH
Toluene diisocyanate		C	0.02 ppm 0.14 mg/m ³	OSHA Z-1
Toluene diisocyanate		TWA	0.005 ppm 0.04 mg/m ³	OSHA P0
Toluene diisocyanate		STEL	0.02 ppm 0.15 mg/m ³	OSHA P0
2-Methyl-m-phenylene diisocyanate	91-08-7	TWA	0.005 ppm	ACGIH
2-Methyl-m-phenylene		STEL	0.02 ppm	ACGIH

CONATHANE® EN-4 Part A Urethane Prepolymer

Version 6

Revision Date 08/02/2022

Print Date 08/02/2022

diisocyanate				
2-Methyl-m-phenylene diisocyanate		C	0.02 ppm 0.14 mg/m3	OSHA Z-1
2-Methyl-m-phenylene diisocyanate		TWA	0.005 ppm 0.04 mg/m3	OSHA P0
2-Methyl-m-phenylene diisocyanate		STEL	0.02 ppm 0.15 mg/m3	OSHA P0

Engineering measures : Use with adequate ventilation.
 All application areas should be ventilated in accordance with applicable OSHA regulations. (e.g. 29 CFR 1910.94)
 Isocyanates may be released during the curing process.
 Repeated overexposure to isocyanates can cause respiratory tract sensitization.
 Formaldehyde may be released during the curing process.
 Formaldehyde is a suspected human carcinogen and a skin and respiratory sensitizer. Prolonged or repeated exposure to vapors may result in respiratory impairment and/or liver, kidney or heart effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection
 Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
 Tightly fitting safety goggles
 Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Avoid contact with skin, eyes and clothing.
 When using do not eat or drink.
 When using do not smoke.
 Wash hands before breaks and immediately after handling the product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Odour Threshold : No data available

CONATHANE® EN-4 Part A Urethane Prepolymer

Version 6

Revision Date 08/02/2022

Print Date 08/02/2022

pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Vapour pressure	:	No data available
Flash point	:	> 201 °F (> 94 °C) Method: No information available. Information taken from reference works and the literature.
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Relative vapour density	:	No data available
Relative Density/Specific Gravity	:	No data available
Density	:	0.9694 g/cm ³ (77 °F (25 °C))
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Ignition temperature	:	No data available
Thermal decomposition	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 21 mm ² /s (104 °F (40 °C))

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

CONATHANE® EN-4 Part A Urethane Prepolymer

Version 6

Revision Date 08/02/2022

Print Date 08/02/2022

Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: No data available
Hazardous decomposition products	: Carbon monoxide in a fire. Nitrogen oxides in a fire. Isocyanates formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Acute toxicity****Product:**

Acute inhalation toxicity : Acute toxicity estimate : 0.69 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:**584-84-9 Toluene diisocyanate:**

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

LD50 (Rat, male): 5,110 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 9,400 mg/kg

LD50 (Rabbit, male and female): > 9,400 mg/kg
Method: OECD Test Guideline 402

91-08-7 2-Methyl-m-phenylene diisocyanate:

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 : Remarks: No data available

Acute dermal toxicity : LD50 : Remarks: No data available

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation and/or dermatitis.

Components:**91-08-7 2-Methyl-m-phenylene diisocyanate:**

CONATHANE® EN-4 Part A Urethane Prepolymer

Version 6

Revision Date 08/02/2022

Print Date 08/02/2022

Species: Rabbit
Result: Moderate skin irritation

Serious eye damage/eye irritation
Product:

Remarks: May cause irreversible eye damage.

Components:
91-08-7 2-Methyl-m-phenylene diisocyanate:

Species: Rabbit
Result: Eye irritation

Respiratory or skin sensitisation
Product:

Remarks: Causes sensitisation.

Carcinogenicity

IARC	Group 2B: Possibly carcinogenic to humans	
	Toluene diisocyanate	584-84-9
	2-Methyl-m-phenylene diisocyanate	91-08-7
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.	
NTP	Reasonably anticipated to be a human carcinogen	
	Toluene diisocyanate	584-84-9
	2-Methyl-m-phenylene diisocyanate	91-08-7

Further information
Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity

No data available

CONATHANE® EN-4 Part A Urethane Prepolymer

Version 6

Revision Date 08/02/2022

Print Date 08/02/2022

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation : 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

: WC: B

EPA Hazardous Waste Code(s) : D003: Reactive

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

UN/ID No. : UN 2206

Proper shipping name : Isocyanates, toxic, n.o.s.
(Toluene diisocyanate)

Class : 6.1

CONATHANE® EN-4 Part A Urethane Prepolymer

Version 6

Revision Date 08/02/2022

Print Date 08/02/2022

Packing group : II
 Labels : Toxic
 Packing instruction (cargo aircraft) : 662
 Packing instruction (passenger aircraft) : 654

IMDG-Code

UN number : UN 2206
 Proper shipping name : ISOCYANATES, TOXIC, N.O.S.
 (TOLUENE DIISOCYANATE)
 :)
 Class : 6.1
 Packing group : II
 Labels : 6.1
 EmS Code : F-A, S-A
 Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number : UN 2206
 Proper shipping name : Isocyanates, toxic, n.o.s.
 (Toluene diisocyanate)
 Class : 6.1
 Packing group : II
 Labels : TOXIC
 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Toluene diisocyanate	584-84-9	100	1371

SARA 304 - Emergency Release Notification

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Toluene diisocyanate	584-84-9	100	1371

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

Components	CAS-No.	Component RQ	Calculated product RQ

CONATHANE® EN-4 Part A Urethane Prepolymer

Version 6

Revision Date 08/02/2022

Print Date 08/02/2022

		(lbs)	(lbs)
Toluene diisocyanate	584-84-9	100	1371

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : The following components are subject to reporting levels established by SARA Title III, Section 302:

Toluene diisocyanate	584-84-9	7.2 %
2-Methyl-m-phenylene diisocyanate	91-08-7	.3 %

SARA 313 : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Toluene diisocyanate	584-84-9	7.2 %
2-Methyl-m-phenylene diisocyanate	91-08-7	.3 %

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

Toluene diisocyanate	584-84-9	7.2 %
----------------------	----------	-------

The following chemical(s) are listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F):

Toluene diisocyanate	584-84-9	7.2 %
----------------------	----------	-------

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):

Toluene diisocyanate	584-84-9	7.2 %
----------------------	----------	-------

Non-volatile (Wt) : Refer to the product technical data sheet for VOC information.

US State Regulations
Massachusetts Right To Know

Toluene diisocyanate	584-84-9
2-Methyl-m-phenylene diisocyanate	91-08-7

CONATHANE® EN-4 Part A Urethane Prepolymer

Version 6

Revision Date 08/02/2022

Print Date 08/02/2022

Pennsylvania Right To Know

TDI/PBD Polymer	68951-56-4
Toluene diisocyanate	584-84-9
2-Methyl-m-phenylene diisocyanate	91-08-7
Benzoyl Chloride	98-88-4

New Jersey Right To Know


New Jersey Trade Secret Registry Number for the product (NJ TSRN) : Not Applicable

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA	: All components of this product are listed active and/or are exempt
Section 4	: Section 4 12(b): Toluene Diisocyanate (584-84-9)
Section 5	Proposed SNUR Toluene Diisocyanate (584-84-9) Only applicable to uses in consumer products.
Section 6	Not applicable

SECTION 16. OTHER INFORMATION
Further information
NFPA:

HMIS III:

HEALTH	3*
FLAMMABILITY	1
PHYSICAL HAZARD	1

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Revision Date : 08/02/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a

CONATHANE® EN-4 Part A Urethane Prepolymer

Version 6

Revision Date 08/02/2022

Print Date 08/02/2022

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.