P Ashland always solving	Page: 1
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip™ 7771B/220 ADHESIVE	Version: 1.7
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
572404	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Pliogrip[™] 7771B/220

ADHESIVE

™ Trademark, Ashland or its subsidiaries, registered in

various countries

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Adhesives

Industrial chemical

Details of the supplier of the safety data sheet
Ashland
P.O. Box 2219
Columbus, OH 43216
United States of America (USA)
+1-614-790-3333

EHSProductSafety@ashland.com

Emergency telephone number
1-800-ASHLAND (1-800-274-5263)

Regulatory Information Number
1-800-325-3751

Product Information
+1-614-790-3333

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Reproductive toxicity : Category 2

Specific target organ systemic toxicity - single

exposure

: Category 3 (Respiratory system)

Ashland always solving	Page: 2
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip™ 7771B/220 ADHESIVE	Version: 1.7
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
572404	

Specific target organ systemic toxicity - repeated exposure (Inhalation) : Category 2 (Respiratory system, Respiratory Tract)

GHS label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficulties

if inhaled.

May cause respiratory irritation.

Suspected of damaging fertility or the unborn child.

May cause damage to organs (Respiratory system, Respiratory

Tract) through prolonged or repeated exposure if inhaled.

Precautionary Statements

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

In case of inadequate ventilation wear respiratory protection.

Response:

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/ attention. If skin irritation or rash occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention.

P Ashland always solving	Page: 3
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip™ 7771B/220 ADHESIVE ™ Trademark, Ashland or its subsidiaries, registered in various countries 572404	Version: 1.7

Take off contaminated clothing and wash before reuse.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

PART A

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
POLYMER	254504001-5759	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Resp. Sens. 1A; H334 Skin Sens. 1A; H317 STOT SE 3; H335 STOT RE 2; H373	>= 10.00 - < 15.00
ALUMINUM SILICATES	254504001-5709	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	>= 10.00 - < 15.00
URETHANE PREPOLYMER	800986-5572P	Resp. Sens. 1; H334	>= 5.00 - < 10.00

Ashland always solving	Page: 4
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip™ 7771B/220 ADHESIVE	Version: 1.7
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
572404	

	Skin Sens. 1; H317	

The identity and concentration of one or more component(s) is being withheld under business confidentiality.

4,4'-DIPHENYLMETHANE DIISOCYANATE	101-68-8	Comb Dust Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 STOT RE 2; H373	35.5153
TALC	14807-96-6	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	10.224
PROPYLENE CARBONATE	108-32-7	Eye Irrit. 2A; H319	1.4964

PART B

Substance / Mixture : Mixture

Hazardous components

<u> </u>		<u> </u>	
Chemical name	I CAS-No.	Classification	Concentration (%)
			Concentration (%)
	10/3-110.		

Ashland always solving ™	Page: 5
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip [™] 7771B/220 ADHESIVE [™] Trademark, Ashland or its subsidiaries, registered in various countries 572404	Version: 1.7

TALC	14807-96-6	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	24.21
PIPERAZINE		Flam. Sol. 1; H228 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1B; H334 Skin Sens. 1B; H317 Repr. 2; H361	0.76

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Call a POISON CENTRE or doctor/physician if exposed or

you feel unwell.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

Call a physician or poison control centre immediately.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : Remove contaminated clothing. If irritation develops, get

medical attention.

If on skin, rinse well with water.

Wash contaminated clothing before re-use.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

P Ashland always solving	Page: 6
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip [™] 7771B/220 ADHESIVE [™] Trademark, Ashland or its subsidiaries, registered in various countries 572404	Version: 1.7

Protect unharmed eye.

If swallowed : Obtain medical attention.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

Pulmonary edema may be delayed.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Cough Headache chest pain

lung edema (fluid buildup in the lung tissue)

Difficulty in breathing Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

May cause respiratory irritation.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

P Ashland always solving	Page: 7
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip [™] 7771B/220 ADHESIVE [™] Trademark, Ashland or its subsidiaries, registered in various countries 572404	Version: 1.7

Hazardous combustion

products

: carbon dioxide and carbon monoxide Hydrogen cyanide (hydrocyanic acid)

Isocyanates

Nitrogen oxides (NOx)

toxic fumes Aldehydes Ketones

halogenated hydrocarbons nitrogen oxides (NOx)

Bromine Hydrocarbons

Specific extinguishing

methods

:

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

P Ashland always solving	Page: 8
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip [™] 7771B/220 ADHESIVE [™] Trademark, Ashland or its subsidiaries, registered	Version: 1.7
in various countries	
572404	

Advice on safe handling

: Avoid formation of aerosol.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Container hazardous when empty.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

: Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

PART A

174171				
Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ALUMINUM SILICATES	254504001- 5709	TWA	1 mg/m3 Respirable fraction (Aluminium)	ACGIH

The identity and concentration of one or more component(s) is being withheld under business confidentiality.

4,4'-DIPHENYLMETHANE DIISOCYANATE	101-68-8	TWA	0.005 ppm	ACGIH
TALC	14807-96-6	TWA	20 Million particles per cubic	OSHA Z-3

S Ashland always solving	Page: 9
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip [™] 7771B/220 ADHESIVE [™] Trademark, Ashland or its subsidiaries, registered in various countries 572404	Version: 1.7

	foot Dust	
TWA	2 mg/m3 respirable dust fraction	OSHA P0
TWA	2 mg/m3 Respirable	NIOSH REL
PEL	2 mg/m3 Respirable dust	CAL PEL
TWA	0.1 fibres per cubic centimeter	ACGIH
TWA	2 mg/m3 Respirable fraction	ACGIH

Hazardous components without workplace control parameters

PART A

Components	CAS-No.
POLYMER	254504001-
	5759
URETHANE PREPOLYMER	800986-
	5572P

PART A

PROPYLENE CARBONATE 108-32-7

PART B

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
TALC	14807-96-6	TWA	20 Million particles per cubic foot Dust	OSHA Z-3
		TWA	2 mg/m3 respirable dust fraction	OSHA P0
		TWA	2 mg/m3 Respirable	NIOSH REL
		PEL	2 mg/m3 Respirable dust	CAL PEL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA	2 mg/m3	ACGIH

Ashland always solving	Page: 10
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip™ 7771B/220 ADHESIVE	Version: 1.7
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
572404	

			Respirable fraction	
CARBON BLACK	1333-86-4	TWA	3 mg/m3 Inhalable fraction	ACGIH
		TWA	3.5 mg/m3	NIOSH REL
		TWA	3.5 mg/m3	OSHA Z-1
		TWA	3.5 mg/m3	OSHA P0
		PEL	3.5 mg/m3	CAL PEL
		TWA	0.1 mg/m3 (PAHs)	NIOSH REL
PIPERAZINE	110-85-0	TWA	0.03 ppm Inhalable fraction and vapor (piperazine)	ACGIH

Hazardous components without workplace control parameters

PART B

Components	CAS-No.
PIPERAZINE	110-85-0

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an

approved filter.

Diisocyanates have poor warning properties. An air-purifying respirator with an organic vapor cartridge and an N95 prefilter can be used safely and effectively to reduce exposure, provided that appropriate cartridge change schedules are developed to ensure that cartridges are changed before breakthrough occurs. The employer is required to select the appropriate respirator for each situation and must consider potential exposure to chemicals in addition to diisocyanates.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for

exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear as appropriate:

Impervious clothing

Ashland always solving	Page: 11
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip™ 7771B/220 ADHESIVE	Version: 1.7
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
572404	

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

PART A

Appearance : viscous

Physical state : liquid

Colour : beige

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : > 392 °F / > 200 °C

Flash point : $> 100 \, ^{\circ}\text{C}$

Evaporation rate : < 1

n-Butyl Acetate = 1

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : < 0.01333 hPa (25 °C)

Relative vapour density : > 1(Air = 1.0)

P Ashland always solving	Page: 12
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip™ 7771B/220 ADHESIVE	Version: 1.7
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
572404	

Relative density : No data available

Density : 1.288 g/cm3 (20 °C)

Solubility(ies)

Water solubility : practically insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : ca. 20,000 mPa.s

Viscosity, kinematic : No data available

Oxidizing properties : No data available

PART B

Physical state : liquid

Colour : black

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : > 93.4 °C

Method: Seta closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Ashland always solving	Page: 13
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip [™] 7771B/220 ADHESIVE [™] Trademark, Ashland or its subsidiaries, registered in various countries 572404	Version: 1.7

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 3 hPa (25 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : 1.225 (77.00 °F)

Density : 1.225 g/cm3 (77.00 °F)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : 20,000 mPa.s

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : heat

Freezing temperatures. Exposure to moisture

Incompatible materials : Acids

Ashland always solving	Page: 14
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip™ 7771B/220 ADHESIVE	Version: 1.7
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
572404	

Alcohols aluminum Amines Ammonia Bases

Copper alloys fluorides Iron

isocyanates Oxidizing agents oxidizers

Phosphorus compounds

strong alkalis

strong reducing agents

water Zinc Humid air

Hazardous decomposition

products carbon dioxide and carbon monoxide

Hydrocarbons

Hydrogen cyanide (hydrocyanic acid)

Isocyanates

Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure

Inhalation
Skin contact

Eye Contact Ingestion

Acute toxicity
Harmful if inhaled.
Components:
POLYMER:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 425

GLP: yes

Acute inhalation toxicity : Assessment: The component/mixture is classified as acute

inhalation toxicity, category 4.

Acute dermal toxicity : (Rabbit): > 9,400 mg/kg

Remarks: Information given is based on data obtained from

Ashland always solving	Page: 1
SAFETY DATA SHEET	Revision Date: 07/31/201
	Print Date: 10/11/201
	SDS Number: 00000009347
Pliogrip™ 7771B/220 ADHESIVE	Version: 1.
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
572404	

similar substances.

Components:

4,4'-DIPHENYLMETHANE DIISOCYANATE:

Acute oral toxicity : LD50 (Rat): 9,200 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.369 mg/l

Exposure time: 4 h

LC50 (Rat): > 2.24 mg/l Exposure time: 1 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The component/mixture is classified as acute

inhalation toxicity, category 4.

Acute dermal toxicity : LD50 (Rabbit): > 7,900 mg/kg

TALC:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 423

PROPYLENE CARBONATE:

Acute oral toxicity : LD50 (Rat): 29.1 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 24 g/kg

PIPERAZINE:

Acute oral toxicity : LD50 (Rat): ca. 2,600 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC0 (Rat, male and female): 1.61 mg/l

Exposure time: 8 h
Test atmosphere: vapour

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

POLYMER:

Result: Irritating to skin.

Remarks: Information given is based on data obtained from similar substances.

P Ashland always solving	Page: 16
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip [™] 7771B/220 ADHESIVE [™] Trademark, Ashland or its subsidiaries, registered in various countries 572404	Version: 1.7

ALUMINUM SILICATES:

Result: Slight, transient irritation

URETHANE PREPOLYMER: Result: No skin irritation

Components:

4,4'-DIPHENYLMETHANE DIISOCYANATE:

Result: Irritating to skin.

TALC:

Species: reconstructed human epidermis (RhE)

Result: No skin irritation

PROPYLENE CARBONATE:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

PIPERAZINE:

Result: Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

POLYMER:

Result: No eye irritation

Remarks: Information given is based on data obtained from similar substances.

Result: Irritating to eyes.

ALUMINUM SILICATES:

Result: Slight, transient irritation

URETHANE PREPOLYMER:

Result: No eye irritation

Components:

4,4'-DIPHENYLMETHANE DIISOCYANATE:

Result: Irritating to eyes.

TALC:

Ashland always solving	Page: 17
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip [™] 7771B/220 ADHESIVE [™] Trademark, Ashland or its subsidiaries, registered in various countries 572404	Version: 1.7

Species: Rabbit

Result: Slight, transient irritation Method: OECD Test Guideline 405

PROPYLENE CARBONATE:

Species: Rabbit

Result: Irritating to eyes.

Method: OECD Test Guideline 405

PIPERAZINE: Result: Corrosive

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: May cause allergy or asthma symptoms or breathing difficulties if

inhaled.

Components: POLYMER:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: May cause sensitisation by skin contact. Result: The product is a skin sensitiser, sub-category 1A.

Assessment: May cause sensitisation by inhalation.

Result: The product is a respiratory sensitiser, sub-category 1A.

URETHANE PREPOLYMER:

Assessment: May cause sensitisation by skin contact.

Assessment: May cause sensitisation by inhalation.

Components:

4,4'-DIPHENYLMETHANE DIISOCYANATE:

Assessment: May cause sensitisation by inhalation.

Assessment: May cause sensitisation by skin contact.

TALC:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Did not cause sensitisation on laboratory animals.

Method: OECD Test Guideline 406

Result: Did not cause sensitisation on laboratory animals.

Ashland always solving	Page: 18
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip™ 7771B/220 ADHESIVE	Version: 1.7
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
572404	

PIPERAZINE:

Assessment: The product is a respiratory sensitiser, sub-category 1B.

Assessment: The product is a skin sensitiser, sub-category 1B.

Germ cell mutagenicity

Not classified based on available information.

Components: POLYMER:

Genotoxicity in vitro : Test Type: Ames test

Result: negative

Remarks: Information given is based on data obtained from

similar substances.

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Test species: Rat

Method: OECD Test Guideline 474

Remarks: Information given is based on data obtained from

similar substances.

Components:

TALC:

Genotoxicity in vitro : Test Type: In vitro gene mutation study in bacteria

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Test Type: In vitro gene mutation study in bacteria

Test species: Saccharomyces cerevisiae

Metabolic activation: with and without metabolic activation

Result: negative

Genotoxicity in vivo : Test Type: dominant lethal test

Test species: Rat (male) Cell type: Bone marrow

Result: negative

PROPYLENE CARBONATE:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test

Test species: Mouse Cell type: Bone marrow

Ashland always solving	Page: 19
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip [™] 7771B/220 ADHESIVE [™] Trademark, Ashland or its subsidiaries, registered in various countries 572404	Version: 1.7

Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

Not classified based on available information.

Product:

Carcinogenicity - Assessment

: Methylene bisphenylisocyanate (MDI) aerosol has been reported to be irritating to lungs at a concentration of 1 mg/m3 with no effect observed at 0.2 mg/m3. Although MDI has been reported to cause an increase in non-carcinogenic lung tumors and a single carcinogenic lung tumor at very high concentrations (6 mg/m3), it is not classified as a carcinogen

by IARC, NTP or OSHA.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components: PIPERAZINE:

Reproductive toxicity -Assessment

: Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT - single exposure

May cause respiratory irritation.

Components: POLYMER:

Exposure routes: Inhalation
Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

Components:

4,4'-DIPHENYLMETHANE DIISOCYANATE:

Exposure routes: Inhalation

Target Organs: Respiratory system

Assessment: May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs (Respiratory system, Respiratory Tract) through prolonged or repeated exposure if inhaled.

Components:

POLYMER:

Exposure routes: Inhalation Target Organs: Respiratory Tract

Assessment: May cause damage to organs through prolonged or repeated exposure.

Components:

4,4'-DIPHENYLMETHANE DIISOCYANATE:

Exposure routes: Inhalation

P Ashland always solving	Page: 20
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip™ 7771B/220 ADHESIVE	Version: 1.7
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
572404	

Target Organs: Respiratory system

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC Group 2B: Possibly carcinogenic to humans

CARBON BLACK 1333-86-4

OSHANo component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic

hazard

: Not classified based on available information.

Long-term (chronic) aquatic

hazard

: Not classified based on available information.

Components:

POLYMER:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 3,000 mg/l

Exposure time: 96 h
Test Type: semi-static test

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other

aquatic invertebrates

(Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 24 h Test Type: static test

Method: OECD Test Guideline 202

Remarks: Information given is based on data obtained from

Ashland always solving ™	Page: 21
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip [™] 7771B/220 ADHESIVE [™] Trademark, Ashland or its subsidiaries, registered in various countries 572404	Version: 1.7

similar substances.

Toxicity to algae : NOEC (Desmodesmus subspicatus (green algae)): 1,640 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

Remarks: Information given is based on data obtained from

similar substances.

4,4'-DIPHENYLMETHANE DIISOCYANATE:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 3,000 mg/l

Exposure time: 96 h
Test Type: semi-static test

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 24 h Test Type: static test

Method: OECD Test Guideline 202

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): > 10 mg/l

Exposure time: 21 d

End point: Reproduction Test Test Type: semi-static test

Method: OECD Test Guideline 211

Remarks: Information given is based on data obtained from

similar substances.

PROPYLENE CARBONATE:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 1,000 mg/l

Exposure time: 96 h
Test Type: semi-static test

Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): > 900 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test

Ashland always solving	Page: 22
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip [™] 7771B/220 ADHESIVE [™] Trademark, Ashland or its subsidiaries, registered in various countries	Version: 1.7
572404	

Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 900 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

PIPERAZINE:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 1,800 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 21 mg/l

: NOEC (Daphnia magna (Water flea)): 12.5 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): >

1,000 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

Exposure time: 21 d

Method: OECD Test Guideline 211

Persistence and degradability

Components: POLYMER:

Biodegradability

: Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 302C

4,4'-DIPHENYLMETHANE DIISOCYANATE:

Biodegradability : Result: Not biodegradable

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 302C

Remarks: Information given is based on data obtained from

similar substances.

TALC:

Biodegradability : Result: The methods for determining biodegradability are not

applicable to inorganic substances.

PROPYLENE CARBONATE:

Biodegradability : Result: Readily biodegradable.

Ashland always solving	Page: 23
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip™ 7771B/220 ADHESIVE	Version: 1.7
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
572404	

Biodegradation: 87.1 % Exposure time: 29 d

Method: OECD Test Guideline 301B

PIPERAZINE:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 70 % Exposure time: 28 d

Method: OECD Test Guideline 301F

No data available

Bioaccumulative potential

Components:

PROPYLENE CARBONATE:

Partition coefficient: n-

octanol/water

: log Pow: -0.41

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Do not re-use empty containers.

23 / 30

					Page: 24
Ashland [™] always solving					
SAFETY DATA SHEET					Date: 07/31/2018
					Date: 10/11/2019 er: 000000093475
Pliogrip [™] 7771B/220 ADHESIVE [™] Trademark, Ashland or its subsidiaries, regis in various countries 572404	stered				Version: 1.7
SECTION 14. TRANSPORT INFORMATION					
International transport regulations REGULATION					
ID NUMBER PROPER SHIPPING NAME	*HAZA	ASS HAZARDS GROUP POLLU		MARINE POLLUTANT / LTD. QTY.	
MX_DG					
Not dangerous goods					
	TION D		050		
INTERNATIONAL AIR TRANSPORT ASSOCIA Not dangerous goods	TION - PA	ASSEN	GER		
INTERNATIONAL AIR TRANSPORT ASSOCIA Not dangerous goods	TION - CA	ARGO			
140t dangerous goods					
INTERNATIONAL MARITIME DANGEROUS G	OODS				
Not dangerous goods					
TDG_INWT_C Not dangerous goods					
TDG_RAIL_C					
Not dangerous goods					
TDG_ROAD_C					
Not dangerous goods					
LIG DOT, INII AND WATERWAY					
U.S. DOT - INLAND WATERWAYS Not dangerous goods					
CFR_RAIL_C					

Not dangerous goods

P Ashland always solving	Page: 25
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip [™] 7771B/220 ADHESIVE [™] Trademark, Ashland or its subsidiaries, registered in various countries 572404	Version: 1.7

Not dangerous goods	

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no	

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

PART A

EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
4,4'-DIPHENYLMETHANE	101-68-8	5000	14078
DIISOCYANATE			

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitisation

Specific target organ toxicity (single or repeated exposure)

SARA 302 : This material does not contain any components with a section

302 EHS TPQ.

SARA 313 The following components are subject to reporting levels

established by SARA Title III, Section 313:

4,4'-DIPHENYLMETHANE 101-68-8 35.51 %

DIISOCYANATE

California Prop 65 which is/are known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

TALC 14807-96-6

QUARTZ / SAND 14808-60-7

Ashland always solving	Page: 26
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip™ 7771B/220 ADHESIVE ™ Trademark, Ashland or its subsidiaries, registered in various countries 572404	Version: 1.7

PART B

KECI

EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ. **SARA 304 Extremely Hazardous Substances Reportable Quantity**This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Reproductive toxicity

SARA 302 : This material does not contain any components with a section

302 EHS TPQ.

SARA 313 This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65 which is/are known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

TALC 14807-96-6

CARBON BLACK 1333-86-4

QUARTZ / SAND 14808-60-7

FURAN 110-00-9

PROPYLENE OXIDE 75-56-9

ACETALDEHYDE 75-07-0

The components of this product are reported in the following inventories:

TSCA : On TSCA Inver

DSL : All components

AICS : On the inventor

ENCS : Exempt

PICCS : Not in complian

On the inventor

P Ashland always solving	Page: 2
SAFETY DATA SHEET	Revision Date: 07/31/201
	Print Date: 10/11/201
	SDS Number: 00000009347
Pliogrip [™] 7771B/220 ADHESIVE [™] Trademark, Ashland or its subsidiaries, registered in various countries 572404	Version: 1.

IECSC : On the inventor

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

Registration: Trade secret


Chemical name	Identification number
POLYMER	254504001-5759
ALUMINUM SILICATES	254504001-5709
URETHANE PREPOLYMER	800986-5572P

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/31/2018

PART A




NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

PART B

NFPA:	HMIS III:

Ashland always solving	Page: 28
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip [™] 7771B/220 ADHESIVE [™] Trademark, Ashland or its subsidiaries, registered in various countries 572404	Version: 1.7



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

PART A	
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
PART B	
H228	Flammable solid.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H361	Suspected of damaging fertility or the unborn child.

Sources of key data used to compile the Safety Data Sheet Ashland internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

P Ashland always solving	Page: 29
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip™ 7771B/220 ADHESIVE	Version: 1.7
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
572404	

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

P Ashland always solving	Page: 30
SAFETY DATA SHEET	Revision Date: 07/31/2018
	Print Date: 10/11/2019
	SDS Number: 000000093475
Pliogrip [™] 7771B/220 ADHESIVE [™] Trademark, Ashland or its subsidiaries, registered in various countries 572404	Version: 1.7

OSHA: Occupational Safety and Health Administration PMRA: Health Canada Pest Management Regulatory Agency RTK: Right to Know WHMIS: Workplace Hazardous Materials Information System