

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

SECTION 1. IDENTIFICATION

Product name : MOLYKOTE(R) G-4500 MULTI-PURPOSE SYNTHETIC GREASE SPRAY

Product code : 000000000004126668

Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road
Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900
CHEMTREC : (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Lubricants and lubricant additives

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Flammable aerosols : Category 1

Gases under pressure : Dissolved gas

Skin irritation : Category 2

Specific target organ system-
mic toxicity - single exposure : Category 3

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.

Precautionary Statements : **Prevention:**
P210 Keep away from heat/sparks/open flames/hot surfaces.

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Organic grease

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Naphtha, Petroleum, Light Alkylate	64741-66-8	>= 29 - <= 36
Dec-1-ene, homopolymer, hydrogenated	68037-01-4	>= 21 - <= 26
Aluminum hydroxide benzoate stearate	54326-11-3	>= 3 - <= 4
Calcium carbonate	471-34-1	>= 3 - <= 4
White mineral oil (petroleum)	8042-47-5	>= 0.9 - <= 1.1

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

- | | |
|---|--|
| If inhaled | : If inhaled, remove to fresh air.
Get medical attention if symptoms occur. |
| In case of skin contact | : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse. |
| In case of eye contact | : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists. |
| If swallowed | : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : Causes skin irritation.
May cause drowsiness or dizziness. |
| Protection of first-aiders | : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists. |
| Notes to physician | : Treat symptomatically and supportively. |

SECTION 5. FIRE-FIGHTING MEASURES

- | | |
|---------------------------------------|---|
| Suitable extinguishing media | : Water spray
Alcohol-resistant foam
Carbon dioxide (CO2)
Dry chemical |
| Unsuitable extinguishing media | : None known. |
| Specific hazards during fire fighting | : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. |
| Hazardous combustion products | : Carbon oxides
Metal oxides |
| Specific extinguishing methods | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area. |

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapors/mists with a water spray jet. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use with local exhaust ventilation. Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential

Advice on safe handling : Do not spray on an open flame or other ignition source. Do not get on skin or clothing. Do not breathe vapors or spray mist. Do not swallow. Avoid contact with eyes. Handle in accordance with good industrial hygiene and safety

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version 5.0 Revision Date: 09/14/2017 SDS Number: 894723-00010 Date of last issue: 03/23/2017
Date of first issue: 12/04/2014

- practice, based on the results of the workplace exposure assessment
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Store locked up.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.
- Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha, Petroleum, Light Alkylate	64741-66-8	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
Aluminum hydroxide benzoate stearate	54326-11-3	TWA	10 mg/m ³	ACGIH
Calcium carbonate	471-34-1	TWA (Respirable)	5 mg/m ³ (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m ³ (Calcium carbonate)	NIOSH REL
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL

Hazardous components without workplace control parameters

Ingredients	CAS-No.
Dec-1-ene, homopolymer, hydrogenated	68037-01-4

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Calcium carbonate

Engineering measures : Minimize workplace exposure concentrations.
Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential
Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
Flame retardant antistatic protective clothing, unless assessment demonstrates that the risk of explosive atmospheres or flash fires is low
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version 5.0	Revision Date: 09/14/2017	SDS Number: 894723-00010	Date of last issue: 03/23/2017 Date of first issue: 12/04/2014
----------------	------------------------------	-----------------------------	---

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a dissolved gas
Color	: off-white
Odor	: slight
Odor Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: Not applicable
Flash point	: Not applicable
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Extremely flammable aerosol.
Self-ignition	: The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Relative density	: 0.695
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-	: No data available

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

octanol/water

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

|| Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.
Vapors may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation

Skin contact

Ingestion

Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

Ingredients:**Naphtha, Petroleum, Light Alkylate:**

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 7.6 mg/l Exposure time: 4 h Test atmosphere: vapor Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: LD50 (Rabbit): > 2,200 - 2,500 mg/kg Remarks: Based on data from similar materials

Dec-1-ene, homopolymer, hydrogenated:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 402 Remarks: Based on data from similar materials

Aluminum hydroxide benzoate stearate:

Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 420 Assessment: The substance or mixture has no acute oral toxicity
Acute dermal toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

Calcium carbonate:

Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 420 Assessment: The substance or mixture has no acute oral toxicity
Acute inhalation toxicity	: LC50 (Rat): > 3 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Causes skin irritation.

Ingredients:**Naphtha, Petroleum, Light Alkylate:**

Species: Rabbit
Method: OECD Test Guideline 404
Result: Skin irritation

Dec-1-ene, homopolymer, hydrogenated:

Species: Rabbit
Result: No skin irritation

Aluminum hydroxide benzoate stearate:

Method: OECD Test Guideline 439
Result: No skin irritation

Calcium carbonate:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

White mineral oil (petroleum):

Species: Rabbit
Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

Ingredients:**Naphtha, Petroleum, Light Alkylate:**

Species: Rabbit
Result: No eye irritation

Dec-1-ene, homopolymer, hydrogenated:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

Aluminum hydroxide benzoate stearate:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

Calcium carbonate:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

White mineral oil (petroleum):

Species: Rabbit
Result: No eye irritation

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Ingredients:**Naphtha, Petroleum, Light Alkylate:**

Test Type: Buehler Test
Routes of exposure: Skin contact
Species: Guinea pig
Result: negative

Dec-1-ene, homopolymer, hydrogenated:

Test Type: Maximization Test
Routes of exposure: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

Aluminum hydroxide benzoate stearate:

Test Type: Local lymph node assay (LLNA)
Routes of exposure: Skin contact
Species: Mouse
Method: OECD Test Guideline 429
Result: negative

Calcium carbonate:

Test Type: Local lymph node assay (LLNA)
Routes of exposure: Skin contact
Species: Mouse
Method: OECD Test Guideline 429
Result: negative

White mineral oil (petroleum):

Test Type: Buehler Test
Routes of exposure: Skin contact
Species: Guinea pig
Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:**Naphtha, Petroleum, Light Alkylate:**

Genotoxicity in vitro	: Test Type: Saccharomyces cerevisiae, gene mutation assay (in vitro) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: Inhalation Result: negative

Dec-1-ene, homopolymer, hydrogenated:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
-----------------------	---

Aluminum hydroxide benzoate stearate:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
	Test Type: In vitro mammalian cell gene mutation test Result: negative

Calcium carbonate:

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

White mineral oil (petroleum):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Ingredients:**Naphtha, Petroleum, Light Alkylate:**

Species: Mouse
Application Route: Skin contact
Exposure time: 102 weeks
Result: negative

White mineral oil (petroleum):

Species: Rat
Application Route: Ingestion
Exposure time: 24 Months
Result: negative

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Ingredients:**Naphtha, Petroleum, Light Alkylate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Inhalation

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

Result: negative

Dec-1-ene, homopolymer, hydrogenated:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Aluminum hydroxide benzoate stearate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Calcium carbonate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

White mineral oil (petroleum):

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Skin contact
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

STOT-single exposure

May cause drowsiness or dizziness.

Ingredients:**Naphtha, Petroleum, Light Alkylate:**

Assessment: May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity**Ingredients:****Naphtha, Petroleum, Light Alkylate:**

Species: Rat
NOAEL: 10 mg/l
Application Route: inhalation (vapor)
Exposure time: 13 Weeks
Method: OPPTS 870.3465

Dec-1-ene, homopolymer, hydrogenated:

Species: Rat
NOAEL: 4,159.4 mg/kg
Application Route: Ingestion
Exposure time: 91 Days

Aluminum hydroxide benzoate stearate:

Species: Rat
NOAEL: > 225 mg/kg
Application Route: Ingestion
Exposure time: 54 Days
Method: OECD Test Guideline 422
Remarks: Based on data from similar materials

Calcium carbonate:

Species: Rat
NOAEL: 1,000 mg/kg
Application Route: Ingestion
Exposure time: 6 Weeks
Method: OECD Test Guideline 422

White mineral oil (petroleum):

Species: Rat
LOAEL: > 160 mg/kg
Application Route: Ingestion
Exposure time: 90 Days

Species: Rat
LOAEL: >= 1 mg/l

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

Application Route: inhalation (dust/mist/fume)
Exposure time: 4 Weeks
Method: OECD Test Guideline 412

Aspiration toxicity

Not classified based on available information.

Ingredients:**Naphtha, Petroleum, Light Alkylate:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Dec-1-ene, homopolymer, hydrogenated:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

White mineral oil (petroleum):

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:****Naphtha, Petroleum, Light Alkylate:**

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 8.2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 4.5 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	: ErC50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 2.6 mg/l Exposure time: 21 d Method: OECD Test Guideline 211

Dec-1-ene, homopolymer, hydrogenated:

Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction
Toxicity to daphnia and other	: EL50 (Daphnia magna (Water flea)): > 1,000 mg/l

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

aquatic invertebrates		Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202
Toxicity to algae	:	EL50 (Scenedesmus capricornutum (fresh water algae)): > 1,000 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 NOELR (Scenedesmus capricornutum (fresh water algae)): 1,000 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOELR (Daphnia magna (Water flea)): 125 mg/l Exposure time: 21 d Test substance: Water Accommodated Fraction Method: OECD Test Guideline 211
Toxicity to microorganisms	:	NOEC: 2 mg/l Exposure time: 28 d Method: OECD Test Guideline 301D

Aluminum hydroxide benzoate stearate:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

Calcium carbonate:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	:	ErC50 (Desmodesmus subspicatus (green algae)): > 14 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

White mineral oil (petroleum):

- | | |
|--|--|
| Toxicity to fish | : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202 |
| Toxicity to algae | : NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201 |
| Toxicity to fish (Chronic toxicity) | : NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l
Exposure time: 28 d |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : NOEC (Daphnia magna (Water flea)): 1,000 mg/l
Exposure time: 21 d |

Persistence and degradability**Ingredients:****Naphtha, Petroleum, Light Alkylate:**

- | | |
|------------------|---|
| Biodegradability | : Result: Readily biodegradable.
Biodegradation: 77 %
Exposure time: 28 d
Method: OECD Test Guideline 301F |
|------------------|---|

Dec-1-ene, homopolymer, hydrogenated:

- | | |
|------------------|--|
| Biodegradability | : Result: Not readily biodegradable.
Biodegradation: 2 %
Exposure time: 28 d
Method: OECD Test Guideline 301D |
|------------------|--|

Aluminum hydroxide benzoate stearate:

- | | |
|------------------|---|
| Biodegradability | : Result: Readily biodegradable.
Biodegradation: 79 %
Exposure time: 28 d
Method: OECD Test Guideline 301B |
|------------------|---|

White mineral oil (petroleum):

- | | |
|------------------|---|
| Biodegradability | : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d |
|------------------|---|

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

Bioaccumulative potential**Ingredients:****Naphtha, Petroleum, Light Alkylate:**

Partition coefficient: n-octanol/water	: log Pow: > 4
Remarks: Based on data from similar materials	

Dec-1-ene, homopolymer, hydrogenated:

Partition coefficient: n-octanol/water	: log Pow: > 6.5
--	------------------

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Resource Conservation and Recovery Act (RCRA)	: When a decision is made to discard this material as supplied, it is classified as a RCRA hazardous waste.
---	---

Waste Code	: D001: Ignitability
------------	----------------------

Waste from residues	: Dispose of in accordance with local regulations.
---------------------	--

Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty (including propellant)
------------------------	--

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1

IATA-DGR

MOLYKOTE(R) G-4500 MULTI-PURPOSE SYNTHETIC GREASE SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

UN/ID No.	: UN 1950
Proper shipping name	: Aerosols, flammable
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: Flammable Gas
Packing instruction (cargo aircraft)	: 203
Packing instruction (passenger aircraft)	: 203

IMDG-Code

UN number	: UN 1950
Proper shipping name	: AEROSOLS (Naphtha, Petroleum, Light Alkylate)
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
EmS Code	: F-D, S-U
Marine pollutant	: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

UN/ID/NA number	: UN 1950
Proper shipping name	: Aerosols
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: FLAMMABLE GAS
ERG Code	: 126
Marine pollutant	: yes(Naphtha, Petroleum, Light Alkylate)

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	: Flammable (gases, aerosols, liquids, or solids) Gases under pressure Skin corrosion or irritation Specific target organ toxicity (single or repeated exposure)
-----------------------------	---

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations**Pennsylvania Right To Know**

Naphtha, Petroleum, Light Alkylate	64741-66-8
Petroleum gases, liquefied, sweetened	68476-86-8
Dec-1-ene, homopolymer, hydrogenated	68037-01-4
Polybutene	9003-29-6
Aluminum hydroxide benzoate stearate	54326-11-3
Calcium carbonate	471-34-1
White mineral oil (petroleum)	8042-47-5

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

California List of Hazardous Substances

White mineral oil (petroleum)	8042-47-5
-------------------------------	-----------

California Permissible Exposure Limits for Chemical Contaminants

Calcium carbonate	471-34-1
White mineral oil (petroleum)	8042-47-5

The ingredients of this product are reported in the following inventories:

NZIoC	: All ingredients listed or exempt.
REACH	: For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.
TSCA	: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
AICS	: All ingredients listed or exempt.
IECSC	: All ingredients listed or exempt.
DSL	: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
KECI	: One or more ingredients are not listed or exempt.
TCSI	: All ingredients listed or exempt.


MOLYKOTE(R) G-4500 MULTI-PURPOSE SYNTHETIC GREASE SPRAY

Version 5.0 Revision Date: 09/14/2017 SDS Number: 894723-00010 Date of last issue: 03/23/2017
Date of first issue: 12/04/2014

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS® IV:

HEALTH	/	2
FLAMMABILITY		4
PHYSICAL HAZARD		3

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse)

**MOLYKOTE(R) G-4500 MULTI-PURPOSE
SYNTHETIC GREASE SPRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 03/23/2017
5.0	09/14/2017	894723-00010	Date of first issue: 12/04/2014

Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/14/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8