



SAFETY DATA SHEET

DOW SILICONES CORPORATION

Product name: SILASTIC™ RTV-4130-J Curing Agent

Issue Date: 10/20/2022

Print Date: 11/15/2023

DOW SILICONES CORPORATION encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: SILASTIC™ RTV-4130-J Curing Agent

Recommended use of the chemical and restrictions on use

Identified uses: Vulcanising agents

COMPANY IDENTIFICATION

DOW SILICONES CORPORATION
2200 WEST SALZBURG ROAD
MIDLAND MI 48686-0994
UNITED STATES

Customer Information Number:

800-258-2436
SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1 800 424 9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Reproductive toxicity - Category 1B

Label elements

Hazard pictograms



Signal word: **DANGER!**

Hazards

May damage fertility or the unborn child.

Precautionary statements**Prevention**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

Keep only in original container.

Wear protective gloves, protective clothing, eye protection and/or face protection.

Response

IF exposed or concerned: Get medical advice/ attention.

Storage

Store in a well-ventilated place.

Store locked up.

Disposal

Dispose of contents and/or container to an approved waste disposal plant.

Other hazards

May generate flammable hydrogen gas. Avoid contact with water, alcohols, acidic, basic, or oxidizing materials.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Silicone

This product is a mixture.

Component	CASRN	Concentration
Chromium oxide (Cr ₂ O ₃)	1308-38-9	>= 4.0 - <= 6.0 %
Methylvinylcyclosiloxane	2554-06-5	>= 0.67 - <= 1.11 %

4. FIRST AID MEASURES

Description of first aid measures**General advice:**

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air and keep comfortable for breathing; consult a physician.

Skin contact: Wash off with plenty of water.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: Rinse mouth with water. No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

May damage fertility or the unborn child.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam. Carbon dioxide (CO₂). Water spray.

Unsuitable extinguishing media: Dry chemical.

Special hazards arising from the substance or mixture

Hazardous combustion products: Silicon oxides. Carbon oxides. Formaldehyde.

Unusual Fire and Explosion Hazards: Applying foam will release significant amounts of hydrogen gas that can be trapped under the foam blanket.. Exposure to combustion products may be a hazard to health.. Fire burns more vigorously than would be expected..

Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers.. Evacuate area.. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations..

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Do not allow extinguishing medium to contact container contents. Most fire extinguishing media will cause hydrogen evolution, and once the fire is put out, may accumulate in poorly ventilated or confined areas and result in flash fire or explosion if ignited. Remove undamaged containers from fire area if it is safe to do so.

Special protective equipment for firefighters: Wear self-contained breathing apparatus for firefighting if necessary.. Use personal protective equipment..

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Remove all sources of ignition. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil

barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Soak up with inert absorbent material. Clean up remaining materials from spill with suitable absorbant. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Materials in contact with water, moisture, acids or bases have the potential to generate hydrogen gas. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Recovered material should be stored in a vented container. The vent must prevent the ingress of water as further reaction with spilled materials can take place which could lead to overpressurization of the container. See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Keep away from water. Protect from moisture. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice.

Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Conditions for safe storage: Keep in properly labelled containers. Store in original container. Product may evolve minute quantities of flammable hydrogen gas which can accumulate. Adequately ventilate to maintain vapors well below flammability limits and exposure guidelines. Do not repackage. Clogged container vents may increase pressure build up. Store in accordance with the particular national regulations. Store in a closed container.

Do not store with the following product types: Strong oxidizing agents.

Unsuitable materials for containers: Do not store in or use containers except the original product package.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Chromium oxide (Cr2O3)	OSHA Z-1	TWA	0.5 mg/m3 , chromium
	ACGIH	TWA Inhalable fraction	0.003 mg/m3 , chromium
Further information: URT irr: Upper Respiratory Tract irritation; skin irr: Skin irritation; A4: Not classifiable as a human carcinogen; varies: varies			

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields).

Skin protection

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl chloride ("PVC" or "vinyl"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Wear clean, body-covering clothing.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	viscous liquid
Color	green
Odor	slight
Odor Threshold	No data available
pH	Not applicable, substance/mixture is non-soluble (in water)
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	> 35 °C (> 95 °F)
Flash point	Pensky-Martens closed cup 148.8 °C (299.8 °F)
Evaporation Rate (Butyl Acetate = 1)	No data available
Flammability (solid, gas)	Not applicable
Flammability (liquids)	Not applicable
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor Pressure	No data available
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	1.03
Water solubility	insoluble
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available

Decomposition temperature	No data available
Kinematic Viscosity	700 cSt at 25 °C (77 °F)
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.
Molecular weight	No data available
Particle size	Not applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents. When heated to temperatures above 180 °C (356 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required. Product may evolve flammable hydrogen gas on contact with water, alcohols, acidic or basic materials, many metals or metallic compounds and can form explosive mixtures in air. Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid: Exposure to moisture

Incompatible materials: Avoid contact with oxidizing materials.

Hazardous decomposition products:

Decomposition products can include and are not limited to: Formaldehyde.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Information on likely routes of exposure

Inhalation, Eye contact, Skin contact, Ingestion.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Acute Toxicity Endpoints:

Not classified based on available information.

Acute oral toxicity

Information for the Product:

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):
LD50, > 5,000 mg/kg Estimated.

Information for components:

Chromium oxide (Cr2O3)

LD50, Rat, male, > 15,000 mg/kg OECD Test Guideline 401

Methylvinylcyclosiloxane

LD50, Rat, > 15,000 mg/kg

Acute dermal toxicity

Information for the Product:

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):
LD50, > 2,000 mg/kg Estimated.

Information for components:

Chromium oxide (Cr2O3)

The dermal LD50 has not been determined.

Methylvinylcyclosiloxane

The dermal LD50 has not been determined.

Based on testing for product(s) in this family of materials: LD50, > 2,000 mg/kg
Estimated.

Acute inhalation toxicity

Information for the Product:

No adverse effects are anticipated from single exposure to vapor.

As product: The LC50 has not been determined.

Information for components:

Chromium oxide (Cr2O3)

No adverse effects are anticipated from single exposure to dust. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs.

LC50, Rat, male and female, 4 Hour, dust/mist, > 5.41 mg/l OECD Test Guideline 403

Methylvinylcyclosiloxane

LC50, Rat, male and female, 4 Hour, vapour, > 1.32 mg/l No deaths occurred at this concentration.

Skin corrosion/irritation

Not classified based on available information.

Information for the Product:

Based on information for component(s):
Brief contact is essentially nonirritating to skin.

Information for components:

Chromium oxide (Cr₂O₃)

Brief contact is essentially nonirritating to skin.

Methylvinylcyclosiloxane

Brief contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation

Not classified based on available information.

Information for the Product:

Based on information for component(s):
May cause slight temporary eye irritation.

Information for components:

Chromium oxide (Cr₂O₃)

Essentially nonirritating to eyes.
Corneal injury is unlikely.

Methylvinylcyclosiloxane

May cause slight eye irritation.

Sensitization

For skin sensitization:

Not classified based on available information.

For respiratory sensitization:

Not classified based on available information.

Information for the Product:

For skin sensitization:
Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization:
No relevant data found.

Information for components:

Chromium oxide (Cr₂O₃)

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:
No relevant data found.

Methylvinylcyclosiloxane

For skin sensitization:
No relevant data found.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Chromium oxide (Cr2O3)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Methylvinylcyclosiloxane

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Aspiration Hazard

Not classified based on available information.

Information for the Product:

Based on physical properties, not likely to be an aspiration hazard.

Information for components:

Chromium oxide (Cr2O3)

Based on physical properties, not likely to be an aspiration hazard.

Methylvinylcyclosiloxane

Based on available information, aspiration hazard could not be determined.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Chromium oxide (Cr2O3)

Based on animal data, breathing high concentrations of dust may produce inflammation in the lungs.

Methylvinylcyclosiloxane

No relevant data found.

Carcinogenicity

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Chromium oxide (Cr2O3)

Did not cause cancer in laboratory animals.

Methylvinylcyclosiloxane

No relevant data found.

Teratogenicity

May damage fertility or the unborn child.

Information for the Product:

Product test data not available.

Information for components:

Chromium oxide (Cr2O3)

For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

Methylvinylcyclosiloxane

Has been toxic to the fetus in lab animals at doses nontoxic to the mother.

Reproductive toxicity

May damage fertility or the unborn child.

Information for the Product:

Product test data not available.

Information for components:

Chromium oxide (Cr2O3)

In animal studies, did not interfere with fertility.

Methylvinylcyclosiloxane

In animal studies, has been shown to interfere with fertility.

Mutagenicity

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Chromium oxide (Cr2O3)

For similar material(s): In vitro genetic toxicity studies were predominantly negative.

Methylvinylcyclosiloxane

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Chromium oxide (Cr2O3)

Acute toxicity to fish

Not expected to be acutely toxic to aquatic organisms.

LC50, Danio rerio (zebra fish), static test, 96 Hour, > 10,000 mg/l, ISO 7346/1

Acute toxicity to algae/aquatic plants

EC50, Desmodesmus subspicatus (green algae), 72 Hour, > 848.6 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC50, 3 Hour, > 10,000 mg/l

Chronic toxicity to fish

NOEC, Danio rerio (zebra fish), 30 d, 1,000 mg/l

Chronic toxicity to aquatic invertebrates

No toxicity at the limit of solubility

NOEC, Daphnia magna (Water flea), 21 d, > 0.02 mg/l

Methylvinylcyclosiloxane

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, Cyprinodon variegatus (sheepshead minnow), 96 Hour, > 1,000 mg/l

Acute toxicity to aquatic invertebrates

EL50, Acartia tonsa, 48 Hour, 221 mg/l, ISO 14669 and PARCOM method

Acute toxicity to algae/aquatic plants

ErC50, Skeletonema sp., 72 Hour, > 988 mg/l, ISO 10253

Persistence and degradability

Chromium oxide (Cr2O3)

Biodegradability: Biodegradation is not applicable.

Methylvinylcyclosiloxane

Biodegradability: For similar material(s): Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

10-day Window: Fail

Biodegradation: 3.7 %

Exposure time: 28 d

Method: OECD Test Guideline 310

Bioaccumulative potential

Chromium oxide (Cr2O3)

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 2.97 Estimated.

Bioconcentration factor (BCF): 39 Fish Estimated.

Methylvinylcyclosiloxane

Bioaccumulation: Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

Partition coefficient: n-octanol/water(log Pow): 6.47

Mobility in soil

Chromium oxide (Cr2O3)

Partition coefficient (Koc): 80 Estimated.

Methylvinylcyclosiloxane

No relevant data found.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated for transport

**Transport in bulk
according to Annex I or II
of MARPOL 73/78 and the
IBC or IGC Code**

Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

Further information:

VENTED PACKAGES ARE FORBIDDEN FOR AIR TRANSPORT.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Reproductive toxicity

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

The following components are subject to reporting levels established by SARA Title III, Section 313:

Components

Chromium oxide (Cr2O3)

CASRN

1308-38-9

Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components

	CASRN
Dimethyl Siloxane, Dimethylvinylsiloxo-terminated	68083-19-2
Siloxanes and Silicones, di-Me, Me hydrogen	68037-59-2
Dimethylvinylated and trimethylated silica	68988-89-6
Chromium oxide (Cr2O3)	1308-38-9

California Prop. 65

WARNING: This product can expose you to chemicals including Ethylbenzene, Chromium, ion (Cr6+), Chromium (VI) compounds, Lead, Cadmium, Arsenic, which is/are known to the State of California to cause cancer, and Chromium, ion (Cr6+), Chromium (VI) compounds, Lead, Cadmium, Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System**NFPA**

Health	Flammability	Instability
0	1	0

HMIS

Health	Flammability	Physical Hazard
1/	1	1

Revision

Identification Number: 4107118 / A713 / Issue Date: 10/20/2022 / Version: 8.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
TWA	8-hour, time-weighted average

Full text of other abbreviations

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP

- Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW SILICONES CORPORATION urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US