

Revision Number: 006.0 Issue date: 07/12/2018

1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

Product name: LOCTITE C 400 SN63 3C 0.56MM S

known as 63/37 C400 3C 0.56MM

0.5KG AM

Product type: Solder Wire Item number: MM01054 Restriction of Use: None identified Region: **United States**

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

Contact information: Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711

450314

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: HARMFUL IF SWALLOWED OR IF INHALED.

MAY CAUSE DROWSINESS OR DIZZINESS.

MAY DAMAGE FERTILITY OR THE UNBORN CHILD.

CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED

EXPOSURE.

| HAZARD CLASS | HAZARD CATEGORY |
|--|-----------------|
| ACUTE TOXICITY ORAL | 4 |
| ACUTE TOXICITY INHALATION | 4 |
| REPRODUCTIVE TOXICITY | 1A |
| SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE | 3 |
| SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE | 1 |

PICTOGRAM(S)



Precautionary Statements

Response:

Storage:

Obtain special instructions before use. Do not handle until all safety precautions have been Prevention:

read and understood. Do not breathe dust or fumes. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-

ventilated area. Wear protective gloves, clothing, eye and face protection.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF INHALED: Remove victim to fresh

air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or

physician if you feel unwell. IF exposed or concerned: Get medical attention. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

IDH number: 450314 Product name: LOCTITE C 400 SN63 3C 0.56MM S known as 63/37 C400 3C 0.56MM 0.5KG AM

Page 1 of 6

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* |
|------------------------|------------|-------------|
| Tin | 7440-31-5 | 60 - 70 |
| Lead | 7439-92-1 | 30 - 40 |

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. If symptoms develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). If symptoms develop and persist, get

medical attention. Wash clothing before reuse.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. If symptoms develop

and persist, get medical attention.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. Do not use water on fires where molten metal is present.

Unusual fire or explosion hazards: None

IDH number: 450314

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Oxides of Metals in Section 3.

Formaldehyde. High temperatures may produce heavy metal dust, fumes or

vapours. The flux will give rise to irritating fumes.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Ensure adequate ventilation. Wear suitable protective clothing, gloves and

eye/face protection. Scrape up spilled material and place in a closed container for disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior

to clean up.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Wear suitable protective clothing, gloves

and eye/face protection. Avoid contact with eyes, skin and clothing. When

using do not eat, drink or smoke. Wash thoroughly after handling.

Storage: For safe storage, store between 15 °C (59°F) and 30 °C (86°F)

Keep cool in accordance with information on label and in Technical Data

Sheets.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|------------------------|------------------------|--|-----------|-------|
| Tin | 2 mg/m3 TWA | 2 mg/m3 PEL (as Sn) | None | None |
| Lead | 0.05 mg/m3 TWA (as Pb) | 0.05 mg/m3 TWA 0.03 mg/m3 OSHA_ACT | None | None |

Engineering controls: Use adequate ventilation to remove molten vapors or fumes. Provide

adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Solid Color: Gray Odor: None

Odor threshold:

pH:

Not available.

Vapor pressure:

Boiling point/range:

Melting point/ range:

Not available.

183 °C (361.4 °F)

Specific gravity: 8.4

IDH number: 450314

Vapor density: Not available. Flash point: Product is a solid. Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flammability: Not applicable Not available. **Evaporation rate:** Solubility in water: Insoluble Partition coefficient (n-octanol/water): Not available. **VOC** content: < 5 % (calculated) Viscosity: Not available. **Decomposition temperature:** Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 450314

Oxides of carbon. Oxides of Metals in Section 3. Formaldehyde Thermal decomposition can

lead to release of irritating gases and vapors.

Incompatible materials: Strong oxidizing agents. Strong acids and strong bases.

Reactivity: Not available.

Conditions to avoid: Solder alloy will react with concentrated nitric acid to produce toxic fumes of nitrogen oxides.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: Harmful if inhaled. Inhalation of processing fumes may be harmful. Vapor overexposure may

cause drowsiness. Dizziness. Fumes and/or dust produced by this product may be hazardous in case of ingestion or inhalation. Rosin thermal decomposition product (as formaldehyde) is classified by NIOSH as a potential occupational carcinogen. Excessive exposure to tin fumes or dust may cause Stannosis, a chronic respiratory disease resulting in reduced lung capacity and benign tumors. Excessive inhalation of fumes from many metals can produce an acute reaction known as "metal fume fever". Symptoms consist of chills and fever (very similar to and easily confused with flu symptoms) which come on a few hours after large exposures. Lead is a cumulative poison and continuous exposure to small amounts over time can raise the body's

content to toxic levels.

May cause skin irritation.

Skin contact: May cause skin irritation. Eye contact: May cause eye irritation.

Ingestion: Harmful if swallowed. Lead is a cumulative poison and continuous exposure to small amounts

over time can raise the body's content to toxic levels. Symptoms of lead poisoning include

abdominal pain, nausea, vomiting, and headache.

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects |
|------------------------|-----------------|---|
| Tin | None | Gastrointestinal, Irritant, Kidney, Liver, Lung, Nervous System |
| Lead | None | Behavioral, Blood, Developmental, Eyes, Gastrointestinal, Kidney, Liver, Muscle, Nervous System, Reproductive, Skin, Some evidence of carcinogenicity, Thyroid |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|------------------------|--|-----------------|--|
| Tin | No | No | No |
| Lead | Reasonably Anticipated to be a Human Carcinogen. | Group 2B | No |

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal. Do not

dispose of in an uncontrolled manner.

Hazardous waste number: D008: Lead

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis. CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Lead (CAS# 7439-92-1).

CERCLA Reportable quantity: Lead (CAS# 7439-92-1) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

Product name: LOCTITE C 400 SN63 3C 0.56MM S known as 63/37 C400 3C 0.56MM 0.5KG AM IDH number: 450314

Page 5 of 6

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Product Safety and Regulatory Affairs

Issue date: 07/12/2018

IDH number: 450314

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.