



Revision Number: 002.0

Issue date: 08/30/2017

## 1. PRODUCT AND COMPANY IDENTIFICATION

|   |   |                     |               |
|---|---|---------------------|---------------|
| <b>Product name:</b>  | <b>LOCTITE 3900 known as Loctite® 3900 Shadowcure® Type</b>   | <b>IDH number:</b>  | 135277        |
| <b>Product type:</b>  | Coating   | <b>Item number:</b> | 18893         |
| <b>Restriction of Use:</b>  | None identified   | <b>Region:</b>      | United States |
| <b>Company address:</b>   | <b>Contact information:</b><br>Telephone: (860) 571-5100<br>MEDICAL EMERGENCY Phone: Poison Control Center<br>1-877-671-4608 (toll free) or 1-303-592-1711<br>TRANSPORT EMERGENCY Phone: CHEMTREC<br>1-800-424-9300 (toll free) or 1-703-527-3887<br>Internet: www.henkelna.com |                     |               |
| Henkel Corporation<br>One Henkel Way<br>Rocky Hill, Connecticut 06067 |   |                     |               |

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**DANGER:** EXTREMELY FLAMMABLE AEROSOL.  
 CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.  
 MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.  
 CAUSES SKIN IRRITATION.  
 CAUSES SERIOUS EYE IRRITATION.  
 MAY CAUSE DROWSINESS OR DIZZINESS.  
 MAY DAMAGE FERTILITY OR THE UNBORN CHILD.  
 MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

| HAZARD CLASS                                       | HAZARD CATEGORY |
|--|-----------------|
| FLAMMABLE AEROSOL                                  | 1               |
| GASES UNDER PRESSURE                               | Compr. Gas      |
| SKIN IRRITATION                                    | 2               |
| EYE IRRITATION                                     | 2A              |
| REPRODUCTIVE TOXICITY                              | 1B              |
| SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE   | 3               |
| SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE | 2               |
| ASPIRATION HAZARD                                  | 1               |

### PICTOGRAM(S)



### Precautionary Statements

#### Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe mist or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, clothing, eye and face protection.

**Response:** IF SWALLOWED: Immediately call a physician or poison control center. IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. Do NOT induce vomiting. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s)   | CAS Number | Percentage* |
|--------------------------|------------|-------------|
| Acetone                  | 67-64-1    | 30 - 40     |
| Toluene                  | 108-88-3   | 20 - 30     |
| Propane                  | 74-98-6    | 10 - 20     |
| Butane                   | 106-97-8   | 10 - 20     |
| Ethyl 3-ethoxypropionate | 763-69-9   | 1 - 5       |

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

**Skin contact:** Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention. Wash clothing before reuse.

**Eye contact:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.

**Symptoms:** See Section 11.

### 5. FIRE FIGHTING MEASURES

**Extinguishing media:** Foam, dry chemical or carbon dioxide.

**Special firefighting procedures:** Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.

**Unusual fire or explosion hazards:** Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.

**Hazardous combustion products:**

Oxides of carbon. Hydrocarbons. Irritating organic vapours.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:**

Do not allow product to enter sewer or waterways.

**Clean-up methods:**

Remove all sources of ignition. Ensure adequate ventilation. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

**Handling:**

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Refer to Section 8.

**Storage:**

Store in original container until ready to use. Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)   | ACGIH TLV   | OSHA PEL  | AIHA WEEL | OTHER                      |
|--------------------------|---|---|-----------|----------------------------|
| Acetone                  | 250 ppm TWA<br>500 ppm STEL   | 1,000 ppm (2,400 mg/m <sup>3</sup> ) PEL                          | None      | None                       |
| Toluene                  | 20 ppm TWA  | 200 ppm TWA<br>300 ppm Ceiling<br>500 ppm MAX.<br>CONC 10 minutes | None      | None                       |
| Propane                  | Included in the regulation but with no data values. See regulation for further details (Simple asphyxiant.) | 1,000 ppm (1,800 mg/m <sup>3</sup> ) PEL                          | None      | None                       |
| Butane                   | 1,000 ppm STEL  | None  | None      | None                       |
| Ethyl 3-ethoxypropionate | None  | None  | None      | 50 ppm TWA<br>100 ppm STEL |

**Engineering controls:**

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Respiratory protection:**

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:**

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

**Skin protection:**

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|  |  |
|--|--|
| Physical state:                          | Aerosol  |
| Color:                                   | Colorless  |
| Odor:                                    | Characteristic   |
| Odor threshold:                          | Not available.   |
| pH:                                      | 7  |
| Vapor pressure:                          | 101.3 kPa (20 °C (68°F))   |
| Boiling point/range:                     | 0 - 342 °F (-17.8 - 172.2 °C)                                    |
| Melting point/ range:                    | Not available.   |
| Specific gravity:                        | 0.71   |
| Vapor density:                           | Not available.   |
| Flash point:                             | -29 °C (-20.2 °F) Pensky Martens closed cup                      |
| Flashback:                               | This product exhibits flashback when tested for flame extension. |
| Flammable/Explosive limits - lower:      | 1 %  |
| Flammable/Explosive limits - upper:      | 12.8 %   |
| Autoignition temperature:                | Not available.   |
| Flammability:                            | Not applicable   |
| Evaporation rate:                        | 5.6 (Butyl acetate = 1)  |
| Solubility in water:                     | Not available.   |
| Partition coefficient (n-octanol/water): | Not available.   |
| VOC content:                             | 70.7 %; 516 g/l  |
| Viscosity:                               | Not available.   |
| Decomposition temperature:               | Not available.   |

## 10. STABILITY AND REACTIVITY

|                                   |  |
|-----------------------------------|--|
| Stability:                        | Stable under normal conditions of storage and use.   |
| Hazardous reactions:              | Will not occur.  |
| Hazardous decomposition products: | Oxides of carbon.  |
| Incompatible materials:           | Acids and bases. Oxidizing agents. Heat.   |
| Reactivity:                       | Not available.   |
| Conditions to avoid:              | Heat, flames, sparks and other sources of ignition. High temperatures. Store away from incompatible materials. |

## 11. TOXICOLOGICAL INFORMATION

|                              |                                   |
|------------------------------|-----------------------------------|
| Relevant routes of exposure: | Skin, Inhalation, Eyes, Ingestion |
|------------------------------|-----------------------------------|

### Potential Health Effects/Symptoms

**Inhalation:** May cause respiratory tract irritation. May cause central nervous system effects.  
**Skin contact:** Causes skin irritation. May cause allergic skin reaction.  
**Eye contact:** Causes serious eye irritation.  
**Ingestion:** May be harmful or fatal if swallowed. May cause gastrointestinal tract irritation if swallowed.

| Hazardous Component(s)   | LD50s and LC50s  | Immediate and Delayed Health Effects                                      |
|--------------------------|--|---|
| Acetone                  | Oral LD50 (Mouse) = 5.2 g/kg<br>Oral LD50 (Mouse) = 3,000 mg/kg<br>Oral LD50 (Rabbit) = 5,340 mg/kg<br>Oral LD50 (Rat) = 5,800 mg/kg<br>Oral LD50 (Rat) = 9,800 mg/kg<br>Dermal LD50 (Rabbit) = 20,000 mg/kg<br>Inhalation LC50 (Rat, 4 h) = 76 mg/l | Central nervous system, Irritant  |
| Toluene                  | Oral LD50 (Rat) = 2.6 g/kg<br>Oral LD50 (Rat) = 5,000 mg/kg<br>Dermal LD50 (Rabbit) = 12,124 mg/kg<br>Inhalation LC50 (Rat, 4 h) = 8000 ppm  | Behavioral, Cardiac, Central nervous system, Developmental, Ear, Irritant |
| Propane                  | None   | Cardiac, Central nervous system, Irritant                                 |
| Butane                   | Inhalation LC50 (Rat, 4 h) = 658 mg/l  | Cardiac, Central nervous system, Irritant                                 |
| Ethyl 3-ethoxypropionate | None   | Irritant  |

| Hazardous Component(s)   | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen<br>(Specifically Regulated) |
|--------------------------|----------------|-----------------|---|
| Acetone                  | No             | No              | No  |
| Toluene                  | No             | No              | No  |
| Propane                  | No             | No              | No  |
| Butane                   | No             | No              | No  |
| Ethyl 3-ethoxypropionate | No             | No              | No  |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** D001: Ignitable.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Aerosols  
**Hazard class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** None  
**DOT Hazardous Substance(s):** Toluene, Acetone

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Aerosols, flammable  
**Hazard class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** None

**Water Transportation (IMO/IMDG)**

|                           |          |
|---------------------------|----------|
| Proper shipping name:     | AEROSOLS |
| Hazard class or division: | 2.1      |
| Identification number:    | UN 1950  |
| Packing group:            | None     |

## 15. REGULATORY INFORMATION

**United States Regulatory Information**

|   |   |
|---|---|
| <b>TSCA 8 (b) Inventory Status:</b>     | All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.   |
| <b>TSCA 12 (b) Export Notification:</b> | None above reporting de minimis   |
| <b>CERCLA/SARA Section 302 EHS:</b>     | None above reporting de minimis.  |
| <b>CERCLA/SARA Section 311/312:</b>     | Fire, Pressure, Immediate Health, Delayed Health  |
| <b>CERCLA/SARA Section 313:</b>         | This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Toluene (CAS# 108-88-3). |
| <b>CERCLA Reportable quantity:</b>      | Acetone (CAS# 67-64-1) 5,000 lbs. (2,270 kg)<br>Toluene (CAS# 108-88-3) 1,000 lbs. (454 kg)<br>Propane (CAS# 74-98-6) 100 lbs. (45.4 kg)<br>Butane (CAS# 106-97-8) 100 lbs. (45.4 kg)                             |
| <b>California Proposition 65:</b>       | This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.  |

**Canada Regulatory Information**

|                             |   |
|-----------------------------|---|
| <b>CEPA DSL/NDL Status:</b> | All components are listed on or are exempt from listing on the Canadian Domestic Substances List. |
|-----------------------------|---|

## 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** New Safety Data Sheet format. 2

**Prepared by:** Victoria Rafferty Maloney, Regulatory Affairs Specialist

**Issue date:** 08/30/2017

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.