

Revision Number: 007.0 Issue date: 09/13/2017

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE SI 5900 known as 5900 RTV IDH number: 230153

SIL

Product type:SiliconeItem number:20167Restriction of Use:None identifiedRegion:United States

Company address:Contact information:Henkel CorporationTelephone: (860) 571-5100

One Henkel Way

Rocky Hill, Connecticut 06067

MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC

1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

WARNING: MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2A
SKIN SENSITIZATION	1
REPRODUCTIVE TOXICITY	2





### **Precautionary Statements**

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Avoid breathing dust or fumes. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear

protective gloves, clothing, eye and face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye

irritation persists: Get medical attention. Wash contaminated clothing before reuse.

Storage: Store locked up.

**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Calcium carbonate	471-34-1	40 - 50	
Butan-2-one O,O',O"- (vinylsilylidyne)trioxime	2224-33-1	1 - 5	
Carbon black	1333-86-4	1 - 5	
Amorphous fumed silica	68611-44-9	1 - 5	
Octamethylcyclotetrasiloxane	556-67-2	0.1 - 1	
Butan-2-one O,O',O",O"'- silanetetrayltetraoxime	34206-40-1	0.1 - 1	

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

Inhalation: Move to fresh air in case of accidental inhalation of vapours or decomposition

products. If symptoms develop and persist, get medical attention.

Skin contact: Wipe off paste with paper towel or cloth. Wash with soap and water. If skin

irritation persists, call a physician.

**Eye contact:** Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

**Ingestion:** Do not induce vomiting. Get medical attention.

Symptoms: See Section 11.

## 5. FIRE FIGHTING MEASURES

**Extinguishing media:** Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self contained breathing apparatus. Prevent inhalation of fumes and

gases.

Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon. Oxides of silicon. Formaldehyde. Irritating organic vapours.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Scrape up as much material as possible. Maintain good ventilation for large

spills. Place scrap material in a well ventilated area and allow to cure to

rubber.

# 7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and

cause eye irritation. Do not wear contact lenses.

**Storage:** Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

IDH number: 230153 Product name: LOCTITE SI 5900 known as 5900 RTV SIL

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Calcium carbonate	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Butan-2-one O,O',O"- (vinylsilylidyne)trioxime	None	None	None	None
Carbon black	3 mg/m3 TWA Inhalable fraction.	3.5 mg/m3 PEL	None	None
Amorphous fumed silica	None	0.8 mg/m3 TWA 20 MPPCF TWA	None	None
Octamethylcyclotetrasiloxane	None	None	10 ppm TWA	None
Butan-2-one O,O',O",O"- silanetetrayltetraoxime	None	None	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use a dust mask for particulate concentrations exceeding the Occupational

Exposure Limit. Use an organic vapor respirator for concentrations exceeding

the Occupational Exposure Limit.

**Eye/face protection:** Safety goggles or safety glasses with side shields. Safety showers and eye

wash stations should be available.

**Skin protection:** Permeation resistant gloves (butyl rubber, nitrile rubber, polyvinyl alcohol).

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:PasteColor:BlackOdor:MildOdor threshold:Not available.

pH: Not available.

Not available.

Not applicable

Vapor pressure: < 5 mm hg (20 °C (68°F))

Boiling point/range: Not applicable

Melting point/ range:

Not applicable
Not available.

Specific gravity:

Vapor density:

Not applicable
Not available.

1.31 at 20 °C (68°F)
Heavier than air.

Flash point: > 93 °C (> 199.4 °F) Tagliabue closed cup

Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Flammability:
Flammability:
Evaporation rate:

Not applicable
Not applicable
Not available.

**Solubility in water:** Polymerises in presence of water.

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Decomposition temperature:

Not available.

Not available.

Not available.

## 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing.

Hazardous decomposition

products:

Methyl ethyl ketoxime formed during cure. Oxides of carbon. Oxides of silicon. Formaldehyde.

**Incompatible materials:** Acids and bases. Oxidizing agents. Polymerizes on contact with water.

Reactivity: Not available.

Conditions to avoid: Excessive heat. Store away from incompatible materials.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

### Potential Health Effects/Symptoms

Inhalation: May cause respiratory tract irritation. When heated to temperatures exceeding 300° F (150° C)

in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and

throat. Safe handling conditions may be maintained by keeping formaldehyde vapor

concentrations below the OSHA permissible limit.

**Skin contact:** May cause skin irritation. May cause allergic skin reaction.

**Eye contact:** Causes serious eye irritation.

Ingestion: Not expected under normal conditions of use. May cause gastrointestinal tract irritation if

swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects  Nuisance dust	
Calcium carbonate	Oral LD50 (Rat) = 6,450 mg/kg Oral LD50 (Mouse) = 6,450 mg/kg		
Butan-2-one O,O',O"- (vinylsilylidyne)trioxime	None	Irritant, Allergen	
Carbon black	Oral LD50 (Rat) = > 8,000 mg/kg	Respiratory, Some evidence of carcinogenicity	
Amorphous fumed silica	None	No Target Organs	
Octamethylcyclotetrasiloxane	None	Irritant	
Butan-2-one O,O',O",O"- silanetetrayltetraoxime	None	Irritant, Allergen	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Calcium carbonate	No	No	No
Butan-2-one O,O',O"- (vinylsilylidyne)trioxime	No	No	No
Carbon black	No	Group 2B	No
Amorphous fumed silica	No	No	No
Octamethylcyclotetrasiloxane	No	No	No
Butan-2-one O,O',O",O"- silanetetrayltetraoxime	No	No	No

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal. Cured

rubber can be incinerated or landfilled following EPA and local regulations.

Hazardous waste number: Not a RCRA hazardous waste.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

Not regulated
None
None
None

Water Transportation (IMO/IMDG)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
None
Exceptions:
Not regulated
None
None
None

## 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.

Immediate Health, Delayed Health
None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status:

All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2, 3, 8, 11

Prepared by: Product Safety and Regulatory Affairs

**Issue date:** 09/13/2017

IDH number: 230153 Product name: LOCTITE SI 5900 known as 5900 RTV SIL

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 230153 Product name: LOCTITE SI 5900 known as 5900 RTV SIL