

Revision Number: 003.0 Issue date: 05/02/2017

# 1. PRODUCT AND COMPANY IDENTIFICATION

**TECHNOMELT PA 633 N Product name:** IDH number:

633

Product type: Hotmelt adhesive Item number: OM-633-I3 Restriction of Use: None identified Region: United States

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

**Contact information:** 

Telephone: (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711

122242

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

MOLTEN ADHESIVE MAY CAUSE SEVERE BURNS.

VAPORS ABOVE MOLTEN ADHESIVE MAY CAUSE EYE, SKIN AND

RESPIRATORY TRACT IRRITATION.

STATIC CHARGES GENERATED BY EMPTYING PACKAGE IN OR NEAR

FLAMMABLE VAPORS MAY CAUSE IGNITION.

HAZARD CLASS	HAZARD CATEGORY
None	None

PICTOGRAM(S)		
None		

#### **Precautionary Statements**

Prevention: Not prescribed Response: Not prescribed Storage: Not prescribed Not prescribed Disposal:

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
None	None	None

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. If symptoms develop and persist, get medical attention.

Skin contact: Molten adhesive may cause severe burns. Cool melted product on skin with

plenty of water. Do not remove solidified product. Cover affected areas with clean sheeting or gauze and seek immediate medical attention. No attempt should be made to remove material from skin or to remove contaminated

clothing as damaged skin can be easily torn.

Eye contact: If eye contact occurs with molten material immediately cool with water. Do not

remove adhesive. Seek medical attention.

**Ingestion:** Ingestion of solid adhesive is not expected to be hazardous. If symptoms

develop and persist, get medical attention.

Symptoms: See Section 11.

### 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: In case of fire, keep containers cool with water spray.

**Hazardous combustion products:** Oxides of carbon. Acrid smoke and fumes.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow material to contaminate ground water system.

Clean-up methods: Ensure adequate ventilation. Wear suitable protective clothing, gloves and

eye/face protection. Sweep up spilled material. Avoid creating dust. Keep in

suitable and closed containers for disposal.

### 7. HANDLING AND STORAGE

**Handling:** Do not place wet or damp solid into melt tank. Follow suggested application

temperature. Always be careful around molten material. Avoid skin contact with molten resins. Do not wear contact lenses. Avoid dust formation.

Storage: Keep cool in accordance with information on label and in Technical Data

Sheets.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
None	None	None	None	None

Engineering controls: Ventilation hoods and fans required when working with organic solvents or in

hot melt applications. Heat only in areas with appropriate exhaust ventilation.

Respiratory protection: Solid Resin: Dust safety masks are recommended when the potential for dust

inhalation exists. Molten Resin: Use a NIOSH approved air-purifying respirator

with an organic vapor cartridge.

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Do not wear

contact lenses.

Skin protection: Insulated gloves and long sleeved clothing are strongly recommended when

working with molten adhesive.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:SolidColor:AmberOdor:SlightOdor threshold:Not available.

pH: Not applicable
Vapor pressure: Not applicable
Boiling point/range: Not determined

Melting point/ range: 110 - 135 °C (230°F - 275°F) (Softening Point)

**Specific gravity:** 1.2 - 1.3 **Vapor density:** Not applicable

Flash point: No flash point up to 200 °C

Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Flammability:
Flammability:
Evaporation rate:
Solubility in water:
Partition coefficient (n-octanol/water):
Not applicable
Insoluble
Not available.

VOC content: 0 g/l

 Viscosity:
 Not available.

 Decomposition temperature:
 Not available.

### 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition Carbon dioxide, carbon monox

products:

Carbon dioxide, carbon monoxide and irritating and/or toxic gases and particulate may be

generated by thermal decomposition or combustion.

**Incompatible materials:** Acids and bases. Oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Excessive heat.

### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

#### Potential Health Effects/Symptoms

Inhalation: Continuous breathing of vapors above molten adhesive may irritate mucous membranes. Dusts

from solid adhesive may cause irritation.

**Skin contact:** Molten adhesive may cause severe burns. Solid adhesive has no hazards.

Eye contact: Molten adhesive in eyes will cause severe and permanant damage. Can cause mechanical

irritation if dusts are generated.

Ingestion: Not expected under normal conditions of use. May cause gastrointestinal tract irritation if

swallowed.

Hazardous Component(s)	LD50s and LC50s	Os and LC50s Immediate and Delayed Health Effects	
None	None	None	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
None	None	None	None

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None
None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

## 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: None above reporting de minimis.

**California Proposition 65:** No California Proposition 65 listed chemicals are known to be present.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other

components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

Please contact Regulatory Affairs for additional details.

# 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Alicia Griffin, Regulatory Affairs Specialist

**Issue date:** 05/02/2017

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.